
QUEUING THEORY: AN INTRODUCTION



OVERVIEW

- Service Utilization Factor & Traffic Intensity
- Little's Formulas
- Classification of Queuing Systems
- Types of Queues of Interest
- Assumption in Queuing Model
- Limitations of Queuing Model

Service Utilization Factor

- Consider an M/M/1 queue with arrival rate = λ and service intensity = μ
- λ = Expected capacity demand per time unit
- μ = Expected capacity per time unit

 \Rightarrow

$$\rho = \frac{Capacity\ Demand}{Available\ Capacity} = \frac{\lambda}{\mu}$$

 Similarly, if there are c servers in parallel, i.e., an M/M/c system but the expected capacity per time unit is then c*μ

$$\Rightarrow \rho = \frac{\text{Capacity Demand}}{\text{Available Capacity}} = \frac{\lambda}{c * \mu}$$

Traffic Intensity

The ratio λ/μ is called the traffic intensity or the utilization factor and it determines the degree to which the capacity of service station is utilized.

$$\rho = \frac{Mean \ Rate \ of \ Arrival \ in \ the \ Queue(\lambda)}{Mean \ Service \ Rate(\mu)}$$

Little's Formulas

- Little's Formulas represent important relationships between L, L_q, W, and W_q.
- These formulas apply to systems that meet the following conditions:
 - Single queue systems,
 - Customers arrive at a finite arrival rate λ, and
 - The system operates under a steady state condition.

$$L = \lambda W$$

$$L_q = \lambda W_q$$

$$L = L_{q} + \lambda/\mu$$

For the case of an infinite population

Little's Formulas

EXAMPLE:


• A monitor on a disk server showed that the average time to satisfy an I/O request was 100 milliseconds. The I/O rate was about 100 requests per second. What was the mean number of requests at the disk server?

• Using Little's law:

Mean number in the disk server


- = Arrival rate × Response time
- = 100 (requests/second) \times (0.1 seconds)
- = 10 requests

1. SINGLE-SERVER SINGLE-STAGE QUEUE



e.g., Your family dentist's office, Library counter, etc.


2. MULTIPLE-SERVER SINGLE-STAGE QUEUE




e.g., Booking at a service station



3. SINGLE-SERVER MULTIPLE-STAGE QUEUE




e.g., Cutting, turning, knurling, drilling, grinding, packaging operation of steel




Pharmacy Conveyor System >>>>

4. MULTIPLE-SERVER MULTIPLE-STAGE QUEUE



5. MULTIPLE, PARALLEL FACILITIES WITH MULTIPLE QUEUES MODEL



e.g., Different cash counters in electricity office

Types of Queues of Interest

- Analytical models for estimating capacity and related metrics
 - Single Server
 - M/M/1, M/G/1, M/D/1, G/G/1, etc.
 - Multiple Server
 - M/M/s, M/G/∞, etc.
 - Multiple Stage
 - Markov Chain models

Assumption in Queuing Model

- The customer arrive for service at a single service facility at random according to Poisson distribution with mean arrival rate λ.
- The service time has exponential distribution with mean service rate μ.
- The service discipline followed is First Come First Served.
- Customer Behavior is Normal
- Service facility behavior is Normal
- The calling source has infinite size
- The mean arrival rate is less than the mean service rate
- The waiting space available for customer in the queue is infinite

Limitations of Queuing Model

- The waiting space for the customer is usually limited
- The arrival rate may be state dependent
- The arrival process may not be stationary
- The population of customers may not be infinite and the queuing discipline may not be First Come First Serve
- Services may not be rendered continuously
- The Queuing system may not have reached the steady state. It may be, instead, in transient state

