Date of publication 15 January 2026, date of current version 25 April 2026.

Digital Object Identifier 10.1109/ACCESS.2026.3389102

Dual-Space Semantic Projection and Adaptive Logit Calibration for Long-Tailed Indonesian Sequence Classification

HASAN DWI CAHYONO
Department of Data Science, Universitas Sebelas Maret, Surakarta 57126, Indonesia (e-mail: hasan.dwi.cahyono@gmail.com)

Corresponding author: Hasan Dwi Cahyono (e-mail: hasan.dwi.cahyono@gmail.com).

This research was supported in part by open-access computational resources and benchmark datasets provided by the Indonesian NLP research community, IndoNLU, IndoLEM, and Hugging Face.

ABSTRACT Real-world natural language processing applications frequently suffer from acute class imbalance and noisy colloquial dialects, causing standard transformer classifiers to collapse into majority categories and exhibit complete blindness toward critical minority classes. While causal autoregressive models (such as GPT-2) offer a mechanism for synthetic minority oversampling, unconstrained text continuation introduces severe semantic drift and hallucination that corrupts downstream decision boundaries. In this paper, we propose a comprehensive, end-to-end framework that unifies dual-space generative data augmentation with automated, data-driven imbalance calibration. First, candidate sequences generated via prefix-constrained autoregression are strictly audited through an adaptive dual-space similarity suite combining continuous sentence embeddings (Euclidean distance and cosine similarity) with discrete token lattices (Jaccard index and sentence-level BLEU precision). Second, to address optimization bottlenecks without manual tuning, we establish an Automated Imbalance Calibrator (AIC) that dynamically derives the Fisher-consistent logit adjustment parameter τ, calculates minority gradient-starvation oversampling ratios, and adjusts label smoothing regularization directly from training class priors. Third, for highly noisy colloquial domains, we incorporate a 359-symbol emoji semantic normalizer grounded in the Multidimensional Lexicon of Emojis and a heterogeneous soft-voting ensemble combining diverse transformer inductive biases. Evaluated across four diverse Indonesian benchmark datasets (SmSA, HoASA, EmoT, and NusaX-Indonesian) spanning imbalance ratios up to $67.43\times$, our framework achieves $+2.40\%$ relative Macro-F1 gain on SmSA reaching 0.9246 (94.00% accuracy, MCC 0.9058), elevates HoASA classification accuracy to 94.41% and multi-class MCC to 0.7913 while advancing Macro-F1 from 0.5897 to 0.6944 ($+17.75\%$ relative gain) and breaking the minority zero-recall barrier ($F_1 = 0.2857$), achieves 0.7883 Macro-F1 with 78.64% accuracy on EmoT ($+1.99\%$ relative gain, $p < 0.001$), and maintains robust generalization on NusaX-Indonesian (0.9017 Macro-F1, 91.00% accuracy, $p < 0.001$).

INDEX TERMS Class imbalance, data augmentation, generative transformers, Indonesian NLP, logit adjustment, long-tailed learning, natural language processing, sentiment analysis.

I. INTRODUCTION

DEEP learning architectures powered by the multi-head self-attention mechanism have advanced contemporary natural language processing [1]–[3]. Bidirectional encoder representations, such as BERT and its domain-adapted variants, demonstrate state-of-the-art capability in extracting rich contextual representations across various text classification tasks. However, the empirical success of these architectures is heavily predicated on the availability of large-scale, high-quality, and symmetrically balanced training corpora. In real-world industrial and diagnostic applications, natural language corpora rarely exhibit balanced class distributions. Consequently, standard cross-entropy minimization causes deep models to develop severe biases toward overrepresented classes.

For languages outside the high-resource anglophone sphere, such as Bahasa Indonesia, developing robust language understanding systems entails compounding structural challenges

[4], [5]. Indonesian represents the fourth most populous nation globally, characterized by intense digital engagement across social media and e-commerce platforms. Yet, computational resources for Indonesian natural language processing remain disproportionately constrained [6]. Furthermore, digital Indonesian discourse frequently exhibits non-standard lexical registers, phonetic acronyms, dialectal particle insertions, and heavy code-switching with regional tongues (e.g., Javanese and Sundanese) [7]. When coupled with acute class imbalance, standard fine-tuning paradigms fail catastrophically on minority categories, frequently producing zero-recall failure modes on critical tail classes.

To address sample poverty without prohibitive manual annotation costs, text data augmentation has emerged as an indispensable research methodology [8], [9]. Conventional rule-based augmentation techniques, such as random word deletion, synonym insertion, and round-trip back-translation [8], [9], operate on localized surface-level perturbations. In colloquial Indonesian, where syntactic meaning is heavily modulated by context and informal abbreviations, naive token swapping frequently alters sentence semantics or destroys grammatical coherence. Recently, autoregressive language decoders and large language model prompting mechanisms [10]–[12] have demonstrated remarkable capability in generating syntactically fluid text continuations. Nevertheless, unguided autoregressive decoding suffers from semantic drift, wherein the generated continuation gradually departs from the conditioning class semantics.

However, naively transplanting generative augmentation into imbalanced classification pipelines introduces substantial optimization risks. Unconstrained synthetic generation generates hallucinations that contaminate the training distribution with noisy pseudo-labels, destabilizing gradient descent. Concurrently, standard empirical loss objectives remain fundamentally uncalibrated for skewed class distributions. Heuristic remedies, such as inverse frequency weighting, often lead to gradient explosions that collapse majority-class precision. To overcome these dual challenges, an effective framework must simultaneously constrain the geometric manifold of synthetic sequences and calibrate the classifier decision boundaries through principled statistical mechanics.

To resolve these interconnected bottlenecks, this article establishes an integrated methodological and empirical framework designed for low-resource and skewed sequence classification. We formulate an analytical data filtering suite that operates concurrently in continuous latent spaces and discrete lexical token graphs. Furthermore, we develop an adaptive logit calibration module that automatically neutralizes empirical class skewness during backpropagation without destabilizing dominant representations. Below, we outline our principal contributions, followed by the complete structural roadmap of this investigation:

1) **Dual-Space Manifold-Constrained Augmentation:** We establish an autoregressive text augmentation pipeline governed by a multi-dimensional similarity evaluation suite comprising continuous embedding distances (ECU, COS) and discrete token lattices (JAC, BLEU), proving that thresholded filtering prevents out-of-distribution hallucinations.
2) **Automated Imbalance Calibrator (AIC):** We introduce a data-driven module that automatically detects minority categories, derives dynamic logit adjustment margins $\tau(IR)$, applies gradient-starvation oversampling, and configures adaptive label smoothing directly from empirical training priors without manual intervention.
3) **Colloquial Normalization and Multi-Model Ensembling:** We ground emoji semantic normalization in the empirical Multidimensional Lexicon of Emojis (MLE) [13] (spanning 359 standardized emojis across 10 emotional dimensions) and formulate a heterogeneous soft-voting ensemble combining distinct pretrained backbones (IndoBERT and IndoBERTweet), resolving affective noise and capturing nuanced colloquial expressions.
4) **Comprehensive Multi-Domain Benchmark Validation:** We validate the proposed framework across four distinct Indonesian corpora (SmSA, HoASA, EmoT, and NusaX-Indonesian), demonstrating that our methodology completely eliminates zero-recall failure modes on minority categories ($F_1 = 0.2857$ on HoASA complaints), yields up to $+14.49\%$ relative Macro-F1 improvement, and maintains Pareto-optimal accuracy on majority classes.

The remainder of this article is structured as follows: Section II surveys foundational literature across text data augmentation, Indonesian language models, and class imbalance mitigation. Section III delineates the end-to-end mathematical architecture of our framework across all five functional phases. Section IV outlines the benchmark corpora, baseline models, training configurations, and evaluation metrics. Section V presents comprehensive empirical results and discusses qualitative confusion transitions. Section VI provides detailed ablation studies and sensitivity analyses, and Section VII concludes the paper with future research directions.

II. RELATED WORK

This section reviews related academic literature across three core areas relevant to our investigation. First, Section II-A discusses the evolution of text data augmentation techniques from lexical substitutions to generative decoders. Second, Section II-B outlines the development of pretrained Indonesian language models and their application domains. Third, Section II-C analyzes contemporary algorithmic strategies for resolving severe class imbalance in deep sequence representation learning.

A. TEXT DATA AUGMENTATION IN NLP

Text data augmentation methodologies broadly divide into heuristic rule-based perturbations and neural generative models [8], [9]. Early techniques focused on surface transformations: rule-based lexical perturbations, including synonym

replacement, random insertion, random swap, and random deletion (e.g., EDA [14]), yield modest performance improvements on simple benchmark tasks [8]. However, heuristic perturbation relies heavily on curated lexical resources such as WordNet, which are severely limited or incomplete for colloquial Indonesian registers. Furthermore, arbitrary token deletions frequently invert sentiment polarity or introduce ungrammatical artifacts that impair representation learning.

Back-translation translates text into an intermediate pivot language and back to generate syntactic paraphrases [8], [9]. While effective for formal corpora, back-translation frequently fails on colloquial dialects because standard translation APIs normalize informal slang into sterile formal prose, eliminating key emotional markers. Contextual augmentation leverages masked language models to substitute tokens conditioned on bidirectional context [15], [16]. With the advent of autoregressive decoders, generative continuation and counterfactual text synthesis have gained prominence [10]–[12], [17]–[20]. Refai et al. [10] demonstrated that transformer generation with cosine filtering improves Arabic text classification. Our work significantly expands this concept by formulating a dual-space metric projection combining continuous embeddings with discrete n-gram lattices.

B. INDONESIAN PRETRAINED LANGUAGE MODELS

The development of transformer backbones [1], [2] tailored to the Indonesian language has accelerated in recent years [4]–[6]. Wilie et al. [4] introduced IndoNLU, establishing the foundational IndoBERT model trained on over 220 million words spanning Indonesian news, Wikipedia, and web corpora. IndoBERT demonstrated marked superiority over multilingual baselines (e.g., mBERT and XLM-RoBERTa) across sequence labeling and sentence classification benchmarks. Concurrently, Koto et al. [3], [5] explored discourse probing and pretrained representations, while introducing IndoBERTweet [21], a model specifically pretrained on over 400 million Indonesian social media tokens. IndoBERTweet effectively captures colloquial vocabulary, informal particles, and slang registers prevalent in digital conversations. More recently, large-scale multi-task and dialect benchmarks such as NusaCrowd [22] and NusaX [23] have broadened linguistic coverage across regional Indonesian languages, complementing earlier foundational colloquial lexicons [7]. Our framework strategically leverages these architectures within a heterogeneous ensemble to capture both formal document syntax and colloquial social nuances.

C. HANDLING SEVERE CLASS IMBALANCE

Class imbalance has long been recognized as a primary failure mode in statistical pattern recognition [24]–[29]. Classical remedies operate at the data level via random oversampling (ROS), random undersampling (RUS), or synthetic minority interpolation such as SMOTE [25]. In natural language domains, continuous interpolation between token embeddings rarely maps to coherent discrete sequences, limiting the utility of naive feature-space interpolation. Consequently, modern deep learning research has concentrated on algorithmic loss formulation, margin adjustments, and decoupled classifiers [30]–[32].

Algorithmically, Weighted Cross-Entropy (WCE) penalizes minority errors by inverse class frequencies [27], [28]. While conceptually straightforward, raw frequency weighting frequently causes gradient instability under acute skewness ($IR > 10$), collapsing majority class accuracy. Margin-aware and cost-sensitive losses attempt to modulate gradients to protect tail categories, including Focal Loss [33], Class-Balanced Loss [34], Label-Distribution-Aware Margin (LDAM) [35], Balanced Meta-Softmax [36], and Seesaw Loss [37]. Other recent approaches explore vector scaling [31], distributional robustness [38], context-rich minority oversampling [39], and label disentanglement [40]. However, recent uncertainty calibration investigations [41]–[44] demonstrated that heuristic margin scaling severely impairs probability calibration and overfits to label noise. Deferred re-weighting schedules and effective-sample weighting also risk inducing minority collapse on severe imbalance [45], [46]. Recently, Menon et al. [30] established logit adjustment, proving that shifting network logits by empirical class log-priors guarantees Fisher consistency for balanced error, while Wang et al. [44] and Li et al. [47] explored calibrated margins and targeted loss formulations for imbalanced sequence classification. Our work unifies logit adjustment with dynamic skew-dependent scaling and targeted mini-batch oversampling.

III. METHODOLOGY AND ARCHITECTURE

The proposed framework integrates generative data synthesis, multi-space quality filtering, and adaptive boundary calibration into a cohesive multi-stage architecture. The operational pipeline is organized into five sequential phases detailed in the subsections below. Specifically, Section III-A presents preprocessing and emoji semantic mapping; Section III-B details autoregressive continuation generation; Section III-C establishes multi-metric semantic similarity filtering; Section III-D derives the Automated Imbalance Calibrator (AIC); and Section III-E describes the heterogeneous multi-model ensembling strategy. Together, these five functional phases establish an end-to-end framework capable of mitigating severe data sparsity while strictly preserving semantic class boundaries.

A. PHASE 1: PREPROCESSING AND EMOJI SEMANTIC MAPPING

Digital text in low-resource and colloquial registers contains heavy orthographic noise that degrades tokenization efficiency. Raw text inputs undergo systematic cleaning: HTML entities, non-standard punctuation clusters, trailing URLs, and social media user tags (@username) are removed. Alphabetic text is case-folded to lower case, while sequences of repeated characters (e.g., “bangeeet”) are normalized to standard lexical forms. To address non-standard dialectal registers and informal orthography, we incorporate the Colloquial Indonesian Lexicon established by Salsabila et al. [7], which

normalizes over 15,000 empirical colloquial word forms into their standard grammatical lemmas, preventing sub-word fragmentation and resolving lexical ambiguity before tokenization. In formal domains, these operations eliminate superficial token noise and reduce vocabulary dispersion.

In colloquial social media text, emotional expression is heavily mediated by graphical emojis and stylized pictograms. Standard NLP pipelines typically strip these characters as unprocessable noise, thereby discarding vital sentiment indicators. Such naive removal obscures critical pragmatic intent, especially in sentiment-heavy conversational contexts. Rather than discarding emojis or relying on ad-hoc heuristics, we establish an empirically grounded emoji semantic mapper utilizing the Multidimensional Lexicon of Emojis (MLE) by Godard and Holtzman [13]. The MLE provides standardized continuous ratings across 359 emojis evaluated along 10 discrete affective and sentiment dimensions (Tables 1 and 2 of [13]). Based on these empirical distributions, each emoji e is systematically projected into canonical Indonesian affective tokens:

$$e \mapsto \begin{cases} \texttt{_emosi_marah_}, & e \in \mathcal{E}_{\text{anger}} \\ \texttt{_emosi_sedih_}, & e \in \mathcal{E}_{\text{sadness}} \\ \texttt{_emosi_takut_}, & e \in \mathcal{E}_{\text{fear}} \\ \texttt{_emosi_cinta_}, & e \in \mathcal{E}_{\text{love}} \\ \texttt{_emosi_bahagia_}, & e \in \mathcal{E}_{\text{joy}} \end{cases} \tag{1}$$

where $\mathcal{E}_c$ denotes the partition of emojis assigned to affective emotion category $c \in \{\text{anger}, \text{sadness}, \text{fear}, \text{love}, \text{joy}\}$ based on empirical valence and arousal ratings from the Multidimensional Lexicon of Emojis [13]. For example, the noisy social text *"Keren bgt filmnya [sedih] sedih banget T_T"* is converted to *"bagus banget filmnya _emosi_sedih_ sedih banget _emosi_sedih_"*. This transformation provides explicit lexical anchors that standard WordPiece tokenizers can encode without sub-word fragmentation. Consequently, the downstream classifier learns to associate emotional iconography with clear semantic vectors. Empirical evaluation demonstrates that this mapping eliminates tokenizer out-of-vocabulary fallback, boosting emotional feature saliency.

B. PHASE 2: AUTOREGRESSIVE CONTINUATION GENERATION

Let $\mathcal{D}_{\text{train}} = \{(x_i, y_i)\}_{i=1}^{N}$ denote the training set of size N, with input sequences $x_i \in \mathcal{X}$ and categorical labels $y_i \in \mathcal{Y} = \{1, \ldots, K\}$. Minority classes are identified via the subset $\mathcal{Y}_{\text{min}} \subset \mathcal{Y}$. For each seed sample (x_i, y_i) where $y_i \in \mathcal{Y}_{\text{min}}$, the original text sequence $x_i = (w_1^{(0)}, \ldots, w_{|x_i|}^{(0)})$ is partitioned into a prompt prefix $x_i^{\text{prefix}} = (w_1^{(0)}, \ldots, w_{L_{\text{prompt}}}^{(0)})$ comprising the initial $L_{\text{prompt}} = \max(3, \lfloor \lambda \cdot |x_i| \rfloor)$ tokens, where $\lambda = 0.5$ denotes the prefix retention fraction. This prefix retention anchors the generation process to genuine linguistic patterns present in the authentic sample.

The prefix is fed to an autoregressive decoder model $\mathcal{M}_{\text{gen}}$ parameterized by weights Θ. Conditioning directly on the prefix forces the generator to maintain grammatical continuity with genuine training utterances. The model samples a synthetic sequence continuation $\hat{x}_i^{\text{gen}} = (w_1, \ldots, w_{L_{\text{gen}}})$ of length $L_{\text{gen}} = |\hat{x}_i^{\text{gen}}|$ according to the factorized causal probability:

$$P(\hat{x}_i^{\text{gen}} \mid x_i^{\text{prefix}}; \Theta) = \prod_{t=1}^{L_{\text{gen}}} P(w_t \mid x_i^{\text{prefix}}, w_1, \ldots, w_{t-1}; \Theta) \tag{2}$$

This autoregressive decomposition ensures that each successive token distribution remains conditioned on both historical seed context and newly generated tokens. Generation is executed using beam-search guided decoding with a beam width $B_{\text{beam}} = 5$, repetition penalty $r = 2.5$, no-repeat n-gram size $n_{\text{ngram}} = 3$, top-p nucleus probability threshold $p_{\text{nuc}} = 0.95$, and decoding temperature $T_{\text{sample}} = 1.0$. The complete augmented candidate text is constructed by concatenating the original seed prompt with the synthetic continuation: $\tilde{x}_i = x_i \circ \hat{x}_i^{\text{gen}}$, assigned the identical ground-truth label y_i. This causal expansion yields grammatically coherent sentences while preserving the thematic premise of the initial seed. Furthermore, the combination of beam search and nucleus sampling prevents degenerative token loops while allowing sufficient lexical diversity.

C. PHASE 3: MULTI-METRIC SEMANTIC SIMILARITY FILTERING

Unconstrained neural generation frequently yields degenerative repetitions or off-topic drifts. Grounded in computational optimal transport and geometric measure theory [48], [49], bounding semantic deviation prevents catastrophic manifold displacement. To ensure that only high-quality, semantically consistent augmentations enter the final training pool, every generated candidate $\tilde{x}_i$ is evaluated against its origin seed x_i across four mathematical metric spaces. The subsections below formalize these individual distance metrics and establish the empirical thresholding criteria utilized to prune off-manifold candidates. In addition, strict zero-leakage hashing protocols are enforced to guarantee the complete separation of training and evaluation data.

1) Dense Embedding Euclidean Distance (ECU)

Dense representations are generated using a multilingual transformer embedding backbone $\phi : \mathcal{X} \to \mathbb{R}^D$ ($D = 768$) [10]. This transformer mapping projects input text sequences into a semantically structured latent metric space. The Euclidean metric measures absolute geometric distance between the origin seed and the candidate continuation:

$$d_{\text{ECU}}(x, \tilde{x}) = \|\phi(x) - \phi(\tilde{x})\|_2 = \sqrt{\sum_{d=1}^{D} (\phi_d(x) - \phi_d(\tilde{x}))^2} \tag{3}$$

A candidate is retained if its distance is within one standard deviation below the empirical distribution mean: $d_{\text{ECU}}(x, \tilde{x}) \leq \mu_{\text{ECU}} - \sigma_{\text{ECU}}$. This strict geometric constraint ensures that the candidate lies in close proximity to the original observation. Consequently, synthetic instances that deviate excessively

in vector magnitude are pruned prior to model training. By enforcing this spherical neighborhood bound, the filtering operator guarantees high manifold fidelity.

2) Dense Embedding Cosine Similarity (COS)

Cosine similarity evaluates directional alignment between normalized sentence vectors in the latent embedding space. Unlike Euclidean distance, cosine similarity isolates angular orientation while remaining invariant to token length or embedding magnitude. The similarity score between original seed x and candidate continuation $\tilde{x}$ is formulated as:

$$S_{\text{COS}}(x, \tilde{x}) = \frac{\phi(x) \cdot \phi(\tilde{x})}{\|\phi(x)\|_2 \|\phi(\tilde{x})\|_2} \tag{4}$$

Candidates are admitted if their angular alignment satisfies $S_{\text{COS}}(x, \tilde{x}) \geq \mu_{\text{COS}} + \sigma_{\text{COS}}$, ensuring that the underlying semantic vector direction is strictly preserved. This directional threshold prevents contradictory sentiment shifts while accommodating diverse lexical paraphrasing. In acute imbalance regimes, directional alignment proves vital for capturing diverse expressions of rare classes. Overall, cosine filtering ensures that synthesized samples remain collinear with the true category concept.

3) Lexical Jaccard Index (JAC)

Discrete lexical overlap is computed over unique token vocabularies to enforce surface terminological consistency. Let $\mathcal{V}(x)$ and $\mathcal{V}(\tilde{x})$ denote the sets of unique lemmatized word tokens in the seed and candidate text, respectively. The Jaccard similarity coefficient quantifies the ratio of shared vocabulary to total vocabulary:

$$J(x, \tilde{x}) = \frac{|\mathcal{V}(x) \cap \mathcal{V}(\tilde{x})|}{|\mathcal{V}(x) \cup \mathcal{V}(\tilde{x})|} \tag{5}$$

Filtering requires $J(x, \tilde{x}) \geq \mu_{\text{JAC}} + \sigma_{\text{JAC}}$, retaining candidates that share core domain terminology with the seed. This lexical constraint prevents the generative decoder from drifting into generic, off-topic vocabulary. It provides an orthogonal filtering signal to dense neural embeddings by operating directly on discrete lexical tokens. As a result, synthetic instances retain domain-specific keywords essential for downstream discriminative learning.

4) Bilingual Evaluation Understudy (BLEU)

Local syntactic collocation is evaluated via sentence-level BLEU-4 with an explicit brevity penalty [8], [50]. While Jaccard measures set-level vocabulary overlap, BLEU evaluates ordered n-gram precision up to 4-grams, capturing local phrase structure. The metric is computed against the seed text as:

$$\text{BLEU}(x, \tilde{x}) = \text{BP}(x, \tilde{x}) \cdot \exp\left(\sum_{n=1}^{4} w_n \ln p_n(x, \tilde{x})\right) \tag{6}$$

where $w_n = 0.25$ denotes uniform weighting across n-gram orders up to 4, $p_n(x, \tilde{x})$ represents modified n-gram precision, and $\text{BP}(x, \tilde{x})$ is the brevity penalty defined as:

$$\text{BP}(x, \tilde{x}) = \begin{cases} 1, & \text{if } |\tilde{x}| > |x| \\ \exp\left(1 - \frac{|x|}{|\tilde{x}|}\right), & \text{if } |\tilde{x}| \leq |x| \end{cases} \tag{7}$$

where $|x|$ and $|\tilde{x}|$ denote the token lengths of the reference seed and candidate continuation, respectively. Candidates are admitted if $\text{BLEU}(x, \tilde{x}) \geq \mu_{\text{BLEU}} + \sigma_{\text{BLEU}}$, ensuring that key structural phrases and idioms are preserved. This rigorous syntactic filter is especially critical for formal text where subtle sentiment hedging relies on precise multi-word collocations. By penalizing arbitrary syntactic permutations, BLEU pruning prevents the insertion of disruptive polarity-inverting clauses. Consequently, the resulting augmented corpus exhibits high grammatical fluency and structural coherence.

5) Empirical Adaptive Thresholding and Zero-Leakage Purging

Rather than imposing static heuristics, thresholds $\theta = \mu \pm \sigma$ are calculated empirically over all generated candidates for each dataset. This data-driven approach adapts automatically to the semantic diversity of each corpus. Following threshold pruning, a strict zero-leakage hash verification cross-references all candidates against the validation ($\mathcal{D}_{\text{val}}$) and test ($\mathcal{D}_{\text{test}}$) sets. Any candidate matching an evaluation instance is immediately purged, guaranteeing zero test set contamination.

D. PHASE 4: ADAPTIVE IMBALANCE CALIBRATION (AIC)

When training deep classifiers on imbalanced augmented datasets, standard cross-entropy remains biased toward majority categories. In the absence of margin adjustments, the network minimizes global empirical risk by sacrificing minority class boundaries. To overcome this limitation, we formulate an Automated Imbalance Calibrator (AIC) executing adaptive parameter derivation directly from the empirical training label counts $\{N_k\}_{k=1}^{K}$. Below, we detail the automated minority detection mechanism, dynamic logit-adjusted loss formulation, gradient-starvation oversampling multiplier, and adaptive label smoothing regularization.

1) Automated Minority Detection

To eliminate manual heuristic thresholding across disparate corpora, AIC implements an automated detection protocol based on empirical class frequencies. The imbalance ratio IR quantifies the disparity between the most and least frequent categories:

$$IR = \frac{\max_k N_k}{\min_k N_k} \tag{8}$$

A class k is designated as a minority category if its empirical prior $\pi_k = \frac{N_k}{N}$ falls below 80% of the uniform prior or its sample count is less than 75% of the median class size:

$$k \in \mathcal{Y}_{\text{min}} \iff \pi_k < \frac{0.80}{K} \ \vee \ N_k < 0.75 \cdot \text{med}(\{N_j\}_{j=1}^{K}) \tag{9}$$

This dual condition robustly identifies tail classes across both multi-class and binary configurations without hyperparameter tuning. By evaluating both uniform deviation and median proximity, the rule reliably flags minority classes in both skewed long tails and isolated minority classes. Once identified, minority categories are routed to targeted oversampling and logit margin calibration.

2) Dynamic Logit-Adjusted Loss

To enforce statistically consistent separation margins without deforming feature representations, we incorporate Fisher-consistent Logit Adjustment [30]. The network outputs unnormalized logits $\mathbf{z} \in \mathbb{R}^K$. During training, the logits are shifted by the empirical class log-priors $\log \boldsymbol{\pi}$:

$$\tilde{z}_k = z_k + \tau(IR) \cdot \log(\pi_k + \epsilon_0) \tag{10}$$

where $\epsilon_0 = 10^{-8}$ is a numerical stabilizer, and the dynamic temperature scaling parameter $\tau(IR)$ is dynamically scaled via a logarithmic rule based on the observed imbalance ratio:

$$\tau(IR) = \begin{cases} 0.0, & IR \leq 2.0 \\ \text{clip}\left(0.45 \cdot \log_{10}(IR),\ 0.35,\ 1.0\right), & IR > 2.0 \end{cases} \tag{11}$$

The Logit-Adjusted Cross-Entropy loss is then computed directly over shifted logits $\tilde{\mathbf{z}}$ as:

$$\begin{aligned} \mathcal{L}_{\text{LA}}(y, \mathbf{z}) &= -\log\left(\frac{\exp(\tilde{z}_y)}{\sum_{j=1}^{K}\exp(\tilde{z}_j)}\right) \\ &= -\log\left(\frac{\mathrm{e}^{z_y+\tau(IR)\log(\pi_y+\epsilon_0)}}{\sum_{j=1}^{K}\mathrm{e}^{z_j+\tau(IR)\log(\pi_j+\epsilon_0)}}\right) \end{aligned} \tag{12}$$

This formulation enforces larger relative margins for rare classes, expanding their decision boundaries in latent representation space. In contrast to heuristic weighting schemes, logit adjustment is provably Fisher-consistent for balanced multiclass error. Furthermore, during inference, if validation tracking detects a density shift where $\pi_k^{\text{val}} > 1.25\pi_k^{\text{train}}$, a post-hoc test prior correction is applied: $\hat{z}_k = z_k - \tau_{\text{eval}} \log(\pi_k + \epsilon_0)$ with $\tau_{\text{eval}} = 0.5\tau(IR)$. This inference-time adjustment guarantees robust generalization across non-stationary test distributions.

3) Gradient-Starvation Target Oversampling

When batch size $B = 64$ and minority prior $\pi_k \ll 1/B$, mini-batches frequently contain zero minority samples, starving the optimizer of minority gradient signals. Under standard uniform sampling, the expected number of minority instances per mini-batch drops well below unity. To overcome this optimization bottleneck, AIC computes an integer replication multiplier m_k inversely proportional to the class prior:

$$m_k = \begin{cases} 1, & k \notin \mathcal{Y}_{\text{min}} \\ \min\left(10,\ \max\left(1,\ \left\lceil \frac{2.0}{B \cdot \pi_k} \right\rceil\right)\right), & k \in \mathcal{Y}_{\text{min}} \end{cases} \tag{13}$$

For HoASA negative samples ($\pi_{\text{neg}} = 0.0131$), $m_{\text{neg}} = \lceil 2.0/(64 \times 0.0131) \rceil = 3$, replicated up to $8\times$ under augmented configurations to guarantee non-zero minority gradient expectation in every mini-batch. By ensuring that every forward-backward pass incorporates valid minority supervision, the model avoids degenerate parameter updates that bias gradients entirely toward the majority class. This steady gradient stream stabilizes representation learning on rare classes without causing excessive epoch latency. Consequently, the optimization trajectory converges smoothly toward a balanced classification boundary.

4) Adaptive Label Smoothing Regularization

To prevent overconfidence on tail classes while accommodating label noise, AIC scales the label smoothing parameter α_{LS} inversely with data skewness. Standard fixed label smoothing can over-regularize majority classes or under-regularize noisy minority samples. Our adaptive formulation dynamically adjusts the smoothing factor according to:

$$\alpha_{\text{LS}} = \text{clip}\left(\frac{0.08}{\sqrt{1 + 0.5 \cdot \log_{10}(IR)}},\ 0.03,\ 0.08\right) \tag{14}$$

For extreme skewness ($IR = 67.43$), $\alpha_{\text{LS}} \approx 0.058$, providing gentle regularization that prevents the classifier from over-memorizing synthetic samples. When the imbalance ratio is low, α_{LS} safely increases toward 0.08 to guard against general label noise. By softening target distributions, this adaptive mechanism prevents the network from assigning arbitrarily high confidence to ambiguous border samples. As a result, calibrated predictive probabilities are maintained across both head and tail categories.

E. PHASE 5: HETEROGENEOUS MULTI-MODEL ENSEMBLING

In complex social media domains characterized by overlapping affective boundaries and dense slang (such as EmoT), single-model architectures frequently plateau. Individual models exhibit idiosyncratic inductive biases that can cause misclassifications on ambiguous dialectal expressions. Such unaligned predictions often lead to inconsistent classifications across subtle emotion pairs like sadness and fear. To maximize predictive diversity, we construct a heterogeneous multi-model ensemble combining models with complementary pretraining inductive biases:

$$P_{\text{ens}}(y = k \mid x) = \sum_{m=1}^{M} w_m \cdot P_m(y = k \mid x) \tag{15}$$

where M is the total number of constituent ensemble models, $P_m(y = k \mid x)$ is the posterior class probability predicted by the m-th model, and $w_m \geq 0$ represents the scalar ensemble weight assigned to model m, subject to the simplex constraint $\sum_{m=1}^{M} w_m = 1$. In our empirical setup, we instantiate $M = 3$ diverse backbones fine-tuned on ECU-filtered, COS-filtered, and baseline training subsets, parameterized with uniform convex weights $w_m = \frac{1}{M} = \frac{1}{3}$. Soft probability pooling effectively reduces predictive variance and smooths out individual model hallucinations. Furthermore, ensembling ensures that

classification confidence is distributed across multiple distinct contextual representations. Empirical evaluation demonstrates that this collective decision mechanism significantly improves discrimination on fine-grained affective boundaries.

IV. EXPERIMENTAL SETUP

To ensure complete reproducibility, this section describes the experimental configurations utilized in our evaluation. We benchmark the proposed methodology across a broad spectrum of linguistic registers, ranging from formal customer reviews to highly fragmented conversational streams. The discussion is structured across three subsections: Section IV-A details the statistical properties and split sizes of the four benchmark corpora; Section IV-B delineates model configurations, hyperparameter values, and adversarial regularization protocols; and Section IV-C defines the mathematical formulations of the six evaluation metrics employed to audit classification performance. This setup guarantees that all comparisons adhere to strict academic standards.

A. BENCHMARK DATASETS

We evaluate our framework across four benchmark datasets spanning diverse task domains, sentence lengths, and class imbalance ratios from the IndoNLU [4] and IndoLEM [5] suites. These corpora were chosen to represent authentic linguistic scenarios in low-resource natural language understanding, encompassing formal customer feedback, aspect-based reviews, social tweets, and conversational text. By testing across these contrasting registers, we verify the broad applicability and domain independence of our proposed methodology. The selected benchmarks cover varying degrees of class imbalance, ranging from balanced sentiment polarity to acute 67:1 label skewness:

1) **SmSA (*Sentiment Analysis on Prosa*):** Document-level sentiment categorized into *positive*, *negative*, and *neutral*. Moderate imbalance where neutral samples represent only 10.4% of the training corpus.
2) **HoASA (*Hotel Aspect-Based Sentiment Analysis*):** Hotel customer reviews evaluated on general aspect sentiment. Characterized by extreme class imbalance ($IR = 67.43\times$) with only 30 negative training samples (1.31%) against 2,023 neutral reviews (88.61%).
3) **EmoT (*Emotion Classification on Twitter*):** Social media tweets classified across five distinct emotion categories: *anger*, *fear*, *happy*, *love*, and *sadness*. Contains dense informal slang and overlapping affective boundaries.
4) **NusaX-Indonesian (*Curated Sentiment Analysis*):** Standardized multi-topic sentiment reviews [23] spanning food, travel, and services, classified into *positive*, *neutral*, and *negative* ($N = 1{,}000$, with 500 train, 100 validation, and 400 test samples; $IR = 1.61\times$). Serves as a high-quality, controlled benchmark balancing formal and colloquial registers.

Detailed partition counts and distribution characteristics are summarized in Table 1. Across all four benchmarks, official partition splits were strictly maintained to ensure fair comparison with existing literature. We compute empirical imbalance ratios to classify corpora into balanced, mildly imbalanced, moderately skewed, and severely skewed categories. This comprehensive taxonomy enables a systematic audit of how performance scales with data distribution properties.

B. MODEL CONFIGURATIONS AND HYPERPARAMETERS

All neural pipelines were implemented in PyTorch using the Hugging Face `transformers` library. Downstream classification utilized IndoBERT (`indobenchmark/indobert-base-p1`) for formal and curated document tasks (SmSA, HoASA, NusaX-Indonesian) and IndoBERTweet (`indolem/indobertweet-base-uncased`) for colloquial social domains (EmoT). Pretrained generative decoders were initialized from Indonesian GPT-2 (`cahya/gpt2-small-indonesian-522M`). Each model was instantiated with its corresponding domain-specific tokenizer to preserve optimal vocabulary alignment and minimize unknown token substitutions.

Models were optimized using the AdamW optimizer with a linear learning rate warmup over the first 10% of total steps, followed by linear decay. Sequence lengths were capped at 128 tokens across all datasets. Training was conducted with a batch size of 64, a base learning rate of 2×10^{-5} (reduced to 1×10^{-5} for EmoT ensembling), and a weight decay coefficient of 0.01. Adversarial regularization via Fast Gradient Method (FGM) [51] was enabled with embedding perturbation $\epsilon = 1.0$. Early stopping with a patience of 5 epochs monitored validation Macro-F1 to trigger model checkpoint restoration.

C. EVALUATION METRICS

Given the severe class imbalance present across multiple targets, relying solely on standard Accuracy is deeply deceptive. A naive majority classifier can report over 94% accuracy on HoASA while failing to classify a single negative complaint correctly. Under severe label skewness, global metrics disproportionately reflect majority performance while masking catastrophic failures on rare classes. To provide a rigorous and balanced evaluation, we evaluate performance using the multi-class confusion matrix $\mathbf{C} \in \mathbb{N}^{K\times K}$, where element C_{jk} denotes the number of test instances with ground-truth label j predicted as class k. We formalize six complementary metrics:

1) **Standard Accuracy (Acc):** Global proportion of correctly classified instances across all classes:

$$\text{Acc} = \frac{\sum_{k=1}^{K} C_{kk}}{\sum_{j=1}^{K}\sum_{k=1}^{K} C_{jk}} \tag{16}$$

2) **Macro-Precision ($\text{Prec}_{\text{macro}}$):** Unweighted arithmetic mean of per-class precisions:

$$\text{Prec}_{\text{macro}} = \frac{1}{K}\sum_{k=1}^{K}\text{Prec}_k = \frac{1}{K}\sum_{k=1}^{K}\frac{C_{kk}}{\sum_{j=1}^{K} C_{jk}} \tag{17}$$

TABLE 1. Benchmark Dataset Statistics and Split Distributions Across the Four Evaluated Corpora

Dataset	Domain / Task	Classes (K)	Train Size	Val Size	Test Size	Label Distribution (Train)	Imbalance Ratio (IR)
SmSA	Document Sentiment	3	11,000	1,260	500	positive: 6416 (58.3%), negative: 3436 (31.2%), neutral: 1148 (10.4%)	5.59× (Moderate)
HoASA	Aspect Hotel Sentiment	3	2,283	285	286	neut: 2023 (88.6%), pos: 230 (10.1%), neg: 30 (1.3%)	67.43× (Extreme)
EmoT	Twitter Emotion Analysis	5	3,521	440	440	anger: 881 (25.0%), happy: 814 (23.1%), sadness: 798 (22.7%), fear: 519 (14.7%), love: 509 (14.5%)	1.73× (Mild)
NusaX-Indonesian	Curated Sentiment Analysis	3	500	100	400	negative: 192 (38.4%), positive: 189 (37.8%), neutral: 119 (23.8%)	1.61× (Mild)

3) **Macro-Recall ($\text{Rec}_{\text{macro}}$):** Unweighted arithmetic mean of per-class recalls:

$$\text{Rec}_{\text{macro}} = \frac{1}{K}\sum_{k=1}^{K}\text{Rec}_k = \frac{1}{K}\sum_{k=1}^{K}\frac{C_{kk}}{\sum_{j=1}^{K}C_{kj}} \tag{18}$$

4) **Macro-F1 (F1_{macro}):** Harmonic mean of precision and recall calculated independently for each category and averaged without weighting:

$$\text{F1}_{\text{macro}} = \frac{1}{K}\sum_{k=1}^{K}\frac{2\cdot\text{Prec}_k\cdot\text{Rec}_k}{\text{Prec}_k+\text{Rec}_k+\epsilon_0} \tag{19}$$

where $\epsilon_0 = 10^{-8}$ prevents division by zero for unpredicted tail classes.

5) **Balanced Accuracy (BAcc):** Equivalent to Macro-Recall, representing the unweighted average recall across all categories: $\text{BAcc} = \text{Rec}_{\text{macro}}$.

6) **Matthews Correlation Coefficient (R_K):** The multi-class generalization of Matthews Correlation Coefficient computed from contingency matrix $\mathbf{C}$ [27]:

$$R_K = \frac{c\cdot s - \sum_{k=1}^{K}p_k t_k}{\sqrt{\left(s^2-\sum_{k=1}^{K}p_k^2\right)\left(s^2-\sum_{k=1}^{K}t_k^2\right)}} \tag{20}$$

where $c = \sum_{k=1}^{K}C_{kk}$ is the total number of correctly classified samples, $s = \sum_{j=1}^{K}\sum_{k=1}^{K}C_{jk}$ is the total evaluation sample count, $p_k = \sum_{j=1}^{K}C_{jk}$ is the total number of predictions for class k, and $t_k = \sum_{j=1}^{K}C_{kj}$ is the true support count for class k.

These metrics collectively capture both fine-grained per-class discrimination and aggregate classification reliability. By reporting both Macro-F1 and Balanced Accuracy, we ensure that minority improvements are evaluated without distortion from class priors. In addition, the Matthews Correlation Coefficient provides a rigorous contingency measure that penalizes asymmetric false positives and false negatives. Together, these indicators establish a robust benchmark for comparing algorithmic interventions under severe class imbalance.

V. RESULTS AND DISCUSSION

This section details the empirical findings obtained across the benchmark suite. We analyze classification trajectories across multiple evaluation criteria to establish the statistical validity of our framework. The analysis is structured into four subsections: Section V-A discusses the overall benchmark performance across all datasets and provides fine-grained breakdowns for SmSA and HoASA; Section V-B evaluates the comparative trade-offs between dense and lexical filtering spaces; Section V-C presents the results of multi-model ensembling on noisy social affect classification; and Section V-D formalizes the unified decision policy guiding optimal pipeline configuration. Together, these subsections demonstrate the generalizability of our proposed architecture.

A. OVERALL CLASSIFICATION BENCHMARK PERFORMANCE

Table 2 presents the comparative evaluation across all benchmark targets and filtering metrics. The results confirm that our framework achieves decisive performance gains across all benchmarks, elevating Macro-F1 on SmSA to 0.9246 ($+2.40\%$ relative gain, 94.00% accuracy, MCC 0.9058), elevating HoASA accuracy to 94.41% and Macro-F1 from 0.5897 to 0.6944 ($+17.75\%$ relative gain) alongside MCC of 0.7913, advancing EmoT Macro-F1 to 0.7883 ($+1.99\%$ relative gain, 78.64% accuracy, MCC 0.7307), and maintaining high baseline fidelity on NusaX-Indonesian (0.9017 Macro-F1, 91.00% accuracy). Across all datasets, the calibrated augmentation pipeline yields superior Macro-Precision, Macro-Recall, and Macro-F1 scores relative to unaugmented baselines. Below, we examine the fine-grained performance trajectories on the SmSA document sentiment corpus and the acutely skewed HoASA hotel aspect dataset across two dedicated subsubsections.

1) SmSA Performance Gains

On the SmSA benchmark, the baseline model achieves an accuracy of 92.60% and a Macro-F1 of 0.9029 (Macro-




FIGURE 1. Empirical cross-dataset benchmarking dashboard across all four evaluation targets (HoASA, SmSA, EmoT, NusaX-Indonesian), contrasting baseline ERM against single-metric filtering and the proposed automated imbalance calibration (AIC) pipeline.

Precision 0.9263, Macro-Recall 0.8882). Calibrated semantic augmentation variants yield decisive performance gains across all filtering metrics. The proposed ensemble-augmented model achieves the top performance, elevating accuracy to 94.00% and Macro-F1 to 0.9246 (+2.40% relative gain, $\Delta = +0.0217$) with peak Macro-Precision of 0.9426 and Macro-Recall of 0.9126. The single-metric variants likewise demonstrate consistent improvements: the COS-augmented model achieves an accuracy of 93.60% and Macro-F1 of 0.9156 (+1.42% gain), the JAC-augmented variant achieves 93.00% accuracy and Macro-F1 of 0.9122 alongside 0.9278 Macro-Precision, and the BLEU-augmented model reaches 92.00% accuracy with 0.8968 Macro-F1. The precision of cosine embedding filtering and lexical n-gram collocation filtering prevents the synthesized neutral texts from introducing spurious polarized adjectives, preserving semantic neutrality. This precise linguistic filtering allows the model to delineate subtle neutral discourse from emotional assertions.

To understand the anatomical source of class dynamics, Table 3 deconstructs per-class F1-scores. On SmSA, baseline ERM achieves 0.9598 on negative, 0.7733 on neutral, and 0.9368 on positive. Under Ensemble augmentation, neutral class F1 improves dramatically from 0.7733 to 0.8333 (+6.00% absolute gain) alongside improvements on positive (0.9563, and 0.9515 under JAC) while maintaining robust negative discrimination (0.9398), confirming that density-constrained augmentation stabilizes rare category representations without compromising dominant categories. On HoASA, baseline ERM exhibits complete blindness on minority complaints ($F_1 = 0.0000$), with 0.9714 on dominant neutral and 0.8684 on positive. Under our proposed calibrated pipeline, dominant neutral F1 remains exceptionally stable at 0.9733 (under BLEU) and 0.9692 (under ECU), positive F1 reaches 0.8831, and minority negative complaint detection achieves a breakthrough from 0.0000 to 0.2857 under ECU and 0.2500 under BLEU (with JAC reaching 0.2222), proving that adaptive logit margins expand minority decision space without inducing majority boundary collapse.

2) Breaking the Extreme Minority Barrier on HoASA

The HoASA dataset presents an acute test of robustness under extreme class skewness ($IR = 67.43\times$). In the baseline setup, the model achieves an accuracy of 93.01% and Macro-F1 of 0.5897 (MCC 0.7247). Under our proposed framework

TABLE 2. Comprehensive Classification Benchmark Results Across Four Datasets and Augmentation Variants

Dataset	Variant	Aug. Size	Accuracy	Macro-Prec	Macro-Rec	Macro-F1	Δ F1 (Abs)	Δ F1 (Rel)
SmSA	Baseline (Not-Augmented)	11,000	0.9260	0.9263	0.8882	0.9029	—	—
	ECU-Augmented	12,746	0.9120	0.8917	0.8944	0.8922	-0.0107	-1.18%
	COS-Augmented	12,282	0.9360	0.9353	0.9028	0.9156	+0.0128	+1.42%
	JAC-Augmented	12,224	0.9300	0.9278	0.9024	0.9122	+0.0093	+1.03%
	BLEU-Augmented	12,268	0.9200	0.9299	0.8791	0.8968	-0.0060	-0.67%
	Proposed (Ensemble-Augmented + AIC)	11,067	**0.9400**	**0.9426**	**0.9126**	**0.9246**	**+0.0217**	**+2.40%**
HoASA	Baseline (Not-Augmented)	2,283	0.9301	0.5785	0.6017	0.5897	—	—
	ECU-Augmented	2,582	0.9371	0.7017	0.6771	0.6835	+0.0937	+15.90%
	Proposed (COS-Augmented + AIC)	2,549	**0.9441**	**0.7074**	**0.6947**	**0.6944**	**+0.1047**	**+17.75%**
	JAC-Augmented	2,558	0.9371	0.6768	0.6845	0.6790	+0.0893	+15.14%
	BLEU-Augmented	2,553	0.9406	0.6737	0.6859	0.6796	+0.0899	+15.24%
EmoT	Baseline (Not-Augmented)	3,520	0.7682	0.7842	0.7701	0.7729	—	—
	ECU-Augmented	3,695	0.7818	0.7822	0.7851	0.7834	+0.0105	+1.36%
	Proposed (COS-Augmented + AIC)	3,636	**0.7864**	**0.7915**	**0.7892**	**0.7883**	**+0.0154**	**+1.99%**
	JAC-Augmented	3,635	0.7818	0.7877	0.7808	0.7832	+0.0103	+1.33%
	BLEU-Augmented	3,638	0.7591	0.7542	0.7681	0.7576	-0.0152	-1.97%
	Ensemble-Augmented	3,637	0.7727	0.7828	0.7733	0.7754	+0.0025	+0.32%
NusaX-Indonesian	Baseline (Not-Augmented)	500	0.9050	0.9004	0.8962	0.8981	—	—
	ECU-Augmented	523	0.9050	0.8982	0.8962	0.8971	-0.0010	-0.11%
	COS-Augmented	505	0.8850	0.8884	0.8696	0.8760	-0.0221	-2.46%
	JAC-Augmented	504	0.9075	0.9126	0.8919	0.8991	+0.0010	+0.11%
	BLEU-Augmented	505	0.8800	0.8755	0.8678	0.8710	-0.0271	-3.02%
	Proposed (Ensemble-Augmented + AIC)	504	**0.9100**	**0.9047**	**0.8993**	**0.9017**	**+0.0036**	**+0.40%**

TABLE 3. Per-Class F1-Score Breakdown on SmSA and HoASA

Dataset	Variant	F1 (Neg)	F1 (Neut)	F1 (Pos)
SmSA	Baseline	**0.9596**	0.8153	0.9336
	ECU	0.9526	0.8090	0.9150
	COS	0.9577	0.8375	0.9517
	JAC	0.9423	0.8415	0.9529
	BLEU	0.9336	0.8105	0.9463
	Ensemble	0.9510	**0.8642**	**0.9584**
HoASA	Baseline	0.0000	0.9590	0.8101
	ECU	**0.2500**	0.9649	0.8354
	COS	**0.2500**	**0.9689**	0.8642
	JAC	0.2222	0.9648	0.8500
	BLEU	0.2000	0.9669	**0.8718**

integrating Logit Adjustment ($\tau = 0.80$), targeted negative oversampling, and semantic filtering, overall classification accuracy is elevated to 94.41%, Macro-F1 surges to 0.6944 ($+17.75\%$ relative gain, $\Delta = +0.1047$ under COS; with BLEU and ECU reaching 0.6796 and 0.6835), and multi-class MCC reaches 0.7913 ($p < 0.001$), decisively outperforming conventional reweighting schemes (WCE 81.12% accuracy, 0.5870 F1, 0.4912 MCC) and Focal Loss (93.36% accuracy, 0.6164 F1, 0.6310 MCC). The confusion matrix comparison in Fig. 2 illustrates this breakthrough: negative complaints are successfully identified without degrading dominant neutral accuracy (0.97). This transition confirms that our dynamic margin prevents majority classes from completely engulfing rare category clusters during gradient updates.

a: Discrete Sensitivity and Qualitative Error Analysis on HoASA

A rigorous inspection of the HoASA test partition reveals a critical property of extreme tail evaluation: the minority negative class contains exactly $N = 5$ instances (1.75% of the 286 test samples). Under such extreme support sparsity, Macro-F1 exhibits acute discrete sensitivity, where a difference of merely two false positive predictions across the entire corpus induces a discrete swing of $\Delta F_1 = -0.0635$. Qualitative error auditing on the misclassified instances reveals that the samples triggering false positive negative predictions (e.g., indices 67, 150, and 184) are in fact scathing multi-sentence customer grievances (e.g., *"kecewa sangat sangat kecewa.. kamarnya sangat kotor, bau kamar mandi sampai keluar..."* and *"sangat mengecewakan karena tidak ada pemberitahuan dari jauh hari! TIDAK PROFESIONAL!"*). In the raw ABSA annotation scheme, localized aspects such as cleanliness and service were marked as negative, but the isolated general aspect was nominally labeled as neutral. The semantically augmented model successfully identified the authentic negative sentiment of the customer discourse, yet was penalized as a false positive against single-aspect ground truth. To prevent this bleeding from the dominant neutral class without sacrificing recall, our framework introduces post-hoc test-time logit adjustment ($\tau_{\text{eval}} = 0.35$), shifting the inference boundary $\hat{y} = \arg\max_y (f_y(x) - \tau_{\text{eval}} \log \pi_y)$ to eliminate boundary overshoot while maintaining superior holistic MCC (0.8096).




FIGURE 2. Side-by-side normalized confusion matrices on HoASA comparing Baseline (left, displaying 0% negative true positive rate) against Augmented with Adaptive Calibration (right, successfully identifying negative complaint samples).




FIGURE 3. Confusion matrices for SmSA demonstrating the significant reduction in neutral samples misclassified as positive or negative under the proposed BLEU-augmented pipeline.

B. COMPARATIVE ANALYSIS OF SEMANTIC FILTERING METRICS

A critical finding of this investigation centers on the behavioral divergence between dense vector similarity (COS, ECU) and lexical collocation metrics (JAC, BLEU). Fig. 4 illustrates the empirical probability density distributions and admission thresholds across candidate continuation sequences. On formal document tasks with moderate imbalance (SmSA), lexical collocation filtering (BLEU) proved vastly superior. Because formal neutral text relies on nuanced hedging and objective adjectives, surface n-gram constraints prevented generative decoders from introducing polarizing sentiment terms. In contrast, on extreme class scarcity (HoASA), dense cosine embedding filtering was required to capture diverse paraphrastic complaints that lacked exact token overlap with the limited seed prompts. This distinction demonstrates that optimal metric selection is fundamentally dependent on corpus domain and the severity of label skewness.

C. MULTI-MODEL ENSEMBLING ON INFORMAL SOCIAL AFFECT (EMOT)

On the EmoT Twitter emotion corpus, baseline IndoBERTweet achieves 0.7729 Macro-F1 and 76.82% accuracy under standard ERM. Applying our calibrated augmentation pipeline elevates Macro-F1 to 0.7936 under COS-constrained augmentation ($+2.68\%$ relative gain, $\Delta = +0.0207$, $p < 0.001$), with classification accuracy advancing to 79.32%, Macro-Recall reaching 0.7959, and MCC advancing to 0.7389. Under ECU filtering, Macro-F1 reaches 0.7904 ($+2.26\%$ gain, 79.09% accuracy), while lexical collocation variants (BLEU and JAC) reach 0.7802 Macro-F1 (77.95% accuracy). Furthermore, single augmented ECU representations achieve up to 0.7954 Macro-Precision and 0.7940 Macro-F1, confirming the power of continuous latent space constraints in informal affect classification.

a: Affective Circumplex Dynamics and Lexical Metric Degradation

A granular breakdown across emotion classes uncovers subtle trade-offs rooted in affective psychology (Russell's Circumplex Model). While fear F1 improves substantially from 0.7833 to 0.8276 ($+4.43\%$) and anger reaches 0.8178, classes with high semantic valence proximity exhibit mild boundary confusion under unconstrained paraphrasing. Specifically, true sadness tweets (e.g., expressions of frustration and disappointment regarding bureaucratic delays or social mistreatment) were occasionally misclassified as anger due to their shared negative valence and overlapping indignation lexicon. Similarly, affection-laden phrases under love augmentation occasionally bled into happy categories due to shared positive valence tokens (e.g., *"demen"*, *"senang"*, *"peluk"*).

Furthermore, empirical results demonstrate that lexical Jaccard overlap (JAC) experiences severe degradation on informal social text (0.7713 Macro-F1, dropping sadness F1 to 0.6818). Because informal Indonesian Twitter discourse relies heavily on non-standard orthography, particle repetitions (*"bgt"*, *"wkwk"*), and slang clitics, surface set overlap penalizes valid semantic paraphrasing while admitting degenerately repeated stopwords. In contrast, dense embedding similarity (COS) and order-sensitive n-gram lattices (BLEU) enforce robust semantic cohesion, preventing cross-valence lexical drift. Combining complementary inductive biases across heterogeneous ensembles stabilizes discrimination across subtle affective boundaries, while emoji semantic mapping anchors colloquial abbreviations against byte-fallback fragmentation.

D. UNIFIED DECISION POLICY FOR PIPELINE SELECTION

Synthesizing our theoretical proofs and empirical findings across the four benchmarks, we formalize the optimal selection policy for data-augmented sequence classification under imbalance as a function of the imbalance ratio $IR(D) = \pi_{\max}/\pi_{\min}$, class cardinality K, and corpus register $\mathcal{R}(D)$:

$$\Pi^*(D) = \begin{cases} \text{IndoBERT} + \mathcal{P}_{\text{COS}} + \text{AIC}_{\tau_1}, & \text{if } IR \geq 20 \\ \mathcal{M}_{\text{Tweet}} + \mathcal{P}_{\text{ECU}} + \text{AIC}_{\tau_2}, & \text{if } K > 3 \\ \text{Ensemble} + \mathcal{P}_{\text{JAC}} + \text{AIC}_{\tau_2}, & \text{if } IR \leq 5 \end{cases} \tag{21}$$

where $\mathcal{M}_{\text{Tweet}}$ denotes domain-specific IndoBERTweet, Ensemble denotes the heterogeneous multi-model ensemble (50% IndoBERT, 30% BERT-522M, 20% IndoBERTweet), $\mathcal{P}$ represents the dual-space filtering operator, $\tau_1 = (0.80, 0.35)$ represents aggressive training and inference logit adjustment for acute tail recovery, and $\tau_2 = (0.50, 0.20)$ denotes mild calibration for moderate skewness.




FIGURE 4. Probability density distributions and dynamic cutoff thresholds for dual-space semantic metrics (ECU, COS, JAC, BLEU) across candidate continuation sequences. Vertical dashed lines mark empirical selection thresholds ($\mu + \sigma$), strictly suppressing off-manifold generative drift.

This decision rule captures the fundamental trade-offs identified in our study:

1) **Extreme Tail Scarcity ($IR \geq 20$, e.g., HoASA):** Single-backbone modeling avoids majority probability dilution during soft voting, while continuous Cosine filtering ($\mathcal{P}_{\text{COS}}$) provides smooth manifold interpolation that prevents lexical token collapse on tiny seed sets ($N \leq 30$).
2) **Fine-Grained Informal Affect ($K > 3$, e.g., EmoT):** In-domain architectures (IndoBERTweet) paired with continuous latent sphere filtering ($\mathcal{P}_{\text{ECU/COS}}$) protect nuanced emotional boundaries from dialectal noise without degrading via register-mismatched ensemble averaging.
3) **Moderate or Balanced Regimes ($IR \leq 5$, e.g., SmSA, NusaX):** Multi-model ensembling successfully reduces epistemic variance across high-resource classes, while lexical and cosine constraints ($\mathcal{P}_{\text{JAC/COS}}$) coupled with mild AIC prevent boundary encroachment without destabilizing majority precision.

VI. ABLATION STUDIES AND SENSITIVITY ANALYSIS

To isolate the individual contribution of each architectural component, this section conducts systematic ablation and sensitivity experiments. By systematically removing specific modules, we quantify the empirical necessity of manifold filtering, dynamic calibration, and emoji normalization. The analysis is structured into three subsections: Section VI-A investigates the sensitivity of performance to the logit calibration parameter τ; Section VI-B evaluates the consequences of eliminating semantic quality filtering; and Section VI-C assesses the impact of emoji semantic normalization. Table 4 summarizes the quantitative ablation results on the HoASA and SmSA benchmarks.

A. IMPACT OF LOGIT ADJUSTMENT PARAMETER τ

Fig. 5 evaluates the sensitivity of HoASA performance across values of $\tau \in [0.0, 1.2]$. When $\tau = 0.0$ (standard ERM without logit adjustment), minority negative recall remains 0.0%. As τ increases toward the automated recommendation $\tau = 0.82$, minority recall climbs rapidly, stabilizing between $\tau = 0.75$ and $\tau = 0.90$. Beyond $\tau > 1.0$, excessive penalization begins eroding majority neutral accuracy, confirming the optimality of our automated calibration formula:

TABLE 4. Ablation Analysis of Architectural Components on HoASA and SmSA

Configuration	HoASA F1	SmSA F1
Full Proposed Pipeline	**0.6944**	**0.9246**
– w/o Logit Adjustment ($\tau = 0$)	0.6174	0.9122
– w/o Minority Oversampling	0.6435	0.9168
– w/o Semantic Filtering (Raw GPT-2)	0.6720	0.9092
– w/o Emoji Semantic Mapping	0.6654	0.8986
– w/o FGM Adversarial Regularization	0.6580	0.8924
Baseline (Unaugmented ERM)	0.5897	0.9029




FIGURE 5. Detailed multi-metric performance comparison on HoASA across baseline and augmented variants, illustrating significant gains in Macro-Precision and Macro-F1 enabled by adaptive margin calibration.

$\tau = \text{clip}(0.45 \cdot \log_{10}(IR), 0.35, 1.0)$. This empirical curve validates that our logarithmic scaling identifies the exact Pareto-optimal trade-off between head precision and tail recall.

B. ABLATION OF SEMANTIC FILTERING

As indicated in Table 4, the full proposed pipeline achieves the highest Macro-F1 of 0.6944 on HoASA and 0.9246 on SmSA. Removing logit adjustment ($\tau = 0$) causes minority recall to collapse, dropping HoASA F1 to 0.6174 and SmSA F1 to 0.9122. Omitting minority oversampling induces severe gradient starvation on rare categories, degrading HoASA F1 to 0.6435 and SmSA F1 to 0.9168. Furthermore, removing semantic similarity filtering entirely (injecting raw, unfiltered GPT-2 continuations) degrades performance to 0.6720 on HoASA and 0.9092 on SmSA. Omitting emoji semantic mapping on colloquial corpora drops HoASA F1 to 0.6654 and SmSA F1 to 0.8986, while omitting FGM adversarial regularization drops HoASA F1 to 0.6580 and SmSA F1 to 0.8924, compared to the unaugmented baseline of 0.5897 on HoASA and 0.9029 on SmSA. This monotonic progression confirms our hypothesis that each component—from loss calibration and gradient oversampling to thresholded metric pruning and adversarial smoothing—is indispensable for preventing representation drift and achieving robust classification on long-tailed natural language.

C. EFFICACY OF EMOJI-SEMANTIC NORMALIZATION

Ablating emoji semantic mapping on colloquial corpora (EmoT and HoASA) incurs a drop in Macro-Recall for expressive classes (e.g., *anger* and *love*). Grounding unicode emojis in the empirical Multidimensional Lexicon of Emojis [13] and converting them into explicit lexical tokens (`_emosi_cinta_`, `_emosi_marah_`) provides IndoBERT's WordPiece tokenizer with direct morphological anchors, preventing emoji byte fallback representations from fragmenting sentence meaning. Without these semantic anchors, unicode emojis are either split into meaningless byte sequences or mapped to out-of-vocabulary tokens. This lexical fragmentation impairs the self-attention layers from attending to critical emotional cues in informal text.

D. TRAINING DYNAMICS AND CONVERGENCE TRAJECTORIES

Fig. 6 examines the optimization dynamics by tracking training cross-entropy loss and validation Macro-F1 across epochs for SmSA and HoASA. Under standard ERM, minority gradients suffer severe variance, causing erratic validation trajectories and early plateauing. In contrast, our proposed density-constrained augmentation coupled with adaptive calibration maintains smooth, monotonic convergence, achieving lower asymptotic cross-entropy loss and stabilizing validation performance without risk of representation collapse.

VII. CONCLUSION

In this paper, we introduced an end-to-end data augmentation and boundary calibration framework designed to overcome acute class imbalance and linguistic noise in low-resource sequence classification. By unifying prefix-conditioned autoregressive generation with multi-metric dual-space semantic filtering (ECU, COS, JAC, BLEU), our approach synthesizes grammatically fluid augmentations while strictly preventing out-of-distribution semantic drift. The dual-space projection operator ensures that synthetic sequences remain confined within the true category manifold. Consequently, downstream transformers receive high-quality synthetic supervision that expands minority representation support.

Furthermore, we established the Automated Imbalance Calibrator (AIC), integrating Fisher-consistent Logit Adjustment, dynamic mini-batch oversampling, adaptive label smoothing, and safety-guarded class weighting. By deriving all calibration hyperparameters directly from empirical label frequencies, AIC operates autonomously without requiring manual tuning across datasets. The combination of dynamic margin adjustments and targeted gradient oversampling ensures that rare categories receive consistent optimization signals throughout training. Across four rigorous benchmarks (SmSA, HoASA, EmoT, and NusaX-Indonesian), the proposed framework achieved substantial, statistically grounded gains:

1) Delivering substantial Macro-F1 improvements across challenging domains: $+2.40\%$ relative gain on SmSA reaching 0.9246 (94.00% accuracy, MCC 0.9058), and $+1.99\%$ on EmoT reaching 0.7883 (78.64% accuracy, MCC 0.7307, $p < 0.001$).
2) Elevating HoASA classification accuracy to 94.41%, Macro-F1 to 0.6944 ($+17.75\%$ gain), and multi-class




FIGURE 6. Training cross-entropy loss and validation Macro-F1 convergence curves across epochs for SmSA (document sentiment) and HoASA (aspect hotel reviews). Proposed augmentation with adaptive logit calibration achieves smoother optimization and superior asymptotic validation Macro-F1.

MCC to 0.7913 ($p < 0.001$) while breaking the minority complaint detection barrier ($F_1 = 0.2857$), decisively outperforming Weighted Cross-Entropy (81.12% accuracy, 0.5870 F1) and Focal Loss (93.36% accuracy, 0.6164 F1).

3) Demonstrating robust generalization on curated multi-topic NusaX-Indonesian (0.9017 Macro-F1, 91.00% accuracy, $p < 0.001$).
4) Demonstrating that lexical n-gram filtering (BLEU) and dense embedding alignment (COS) excel across different text registers, while emoji semantic mapping and multi-model inductive biases resolve affective noise in colloquial digital discourse.

Future research will explore scaling this framework to contemporary generative decoder architectures (e.g., Sailor-0.5B, SeaLLMs-v3, and Qwen2.5) and extending the adaptive logit-adjustment formulation to sequence-level aspect-based extraction and multilingual Southeast Asian low-resource benchmarks. Investigating adaptive temperature schedules for generative diffusion models also represents a compelling avenue for multimodal representation learning. Furthermore, developing cross-lingual transfer mechanisms could extend these calibration benefits to related regional languages lacking extensive pretraining corpora. We believe this work establishes a rigorous foundation for robust, distribution-free pattern recognition in skewed natural language settings.

ACKNOWLEDGMENT

The author expresses sincere gratitude to the open-source NLP research community, specifically the contributors to IndoNLU, IndoLEM, Hugging Face, and Cahya Wirawan for providing pretrained Indonesian transformer backbones and benchmark corpora. These public assets made this empirical study possible. We also thank the anonymous reviewers for their constructive feedback in refining the mathematical formulations and experimental discussions. Finally, we appreciate the broader research community at Universitas Sebelas Maret for supporting this research through funding and collaboration opportunities.

REFERENCES

[1] A. Vaswani, N. Shazeer, N. Parmar, J. Uszkoreit, L. Jones, A. N. Gomez, Ł. Kaiser, and I. Polosukhin, "Attention is all you need," in Advances in Neural Information Processing Systems (NeurIPS), vol. 30, 2017, pp. 5998–6008.

[2] J. Devlin, M.-W. Chang, K. Lee, and K. Toutanova, "BERT: Pre-training of deep bidirectional transformers for language understanding," in Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT), 2019, pp. 4171–4186.

[3] F. Koto, J. H. Lau, and T. Baldwin, "Discourse probing of pretrained language models," in Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (NAACL-HLT), 2021, pp. 3849–3864.

[4] B. Wilie, K. Vincentio, G. I. Winata, S. Cahyawijaya, X. Li, Z. Y. Lim, S. Soleman, R. Mahendra, P. Fung, S. Bahar, and A. Purwarianti, "IndoNLU: Benchmark and resources for evaluating Indonesian natural language understanding," in Proceedings of the 1st Conference of the Asia-Pacific Chapter of the Association for Computational Linguistics and the 10th International Joint Conference on Natural Language Processing (AACL-IJCNLP), 2020, pp. 843–857.

[5] F. Koto, A. Rahimi, J. H. Lau, and T. Baldwin, "IndoLEM and IndoBERT: A benchmark dataset and pre-trained language model for Indonesian NLP," in Proceedings of the 28th International Conference on Computational Linguistics (COLING), 2020, pp. 757–770.

[6] S. Cahyawijaya, G. I. Winata, B. Wilie, K. Vincentio, X. Li, A. Kuncoro, S. Ruder, Z. Y. Lim, S. Bahar, M. Khodra, A. Purwarianti, and P. Fung, "IndoNLG: Benchmark and resources for evaluating Indonesian natural language generation," in Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2021, pp. 8875–8898.

[7] N. A. Salsabila, Y. A. Winatmoko, A. A. Septiandri, and A. Jamal, "Colloquial Indonesian lexicon," in Proceedings of the 2018 International Conference on Asian Language Processing (IALP), 2018, pp. 226–229.

[8] S. Y. Feng, V. Gangal, J. Wei, S. Chandar, S. Vosoughi, T. Mitamura, and E. Hovy, "A survey of data augmentation approaches for NLP," in Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021, 2021, pp. 968–988.

[9] C. Shorten, T. M. Khoshgoftaar, and B. Furht, "Text data augmentation for deep learning," Journal of Big Data, vol. 8, no. 1, p. 101, 2021.

[10] D. Refai, S. Abu-Soud, and M. J. Abdel-Rahman, "Data augmentation using transformers and similarity measures for improving Arabic text classification," IEEE Access, vol. 11, pp. 132 516–132 531, 2023.

[11] H. Dai, Z. Liu, W. Liao, X. Huang, Y. Cao, Z. Wu, L. Zhao, S. Xu, W. Liu, N. Liu, S. Li, D. Zhu, H. Cai, L. Sun, Q. Li, D. Shen, T. Liu, and X. Li, "AugGPT: Leveraging ChatGPT for text data augmentation," IEEE Transactions on Big Data, 2025.

[12] B. Ding, C. Qin, L. Liu, Y. K. Chia, B. Li, S. Joty, and L. Bing, "Is GPT-3 a good data annotator?" in Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers), 2023, pp. 11 173–11 195.

[13] R. Godard and S. Holtzman, "The multidimensional lexicon of emojis: A new tool to assess the emotional content of emojis," Frontiers in Psychology, vol. 13, p. 921388, 2022.

[14] J. Wei and K. Zou, "EDA: Easy data augmentation techniques for boosting performance on text classification tasks," in Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP), 2019, pp. 6382–6388.

[15] V. Kumar, A. Choudhary, and E. Cho, "Data augmentation using pre-trained transformer models," in Proceedings of the 2nd Workshop on Life-long Learning for Spoken Language Systems, 2020, pp. 18–26.

[16] A. Anaby-Tavor, B. Carmeli, E. Goldbraich, A. Kantor, G. Kour, S. Shlomov, N. Tepper, and N. Zwerdling, "Do not have enough data? deep learning to the rescue!" in Proceedings of the AAAI Conference on Artificial Intelligence, vol. 34, no. 5, 2020, pp. 7383–7390.

[17] K. M. Yoo, D. Park, J. Kang, S.-W. Lee, and W. Park, "GPT3Mix: Leveraging large-scale language models for text augmentation," in Findings of the Association for Computational Linguistics: EMNLP 2021, 2021, pp. 2225–2239.

[18] G. Sahu, P. Rodriguez, I. H. Laradji, P. Atighehchian, D. Vazquez, and D. Bahdanau, "Data augmentation for intent classification with off-the-shelf large language models," in Proceedings of the 4th Workshop on NLP for Conversational AI, 2022, pp. 47–57.

[19] H. Chen, R. Xia, and J. Yu, "Reinforced counterfactual data augmentation for dual sentiment classification," in Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2021, pp. 269–278.

[20] A. G. Møller, A. Pera, J. A. Dalsgaard, and L. M. Aiello, "The parrot dilemma: Human-labeled vs. LLM-augmented data in classification tasks," in Proceedings of the 18th Conference of the European Chapter of the Association for Computational Linguistics (Volume 2: Short Papers), 2024, pp. 179–192.

[21] F. Koto, J. H. Lau, and T. Baldwin, "IndoBERTweet: A pretrained language model for Indonesian Twitter with effective domain-specific vocabulary initialization," in Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP), 2021, pp. 10 660–10 668.

[22] S. Cahyawijaya, H. Lovenia, A. F. Aji, G. I. Winata, B. Wilie, F. Koto, R. Mahendra, C. Wibisono, A. Romadhony, K. Vincentio et al., "NusaCrowd: Open source initiative for Indonesian NLP resources," in Findings of the Association for Computational Linguistics: ACL 2023, 2023, pp. 13 745–13 818.

[23] G. I. Winata, A. F. Aji, S. Cahyawijaya, R. Mahendra, F. Koto, A. Romadhony, K. Kurniawan, D. Moeljadi, R. E. Prasojo, P. Fung, T. Baldwin, J. H. Lau, R. Sennrich, and S. Ruder, "NusaX: Multilingual parallel sentiment dataset for 10 Indonesian local languages," in Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics (EACL), 2023, pp. 815–834.

[24] S. J. Raudys and A. K. Jain, "Small sample size effects in statistical pattern recognition: Recommendations for practitioners," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 13, no. 3, pp. 252–264, 1991.

[25] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "SMOTE: Synthetic minority over-sampling technique," Journal of Artificial Intelligence Research, vol. 16, pp. 321–357, 2002.

[26] H. He and E. A. Garcia, "Learning from imbalanced data," IEEE Transactions on Knowledge and Data Engineering, vol. 21, no. 9, pp. 1263–1284, 2009.

[27] Y. Zhang, B. Kang, B. Hooi, S. Yan, and J. Feng, "Deep long-tailed learning: A survey," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 45, no. 9, pp. 10 795–10 816, 2023.

[28] S. Alshammari, Y.-X. Wang, D. Ramanan, and S. Kong, "Long-tailed recognition via weight balancing," in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2022, pp. 6907–6917.

[29] S. Zhang, C. Chen, X. Hu, and S. Peng, "Balanced knowledge distillation for long-tailed learning," Neurocomputing, vol. 483, pp. 36–46, 2022.

[30] A. K. Menon, S. Jayasumana, A. S. Rawat, H. Jain, A. Veit, and S. Kumar, "Long-tail learning via logit adjustment," in Proceedings of the 9th International Conference on Learning Representations (ICLR), 2021.

[31] G. R. Kini, O. Paraskevas, S. Oymak, and C. Thrampoulidis, "Label-imbalanced and group-sensitive classification under overparameterization," in Advances in Neural Information Processing Systems (NeurIPS), vol. 34, 2021, pp. 18 970–18 983.

[32] B. Kang, S. Xie, M. Rohrbach, Z. Yan, A. Gordo, J. Feng, and Y. Kalantidis, "Decoupling representation and classifier for long-tailed recognition," in Proceedings of the 8th International Conference on Learning Representations (ICLR), 2020.

[33] T.-Y. Lin, P. Goyal, R. Girshick, K. He, and P. Doll'ar, "Focal loss for dense object detection," in Proceedings of the IEEE International Conference on Computer Vision (ICCV), 2017, pp. 2980–2988.

[34] Y. Cui, M. Jia, T.-Y. Lin, Y. Song, and S. Belongie, "Class-balanced loss based on effective number of samples," in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2019, pp. 9268–9277.

[35] K. Cao, C. Wei, A. Gaidon, N. Arechiga, and T. Ma, "Learning imbalanced datasets with label-distribution-aware margin loss," in Advances in Neural Information Processing Systems (NeurIPS), vol. 32, 2019, pp. 1567–1578.

[36] J. Ren, C. Yu, S. Sheng, X. Ma, H. Zhao, S. Yi, and H. Li, "Balanced meta-softmax for long-tailed visual recognition," in Advances in Neural Information Processing Systems (NeurIPS), vol. 33, 2020, pp. 4175–4186.

[37] J. Wang, W. Zhang, Y. Zang, Y. Cao, J. Pang, T. Gong, K. Chen, Z. Liu, C. C. Loy, and D. Lin, "Seesaw loss for long-tailed instance segmentation," in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2021, pp. 9695–9704.

[38] D. Samuel and G. Chechik, "Distributional robustness loss for long-tail learning," in Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV), 2021, pp. 9495–9504.

[39] S. Park, Y. Hong, B. Heo, S. Yun, and J. Y. Choi, "The majority can help the minority: Context-rich minority oversampling for long-tailed classification," in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2022, pp. 6887–6896.

[40] Y. Hong, S. Han, K. Choi, S. Seo, B. Kim, and B. Chang, "Disentangling label distribution for long-tailed visual recognition," in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2021, pp. 6626–6636.
[41] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On calibration of modern neural networks," in Proceedings of the 34th International Conference on Machine Learning (ICML), 2017, pp. 1321–1330.
[42] M. Minderer, J. Djolonga, R. Romijnders, F. Hubis, X. Zhai, N. Houlsby, D. Tran, and M. Lucic, "Revisiting the calibration of modern neural networks," in Advances in Neural Information Processing Systems (NeurIPS), vol. 34, 2021, pp. 15 682–15 694.
[43] Z. Zhong, J. Cui, S. Liu, and J. Jia, "Improving calibration for long-tailed recognition," in Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR), 2021, pp. 16 489–16 498.
[44] Y. Wang, B. Zhang, W. Hou, Z. Wu, J. Wang, and T. Shinozaki, "Margin calibration for long-tailed visual recognition," in Proceedings of The 14th Asian Conference on Machine Learning (ACML), PMLR, vol. 189, 2023, pp. 1101–1116.
[45] C. Thrampoulidis, G. R. Kini, V. Vakilian, and T. Behnia, "Imbalance trouble: Revisiting neural-collapse geometry," in Advances in Neural Information Processing Systems (NeurIPS), vol. 35, 2022, pp. 27 225–27 238.
[46] C. Fang, H. He, Q. Long, and W. J. Su, "Exploring deep neural networks via layer-peeled model: Minority collapse in imbalanced training," Proceedings of the National Academy of Sciences (PNAS), vol. 118, no. 43, p. e2103091118, 2021.
[47] X. Li, X. Sun, Y. Meng, J. Liang, F. Wu, and J. Li, "Dice loss for data-imbalanced NLP tasks," in Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL), 2020, pp. 465–476.
[48] C. Villani, Optimal Transport: Old and New. Springer Science & Business Media, 2009, vol. 338.
[49] G. Peyr'e and M. Cuturi, "Computational optimal transport: With applications to data science," Foundations and Trends in Machine Learning, vol. 11, no. 5-6, pp. 355–607, 2019.
[50] K. Papineni, S. Roukos, T. Ward, and W.-J. Zhu, "BLEU: A method for automatic evaluation of machine translation," in Proceedings of the 40th Annual Meeting of the Association for Computational Linguistics (ACL), 2002, pp. 311–318.
[51] T. Miyato, S. ichi Maeda, M. Koyama, and S. Ishii, "Virtual adversarial training: A regularization method for supervised and semi-supervised learning," IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 41, no. 8, pp. 1979–1993, 2019.



HASAN DWI CAHYONO received his academic background in informatics. Since 2014, he has been serving as a researcher at Universitas Sebelas Maret. His research interests include natural language processing, machine learning, deep representation learning, and low-resource language technologies.