Maintainer Prioritization in npm Supply Chains: Objectives, Representation Sensitivity, and Metadata Limits

Anonymous Author(s)

Abstract—Selecting maintainer accounts for review raises three different questions: how many repositories are reached, how much account-origin exposure is represented, and whether every observed source of a repository is selected. We compare these objectives in a retained npm graph of 25,228 identifiers, including 2,745 bundled contexts, and 12,217 maintainer usernames. At budget 100, greedy coverage reaches 5,538 of 7,171 workflow-associated repositories, whereas exact-union ranking reaches 4,407. Under a uniform single-account-origin scenario with perfect selected-source hardening, their exposure reductions are 11.48% and 33.79%, respectively. A heuristic aimed at all-source exclusion counts 1,022 repositories, compared with greedy's 800. Seven scalarization settings show intermediate coverage–exposure tradeoffs; assumed heterogeneous weights change which accounts are favored. Preserving exact version continuity reduces account–repository pairs by 42.44%, although both representations remain observed unions. A separate bounded historical metadata reconstruction resolves 1,841 of 1,848 recorded edges; it does not recover historical installations or establish publishing authority. These results support explicit objective and observation choices in structural prioritization, without estimating compromise probabilities or deployed-control effects.

Index Terms—Software supply chain security, npm ecosystem, maintainer prioritization, multi-objective optimization, dependency graphs, release authority.

1 Introduction

NPM dependency and maintainer relations can concentrate downstream reach in a small set of accounts. Earlier ecosystem studies measured this concentration and proposed maintainer vetting and metadata-based review signals [1], [2]. A defensive program still needs to decide what a limited account-review budget should accomplish. Distinct repository coverage, exposure across account-origin scenarios, and selection of every observed source are different quantities.

Consider two accounts whose package portfolios reach many of the same repositories. Selecting the first may leave little additional coverage for the second. Nevertheless, an unselected second account remains a possible origin in the structural model. A repository can therefore be covered while retaining most of its observed sources. This is an objective distinction, not evidence that either account was compromised or that review would prevent compromise.

Our study extends established reach and greedy-coverage baselines [1], [3] by measuring three objectives on the same observed incidence relation. We evaluate five deterministic selection rules, 200 random orders and six budgets. We then examine exact-version continuity, endpoint deduplication, observation exclusions, and hybrid and exclusion-oriented selections. The graph contains 25,228 identifiers and 12,217 usernames; workflow-positive package observations map to 7,171 repository keys. These are the units in a seeded expansion, rather than a representative sample of npm installations.

October 2026 reports illustrate boundaries that this graph cannot resolve. LiteLLM described master-key exposure, CI secret theft and misuse of developer tokens [4], with published artifacts differing from a source tag [5]. The incident concerns PyPI/container releases, not an npm validation case. Pillar's OpenCode disclosure concerned a legacy npm dependency on Windows/WSL [6]. Railway described possible environment-variable exposure and a deployment pause [7], [8]. SlugFest concerned publishing trust bindings [9], [10]; the Node.js Brotli disclosure concerns a runtime outside the package graph [11]. We retain these as contextual boundaries, without deriving intervention efficacy from them.

We ask five questions:

- **RQ1:** How do distinct coverage and additive scenario exposure differ at equal account budgets?
- **RQ2:** How many covered repositories retain unselected sources, and what does an exclusion-oriented heuristic change?
- **RQ3:** How do graph representation and selection/evaluation combinations affect the measured results?
- **RQ4:** What tradeoffs arise under scalarized objectives and assumed heterogeneous weights?
- **RQ5:** Which historical metadata can be reconstructed, and which evidence remains missing for authority-aware outcome evaluation?

The contribution is a measured comparison of established structural objectives, their representation and obser-

• *Anonymized for double-anonymous peer review.*

vation sensitivities, and the limits of the retained metadata. The scalarized objective has a standard submodular guarantee; our seven greedy settings do not certify a global Pareto frontier. The direct exclusion rule is a heuristic. The historical companion and frozen prospective acquisition pilot supply feasibility evidence, without a fitted forecasting model or deployed-control evaluation.

2 Related Work

Our research intersects five major areas of empirical software engineering and software supply-chain security: structural ecosystem measurement, malicious package detection, continuous-integration workflow analysis, registry governance and provenance, and temporal dependency reconstruction.

2.1 Ecosystem Structure and Centrality-Based Prioritization

Pioneering empirical studies established that open-source package registries exhibit extreme structural asymmetry and small-world properties. Zimmermann et al. [1] analyzed npm's dependency topology, revealing that a tiny core of central packages and maintainers transitively affects a vast majority of the ecosystem. Zahan et al. [2] study metadata weak-link signals, while Liu et al. [12] examine dependency-tree vulnerability propagation.

Zimmermann et al. [1] already studied maintainer-union reach, greedy coverage, and vetting. Wang [13] evaluates package-node protection in cascade simulations. Our contribution is an empirical comparison of coverage, account-origin exposure, and all-source exclusion at workflow-associated repository endpoints. We evaluate established baselines and a stated heuristic, without claiming a new coverage algorithm or demonstrating that PageRank fails in an experiment where it was not evaluated.

2.2 Malicious Package Benchmarks and Detection Limits

A parallel line of security research focuses on detecting malicious packages published via typosquatting, dependency confusion, and account takeovers [14], [15]. Benchmark evaluations, such as Guo et al.'s extensive study of npm malware detectors [16], show that static analysis tools face severe limitations due to obfuscation, dynamic runtime execution, and environment-keyed payloads.

Because reactive post-publication malware detection suffers from non-trivial evasion rates, proactive hardening of legitimate, high-leverage maintainer accounts is a complementary research direction [17], [18]. Our work complements malware detection by optimizing how defenders allocate proactive security interventions before credentials or tokens are compromised.

2.3 Continuous-Integration Workflows and Reachability Limits

Software supply-chain risks manifest concretely in downstream CI/CD pipelines. Koishybayev et al. [19] and Muralee et al. [20] demonstrated that GitHub Actions workflows frequently execute third-party build scripts with access to repository secrets, cloud deployment credentials, and package publish tokens. Recent incidents motivate artifact-level checks: Railway's preliminary report describes potential secret exposure affecting at most 1.85% of workspaces, approximately 100,000, and notes that builds had resumed [7]. LiteLLM reported a release workflow redirected to attacker-controlled source, with separate approval and log-deletion credentials [4]. These are contextual examples rather than observations in our npm graph.

Crucially, recent empirical studies have emphasized that package-level dependency relationships do not equal actual code execution. Weeraddana, Alfadel, and McIntosh [21] studied CI time spent updating unused npm dependencies. Shen et al. [22] reported that 99% of client vulnerabilities in their studied corpus arose from dependencies and 81.26% of package-level findings were false positives under finer analysis. These corpus-specific results do not establish registry-wide false-positive rates. Jayasuriya et al. [23] observed similar granularity effects when analyzing syntactic breaking changes across versions. In our work, we address this fundamental reachability gap by evaluating both coarse package-name projections and version-continuous graphs, treating topological reach as a conditional review surface rather than installed-code evidence.

2.4 Registry Governance, Cryptographic Provenance, and Signing

In response to account compromises, registries and standards bodies have introduced cryptographic signing and provenance attestations. Schorlemmer et al. [17] audited signing across Maven, PyPI, Docker Hub, and Hugging Face, finding that adoption remains minimal and unevenly distributed. Kalu et al. [18] interviewed industry practitioners, revealing significant operational friction in managing cryptographic keys and configuring automated pipeline attestations. Bloom Security's SlugFest disclosure concerns mutable repository-name bindings before a first trusted publish, rather than a break of OIDC cryptography [9]. GitHub announced expiry of unvalidated bindings on October 2 [10]; reported exposure is not evidence that all affected packages were maliciously published. Pillar's October 19 OpenCode report describes a September 28 dependency fix without a CVE [6], illustrating a coverage gap for CVE-indexed detection.

Simultaneously, He, Vasilescu, and Kästner [24] demonstrated that local dependency version pinning is insufficient to protect clients against upstream attacks, as adversaries exploit unpinned sub-dependencies and registry-level re-resolutions. These findings motivate examining account controls alongside version and artifact evidence; they do not establish control efficacy in our graph.

2.5 Temporal Reconstruction and Empirical Standards

A critical methodological vulnerability in supply-chain studies is future-leakage bias—evaluating historical attacks using contemporary registry graphs. Pinckney et al. [25] introduced `npm-follower` to mirror registry event streams, while Rahman et al. [26] released `CHRONO-RESOLUTION` to reconstruct exact dependency trees at release points. Shafin and Ahmed [27] highlighted the necessity of time-indexed forecasting.

Our reporting is informed by the ACM SIGSOFT Empirical Standards [28]. By avoiding pseudo-replication—specifically rejecting the treatment of fixed-graph nested budgets or repeated random orders as independent sampling units—our study provides reproducible descriptive comparisons and exploratory scalarization results.

3 Data Corpus and Graph Construction

3.1 Collection and Units

The collector seeds a high-impact npm list, expands dependencies through deps.dev [29], requests registry metadata, and checks linked GitHub repositories for a `.github/workflows` directory at HEAD. Queue dates span June 13–16, 2026, but individual fields lack a common acquisition cutoff. The retained archive analyzed on October 20 contains 25,228 graph identifiers, 22,340 version-metadata rows, 12,217 maintainer usernames, and 79,405 package–maintainer relations. Maintainer membership is not a historical publisher log.

Among these identifiers, 2,745 encode bundled contexts rather than independently registered packages. The 121,885 retained version-edge rows project to 88,113 distinct name adjacencies. Stored `DIRECT/INDIRECT` labels describe a target node relative to an extraction root; their 48,705/73,180 row counts do not partition global direct and transitive edges [29]. We reverse every explicit declaring-to-dependency adjacency to measure downstream reach.

The 15,233 workflow-positive package names map to 7,171 normalized repository keys. Owner/name pairs are case-folded and trailing transport `.git` is removed. This is lexical deduplication, without redirect or commit verification. There are 3,081 identifiers without maintainer mappings and 3,772 without completed workflow flags. Zero flags conflate directory absence with repository unavailability. Workflow endpoints require a positive observation; missing and zero flags are not evidence of safety. Coverage uses all 7,171 repository endpoints. Only 7,158 have an observed source identity; the other 13 are excluded from source-exclusion counts.

Figure 2 separates graph units, observed workflow endpoints, and the prospective selection frame. This distinction matters because directory observation and metadata acquisition do not validate a historical installation or a future outcome.

3.2 Name Projection and Exact-Version Continuity

The name graph merges retained versions sharing an identifier. The sensitivity graph retains 40,806 exact (package, version) nodes and joins paths only at matching version keys. A maintained package seeds every retained version; without a version node, it contributes only its eligible seed endpoint. Both representations use the same package-level workflow flags. Neither reproduces npm installation or historical lockfile behavior: contexts and acquisition times remain mixed.

3.3 Cycles, Mapping Disagreements and Contexts

The name graph has 82 nontrivial strongly connected components (SCCs) containing 403 nodes; the exact-version union has 68 containing 304 nodes. The largest component has 61 nodes in each. SCC condensation preserves reach and permits exact bitset propagation over a directed acyclic graph; the implementation uses arbitrary-precision Python integers, not fixed 64-bit sets. This is a computation technique, not an intervention that removes cycles.

The URL audit finds 658 identifier-level parser disagreements. Excluding 60 inconsistent positive observations reduces the workflow repository universe to 7,147; greedy at budget 100 gives $C = 5{,}524$ and $P = 799$. We discard ambiguous flags rather than transferring them to a corrected URL without reacquisition. Removing bundled-context nodes preserves all 462,170 primary account–repository incidences for fixed selections, although workflow-package incidence changes. That invariance does not apply automatically to every endpoint definition or individual-package ranking.

4 Objectives and Optimization Framework

Maintainer prioritization in package registries represents a multi-objective decision problem under a fixed hardening budget $k = |S|$. Let M denote the universe of maintainers ($|M| = 12,217$) and R_{wf} denote the universe of downstream workflow repositories ($|R_{\text{wf}}| = 7,171$). For each maintainer $m \in M$, let $E_m \subseteq R_{\text{wf}}$ denote the set of repositories reachable from packages associated with m, and let $\text{Sources}(r) = \{m \in M : r \in E_m\}$ denote the upstream maintainer set of repository r.

4.1 Formal Objective Definitions

We formalize three fundamental defensive quantities:

4.1.1 Submodular Distinct Coverage ($C(S)$)

Defenders seeking broad ecosystem review prioritize distinct downstream client repositories:

$$C(S) = \left| \bigcup_{m \in S} E_m \right| \tag{1}$$

Property: $C(S)$ is normalized, monotone non-decreasing, and submodular. For any subsets $A \subseteq B \subseteq M$ and element $m \notin B$:

$$C(A \cup \{m\}) - C(A) \geq C(B \cup \{m\}) - C(B) \tag{2}$$

The classic result of Nemhauser, Wolsey, and Fisher [3] establishes that the greedy algorithm selecting $m^* = \arg\max_{m \notin S} |E_m \setminus \bigcup_{u \in S} E_u|$ achieves a $(1 - 1/e) \approx 63.2\%$ approximation of the optimal coverage.

4.1.2 Modular Scenario Exposure Reduction ($H(S)$)

Suppose exactly one account is the hypothetical origin and has a fixed nonnegative weight w_m. A perfect control removes that origin when selected while leaving all other paths unchanged. We measure its share of weighted exposure as:

$$H(S) = \frac{\sum_{m \in S} w_m |E_m|}{\sum_{v \in M} w_v |E_v|} \tag{3}$$

Property: $H(S)$ is normalized, monotone, and strictly *modular* (additive linear). For any disjoint sets $A, B \subseteq M$,

TABLE 1: Selected literature and the scope of our empirical investigation relative to major related literature.

Research Dimension	Structural Topology & Centrality	Malicious Package Detectors	CI/CD & Function Call-Graphs	This Study (Q1 Journal Expansion)
Focus Literature	Zimmermann [1], Zahan [2], Wang [13]	Ohm [14], Sejfia [15], Guo [16]	Koishybayev [19], Weeraddana [21], Shen [22]	Structural objectives (C, H, P, J_α), version continuity, field availability
Prioritization Metric	Dependency and maintainer reach; coverage; metadata signals	Reactive post-event incident signatures	Taint analysis on workflows, call-graph reachability	Submodular coverage, modular exposure reduction, supermodular all-source exclusion
Graph Representation	Dependency graphs and resolved trees	Isolated package tarballs	Dynamic execution traces, static ASTs	Dual evaluation: Package-projected vs. Version-continuous closures (42.4% pair diff)
Maintainer Risk Prior	Uniform equal weight	Unweighted	Unweighted	Heterogeneous weights: Solo bottlenecks (H_{sole}), log-portfolio ($H_{\log}$), package-level sole reach ($H_{\text{pkg-sole}}$)
Temporal Grounding	Static single snapshot	Retrospective positive-only datasets	Static GitHub Actions scripts	45 root records (44 distinct tuples), 1,848 bounded edge attempts ($t_{\text{cutoff}} < t_{\text{incident}}$), 90-day prospective cohort

$H(A \cup B) = H(A) + H(B)$. Consequently, exact-union ranking (sorting maintainers in descending order of weighted reach $w_m|E_m|$) is mathematically guaranteed to achieve the exact global optimum for $H(S)$ at any budget k.

4.1.3 Supermodular All-Source Exclusion ($P(S)$)

Under the same idealized model, an endpoint has no remaining observed source when every member of its nonempty source set is selected:

$$P(S) = \sum_{r \in R_{\text{wf}}} \mathbb{I}[\varnothing \neq \text{Sources}(r) \subseteq S] \tag{4}$$

Property: $P(S)$ is *supermodular*. Selecting maintainer m contributes zero gain to r until its final unselected source is selected. For $A \subseteq B$ and $m \notin B$,

$$P(A \cup \{m\}) - P(A) \leq P(B \cup \{m\}) - P(B). \tag{5}$$

4.1.4 Strict Zero-Anchored Threshold Exclusion (P_k)

Let $R_+ = \{r \in R_{\text{wf}} : \text{Sources}(r) \neq \varnothing\}$, $n_r = |\text{Sources}(r)|$, and $t_r(S) = |\text{Sources}(r) \setminus S|$. We define the hypothetical strict threshold count

$$P_k(S) = \sum_{r \in R_+} \mathbb{I}\left[t_r(S) = 0 \ \vee \ (n_r \geq k \ \wedge \ t_r(S) < k)\right]. \tag{6}$$

For $n_r < k$, only complete source exclusion is credited. For $n_r \geq k$, fewer than k remaining sources suffice under the hypothetical threshold rule. Thus $P_k(\varnothing) = 0$, $P_1(S) = P(S)$, and every counted endpoint has a hardened source. The function is monotone in S for fixed k, but need not be monotone in k: an endpoint with $n_r = 2$ and $t_r(S) = 1$ is counted at $k = 2$ and not at $k = 3$. The superficially compact condition $t_r(S) < \min(k, n_r)$ is not equivalent to Eq. 6. No claim about the submodularity or supermodularity of P_1 is extended to general P_k.

The cardinality guard removes zero-budget credit but does not supply missing authorization semantics. It is an explicit modeling convention, not evidence that a repository actually implements a k-person approval policy; upstream source sets may span independently compromised packages.

4.2 Proposition 1: Monotone Submodularity of Hybrid Scalarization $J_\alpha(S)$

To examine choices between coverage and conditional exposure, we evaluate the standard scalarization:

$$J_\alpha(S) = \alpha \cdot \frac{C(S)}{|R_{\text{wf}}|} + (1 - \alpha) \cdot H(S) \tag{7}$$

where $\alpha \in [0, 1]$ parameterizes defensive posture between broad coverage ($\alpha = 1$) and scenario exposure reduction ($\alpha = 0$).

Proposition 1. For any $\alpha \in [0, 1]$, the objective $J_\alpha(S)$ is monotone non-decreasing and submodular.

Proof: Let $A \subseteq B \subseteq M$ and $m \notin B$. The marginal gain is:

$$\Delta J_\alpha(m \mid S) = \alpha \frac{|E_m \setminus \bigcup_{u \in S} E_u|}{|R_{\text{wf}}|} + (1 - \alpha) \frac{w_m |E_m|}{\sum_{v \in M} w_v |E_v|} \tag{8}$$




Fig. 1: Implemented measurement architecture. Icons denote logical roles and topology is illustrative. Counts and displayed greedy outcomes are empirical; workflow presence does not establish execution.

Graph identifiers

Retained graph IDs	25,228
Ordinary-shaped names	22,483
Bundled contexts	2,745

Shape does not verify registry existence.

Workflow endpoint map

Positive package names	15,233
Repository keys	7,171
With observed sources	7,158

15,233 packages map to 7,171 keys;
13 keys have no observed source.

Frozen metadata pilot

Selected graph IDs	100
Ordinary-shaped names	92
Metadata captures	90

Eight contexts: HTTP 405
Two ordinary names: HTTP 404
All 100 outcomes pending.

Fig. 2: Observation units and prospective acquisition. Panels describe separate populations; their missingness counts must not be added across panels. Context identifiers are retained graph units, not separate registry packages. The prospective selection was frozen before requests; all 100 outcomes remain pending.

The second term is constant with respect to S (modular), so its marginal difference across A and B is exactly zero. The first term satisfies submodularity by set-theoretic inclusion:

$$|E_m \setminus \bigcup_{u \in A} E_u| \geq |E_m \setminus \bigcup_{u \in B} E_u| \tag{9}$$

Because the sum of a submodular set function and a modular set function is submodular, $J_\alpha(S)$ is submodular for all $\alpha \in [0, 1]$. By the Nemhauser bound [3], accelerated lazy greedy optimization achieves at least a $(1 - 1/e)$ approximation of the optimum scalarized objective. □

4.3 Supermodular Minimum-Remaining-Source Heuristic for $P(S)$

Because $P(S)$ is supermodular, greedy coverage and exact union achieve all-source exclusion purely as an unoptimized side-effect. To directly optimize $P(S)$, we design an adaptive minimum-remaining-source heuristic. At each step, let $\text{rem}(r) = \text{Sources}(r) \setminus S$. Candidate maintainers are drawn from endpoints with one to ten remaining sources; if none exist, all unselected maintainers are considered. The implementation maximizes a lexicographic tuple: (i) the number of endpoints immediately completed, (ii) the sum of $1/|\text{rem}(r)|$ over affected endpoints with more than one remaining source, (iii) marginal coverage, and (iv) ascending maintainer index. This is a heuristic with no global optimality guarantee for $P(S)$.

4.4 Heterogeneous Maintainer Risk Formulations

We evaluate three structural models of non-uniform maintainer risk:




Fig. 3: Illustrative version splicing. Collapsing intermediate versions creates a name-level path without an exact-version counterpart. Reverse-reach arrows do not describe a measured installation.




Fig. 4: Analysis methodology and correctness checks. All evaluation quantities share the same observed graph; additional sensitivities do not constitute independent outcome samples.

1) **Single-Maintainer Bottlenecks (w_m^{sole}):** Packages with $|M(p)| = 1$ have one observed maintainer; actual review practices are unobserved. We weight maintainers by $w_m^{\text{sole}} = 1 + |\{p \in P_m : |M(p)| = 1\}|$.
2) **Log-Portfolio Activity ($w_m^{\log}$):** As an assumed portfolio-size sensitivity, define: $w_m^{\log} = 1 + \log_2(1 + |P_m|)$.
3) **Package-Level Sole-Maintainer Reach ($H_{\text{pkg-sole}}$):** Instead of weighting all reachable repositories of maintainer m, we isolate repositories reachable strictly through m's sole-maintained packages: $E_m^{\text{sole}} = \bigcup_{p \in P_m, |M(p)|=1} \mathcal{D}(p)$.

4.5 Analytic Expectations and Empirical Standard Errors

Under a finite population of $|M| = 12,217$ maintainers, random selection of budget k yields exact expected coverage and exposure under the hypergeometric distribution:

$$E[H_{\text{rand}}(k)] = \frac{k}{|M|}, \tag{10}$$




Fig. 5: Budget-100 repository partition. Each bar separates all-source exclusion, coverage with residual sources, and uncovered endpoints. The 13 source-free endpoints are omitted. Structural coverage and complete exclusion differ for every baseline.

$$E[C_{\text{rand}}(k)] = \sum_{r \in R_{\text{wf}}} \left(1 - \frac{\binom{|M| - |\text{Sources}(r)|}{k}}{\binom{|M|}{k}}\right). \tag{11}$$

For $k = 100$, exact finite-population expectations are $E[C] = 1,716.8$ and $E[H] = 0.819\%$. Across 200 simulation seeds, the sample mean coverage is 1,680.6 (sample standard deviation $\text{SD}_C = 530.7$, Monte Carlo Standard Error $\text{MCSE}_C = 37.5$), and sample mean exposure reduction is 0.80% ($\text{SD}_H = 0.373$ pp, $\text{MCSE}_H = 0.026$ pp). Replicated offline execution across 3 independent runs averaged 39.50 s wall-clock time with $1,038.43$ MiB peak RSS.

4.6 Use of AI Assistance

AI assistance was used for manuscript drafting and revision, code revision, analysis checks, and source verification, including assistance through OpenAI's Codex interface. This use extended beyond spelling and grammar correction. AI-generated text and suggestions are not observational evidence: numerical claims are tied to retained data and executable consistency checks, and literature claims require their cited sources. The authors retain responsibility for the final manuscript, interpretation, code, and references.

5 Empirical Results: RQ1 to RQ3

We first report our empirical findings for Research Questions 1 through 3 on the retained 25,228-identifier graph, spanning multi-budget trade-offs, multi-homing mechanics, and representation fidelity.

5.1 RQ1: Coverage vs. Additive Exposure Trade-Off

Table 2 reports empirical prioritization outcomes across maintainer budgets $|S| \in \{1, 5, 10, 25, 50, 100\}$. The top 100 maintainers represent only 0.819% of the 12,217 unique maintainers in our ecosystem, yet their prioritization commands vast reach over downstream workflow repositories.

TABLE 2: Workflow-repository outcomes from the retained baseline experiment. Random entries are 200-order sample means and Monte Carlo standard errors, not population confidence intervals.

Budget	Metric	Portfolio	Sum	Max	Exact union	Greedy	Random mean ± MCSE
1	C (%)	23.43	33.02	28.75	35.46	35.46	0.65 ± 0.19
1	H (%)	0.36	0.51	0.45	0.55	0.55	0.01 ± 0.00
1	P	1	26	2	269	269	0.28 ± 0.15
5	C (%)	46.00	49.25	42.14	50.96	54.00	2.61 ± 0.36
5	H (%)	1.16	2.15	2.23	2.45	2.09	0.04 ± 0.01
5	P	316	325	80	329	327	0.69 ± 0.17
10	C (%)	47.90	51.75	42.81	54.53	60.40	4.73 ± 0.46
10	H (%)	1.59	2.68	4.06	4.48	3.79	0.08 ± 0.01
10	P	391	399	111	343	351	1.21 ± 0.19
25	C (%)	56.71	60.95	45.29	59.74	67.69	10.15 ± 0.55
25	H (%)	4.38	7.45	9.00	9.86	6.08	0.21 ± 0.01
25	P	430	480	116	427	514	2.86 ± 0.26
50	C (%)	62.00	63.78	45.56	60.26	72.46	16.73 ± 0.56
50	H (%)	6.14	13.72	17.19	18.09	8.73	0.43 ± 0.02
50	P	503	576	117	441	638	5.97 ± 0.38
100	C (%)	63.85	67.42	59.52	61.46	77.23	23.44 ± 0.52
100	H (%)	7.96	21.98	33.59	33.79	11.48	0.80 ± 0.03
100	P	577	704	533	534	800	12.78 ± 1.42




Fig. 6: Multi-budget trade-off trajectories across maintainer budgets $|S| \in [1, 100]$: (a) submodular coverage $C(S)$, (b) modular scenario exposure reduction $H(S)$, using five deterministic rules and the exact random expectation. Budget-100 markers show hybrid and direct-exclusion selections.

At budget $|S| = 100$, **Greedy Coverage** achieves $C(S) = 5{,}538$ repositories (77.23%), establishing a descriptive lead of $+1{,}131$ repositories ($+15.77$ percentage points) over **Exact Union** ($C(S) = 4{,}407$, 61.46%). However, when evaluated under scenario-weighted additive exposure reduction $H(S)$, Exact Union achieves 33.79%, outpacing Greedy Coverage (11.48%) by $+22.30$ **percentage points** ($2.94\times$ relative advantage).

Exact union's H advantage follows from its additive objective under equal costs. The experiment measures the accompanying loss in distinct coverage. Greedy offers the largest measured coverage among the compared baseline selections; it is an approximation to maximum coverage, not a proved global optimum. Portfolio size gives 63.85% coverage and 7.96% H at this budget, showing that portfolio count and measured downstream reach need not agree.

5.2 RQ2: Multi-Homing Residual Exposure and Single-Source Fragility

A repository can have many source accounts even when a single account already covers it. Across the 7,158 repositories with observed sources, mean source cardinality is 64.57 and the maximum is 1,502. These are graph source identities, not measured permissions or independent compromises. Figure 7 shows their distribution and the remaining-source distributions after budget-100 selections.

Greedy's $P = 800$ is 11.18% of source-reachable repositories; exact union gives $P = 534$. Consequently, 6,358 source-reachable repositories retain at least one unselected source after greedy selection. A four-source illustration would retain three source identities when one is selected, but that fraction is not an estimated compromise probability.

5.3 RQ3: Version-Continuity Representation and Selection Penalties

Comparing the package-projected name graph against the version-continuous SemVer dependency graph reveals substantial sensitivity to representation:

1) **Exposure Shrinkage:** Preserving version continuity contracts total maintainer-repository exposure pairs from 462,170 to 266,016—an exact reduction of 42.44%.
2) **Root Scope Changes:** 8,587 out of 25,228 packages (34.04%) exhibit divergent downstream




Fig. 7: Observed source multiplicity and residual-source distributions at budget 100. All curves use the same 7,158 source-reachable repositories; 13 source-free endpoints are excluded. Zero remaining sources identify all-source exclusions. Horizontal scales are logarithmic above one. Account origins are structural scenarios, not observed compromises.




Fig. 8: Cross-representation divergence: preserving exact-version continuity removes some paths introduced by version merging and reduces total identity-repository exposure pairs by 42.44%, shifting maintainer leverage.

reach scopes between name-collapsed and version-continuous representations.

3) **Cycle Condensation:** Kosaraju condensation detects 403 nodes in 82 nontrivial strongly connected components in the name graph, compared to 68 cyclic components across 40,806 version nodes in the version-continuous graph.
4) **Version-Splicing Witnesses:** Retained representation diagnostics include five illustrative roots whose name-level paths lack a continuous counterpart in the retained version graph: `pseudomap`, `is`, `foreach`, `indexof`, and `has-color`.

5.3.1 The Cross-Representation Selection Penalty

When maintainers are selected based on name-projected heuristics but evaluated on the observed version-continuous graph, measured exposure changes. For the `sum_package_reach` heuristic at budget 100, ranking directly on version-continuous topologies captures 34.34% of version exposure, compared to only 20.91% when using name-projected rankings—an improvement of +13.43 **percentage points** (+64.2% relative gain).

5.3.2 Real-World Compromise Case Study

Table 3 details reach metrics and maintainer prioritization ranks across the 16 incident-associated records whose package names occur in the retained graph.

The individual-package comparison shows representation-dependent reach: `simple-swizzle` has 120 name-projected and 31 exact-version-continuous workflow endpoints; `chalk` has 1,125 and 587; `ansi-styles` has 1,376 and 740; `debug` has 1,462 and 1,162. These differences do not prove which paths an actual installation could execute.

The account-level example uses the same workflow endpoint definition. `qix` reaches 1,942 workflow repositories and ranks #7 by exact union; version continuity yields 1,476 and rank #5. It is beyond greedy's first 100 selections, while the hybrid places it #35. This illustrates overlap in current retained memberships, not a successful pre-event forecast or historical publisher attribution.

Figure 9 separates the representation used for selection from the one used for evaluation. Comparisons of H within an evaluation row share a denominator; comparisons across rows change that denominator. A change in representation can therefore change both the selection and the quantity being measured.

6 Scalarized Tradeoffs and Heterogeneous Weights: RQ4

6.1 Exploratory Scalarization

We evaluate $J_\alpha(S) = \alpha C(S)/|R_{\text{wf}}| + (1-\alpha)H(S)$ at seven weights, $\alpha \in \{0, 0.10, 0.25, 0.50, 0.75, 0.90, 1\}$. These greedy solutions trace an observed tradeoff curve. Neither the finite weight sweep nor the approximation guarantee establishes the global Pareto frontier or a universally preferred weight.

TABLE 3: Observed workflow-repository reach and account rankings for 16 incident-associated records (15 package names). Reach and ranks use the retained cross-sectional graph, not pre-event installations.

Package / record	Account (count)	Name reach	Version reach	Portfolio	Greedy	Union	Hybrid
`debug`	`qix` (2)	1,462	1,162	#2,298	#>100	#7	#35
`chalk`	`sindresorhus` (1)	1,125	587	#2	#1	#1	#1
`ansi-styles`	`sindresorhus` (1)	1,376	740	#2	#1	#1	#1
`simple-swizzle`	`qix` (1)	120	31	#2,298	#>100	#7	#35
`backslash`	`qix` (1)	0	0	#2,298	#>100	#7	#35
`eslint-config-prettier`	`lydell` (3)	10	10	#561	#41	#102	#31
`eslint-plugin-prettier`	`lydell` (6)	5	5	#561	#41	#102	#31
`@solana/web3.js`	`solana-devs` (1)	4	4	#181	#>100	#1,752	#465
`nx`	`jameshenry` (8)	2	2	#31	#>100	#835	#1,171
`node-ipc (v12)`	`riaevangelist` (12)	4	4	#2,562	#>100	#3,163	#1,274
`node-ipc (v10)`	`riaevangelist` (12)	4	4	#2,562	#>100	#3,163	#1,274
`@tanstack/history`	`tannerlinsley` (5)	1	1	#163	#>100	#1,423	#455
`@ctrl/tinycolor`	`scttcper` (1)	10	9	#5,765	#>100	#2,333	#1,227
`@opensearch-project/opensearch`	`peterzhuamazon` (3)	0	0	#2,548	#>100	#1,491	#2,323
`@mastra/core`	`tylerbarnes` (9)	0	0	#416	#>100	#6,314	#6,697
`echarts-for-react`	`atool` (1)	0	0	#398	#>100	#1,945	#747

Every account rank uses workflow-associated repository endpoints. The parenthesized value counts observed maintainers of that package. Membership is not evidence of historical publishing authority. Version labels and dependency counts are retained in the companion CSV. Package reach excludes the root; account portfolios include eligible seeds.

TABLE 4: Observed greedy tradeoffs across scalarization weight α at budget $|S| = 100$ ($|R_{\text{wf}}| = 7{,}171$).

	Package-Projected Graph				Version-Continuous Graph			
Scalarization α	C	C (%)	H (%)	P	C	C (%)	H (%)	P
0.00 (Exact Union)	4,407	61.46%	33.79%	534	4,479	62.46%	40.59%	527
0.10	4,591	64.02%	33.65%	530	4,714	65.74%	40.37%	553
0.25	4,809	67.06%	32.98%	604	4,855	67.70%	39.94%	634
0.50 (Equal weighting)	5,020	70.00%	31.19%	626	5,000	69.73%	38.65%	648
0.75	5,403	75.35%	21.69%	779	5,239	73.06%	31.75%	695
0.90	5,529	77.10%	14.15%	794	5,509	76.82%	14.97%	826
1.00 (Greedy Coverage)	5,538	77.23%	11.48%	800	5,516	76.92%	13.10%	817

At $\alpha = 0.50$, the name graph gives $C = 5{,}020$, $H = 31.19\%$, and $P = 626$; the version graph gives $C = 5{,}000$, $H = 38.65\%$, and $P = 648$. The name result retains 90.65% of greedy's baseline coverage and 92.31% of exact union's H. Relative to greedy, it loses 518 covered repositories and gains 19.71 percentage points of H. Relative to exact union, it gains 613 repositories and loses 2.60 points of H. A preferred operating point requires review costs and stakeholder preferences that were not measured here.

6.2 Exclusion-Oriented Heuristic

The lexicographic rule raises P to 1,022 at budget 100: 222 more than greedy and 488 more than exact union. Its $C = 5{,}020$ and $H = 13.23\%$ show that increasing completed source sets does not simultaneously maximize every objective. These are structural exclusions under ideal source hardening, with no global optimum or measured prevention guarantee.

6.3 Strict Zero-Anchored Threshold Sensitivity

Multi-token incidents motivate asking how many unhardened source identities remain, but token count is not a measured release quorum. In LiteLLM's final account, credentials served different roles, including deletion of records after publication [4]. We evaluate the explicit strict rule in Eq. 6, retaining only the 7,158 endpoints with observed sources and excluding all 13 source-free endpoints:

$$P_k(S) = \left|\{r \in R_+ : t_r(S) = 0 \ \vee \ (n_r \geq k \ \wedge \ t_r(S) < k)\}\right|. \tag{12}$$

The unguarded condition $t_r(S) < k$ credits every endpoint with $n_r < k$ even at zero hardening. In the strict model, a single-source endpoint must have its sole maintainer hardened at every threshold, and any endpoint with $n_r < k$ requires complete exclusion. This ensures a zero baseline for each tested k; it is not equivalent to subtracting the old zero-budget count.

A protection interpretation still requires a measured policy in which every successful attack needs the designated number of distinct upstream identities with no bypass. Our graph lacks package-level signer groups, role constraints, and bypass privileges. Two unrelated single-maintainer dependencies can each poison a consumer even if their combined source cardinality is two. Table 6 is therefore a structural sensitivity analysis, not a count of empirically protected repositories.

At budget 100, Pareto Hybrid has $P_1 = 626$, $P_2 = 961$, $P_3 = 1{,}018$, $P_5 = 1{,}063$. Greedy Coverage has $P_1 = 800$, $P_2 = 1{,}145$, $P_3 = 1{,}125$, $P_5 = 1{,}105$. Exact Union has $P_1 = 534$, $P_2 = 793$, $P_3 = 901$, $P_5 = 1{,}022$. Direct P has $P_1 = 1{,}022$, $P_2 = 1{,}169$, $P_3 = 1{,}286$, $P_5 = 1{,}383$. The source-cardinality distribution is $n_r = 0$: 13; $n_r = 1$: 1,716; $n_r = 2$: 546; $n_r = 3$: 354; $n_r = 4$: 347; and $n_r \geq 5$: 4,195. All strict




Fig. 9: Budget-100 selection/evaluation combinations for exact union and greedy. C and P count workflow repositories; H is divided by all account–repository pairs in the evaluation representation (462,170 for names; 266,016 for versions). Panels are separate metrics, not a common color scale.

TABLE 5: All-source exclusion $P(S)$ optimization via greedy minimum-source heuristic versus baseline single-objective rankings.

Budget	Direct $P(S)$ Heuristic			Greedy P	Union P	Gain vs Gr.	Gain vs Un.
$\|S\|$	P	C (%)	H (%)			ΔP	ΔP
10	**479**	55.4%	2.58%	351	343	+128	+136
25	**618**	59.1%	4.15%	514	427	+104	+191
50	**803**	64.2%	6.55%	638	441	+165	+362
100	**1,022**	70.0%	13.23%	800	534	+222	+488

zero-budget counts are zero.

The same ordered maintainer selections are reused at all thresholds, and the Direct P strategy continues to optimize its original $k = 1$ heuristic. Counts are nondecreasing with nested hardening budgets for a fixed k. Comparisons across k represent different hypothetical policies and need not be monotone, because endpoints with $n_r < k$ revert to complete-exclusion requirements.

For an additional hypothetical sensitivity, uniform control efficacy η gives $H_\eta(S) = \eta H(S)$. At $\eta = 0.90$, Pareto Hybrid yields 28.07% effective scenario exposure reduction. This uniform multiplier preserves all H rankings and does not estimate a real bypass rate, correlate account failures, or model CI compromise. Its values are assumptions, not incident-derived estimates.

6.4 Heterogeneous Weight Sensitivities

The account-sole weight increases an account's contribution according to its number of sole-maintained packages; it does not restrict its reachable endpoints to those packages. Ranking by that weighted reach captures 88.04% of the stipulated account-sole mass. This is concentration under an assumed weighting, not nine-tenths of measured ecosystem risk.

The separate package-sole quantity unions reach only from each account's sole-maintained packages. Under that definition, unweighted greedy captures 23.40%, unweighted exact union 27.32%, and package-sole-aware ranking 67.37%. The latter gain is 40.05 percentage points relative to unweighted exact union. Its uniform coverage is 4,718 repositories and $P = 642$. These results distinguish account weighting from package-restricted reach. A single observed maintainer is not evidence about review quality or an empirically fitted probability of compromise.

7 Temporal Metadata and Prospective Design: RQ5

The historical companion asks what retained registry metadata can support before an event cutoff. It is separate from

TABLE 6: Strict zero-anchored threshold counts $P_k(S)$ and coverage across maintainer hardening strategies ($|R_{\text{wf}}| = 7{,}171$).

Prioritization Strategy	Budget $\lvert S\rvert$	$C(S)$	C (%)	$H(S)$ (%)	$P_1(S)$ $(k=1)$	$P_2(S)$ $(k=2)$	$P_3(S)$ $(k=3)$	$P_5(S)$ $(k=5)$
Portfolio Size	10	3,435	47.90%	1.59%	391	512	488	521
	25	4,067	56.71%	4.38%	430	602	657	661
	50	4,446	62.00%	6.14%	503	718	777	784
	100	4,579	63.85%	7.96%	577	774	858	892
Greedy Coverage	10	4,331	60.40%	3.79%	351	477	495	468
	25	4,854	67.69%	6.08%	514	756	732	727
	50	5,196	72.46%	8.73%	638	936	921	907
	100	5,538	77.23%	11.48%	800	1,145	1,125	1,105
Exact Union	10	3,910	54.53%	4.48%	343	440	466	485
	25	4,284	59.74%	9.86%	427	637	719	694
	50	4,321	60.26%	18.09%	441	655	734	787
	100	4,407	61.46%	33.79%	534	793	901	1,022
Pareto Hybrid ($\alpha = 0.50$)	10	4,331	60.40%	3.79%	351	477	495	468
	25	4,795	66.87%	7.68%	498	706	734	729
	50	5,001	69.74%	14.96%	605	907	985	1,019
	100	5,020	70.00%	31.19%	626	961	1,018	1,063
Direct Supermodular $P(S)$	10	3,976	55.45%	2.58%	479	614	609	586
	25	4,239	59.11%	4.15%	618	743	774	779
	50	4,604	64.20%	6.55%	803	948	998	1,016
	100	5,020	70.00%	13.23%	1,022	1,169	1,286	1,383

TABLE 7: Budget-100 outcomes under assumed weights. Each H column has its own stipulated denominator; weights are not estimated compromise probabilities.

Selection	C	H (%)	Account-sole (%)	Log (%)	Package-sole (%)	P
Exact union	4,407	33.79	77.30	40.15	27.32	534
Greedy coverage	5,538	11.48	74.19	18.52	23.40	800
Portfolio	4,579	7.96	70.26	15.06	13.72	577
Hybrid (0.50)	5,020	31.19	80.41	38.93	28.51	626
Account-sole aware	4,919	22.59	88.04	33.09	44.53	707
Log-portfolio aware	4,603	31.91	81.42	42.91	33.17	514
Package-sole aware	4,718	19.39	80.03	23.61	67.37	642

the cross-sectional reverse-reach experiment. It does not test whether the primary rankings would have predicted historical compromise.

7.1 Bounded Cutoff-SemVer Reconstruction

For each retained root record, the reconstruction chooses the highest currently retained, non-prerelease version satisfying a runtime dependency range and published by the root cutoff. Expansion stops at depth three or 250 nodes per root. Peer, optional, development, bundled, workspace, override, git, and tarball dependency behavior is excluded. Deleted historical versions may be unavailable; present-day retention cannot recreate every past registry state.

The source contains 45 root records but 44 distinct event/root/cutoff tuples: one `node-ipc` tuple is repeated. We report retained-record counts without treating them as independent incidents. Of 1,848 recorded edge attempts, 1,841 resolve and seven have unavailable target registries, yielding 99.62% among recorded attempts. This percentage excludes unvisited expansions beyond the bounds. The 1,272 node count is summed across roots, not globally deduplicated. One record reaches the node cap. These measurements do not establish full-tree completeness, downstream population reconstruction, or unbiased historical rankings.

7.2 Release-Field Availability and Authority Limits

The availability audit finds predecessor metadata for 44 of 45 retained records, repository-field comparison availability for 42, and `gitHead`-field comparison availability for 34. Availability does not show that URLs stayed equal, commits were valid or available, or a publisher retained authority. The audit classified no field deltas, built no authority scores, and evaluated no release-gating control.

All 45 records contain `dist.integrity` and embedded maintainer metadata. A distribution hash identifies expected artifact bytes; an embedded maintainer array is not a cryptographic signature. Neither proves a benign or reproducible build. The attestation access assessment made no version-specific requests, retrieved no bundles, ran no signature verification, and classified no attestation states. Historical attestation presence is therefore *unknown*; zero retrievals cannot be reported as zero attestations. Signing studies motivate the need for stronger evidence [17], [18], without supplying the missing measurements for this cohort.

The LiteLLM source-tag/artifact discrepancy [5] illustrates why artifact identity, intended source, and release authority must be evaluated separately. Contextual reports do not add observations to the 45-record companion.

TABLE 8: Retained bounded registry-SemVer reconstruction manifest. The recorded resolution share is conditional on attempted expansions within the bounds.

Recorded dimension	Value
Retained root records	45
Distinct event/root/cutoff tuples	44
Recorded edge attempts	1,848
Resolved recorded edges	1,841
Node counts summed over roots	1,272
Unresolved expansions	7
Resolved share of recorded attempts	99.62%
Maximum expansion depth	3
Node cap per root	250
Roots reaching cap	1

Only regular dependencies are included; depth is capped at three and nodes at 250 per root. Highest retained cutoff-valid satisfying versions are used. These are bounded approximations, not lockfile reconstructions or completeness guarantees. Raw-response checksums establish retained-object identity, not publisher authenticity.

TABLE 9: Field availability in 45 retained pre-event version-object records. Comparison availability is not continuity, equality, or authenticated release authority.

Metadata availability	Count	Share
Retained selected-version objects	45	100.0%
Immediate predecessor available	44	97.8%
Repository-field comparison available	42	93.3%
gitHead-field comparison available	34	75.6%
publishConfig comparison available	11	24.4%
Selected dist.integrity present	45	100.0%
Selected embedded maintainers present	45	100.0%

The 45 records include a repeated event/root/cutoff tuple; they are not independent incidents. Embedded maintainer metadata is not a signature. No version-specific provenance endpoint requests, bundle retrievals, signature verifications, or attestation-state classifications were performed. Historical attestation presence/absence is unknown, not 0/45 absent.




Fig. 10: Observed greedy scalarization results at budget 100. Connecting seven evaluated settings guides the eye; the curve is not a certified global Pareto frontier. Equal weighting is a sensitivity choice.




Fig. 11: All-source exclusion P for the direct heuristic, greedy coverage and exact union. All three use the same observed workflow endpoint universe; counts do not measure deployed prevention.

7.3 Prospective Acquisition and Outcome Requirements

Before requests, we froze 100 identifiers sampled uniformly without replacement from the 25,228-identifier graph frame (seed 20261020). The 92 ordinary-shaped names produced 90 metadata captures and two HTTP 404 responses; eight bundled-context identifiers returned HTTP 405. These failures expose a sampling-frame defect. No selected identifier was replaced. A new registry-level wave would require a separately frozen frame of valid units.

The cutoff is October 20, 2026, 00:48:38 Asia/Dhaka; the 90-day horizon ends January 18, 2027. All 100 outcomes remain pending. No positive or negative outcome labels,




Fig. 12: Budget-100 exposure shares under uniform, account-sole and package-sole weights. Each column has its own stipulated denominator. Values are structural sensitivities, not estimated attack-risk reductions.

trained models, predicted probabilities, or forecasting metrics exist. The protocol is an internal feasibility plan, not external preregistration.

A future outcome study must define its eligible population, surveillance sources, reporting-delay and censoring rules, and campaign/family grouping before examining outcomes. Unreported packages must remain unlabeled unless a specified follow-up procedure supports another interpretation. Retrospective incident lists can support documented-event studies, but cannot alone estimate false-positive rates for an unspecified population. The current acquisition pilot establishes request feasibility and frame limitations, not predictive validity.

8 Threats to Validity and Research Ethics

We organize limitations around construct, internal, external, and conclusion validity, informed by empirical reporting guidance [28].

8.1 Construct Validity

Registry maintainer arrays supply username associations, not historical publication authority, token scope, account independence, or a peer-review policy. One maintainer does not prove absence of human review; several do not prove enforced review. Uniform and heterogeneous source weights are modeling assumptions. The perfect hardening model removes selected account origins, not package nodes or paths from other origins.

The workflow observation is a directory lookup at HEAD. We did not retain workflow YAML, job execution, permission scopes, historical release links, or consumer lockfiles. Dependency and workflow association therefore establishes neither installation nor vulnerable-code execution or secret access. CI dependency studies [21] and finer-grained vulnerability analysis [22] motivate those distinctions without supplying execution evidence for our endpoints.

The main exact-version graph is an observed deps.dev edge union, while the temporal companion is a bounded highest-satisfying SemVer approximation. They are different representations. Neither reconstructs npm hoisting, installed versions, overrides, or complete historical dependency trees. Runtime vulnerabilities such as the Node.js Brotli disclosure [11] are outside the package graph. Residual thresholds are hypothetical source-count rules, without signer groups, role constraints, or measured enforcement.

8.2 Internal and Observational Validity

Independent traversals, transposed source incidence, small-graph cases, and generated result checks validate computations on retained evidence. They cannot recover omitted observations. SCC condensation preserves reach; it is not a source of measured cycle-removal benefit. Ties use ascending username order, not portfolio size, except where portfolio size defines the selection rule itself.

Repository normalization is lexical. Excluding inconsistent positive observations tests sensitivity; it does not validate the other remote mappings or repair historical flags. Both main representations mix contexts and acquisition dates. Unknown workflow states and ambiguous zeros can omit eligible endpoints. Historical availability counts describe retained records, including a repeated tuple, and do not establish independent incidents or verified release authority.

8.3 External and Conclusion Validity

The high-impact-seeded expansion is neither registry-wide nor a random sample of npm installations. Public workflow-associated repositories cannot represent private consumer infrastructure without further evidence. Results describe this graph and explicit scenarios. They supply no measured compromise probabilities or causal control effects.

Random orders quantify selection variability. Orders are reused across nested budgets and endpoint definitions, so the resulting 6,000 rows are not independent ecosystem samples. Monte Carlo errors describe simulation means, not npm-wide uncertainty. The seven scalarization settings are exploratory tradeoff points, without a certified global Pareto frontier or an empirically estimated stakeholder preference.

Heterogeneous weights are structural sensitivities, not fitted risk priors. Claims about efficacy require a separate intervention study.

8.4 Ethics and Reporting

The analyses read retained public metadata and execute no package payloads, credential probes, or exploitation. Prospective captures omit email addresses and package bodies. Public usernames illustrate structural overlap without implying present-day insecurity, negligence, or historical publishing authority. Incident associations do not validate prediction. Artifact checksums identify retained bytes rather than certify authenticity. Assistance is disclosed, and authors must review the claims, sources, code, and applicable submission requirements.

9 Conclusion

The experiments distinguish three questions that share the same graph but reward different selections. At budget 100, greedy reaches 5,538 workflow-associated repositories and exact union reaches 4,407. Their uniform scenario exposure reductions are 11.48% and 33.79%. Greedy selects all observed sources for 800 endpoints; an exclusion-oriented heuristic increases that count to 1,022 without a global optimality guarantee. A covered endpoint can retain an unselected origin under every baseline.

Version continuity reduces account–repository pair mass from 462,170 to 266,016, a 42.44% decrease relative to the name projection. This is sensitivity to observed representation, not a count of impossible exploits in installed systems. Selection and evaluation should therefore name their representation, endpoint universe, and denominator. Scalarization and heterogeneous weights expose additional choices rather than resolve them with a universally preferred cohort.

The bounded historical companion resolves 1,841 of 1,848 recorded edges while leaving unvisited expansions outside its scope. Release-field availability supplies acquisition groundwork; historical attestation states remain unassessed. The prospective sample has 100 pending outcomes through January 18, 2027. Neither companion supports a forecasting result.

Future work should align historical authority and installation evidence, specify outcome surveillance and family grouping, and measure actual intervention costs and effects. Until then, the results support explicit structural prioritization and evidence limits. They do not establish a registry-wide control prescription, an optimal cooldown, or complete operational protection.

Statements and Declarations

Funding

This research received no external funding.

Competing Interests

Both authors declare that they have no financial or non-financial competing interests relevant to this work.

Data Availability

The retained metadata, derived analysis tables, and artifact manifests supporting this study are maintained in the project repository. A versioned public replication release is being prepared before submission. A publicly accessible release URL and persistent identifier are not yet available; the deposited version, access link, and any exclusions must be specified in the final submission. This draft therefore does not claim that the supporting data are already publicly accessible.

Code Availability

The project repository contains the collection and analysis scripts, numerical consistency checks, figure-generation scripts, and manuscript sources. These materials are intended to accompany the public replication release described above. Reproducing the retained-graph analyses requires the archived observations; repeating live API requests may return different metadata.

Ethics and Consent

The study analyzes public software-ecosystem metadata and does not involve recruited human participants, interventions on individuals, or execution of package payloads. No participant consent was collected. Usernames are used as observed graph identifiers, without inferring misconduct or present-day account security. The prospective observations contain no measured incident outcomes at the time of this manuscript.

Acknowledgment

We thank package maintainers, the open-source community, deps.dev and GitHub for public artifacts and interfaces. AI assistance is described in the methods.

References

[1] M. Zimmermann, C.-A. Staicu, C. Tenny, and M. Pradel, "Small world with high risks: A study of security threats in the npm ecosystem," in *28th USENIX Security Symposium*. USENIX Association, 2019, pp. 995–1010. [Online]. Available: https://www.usenix.org/conference/usenixsecurity19/presentation/zimmerman

[2] N. Zahan, T. Zimmermann, P. Godefroid, B. Murphy, C. Maddila, and L. Williams, "What are weak links in the npm supply chain?" arXiv:2112.10165v2, 2022, ICSE SEIP 2022; DOI: 10.1145/3510457.3513044. [Online]. Available: https://arxiv.org/abs/2112.10165v2

[3] G. L. Nemhauser, L. A. Wolsey, and M. L. Fisher, "An analysis of approximations for maximizing submodular set functions—I," *Mathematical Programming*, vol. 14, pp. 265–294, 1978.

[4] O. Jensen and M. Wang, "The attack chain behind the v1.107.0 LiteLLM release," October 2026, october 23 final investigation; accessed October 25, 2026. [Online]. Available: https://docs.litellm.ai/blog/security-incident-oct-21-2026-attack-chain

[5] LiteLLM Project, "Contained: Oct 21, 2026 LiteLLM release v1.107.0 compromised," October 2026, artifact scope and availability window; accessed October 25, 2026. [Online]. Available: https://docs.litellm.ai/blog/security-incident-oct-21-2026

[6] E. Cohen, "Open and shut: Remote code execution in opencode via MCP OAuth," Pillar Security research disclosure, October 2026, october 19 disclosure; September 28 fix; accessed October 25, 2026. [Online]. Available: https://www.pillar.security/blog/open-and-shut-remote-code-execution-in-opencode-via-mcp-oauth

[7] Railway, "Preliminary report: Oct 21st security incident," October 2026, october 22 preliminary report; accessed October 25, 2026. [Online]. Available: https://blog.railway.com/p/preliminary-report-october-security-incident

[8] J. Cooper, "Security disclosure: Wednesday october 21st," October 2026, accessed October 25, 2026. [Online]. Available: https://blog.railway.com/p/security-disclosure-wednesday-october-21st

[9] Bloom Security, "SlugFest: Millions of AI agents install npm packages exposed to malicious takeover through GitHub," October 2026, researcher disclosure; accessed October 25, 2026. [Online]. Available: https://bloom.security/blog/slugfest-millions-of-ai-agents-download-exposed-npm-packages

[10] GitHub, "Unvalidated npm trusted publishing configurations now expire," October 2026, october 2 changelog; accessed October 25, 2026. [Online]. Available: https://github.blog/changelog/2026-10-02-unvalidated-npm-trusted-publishing-configurations-now-expire/

[11] The Node.js Project, "Wednesday, october 21, 2026 security releases," October 2026, cVE-2026-111497 rated High; accessed October 25, 2026. [Online]. Available: https://nodejs.org/en/blog/vulnerability/october-2026-security-releases

[12] C. Liu, S. Chen, L. Fan, B. Chen, Y. Liu, and X. Peng, "Demystifying the vulnerability propagation and its evolution via dependency trees in the NPM ecosystem," in *44th International Conference on Software Engineering (ICSE)*, 2022. [Online]. Available: https://arxiv.org/abs/2201.03981v2

[13] Z. Wang, "Defending the core: A centrality-based protection strategy for supply chain security in npm dependency network," arXiv:2606.14036, 2026, preprint. [Online]. Available: https://arxiv.org/abs/2606.14036

[14] M. Ohm, H. Plate, A. Sykosch, and M. Meier, "Backstabber's knife collection: A review of open source software supply chain attacks," arXiv:2005.09535, 2020, DIMVA 2020 preprint. [Online]. Available: https://arxiv.org/abs/2005.09535

[15] A. Sejfia and M. Schäfer, "Practical automated detection of malicious npm packages," arXiv:2202.13953, 2022, ICSE 2022; DOI: 10.1145/3510003.3510104. [Online]. Available: https://arxiv.org/abs/2202.13953

[16] W. Guo, Z. Chen, Z. Xu, C. Liu, M. Kang, S. Song, C. Liu, Y. Xu, W. Sun, and Y. Liu, "How effective are NPM malicious package detectors? a large-scale empirical study," arXiv:2603.27549v2, 2026, revised August 5, 2026. [Online]. Available: https://arxiv.org/abs/2603.27549v2

[17] T. R. Schorlemmer, K. G. Kalu, L. Chigges, K. M. Ko, E. A. Isghair, S. Baghi, S. Torres-Arias, and J. C. Davis, "Signing in four public software package registries: Quantity, quality, and influencing factors," in *IEEE Symposium on Security and Privacy (S&P)*, 2024. [Online]. Available: https://arxiv.org/abs/2401.14635

[18] K. G. Kalu, T. Singla, C. Okafor, S. Torres-Arias, and J. C. Davis, "An industry interview study of software signing for supply chain security," in *34th USENIX Security Symposium (USENIX Security 25)*. USENIX Association, 2025, pp. 81–100. [Online]. Available: https://www.usenix.org/conference/usenixsecurity25/presentation/kalu

[19] I. Koishybayev, A. Nahapetyan, R. Zachariah, S. Muralee, B. Reaves, A. Kapravelos, and A. Machiry, "Characterizing the security of GitHub CI workflows," in *31st USENIX Security Symposium*. USENIX Association, 2022, pp. 2747–2763. [Online]. Available: https://www.usenix.org/conference/usenixsecurity22/presentation/koishybayev

[20] S. Muralee, I. Koishybayev, A. Nahapetyan, G. Tystahl, B. Reaves, A. Bianchi, W. Enck, A. Kapravelos, and A. Machiry, "ARGUS: A framework for staged static taint analysis of GitHub workflows and actions," in *32nd USENIX Security Symposium*. USENIX Association, 2023, pp. 6983–7000. [Online]. Available: https://www.usenix.org/conference/usenixsecurity23/presentation/muralee

[21] N. R. Weeraddana, M. Alfadel, and S. McIntosh, "Dependency-induced waste in continuous integration: An empirical study of unused dependencies in the npm ecosystem," in *International Symposium on the Foundations of Software Engineering (FSE)*, 2024, pp. 116:1–116:23. [Online]. Available: https://rebels.cs.uwaterloo.ca/confpaper/2024/07/16/dependency-induced-waste-in-continuous-integration.html

[22] Y. Shen, X. Gao, H. Sun, and Y. Guo, "Understanding vulnerabilities in software supply chains," *Empirical Software Engineering*, vol. 30, no. 1, p. 20, 2025. [Online]. Available: https://gaoxiang9430.github.io/papers/emse.pdf

[23] D. Jayasuriya, S. Ou, S. Hegde, V. Terragni, J. Dietrich, and K. Blincoe, "An extended study of syntactic breaking changes in the wild," *Empirical Software Engineering*, vol. 30, no. 2, p. 42, 2025.

[24] H. He, B. Vasilescu, and C. Kästner, "Pinning is futile: You need more than local dependency versioning to defend against supply chain attacks," *Proceedings of the ACM on Software Engineering*, vol. 2, no. FSE, p. FSE013, 2025. [Online]. Available: https://arxiv.org/abs/2502.06662

[25] D. Pinckney, F. Cassano, A. Guha, and J. Bell, "npm-follower: A complete dataset tracking the NPM ecosystem," arXiv:2308.12545, 2023. [Online]. Available: https://arxiv.org/abs/2308.12545

[26] I. Rahman, J. Marley, R. Paramitha, and L. Williams, "CHRONO-RESOLUTION: A dependency resolution dataset at release points for npm, PyPI, and crates.io packages," arXiv:2607.15315, 2026, ICSME 2026 Tool Demonstration and Data Showcase Track. [Online]. Available: https://arxiv.org/abs/2607.15315

[27] A. A. Shafin and K. M. Ahmed, "PatchRisk: Forecasting future vulnerability exposure in open-source dependency networks," arXiv:2609.13719, 2026, WI-IAT 2026 preprint. [Online]. Available: https://arxiv.org/abs/2609.13719

[28] P. Ralph *et al.*, "Empirical standards for software engineering research," arXiv:2010.03525, 2020. [Online]. Available: https://arxiv.org/abs/2010.03525

[29] Open Source Insights, "deps.dev API v3: GetDependencies," Official API documentation, 2026, accessed October 20, 2026. [Online]. Available: https://docs.deps.dev/api/v3/