

Finalize Shopping

Introduction

The **FinalizeShopping** method is used after the MakePayment stage to confirm the selected flights in a shopping cart and finalize the reservation.

Limits and Features

Parameters

SessionId: The session ID for the current request.

SessionToken: The session token required for authorization.

ShoppingFileId: It is a unique identifier associated with the shopping session or reservation. This identifier is generated during the **MakePayment** phase.

Basic Request Structure

Below is an example of a basic **FinalizeShopping** request using SOAP:

```

1  <soapenv:Body>
2    <tem:FinalizeShopping>
3      <tem:request>
4        <trev:AuthenticationHeader>
5          <trev:SessionId>5431232788</trev:SessionId>
6          <trev:SessionToken>5d8bc049-aa-aef0-cc79dc75c660</trev:SessionToken>
7        </trev:AuthenticationHeader>
8        <trev1:Form>
9          <trev1:BillingInfo>
10             <trev2:Address_City>ISTANBUL</trev2:Address_City>
11             <trev2:Address_Detail>COBANCESME SAN. CD.</trev2:Address_Detail>
12             <trev2:Address_District>BAHCELIEVLER</trev2:Address_District>
13             <trev2:Address_ZipCode>0000</trev2:Address_ZipCode>
14             <trev2:BillingName>TEST</trev2:BillingName>
15             <trev2:CountryCode>TR</trev2:CountryCode>
16             <trev2:IfCompany>1</trev2:IfCompany>
17             <trev2:TaxNo>1111111111</trev2:TaxNo>
18             <trev2:TaxOffice>test</trev2:TaxOffice>
19          </trev1:BillingInfo>
20          <trev1:ShoppingFileId>7a4219c48e-4ab4-9112-83fa3bf15869</trev1:ShoppingFileId>
21        </trev1:Form>
22      </tem:request>
23    </tem:FinalizeShopping>
24  </soapenv:Body>

```

FinalizeShopping Request

AuthenticationHeader

Parameters	Description	Optional
SessionId	A unique identifier used to define a specific session in which a user is granted access to an API for a certain period. You should get this parameter from the response of the Login Method.	M
SessionToken	Unique authentication used to represent a specific session in which a user has access to an API. You should get this parameter from the response of the Login Method.	M

From

From/BillingInfo

Parameters	Description	Optional
Address_City	It represents the city information associated with the billing address.	M
Address_Detail	It is a field for detailed information related to the billing address.	M
Address_District	It represents the district/neighborhood information within the billing address.	M
Address_ZipCode	It represents the postal code associated with the billing address.	M
BillingName	It represents the name of the company or individual for the billing process.	M
CountryCode	It specifies the country code of the billing address.	M
IfCompany	It indicates whether the invoice is a corporate or individual invoice within the billing information. ▶ IfCompany = 1 → Indicates that the payer is a company. ▶ IfCompany = 0 or missing → Indicates that the payer is an individual customer.	M
TaxNo	It represents the tax identification number of the individual or company for billing purposes.	M
TaxOffice	It represents the tax office to which the individual or company is registered for billing purposes.	M

From/ShoppingFileId

Parameters	Description	Optional
------------	-------------	----------

ShoppingFileId	It is a unique identifier representing the shopping session where the user's data is stored during the flight booking process.	M
----------------	--	---

FinalizeShopping Response

Result

Field	Description
HasError	It is a status used to indicate whether an error occurred during the process. ▸ true: Indicates that an error occurred during the process. In this case, the payment transaction may have failed, and further error details should be reviewed. ▸ false: Indicates that the process was completed without errors and is generally considered successful.
ServiceError	ServiceError represents a technical or business-related error that occurs during the payment process. This error is usually returned in the form of a code or message, helping the developer understand the issue.
SystemLogs	It typically contains information or error messages related to system events that occur during the transaction. This field provides details about the situations encountered by the API server during the payment process.

ShoppingFile

Index	Field	Description
1	Id	It is the unique identifier for the ShoppingFile. This ID is used to track transactions performed during the session.
2	IfFinalized	It is a value that indicates whether the reservation has been finalized or is in a state where no further changes can be made. This parameter specifies whether passenger information can still be updated or if the transaction is locked in its final stage.
3	IsFlightInfoChanged	It indicates whether the flight details have changed (e.g., flight times, airline, departure/arrival airports). ▸ true: There are changes in the flight details. ▸ false: The flight details remain the same.
4	IsPriceChanged	It indicates whether the price has changed between the initial shopping process and finalization. ▸ true: The price has changed. ▸ false: The price remains the same.
5	IsReservationCancelled	It indicates whether the reservation has been canceled.

		▶ true: The reservation has been canceled. ▶ false: The reservation is active.
7	Is_CC_Payment_Enabled	It indicates whether the credit card payment option is available. ▶ true: Payment can be made using a credit card. ▶ false: Payment via credit card is not available.
8	Is_RA_Payment_Enabled	It indicates whether payment can be made using the Running Account (RA), a method used for corporate or airline-agreement payments. ▶ true: Payment can be made using RA. ▶ false: Payment via RA is not available.
9	RemainingSum	It represents the remaining amount to be paid during the purchase or update of the ticket. This amount shows the balance the passenger needs to pay to complete the transaction and is typically updated after changes or additional services are applied.

ShoppingFile/AirBookings

ShoppingFile/AirBookings/AirBooking

Index	Field	Description
1	BaseFare	The fare represents the cost of the ticket. This cost refers exclusively to the flight itself and does not include any additional expenses such as taxes, fees, or extra services.
2	BookingCode	This field is used to retrieve or query the unique identifier of a flight reservation. Typically, this is an alphanumeric code generated at the time of booking, which is used to track your ticket, flight details, and reservation status.
3	Currency	This field is used to query or set the currency used for ticket prices, fees, and other financial transactions. It is typically employed in operations such as purchasing flight tickets, pricing additional services, or making payments for services, to determine the relevant currency.
4	ExchangeCurrencyCode	It is necessary to convert ticket prices, fees, or other services into the currency of the user's location or the local market where the transaction takes place. This field is typically used to determine or query the code of the target currency during currency conversions. This method is especially important for international flights or for airlines that accept different currencies.
5	IsRefundable	Whether a ticket is refundable. This field provides information on whether the ticket purchased by the passenger can be refunded under certain conditions.
6	LastSellerCommission	The commission amount/service fee determined by the seller (client).
7	NetFare	It refers to the base fare to be charged to a passenger for a flight.
8	ProductId	It refers to a unique product identifier (ID) defined for a specific flight or service. This ID enables the identification and processing of the flight or additional service by the system.

Index	Field	Description
9	SystemServiceFee	This element represents the system service fee associated with a transaction or service.
11	ServiceFee	This element represents the service fee associated with a transaction or service. For example, if the service fee amount is 3, it is indicated as 3 in this field. ▸ ServiceFee= SystemServiceFee+LastSellerCommission
12	Status	It represents the current status of the reservation process. This field indicates whether the reservation has been successfully completed.
13	Taxes	This XML element is used to denote the total amount of taxes applicable to a transaction or service within the Trevoo.WS.Entities.Shopping schema.
14	TotalFare	The TotalFare element represents the complete amount to be paid for a transaction or service. ▸ TotalFare=BaseFare+Taxes+ServiceFee
15	Type	The Type field typically indicates the type of reservation made. ▸ Flight → Flight ticket reservation.
16	CanBeReserved	It indicates whether a specific flight is eligible for reservation. CanBeReserved = True The selected flight is available for booking under the given conditions. A seat can be allocated for the passenger, and a reservation record can be created. CanBeReserved = False The flight is not available for reservation. This may be due to one of the following reasons: ▸ Reservation is not allowed based on the selected fare rules. ▸ The airline has imposed restrictions on booking. ▸ There are limitations specific to a particular sales channel. ▸ Capacity or sales limits have been reached.

ShoppingFile/AirBookings/AirBooking/TimeTable

Index	Field	Description
1	CreationDate	It shows the date and time when the ticket was initially created.
2	Prebooking_ExpiresAt	This field represents the expiration date and time of a prebooking. In other words, it indicates the deadline by which the customer must complete the reservation before making the payment.
3	ReservationDate	It indicates the date when the reservation was made.

4	Reservation_ExpiresAt	This field specifies the date and time when a reservation's validity expires. It represents the time period during which the reservation remains valid before payment is made.
---	-----------------------	--

ShoppingFile/AirBookings/BookingItems

ShoppingFile/AirBookings/BookingItems/AirBookingItem

Index	Field	Description
1	BaseFare	The fare represents the cost of the ticket. This cost refers exclusively to the flight itself and does not include any additional expenses such as taxes, fees, or extra services.
2	ProductItemId	This element contains a unique identifier (UUID) corresponding to a specific product item within the Trevoo.WS.Entities.Shopping schema. For example, the value 289af8a3-554b-469c-b28a-7ace0feb5487 uniquely identifies the product item associated with this XML entity.
3	LastSellerCommission	The commission amount/service fee determined by the seller (client).
4	SystemServiceFee	This element represents the system service fee associated with a transaction or service.
5	ServiceFee	This element represents the service fee associated with a transaction or service. For example, if the service fee amount is 3, it is indicated as 3 in this field. ► ServiceFee= SystemServiceFee+LastSellerCommission
6	Baggage	It refers to the passenger's allocated baggage allowance for the flight. This field includes details and limitations regarding the baggage the passenger is permitted to carry.
7	VQ	It is a field that indicates additional fees or service charges related to the journey or ticket.
8	YR	It generally refers to a type of additional fee or surcharge applied during the ticketing process.

ShoppingFile/AirBookings/BookingItems/AirBookingItem/PaxReference

Index	Field	Description
1	Age	It typically represents the passenger's age.
2	LocalPaxType	It represents the passenger's local type and classifies passengers based on their age or special conditions. This parameter is used in aviation systems to ensure that passengers receive appropriate services and that fare classifications are correctly applied. Typically, the 'LocalPaxType' parameter includes the following categories: ADT (Adult): Adult passenger (generally 12 years and older). CNN (Child): Child passenger (between 2-12 years old). INF (Infant): Infant passenger (0-2 years old, usually traveling on lap). SRC

		(Senior Citizen): Senior passenger (passengers above a certain age, depending on the airline). STU (Student): Student passenger (may qualify for special student discounts). MIL (Military): Military personnel passenger. CHD: Unaccompanied child passenger.
3	LocalSequenceNo	It refers to the local sequence number of the passenger in a reservation or ticketing process. This parameter is used to identify multiple passengers within the same reservation record (PNR - Passenger Name Record) in a specific order.
4	PassengerId	It is a value that represents the passenger's unique identification number.
5	PaxReferenceId	It is a unique reference number assigned to the passenger.

ShoppingFile/AirBookings/BrandedFares

ShoppingFile/AirBookings/BrandedFares/BrandedFareItems

Index	Field	Description
1	BrandedFareItemId	It uniquely identifies a specific "branded fare" option, providing a unique ID corresponding to each package.

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/BrandedFarePassengers

Index	Field	Description
1	PassengerCount	It indicates the number of passengers included in the pricing for each Branded Fare.
2	PassengerType	It is a field that specifies the passenger's category or type. ▸ ADT (Adult): Adult passenger (typically 12 years and older). ▸ CHD (Child): Child passenger (typically between 2-11 years old). ▸ INF (Infant): Infant passenger (typically under 2 years old, traveling on a lap).

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/BrandedFarePassengers/FareComponents

Index	Field	Description
1	BrandId	Identifier that represents the brand identity of a specific airline or scheduled flight. This identifier helps distinguish between different fare levels or service packages offered to passengers. For example, some airlines offer different classes and service packages such as economy, premium economy, and business class under different brand identities. BrandId is used to distinguish these different service packages and provide information about a specific class or service package. BrandId is an identifier that represents the brand identity of a specific airline or scheduled flight. This identifier helps distinguish between different fare levels or service packages offered to passengers. For example, some airlines offer different classes and service packages such as economy, premium economy, and business class under different brand identities. BrandId is used to distinguish these different service packages and provide information about a specific class or service package.
2	BookingClass	"BookingClass" refers to the reservation class of a specific branded fare item. This field determines the class in which the passenger will travel and the services,

		flexibilities, and advantages offered by that class. It is usually represented by a single letter or a combination of letters.
3	CabinClass	It specifies the cabin class in which the passenger will be seated during the flight. This field defines different cabin classes that passengers can choose from based on their flight experiences and level of service preferences.
4	FareBasisCode	"FareBasisCode" refers to the basic fare code that determines the pricing rules and conditions of the ticket. This code defines the fare class applicable to a flight and the flexibility, change, and cancellation conditions of the ticket. It is usually presented as a combination of letters and numbers (e.g., Y26, QFL, or E14NR). The FareBasisCode field indicates the pricing rules and conditions under which the ticket is sold.
5	FreeBaggageAllowanceId	FreeBaggageAllowanceId is an identifier that defines the free baggage allowance offered for a specific flight or fare class. This identifier indicates how much free baggage allowance passengers have when traveling in a specific fare class.
6	SeatsAvailable	It refers to the number of seats available for booking on a flight. This indicates the occupancy rate and remaining capacity of the flight.
7	SegmentId	SegmentId is an identifier that represents the identity of a specific flight or flight segment. Particularly in cases of multi-stop or connecting flights, there are different SegmentIds for each flight section. This allows passengers and systems to understand which part of a particular flight is being referred to.

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/BrandedFarePassengers/PassengerFareInfo

Index	Field	Description
1	BaseFare	The fare represents the cost of the ticket. This cost refers exclusively to the flight itself and does not include any additional expenses such as taxes, fees, or extra services.
2	Currency	It indicates the currency in which the specified amount (Amount) for a particular flight or reservation is expressed. This specifies in which currency the ticket prices, taxes, and other fees are calculated and will be paid.
3	PaxSequence	It is a field that specifies the sequence of passengers' reservations. It refers to the numbering of passengers in a specific order during the reservation process.
4	PaxType	It refers to the classification of passengers based on their age and status. It is important for ticket pricing, baggage allowance, service level, and other passenger services. The PaxType field helps airlines and travel agencies accurately classify passenger information and develop appropriate service and pricing strategies for each passenger type.
5	Taxes	This XML element is used to denote the total amount of taxes applicable to a transaction or service within the Trevoo.WS.Entities.Shopping schema.
6	TotalFare	The TotalFare element represents the complete amount to be paid for a transaction or service. ► $\text{TotalFare} = \text{BaseFare} + \text{Taxes} + \text{ServiceFee}$

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/BrandedFarePassenger/Policy

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/BrandedFarePassenger/Policy/CancellationPolicies

Index	Field	Description
1	Amount	This field specifies the monetary value associated with the change policy of a flight. It indicates the cost that applies when a policy is changed. This ensures accurate and transparent management of fees related to policy Cancellation for flights.
2	Applicability	It is a field that specifies under which conditions a ticket can be canceled and in which situations the cancellation is valid. ▸ BeforeDeparture → The cancellation policy applies before the flight departs. ▸ AfterDeparture → The cancellation policy applies after the flight has departed.
3	MinutesToDeparture	It indicates the amount of time remaining (in minutes) until a flight's departure and determines the impact of this duration on the cancellation of the ticket. It specifies the remaining time for a ticket to be canceled and describes the effect of this time on cancellation policies. This information helps passengers understand how much time they have in case of a flight cancellation and how the cancellation can be executed.
4	Currency	It indicates the currency in which the specified monetary values are denominated. This field specifies the currency used for calculating and displaying ticket prices, taxes, service fees, and other costs, such as TRY (Turkish Lira), USD (US Dollar), EUR (Euro), and GBP (British Pound).
5	IsRefundable	Whether a ticket is refundable. This field provides information on whether the ticket purchased by the passenger can be refunded under certain conditions.

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/BrandedFarePassenger/Policy/ChangePolicies

Index	Field	Description
1	Amount	This field specifies the monetary value associated with the change policy of a flight. It indicates the cost that applies when a policy is changed. This ensures accurate and transparent management of fees related to policy changes for flights.
2	Applicability	It refers to a field that specifies under what conditions and in what manner ticket changes can be implemented. ▸ BeforeDeparture: Refers to the change policies that can be applied before the flight departs. ▸ AfterDeparture: Specifies changes or penalties applicable after the flight has departed.
3	MinutesToDeparture	It expresses how much time (in minutes) is left until a flight's departure and specifies the impact of this time on ticket changes. It determines the permissible time frame for ticket changes and shows how long before the flight passengers can make changes to their tickets.
4	Currency	It indicates the currency in which the specified monetary values are denominated. This field specifies the currency used for calculating and displaying ticket prices, taxes, service fees, and other costs, such as TRY (Turkish Lira), USD (US Dollar), EUR (Euro), and GBP (British Pound).

5	IsChangeable	This field provides information on whether the ticket purchased by the passenger can be exchanged under certain conditions.
---	--------------	---

ShoppingFile/AirBookings/BrandedFares/BrandedFareItem/TotalFareInfo

Index	Field	Description
1	TotalFare	The TotalFare element represents the complete amount to be paid for a transaction or service. ▸ TotalFare=BaseFare+Taxes+ServiceFee
2	TotalTaxes	It includes the total amount of all taxes added to the passenger's ticket price.

ShoppingFile/AirBookings/BrandedFares/BrandedItem

Index	Field	Description
1	BrandCode	Is a code that represents the brand identity of a specific airline or flight. This code is used to distinguish between different fare levels or service packages. BrandCode helps passengers determine which services or benefits they will receive when making a reservation. Airlines typically offer various service packages under different brand identities, and these packages may include different features, benefits, or limitations.
2	BrandId	Identifier that represents the brand identity of a specific airline or scheduled flight. This identifier helps distinguish between different fare levels or service packages offered to passengers. For example, some airlines offer different classes and service packages such as economy, premium economy, and business class under different brand identities. BrandId is used to distinguish these different service packages and provide information about a specific class or service package.BrandId is an identifier that represents the brand identity of a specific airline or scheduled flight. This identifier helps distinguish between different fare levels or service packages offered to passengers. For example, some airlines offer different classes and service packages such as economy, premium economy, and business class under different brand identities. BrandId is used to distinguish these different service packages and provide information about a specific class or service package.
3	BrandName	BrandName refers to the name of a specific fare class or service package. BrandName is used to describe the different service levels or benefit packages offered by airline companies.

ShoppingFile/AirBookings/BrandedFares/BrandedItem/BrandedRule

Index	Field	Description
1	Application	That specifies the conditions and manner under which a particular fare class or service package is applied. This field explains the circumstances in which a specific fare or service package is valid and the restrictions that apply to it. ▸ N : Not Applicable ▸ F : Free ▸ C : Chargeable
2	DisplayType	DisplayType is a field that specifies how a particular fare or service package will be displayed to the user. DisplayType controls how this information is presented in the user

		interface.
3	RuleDescription	RuleDescription contains the description of the rules and conditions associated with a specific fare class or service package. This description aims to provide passengers with detailed information about a particular fare or service package. The RuleDescription field typically includes information such as: • Baggage Allowance: Free baggage allowance, carry-on baggage allowance, additional baggage fees, etc. • Change and Cancellation Policies: Reservation changes, cancellations, refund conditions, etc. • Services and Benefits: Included services (meal service, lounge access, extra legroom, etc.). • Other Conditions: Special situations, restrictions, additional fees, etc.
4	ServiceGroup	That categorizes the services and benefits associated with a specific fare class or service package. This field allows for the presentation of services and benefits offered to passengers under specific groups.

ShoppingFile/AirBookings/BrandedFares/FreeBaggageAllowance

ShoppingFile/AirBookings/BrandedFares/FreeBaggageAllowance/PaxBaggageAllowance

Index	Field	Description
1	Allowance	The "allowance" method is commonly used to access information about passengers' baggage entitlements, detailing how much luggage they can carry. This method may include specifics such as the maximum weight and dimensions allowed for both carry-on and checked baggage. Additionally, it can provide information on fees for excess baggage and regulations for special items, such as sports equipment or musical instruments.
2	Category	Specifies the type of baggage. ▸ Example: "Checked" indicates that the baggage is checked in at the airport and transported in the aircraft's cargo hold. ▸ Example: "Cabin" indicates that the baggage is carried into the cabin by the passenger and stored in the overhead bin or under the seat.
3	Type	Defines how the quantity of the baggage is measured. ▸ Example: "Weight" indicates that the baggage is measured based on its weight. ▸ Example: "Piece" indicates that the baggage is measured based on the number of pieces.
4	Unit	Indicates the unit of measurement for the baggage. ▸ Example: "K" represents "Kilograms". ▸ Example: "N" represents "Piece".

5	PaxType	It refers to the classification of passengers based on their age and status. It is important for ticket pricing, baggage allowance, service level, and other passenger services. The PaxType field helps airlines and travel agencies accurately classify passenger information and develop appropriate service and pricing strategies for each passenger type.
---	---------	---

ShoppingFile/AirBookings/Segments

Index	Field	Description
1	SegmentId	SegmentId is an identifier that represents the identity of a specific flight or flight segment. Particularly in cases of multi-stop or connecting flights, there are different SegmentIds for each flight section. This allows passengers and systems to understand which part of a particular flight is being referred to.
2	ArrivalDay	It indicates the day when the airplane reaches its destination. This information provides users with details about the flight's arrival date and day. For example, knowing on which day the flight will arrive is particularly important for long-haul flights across different time zones.
3	ArrivalTime	"ArrivalTime" refers to the arrival time of the flight. This field indicates the time when the flight lands at the designated destination airport.
4	BookingClass	"BookingClass" refers to the flight reservation class. This field indicates the class in which the passenger will travel during the flight and is usually represented by a single letter. For example: ► Economy ► Business ► First ► Comfort
5	DepartureDay	"DepartureDay" refers to the departure day of the flight. This field indicates the scheduled departure date of the flight and is usually presented in date format (e.g., YYYY-MM-DD).
6	DepartureTime	"DepartureTime" refers to the departure time of the flight. This field indicates the scheduled departure time of the flight and is usually presented in hour and minute format (e.g., HH).
7	DestinationCode	"DestinationCode" refers to the destination of the flight. This field indicates the code of the airport where the flight will arrive. Usually, three-letter airport codes determined by IATA (International Air Transport Association) are used. For example: JFK: New York John F. Kennedy Airport LHR: London Heathrow Airport CDG: Paris Charles de Gaulle Airport
8	Duration	"Duration" refers to the total duration of the flight. This field indicates the time elapsed from the departure point to the arrival point and is presented in minutes.
9	Equipment	Refers to the type or model of aircraft used for the flight. This field indicates which aircraft model will be used for a specific flight segment and is usually presented in three-letter codes determined by IATA.

Index	Field	Description
10	FareBasis	"FareBasis" refers to the basic fare code that determines the pricing rules and conditions of the ticket. This code defines the fare class applicable to a flight and the flexibility, change, and cancellation conditions of the ticket. It is usually presented as a combination of letters and numbers (e.g., Y26, QFL, or E14NR). The FareBasis field indicates the pricing rules and conditions under which the ticket is sold.
11	FareType	It refers to the fare type or tariff of the booked ticket. The 'FareType' indicates which fare category or class the ticket belongs to.
12	FlightNumber	"FlightNumber" refers to the number that identifies a specific flight. This number is uniquely assigned to each flight by the airline and is usually used in conjunction with the airline code. For example, "BA123" denotes a British Airways flight, while "TK270" refers to a Turkish Airlines flight.
13	MarketingAirline	Refers to the airline that markets and sells the flight. This airline is considered the brand that appears during the booking and ticketing process and is usually represented by a two-letter code assigned by IATA. For example: ▶ AA: American Airlines ▶ TK: Turkish Airlines ▶ BA: British Airways
14	OD_DestinationCode	"OD_DestinationCode" refers to the final destination of the trip.
15	OD_OriginCode	"OD_OriginCode" refers to the origin point of the flight.
16	OperatingAirline	"OperatingAirline" refers to the airline that actually operates the flight. This field may differ from the airline that markets or tickets the flight (MarketingAirline). The OperatingAirline field indicates the airline that physically operates the flight and is usually represented by a two-letter code assigned by IATA (International Air Transport Association).
17	OriginCode	"OriginCode" refers to the origin point of the flight. This field indicates the code of the airport where the flight begins and usually uses the three-letter airport codes determined by IATA (International Air Transport Association).
18	SelectedBrandedFareItemId	It is a unique identifier representing the selected branded fare type for a specific flight segment.
19	SequenceNo	"SequenceNo" refers to the number that indicates the order or position of a specific segment in a flight search. This field is used to denote the sequence of each segment in cases where there are multiple flight segments. For example, a flight route might consist of multiple segments as follows: ▶ Segment 1: Istanbul (IST) -> London (LHR) ▶ Segment 2: London (LHR) -> New York (JFK) In this example, the SequenceNo could be:

Index	Field	Description
		‣ Segment 1: SequenceNo = 1 ‣ Segment 2: SequenceNo = 2

ShoppingFile/BillingInformation

Index	Field	Description
1	Address_City	It represents the city information associated with the billing address.
2	Address_Detail	It is a field for detailed information related to the billing address.
3	Address_District	It represents the district/neighborhood information within the billing address.
4	Address_ZipCode	It represents the postal code associated with the billing address.
5	BillingName	It represents the name of the company or individual for the billing process.
6	CountryCode	It specifies the country code of the billing address.
7	IfCompany	It indicates whether the invoice is a corporate or individual invoice within the billing information. ‣ IfCompany = 1 → Indicates that the payer is a company. ‣ IfCompany = 0 or missing → Indicates that the payer is an individual customer.
8	TaxNo	It represents the tax identification number of the individual or company for billing purposes.
9	TaxOffice	It represents the tax office to which the individual or company is registered for billing purposes.

ShoppingFile/CustomerInfo

Index	Field	Description
1	BusinessId	It refers to the unique identifier of the customer making the reservation or transaction (usually a company or business). This parameter is typically an identification number used for corporate clients.
2	BusinessName	It refers to the name of the commercial entity or company that makes the reservation or handles the ticketing process. This parameter is used to identify the company responsible for the booking, especially in corporate or business-related travel.
3	Email	It refers to the email address of the customer who made the reservation or received information about the flight. This field is used to communicate with the customer, share reservation details, send e-tickets, and provide flight-related updates.

Index	Field	Description
4	Key	It refers to a unique identifier used to define or access customer information. This field is used to ensure that the information related to a customer or passenger is accurately processed and managed within the system.
5	Phone	It refers to the phone number of the customer or passenger. This field is used to communicate with the customer, provide updates during the reservation process, or contact them in case of emergencies.
6	Username	It refers to the username of the customer who made the reservation or transaction. This username is used to identify and manage the customer's information and account.

ShoppingFile/Passengers

ShoppingFile/Passengers/Passenger

Index	Field	Description
1	BirthDate	It refers to the passenger's date of birth. The 'BirthDate' parameter should be in the correct format, which is YYYY-MM-DD.
2	CitizenNo	For domestic flights within Turkey, Turkish citizens are required to provide their National ID number, while non-Turkish citizens must enter 11 zeros (00000000000).
3	Email	It refers to the email address of the customer who made the reservation or received information about the flight. This field is used to communicate with the customer, share reservation details, send e-tickets, and provide flight-related updates.
4	FirstName	The 'FirstName' parameter refers to the passenger's First Name and the Middle Name also(if any). If there are more than one name,then all the names need to be written without any blank between them. <u>Wrong Spelling:</u> <FirstName>JOHN SPENCER</FirstName> <u>Correct Spelling:</u> <FirstName>JOHNSPENCER</FirstName>
5	Gender	The 'Gender' parameter refers to the passenger's gender. This parameter is typically indicated as 'M' (Male) or 'F' (Female).
6	IfContact	This field typically indicates whether a passenger is designated as the contact person in the passenger information. Contact Person: Determines whether a person in the passenger group is marked as the primary contact. For example, in a reservation with multiple passengers, the IfContact value is usually set as true/false: ▸ true: This passenger is the primary contact person for the reservation. ▸ false: This passenger is not the contact person.
7	LastName	The 'LastName' parameter refers to the passenger's last name.

Index	Field	Description
8	Nationality	The 'Nationality' parameter refers to the passenger's nationality or citizenship information. This parameter is typically entered using the two-letter ISO country code (e.g., 'TR' for Turkey, 'US' for the United States).
9	PassportCountry	The 'PassportCountry' parameter refers to the country that issued the passenger's passport. This parameter is typically specified in country code format (e.g., 'TR' for Turkey, 'US' for the United States using ISO 3166-1 alpha-2 country codes) and is used to validate passport information.
10	PassportNo	It refers to the passenger's passport number. This parameter is used to verify the passenger's identity for international flights.
11	PassportValidDate	The 'PassportValidDate' parameter indicates the expiration date of the passenger's passport. This date is typically provided in the YYYY-MM-DD format and shows until which date the passport is valid.
12	Phone	The 'Phone' parameter refers to the passenger's phone number.
13	Type	The 'Type' parameter specifies the passenger's ticketing or reservation type. This parameter is typically used to define the passenger's age group or fare class. Standard 'Type' values used in the aviation industry include: 'ADT' (Adult): Adult passenger (typically 12 years and older) 'CHD' (Child): Child passenger (between 2-11 years old) 'INF' (Infant): Infant passenger (0-2 years old, traveling on lap)
14	WheelChairServiceType	It is a parameter that indicates whether the passenger requires wheelchair service: 0 → No wheelchair service requested (default). 1 → Wheelchair service requested at the airport.

ShoppingFile/Passengers/Passenger/PaxReferences

ShoppingFile/Passengers/Passenger/PaxReferencesForwardPaxReference

Index	Field	Description
1	ProductId	It refers to the unique identifier of a specific product or service that has been purchased or priced. This identifier is used to track and manage each product or service within the system.
2	ProductItemId	This element contains a unique identifier (UUID) corresponding to a specific product item within the Trevoo.WS.Entities.Shopping schema. For example, the value 289af8a3-554b-469c-b28a-7ace0feb5487 uniquely identifies the product item associated with this XML entity.

ShoppingFile/Payments

ShoppingFile/Payments/Payment

Index	Field	Description
1	CC_BankName	The name of the bank to which the credit card belongs.

2	CC_BonusInstallmentCount	The number of installments specifically available for bonus credit cards.
3	CC_CardHolder	The name of the credit cardholder.
4	CC_CardNumber	The masked credit card number (typically showing only the last four digits).
5	CC_InstallmentCount	The total number of installments for the payment made with the credit card.
6	CC_MonthlyPayment	The monthly payment amount for an installment-based credit card transaction.
7	CurrentHandling_FinalizedDate	The date and time when the payment was successfully completed.
8	Id	A unique identifier assigned to the payment transaction.
9	InterestAmount	The interest amount applied to installment transactions.
10	LastApprovedCommand	The last approved transaction command.
11	LastCommand	The last submitted payment command.
12	OriginalAmount	The original payment amount before any discounts or currency conversions.
13	PaymentAmount	The actual payment amount.
14	PaymentConfirmedAmount	The finalized amount after the payment has been confirmed.
15	PaymentCurrency	The currency in which the payment was made (e.g., "USD", "EUR").
16	PaymentType	The payment method (e.g., "CreditCard").
17	SellingCurrency	The currency in which the sale was conducted (e.g., "TRY", "USD").
18	T_Credit_TransactionDate	The date when the credit transaction was executed.
19	T_PostAuth_TransactionDate	The date when the post-authorization (payment finalization) transaction was performed.
20	T_PreAuth_TransactionDate	The date when the pre-authorization (payment hold) transaction was initiated.
21	TotalAmount	The total amount to be paid, including interest if applicable.

ShoppingFile/PriceSummary

Index	Field	Description
1	GrandTotal	It refers to the total final amount the passenger is required to pay for a reservation.

ShoppingFile/PriceSummary/PriceItems

ShoppingFile/PriceSummary/PriceItems/PriceItem

Index	Field	Description
1	InCart	It indicates whether the relevant fee or ticket is currently in the shopping cart. This parameter is used to determine the stage of the transaction process and the status of the ticket in the reservation workflow. ► True

Index	Field	Description
		▸ False
2	ProductId	It refers to the unique identifier of a specific product or service that has been purchased or priced. This identifier is used to track and manage each product or service within the system.
3	ProductType	It refers to the type of the service or product being priced.
4	Total	It refers to the total amount to be paid for the reservation or ticket.