Table 1: General protocol specification

Start Command [0xFE]	Command type [0x11 – 0x90]	Value	
1 byte	1 byte	4 or 24 bytes	

Table 2: Protocol description

Command	Command Types	Description
ranges		
	0x11	Get clothes from particular scanner number
	0x12	Get bin number from particular tag
	0x13	
	0x14	
	•••	
	0x70	Create new file
General	0x71	Flush existing file
commands	0x72	Remove file
	•••	
	0x77	File transferring
	0x90	
	0x00	
	0x01	
	•••	
Reserved	0x91	
commands	•••	
	0xFE	Start command, definition of protocol. Other protocols can start with other
		reserved commands (here just idea)
İ	0xFF	

1. 0x11

Example 1: Get clothes from particular scanner number

Method: char[]:= getClothes(scannerNumber)

Table 3: Command packet (from client to server)

	Protocol type	Command type	Value
Value	0xFE	0x11	-
Bytes	1	1	4

Table 4: Command packet (from server to client)

	Protocol type	Command type	Number of values	Value	Value	Value
Value	0xFE	0x11	-	937021100000001A000006A9*	937021100000001A000006A6*	-
Bytes	1	1	4	24	24	

2. 0x12

Example 2: Get bin number from particular tag

Method: int:=getBin(tagID)

Table 5: Command packet (from client to server)

Table .	Table 5. Command packet (from cheft to server)								
	Protocol type	Command type	Value						
Value	0xFE	0x12	937021100000001A000006A9*						
Bytes	1	1	24						

Table 6: Command packet (from server to client)

	Protocol type	Command type	Value	
Value	0xFE	0x12	=	
Bytes	1	1	4	

Notes: * Ta

3. **0x77** - File transferring

3.1. 0x70 - Create new file

	Protocol type	Command type	Command type	Size	Data	Checksum
Bytes	1	1	2	4	1012	4

Example

			1		1	
	Protocol type	Command type	Command type	Size	Data	Checksum
Value	0xFE	0x77	0x70	21	Data	-

Data: "C:\hereMyNewFile.bmp"

3.2. 0x71 - Flush existing file

	Protocol type	Command type	Command type	Size	Data	Checksum
Bytes	1	1	2	4	1012	4

Example

	Protocol type	Command type	Command type	Size	Data	Checksum
Value	0xFE	0x77	0x71	1011	Data	-

$3.3. \quad 0x72 - Remove file$

	Protocol type	Command type	Command type	Size	Data	Checksum
Bytes	1	1	2	4	1012	4

Example

	Protocol type	Command type	Command type	Size	Data	Checksum
Value	0xFE	0x77	0x72	21	Data	-

Data: "C:\\hereMyNewFile.bmp"

^{*} Tag ID format example