Recognize the files and records

SYNTHETIC EXAMPLES • Independent panels, not one linked biological case

Samples → patients

sample_id	patient_id	input
S1	P1	S1.vcf
S2	P1	S2.vcf
S3	P2	S3.vcf

Patient HLA (you supply it)

```
P1: HLA-A*02:01, HLA-B*07:02
P2: HLA-A*03:01
Class II: explicit alpha~beta pair
HLA-DRA*01:01~HLA-DRB1*15:01
```

S1.vcf — one sample column, fields separated by tabs

```
##fileformat=VCFv4.2
##FORMAT=<ID=GT,Number=1,Type=String,Description="Genotype">
#CHROM  POS     ID      REF     ALT     QUAL    FILTER  INFO    FORMAT  S1
chr1    4       .       G       A       .       PASS    .       GT      0/1
```

External reference files

```
genome.fa + genome.fa.fai
gencode.v50.*.gtf / *.fa
+ selenocysteine metadata
MANE.GRCh38.v1.5.*.txt / *.gtf
```

GRCh38.p14 • GENCODE 50 • MANE 1.5

Optional observations

RNA counts / expression • CCF • MS
Supply their supported tables separately.
No file ≠ a measured negative.

Official Quick Start outputs

Event	`chr1:4 G>A`
Origin	transcript TA → translation path
Peptide	`KPK (3-aa technical window)`
Candidate	`KPK + HLA-A*02:01`
Result	`NOT_RUN / NOT_GRADED`
Explain	candidate → origins → events

Tiny demo windows and reference bytes are technical fixtures, not human-analysis settings.