
Data Structures

BS (CS) _Fall_2025

Lab_05 Task



Learning Objectives:

1. Singly Linked List

Task 1: Generic Linked List Class using Templates in C++

Class Requirements

You need to design a singly linked list class using templates.

It should have:

- **Node<T>** class: contains
 - T data
 - Node<T>* next
- **LinkedList<T>** class: contains
 - Node<T>* head (pointer to first node)
 - int counter (tracks number of nodes)

Operations to Implement

Insertion Functions

- **insertAtHead(T item)**
Insert a new node at the start of the list.
- **insertAtTail(T item)**
Insert a new node at the end of the list.
- **insertAfter(T itemToInsert, T existingItem)**
Find existingItem and insert itemToInsert after it.
- **insertBefore(T itemToInsert, T existingItem)**
Find existingItem and insert itemToInsert before it.

Removal Functions

- **remove(T item)**
Remove the node containing the given item (if found).
- **removeBefore(T item)**
Find item and remove the node just before it.
Example: {1 → 2 → 3 → 4}, removeBefore(3) → {1 → 3 → 4}
- **removeAfter(T item)**
Find item and remove the node just after it.
Example: {1 → 2 → 3 → 4 → 5}, removeAfter(3) → {1 → 2 → 3 → 5}

Utility Functions

- **isEmpty()**
Returns true if the list has no elements.
- **search(T item)**
Returns the pointer to node (or index-like position) if found, otherwise nullptr / -1.
- **print()**
Prints all elements of the list.

- **reverse()**
Reverses the list in-place.

Gtest :

```
// ----- INSERTION TESTS -----
TEST(LinkedListTest, InsertAtHeadEmpty) {
    LinkedList<int> list;
    list.insertAtHead(10);
    EXPECT_FALSE(list.isEmpty());
    EXPECT_EQ(list.search(10)->data, 10);
}

TEST(LinkedListTest, InsertAtHeadNonEmpty) {
    LinkedList<int> list;
    list.insertAtHead(10);
    list.insertAtHead(5);
    EXPECT_EQ(list.search(5)->data, 5);
}

TEST(LinkedListTest, InsertAtTailEmpty) {
    LinkedList<int> list;
    list.insertAtTail(20);
    EXPECT_EQ(list.search(20)->data, 20);
}

TEST(LinkedListTest, InsertAtTailNonEmpty) {
    LinkedList<int> list;
    list.insertAtHead(10);
    list.insertAtTail(30);
    EXPECT_EQ(list.search(30)->data, 30);
}

TEST(LinkedListTest, InsertAfterMiddle) {
    LinkedList<int> list;
    list.insertAtTail(5);
    list.insertAtTail(10);
    list.insertAtTail(30);
    list.insertAfter(25, 10);
    EXPECT_NE(list.search(25), nullptr);
}

TEST(LinkedListTest, InsertAfterNonExistent) {
    LinkedList<int> list;
```

```

    list.insertAtTail(5);
    list.insertAfter(100, 50); // should not insert
    EXPECT_EQ(list.search(100), nullptr);
}

TEST(LinkedListTest, InsertBeforeHead) {
    LinkedList<int> list;
    list.insertAtTail(5);
    list.insertBefore(1, 5);
    EXPECT_NE(list.search(1), nullptr);
}

TEST(LinkedListTest, InsertBeforeNonExistent) {
    LinkedList<int> list;
    list.insertAtTail(10);
    list.insertBefore(99, 50);
    EXPECT_EQ(list.search(99), nullptr);
}

// ----- REMOVAL TESTS -----
TEST(LinkedListTest, RemoveMiddle) {
    LinkedList<int> list;
    list.insertAtTail(1);
    list.insertAtTail(5);
    list.insertAtTail(10);
    list.remove(5);
    EXPECT_EQ(list.search(5), nullptr);
}

TEST(LinkedListTest, RemoveHead) {
    LinkedList<int> list;
    list.insertAtTail(5);
    list.insertAtTail(10);
    list.remove(5);
    EXPECT_EQ(list.search(5), nullptr);
}

TEST(LinkedListTest, RemoveTail) {
    LinkedList<int> list;
    list.insertAtTail(5);
    list.insertAtTail(10);
    list.remove(10);
    EXPECT_EQ(list.search(10), nullptr);
}

```

```

TEST(LinkedListTest, RemoveNonExistent) {
    LinkedList<int> list;
    list.insertAtTail(5);
    list.remove(99);
    EXPECT_NE(list.search(5), nullptr); // unchanged
}

TEST(LinkedListTest, RemoveBeforeMiddle) {
    LinkedList<int> list;
    list.insertAtTail(1);
    list.insertAtTail(2);
    list.insertAtTail(3);
    list.insertAtTail(4);
    list.removeBefore(3); // removes 2
    EXPECT_EQ(list.search(2), nullptr);
}

TEST(LinkedListTest, RemoveBeforeHeadNoChange) {
    LinkedList<int> list;
    list.insertAtTail(1);
    list.insertAtTail(2);
    list.removeBefore(1); // nothing happens
    EXPECT_NE(list.search(1), nullptr);
}

TEST(LinkedListTest, RemoveAfterMiddle) {
    LinkedList<int> list;
    list.insertAtTail(1);
    list.insertAtTail(2);
    list.insertAtTail(3);
    list.insertAtTail(4);
    list.removeAfter(2); // removes 3
    EXPECT_EQ(list.search(3), nullptr);
}

TEST(LinkedListTest, RemoveAfterTailNoChange) {
    LinkedList<int> list;
    list.insertAtTail(1);
    list.insertAtTail(2);
    list.removeAfter(2); // nothing happens
    EXPECT_NE(list.search(2), nullptr);
}

// ----- UTILITY TESTS -----
TEST(LinkedListTest, IsEmpty) {

```

```

    LinkedList<int> list;
    EXPECT_TRUE(list.isEmpty());
    list.insertAtHead(10);
    EXPECT_FALSE(list.isEmpty());
}

TEST(LinkedListTest, SearchFound) {
    LinkedList<int> list;
    list.insertAtTail(5);
    EXPECT_NE(list.search(5), nullptr);
}

TEST(LinkedListTest, SearchNotFound) {
    LinkedList<int> list;
    list.insertAtTail(5);
    EXPECT_EQ(list.search(50), nullptr);
}

TEST(LinkedListTest, ReverseList) {
    LinkedList<int> list;
    for (int i = 1; i <= 4; i++) list.insertAtTail(i);
    list.reverse(); // should be 4 → 3 → 2 → 1
    EXPECT_NE(list.search(4), nullptr);
    EXPECT_NE(list.search(1), nullptr);
}

TEST(LinkedListTest, ReverseEmpty) {
    LinkedList<int> list;
    list.reverse(); // should not crash
    EXPECT_TRUE(list.isEmpty());
}

TEST(LinkedListTest, ReverseSingle) {
    LinkedList<int> list;
    list.insertAtTail(10);
    list.reverse();
    EXPECT_NE(list.search(10), nullptr);
}

// ----- EDGE & STRESS TEST -----
TEST(LinkedListTest, LargeInsertAndRemove) {
    LinkedList<int> list;
    for (int i = 0; i < 1000; i++) list.insertAtTail(i);
    EXPECT_EQ(list.search(500)->data, 500);
    list.remove(500);
}

```

```
EXPECT_EQ(list.search(500), nullptr);  
}
```

Task 2: Remove Duplicates from Unsorted Linked List

Problem Statement

A linked list may contain duplicate values at different positions. Your task is to extend your singly linked list class by implementing a function:

```
void removeDuplicates();
```

The function should remove all duplicate nodes so that only the first occurrence of each element remains in the list.

Input/Output Example

- **Input:**
List = {1 , 3 , 2 , 3 , 4 , 2}
- **Output after function call:**
List = {1 , 3 , 2 , 4}

Requirements

- The operation should be performed in-place (no extra arrays/vectors allowed).
- You may use nested traversal (for each node, check duplicates ahead and remove them).

Gtest :

```
TEST(RemoveDuplicatesTest, NoDuplicates) {  
    LinkedList<int> list;  
    list.insertAtTail(1);  
    list.insertAtTail(2);  
    list.insertAtTail(3);  
  
    list.removeDuplicates();  
  
    Node<int>* curr = list.head;  
    EXPECT_EQ(curr->data, 1); curr = curr->next;  
    EXPECT_EQ(curr->data, 2); curr = curr->next;  
    EXPECT_EQ(curr->data, 3); curr = curr->next;  
    EXPECT_EQ(curr, nullptr); // list ends  
}  
  
TEST(RemoveDuplicatesTest, WithDuplicates) {  
    LinkedList<int> list;
```

```

list.insertAtTail(1);
list.insertAtTail(3);
list.insertAtTail(2);
list.insertAtTail(3);
list.insertAtTail(4);
list.insertAtTail(2);

list.removeDuplicates();

Node<int>* curr = list.head;
EXPECT_EQ(curr->data, 1); curr = curr->next;
EXPECT_EQ(curr->data, 3); curr = curr->next;
EXPECT_EQ(curr->data, 2); curr = curr->next;
EXPECT_EQ(curr->data, 4); curr = curr->next;
EXPECT_EQ(curr, nullptr);
}

TEST(RemoveDuplicatesTest, AllSameValues) {
    LinkedList<int> list;
    list.insertAtTail(5);
    list.insertAtTail(5);
    list.insertAtTail(5);
    list.insertAtTail(5);

    list.removeDuplicates();

    Node<int>* curr = list.head;
    EXPECT_EQ(curr->data, 5);
    EXPECT_EQ(curr->next, nullptr); // only one node remains
}

TEST(RemoveDuplicatesTest, EmptyList) {
    LinkedList<int> list;

    list.removeDuplicates();

    EXPECT_TRUE(list.isEmpty());
}

TEST(RemoveDuplicatesTest, SingleElement) {
    LinkedList<int> list;
    list.insertAtTail(42);

    list.removeDuplicates();

```

```
Node<int>* curr = list.head;  
EXPECT_EQ(curr->data, 42);  
EXPECT_EQ(curr->next, nullptr);  
}
```