

Hashdist – A tool for building and managing your scientific software distribution(s)

Chris Kees (US Army ERDC) and the HashDist Developers

Coastal and Hydraulics Laboratory
U.S. Army ERDC

Sage Days 58, June 16-20, 2014

<http://github.com/hashdist>

Acknowledgements

- ▶ Dag Sverre Seljebotn, Ondřej Čertík, Aron Ahmadia, Robert Maynard, Jimmy Tang, Lane Wittgen,...
- ▶ Dag Sverre's work for Simula Innovation was funded by a grant from the International Research Office, US Army Engineer Research and Development Center (BAA contract W911NF-12-1-0604)
- ▶ Ondřej's work for UT was funded by the US Army Engineer Research and Development Center (BAA Contract BAA12-4941)
- ▶ Part of Aron's work was supported by the CHL Research Participation Program administered by the Oak Ridge Institute for Science and Education

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.
- ▶ Problem: My software needs libfoo, which you don't have.

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.
- ▶ Problem: My software needs libfoo, which you don't have.
- ▶ Problem: My software needs libfoo, which you DO have in a really weird location.

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.
- ▶ Problem: My software needs libfoo, which you don't have.
- ▶ Problem: My software needs libfoo, which you DO have in a really weird location.
- ▶ Problem: I built my software on an old Linux machine, you need it on OS X.

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.
- ▶ Problem: My software needs libfoo, which you don't have.
- ▶ Problem: My software needs libfoo, which you DO have in a really weird location.
- ▶ Problem: I built my software on an old Linux machine, you need it on OS X.
- ▶ Problem: You need to run my software on an HPC machine.

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.
- ▶ Problem: My software needs libfoo, which you don't have.
- ▶ Problem: My software needs libfoo, which you DO have in a really weird location.
- ▶ Problem: I built my software on an old Linux machine, you need it on OS X.
- ▶ Problem: You need to run my software on an HPC machine.
- ▶ Problem: You don't have root access to your machine.

What's the problem?

- ▶ I wrote some math software and I want YOU to use it.
- ▶ Problem: My software needs libfoo, which you don't have.
- ▶ Problem: My software needs libfoo, which you DO have in a really weird location.
- ▶ Problem: I built my software on an old Linux machine, you need it on OS X.
- ▶ Problem: You need to run my software on an HPC machine.
- ▶ Problem: You don't have root access to your machine.
- ▶ Solution: I need to add my software to a distribution that can handle all these cases.

Rest of the world in 2013, 2014?,...

- ▶ Debian/RedHat distributions (Linux only)

Rest of the world in 2013, 2014?,...

- ▶ Debian/RedHat distributions (Linux only)
- ▶ App store (Mac only)

Rest of the world in 2013, 2014?,...

- ▶ Debian/RedHat distributions (Linux only)
- ▶ App store (Mac only)
- ▶ Web apps (still needs good distribution)

Rest of the world in 2013, 2014?,...

- ▶ Debian/RedHat distributions (Linux only)
- ▶ App store (Mac only)
- ▶ Web apps (still needs good distribution)
- ▶ MATLAB environment (a kind of distribution)

Rest of the world in 2013, 2014?,...

- ▶ Debian/RedHat distributions (Linux only)
- ▶ App store (Mac only)
- ▶ Web apps (still needs good distribution)
- ▶ MATLAB environment (a kind of distribution)
- ▶ Modules on HPC machines.

Background

- ▶ Proteus toolkit for PDEs was building its own stack with custom scripts, makefiles, and config files
- ▶ FENICS toolkit for PDEs had its own system (Dorsal)
- ▶ Various other DoD groups had their own Python distributions
- ▶ Could possibly have added to Sage or Enthought distributions but would require many new packages and modifications to reuse “host” packages (e.g. vendor MPI)

Requirments for new system

- ▶ Must support mixing source and “host” packages (e.g. vendor MPI)
- ▶ Must support version control and reproducibility across users
- ▶ Must support many kinds of packages (Python, C++, Fortran,...)
- ▶ Must support needs of developers (building from Git repos, trying new packages,...)

Scientific code

- ▶ Dependencies are bad: Hard to build, move between clusters

Scientific code

- ▶ Dependencies are bad: Hard to build, move between clusters
- ▶ Dependencies are good: Can build on works of others

Scientific code

- ▶ Dependencies are bad: Hard to build, move between clusters
- ▶ Dependencies are good: Can build on works of others
- ▶ Often happens: “Large frameworks” bundling things together

Scientific code

- ▶ Dependencies are bad: Hard to build, move between clusters
- ▶ Dependencies are good: Can build on works of others
- ▶ Often happens: “Large frameworks” bundling things together
 - ▶ PETSc and Trilinos for solving PDEs

Scientific code

- ▶ Dependencies are bad: Hard to build, move between clusters
- ▶ Dependencies are good: Can build on works of others
- ▶ Often happens: “Large frameworks” bundling things together
 - ▶ PETSc and Trilinos for solving PDEs
 - ▶ As soon as you want to push boundaries there's a lot of dirty work ahead

What makes scientific codes so special?

- ▶ No root access

What makes scientific codes so special?

- ▶ No root access
- ▶ Sometimes you **need** the very latest version

What makes scientific codes so special?

- ▶ No root access
- ▶ Sometimes you **need** the very latest version
- ▶ Fortran/C++ instead of C/Java/.NET

What makes scientific codes so special?


- ▶ No root access
- ▶ Sometimes you **need** the very latest version
- ▶ Fortran/C++ instead of C/Java/.NET
- ▶ Intersection of “need speed” and “do not pay dedicated application sysadmins”

Combinatorial explosion

```
/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so
```

Combinatorial explosion

```
/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so
```



× LAPACK × FFT library × IDL/Python version...

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only
 - ▶ Deals “not well enough” with combinatorial explosion

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only
 - ▶ Deals “not well enough” with combinatorial explosion
- ▶ HPC environment modules

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only
 - ▶ Deals “not well enough” with combinatorial explosion
- ▶ HPC environment modules
 - ▶ The sysadmins hate them

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only
 - ▶ Deals “not well enough” with combinatorial explosion
- ▶ HPC environment modules
 - ▶ The sysadmins hate them
 - ▶ The users need newer/their own libraries

Current solutions

- ▶ Build yourself from source

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work, some packages are very difficult to build...

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work, some packages are very difficult to build...
- ▶ Aha! Make a script to build from source...
 - ▶ Simula: dorsal
 - ▶ 5 different within DoD (incl. python-hpcmp)
 - ▶ Sage
 - ▶ Bilder (<http://sourceforge.net/p/bilder/wiki/Home/>)
 - ▶ Lots of others ("everybody" does it)

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work, some packages are very difficult to build...
- ▶ Aha! Make a script to build from source...
 - ▶ Simula: dorsal
 - ▶ 5 different within DoD (incl. python-hpcmp)
 - ▶ Sage
 - ▶ Bilder (<http://sourceforge.net/p/bilder/wiki/Home/>)
 - ▶ Lots of others ("everybody" does it)
- ▶ Easy to do oneself \Rightarrow difficult for one to get momentum

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work, some packages are very difficult to build...
- ▶ Aha! Make a script to build from source...
 - ▶ Simula: dorsal
 - ▶ 5 different within DoD (incl. python-hpcmp)
 - ▶ Sage
 - ▶ Bilder (<http://sourceforge.net/p/bilder/wiki/Home/>)
 - ▶ Lots of others ("everybody" does it)
- ▶ Easy to do oneself \Rightarrow difficult for one to get momentum
- ▶ The details are different for everybody

Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal are all about curated software stacks

Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal are all about curated software stacks
- ▶ Perhaps you want 60% curated, 20% bleeding edge or manually tweaked, 20% your own code...

Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal are all about curated software stacks
- ▶ Perhaps you want 60% curated, 20% bleeding edge or manually tweaked, 20% your own code...
- ▶ The community using and supporting a distribution is as important as most of the other details.

HashDist Theory

Stateful vs. Functional

- ▶ Our software environment is usually defined by the STATE of the file system

Stateful vs. Functional

- ▶ Our software environment is usually defined by the STATE of the file system
- ▶ If I change the source or options for libfoo, then I rebuild it in `/usr/lib/libfoo.so`.

Stateful vs. Functional

- ▶ Our software environment is usually defined by the STATE of the file system
- ▶ If I change the source or options for libfoo, then I rebuild it in `/usr/lib/libfoo.so`.
- ▶ Stateful systems are fine when you control everything (a Linux distribution, Sage distribution)

Stateful vs. Functional

- ▶ Our software environment is usually defined by the STATE of the file system
- ▶ If I change the source or options for libfoo, then I rebuild it in `/usr/lib/libfoo.so`.
- ▶ Stateful systems are fine when you control everything (a Linux distribution, Sage distribution)
- ▶ An alternative view is to think of the build stage as a mapping from the input domain (input space = dependency states \oplus source code states \oplus option states) to a range containing binary “artifacts” (output space of “coordinates” of unique libfoo.a’s).

Stateful vs. Functional

- ▶ Our software environment is usually defined by the STATE of the file system
- ▶ If I change the source or options for libfoo, then I rebuild it in `/usr/lib/libfoo.so`.
- ▶ Stateful systems are fine when you control everything (a Linux distribution, Sage distribution)
- ▶ An alternative view is to think of the build stage as a mapping from the input domain (input space = dependency states \oplus source code states \oplus option states) to a range containing binary “artifacts” (output space of “coordinates” of unique libfoo.a’s).
- ▶ Main idea: create build artifact coordinates by hashing the input state and store the build artifacts in a “database” keyed on those hashes.

Stateful vs. Functional

- ▶ Our software environment is usually defined by the STATE of the file system
- ▶ If I change the source or options for libfoo, then I rebuild it in `/usr/lib/libfoo.so`.
- ▶ Stateful systems are fine when you control everything (a Linux distribution, Sage distribution)
- ▶ An alternative view is to think of the build stage as a mapping from the input domain (input space = dependency states \oplus source code states \oplus option states) to a range containing binary “artifacts” (output space of “coordinates” of unique libfoo.a’s).
- ▶ Main idea: create build artifact coordinates by hashing the input state and store the build artifacts in a “database” keyed on those hashes.
- ▶ Using the hash idea we can treat package building in a functional manner rather than a stateful manner (idea comes from Eelco Doltstra/Nix)

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3
- ▶ Mathematical research topic to make h such that no information about input is revealed

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3
- ▶ Mathematical research topic to make h such that no information about input is revealed

$h(\text{'The dark fox'}) = h(546865206461726b20666f78 \text{ hex})$
 $= b6589fc6ab0dc82cf12099d1c2d40ab994e8410c \text{ hex}$

Cryptographic/secure hashing


- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3
- ▶ Mathematical research topic to make h such that no information about input is revealed

$h(\text{'The dark fog'}) = h(546865206461726b20666f67 \text{ hex})$
 $= \text{da4b9237baccdf19c0760cab7aec4a8359010b0 hex}$

Example: Git

```
$ (cd code/hashdist/.git/objects; find)
./59/5a2f8e3890d0ece24514f3e32ae874f1f03ac2
./2f/780151688e1f122a5b9072d42009c80c36140c
./2f/4b2eef40b51bc2d46027d1864653b37dd05f8f
./2f/237d74e3f81f498212629ac0b96bedac4b0b36
./2f/df799c54fed6fe96a91e1d5f1593996228ebc
./2f/27bd4efa5f8521fb98eb82181a67aae97b7f1a
./2f/3fedf882f1b28905199961356f4e00281ddf76
```

Example: Git



[Explore](#) [Gist](#) [Blog](#) [Help](#)[dagss](#)[cython / cython](#)[Pull Request](#)[Unwatch](#)[Unstar](#)

310

[Fork](#)

113

[Code](#)[Network](#)[Pull Requests](#) 14[Wiki](#)[Graphs](#)[Settings](#)[Graph](#)[Members](#)


The cython network graph

Keyboard shortcuts available

All branches in the network using cython/cython as the reference point. [Read our blog post about how it works.](#)

[Show Help](#)

Last updated: 12 minutes ago



Hashdist

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Even

`h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_abel_debug`
`incomplete`

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Even

`h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_abel_debug`
incomplete

- ▶ Abel is new and small; US Army clusters have 20-30 versions of every package.

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Even

`h5py-hdf5-1.8.9_pgi-python2.7-numpy1.6.3-abel-debug`
incomplete

- ▶ Abel is new and small; US Army clusters have 20-30 versions of every package.

- ▶ Hashdist:

`~/hashdist/bld/hdf5/pe7156vsagg43`

`~/hashdist/bld/hdf5/tkiwsppxzc3r`

(really `hdf5/tkiwsppxzc3ro3q7pyjjxq45jgh3wwcd`)

Step 1: Hash the build

Internal protocol!

```
{
  "build" : {
    "commands" : [
      {
        "cmd" : [
          "$BASH",
          "_hashdist/build.sh"
        ]
      },
    ],
    "import" : [
      {
        "id" : "zlib/3vq2jgzdjakdhpzvpvtrbzbcrtg6etrh",
        "ref" : "ZLIB"
      }
    ]
  },
  "name" : "hdf5",
  "sources" : [
    {
      "key" : "tar.bz2:l2q3vax4o42q5zriw6k243w6ax7ov4og",
```

Step 1: Hash the build

Internal protocol!

```
{
  "build" : {
    "commands" : [
      {
        "cmd" : [
          "$BASH",
          "_hashdist/build.sh"
        ]
      },
    ],
    "import" : [
      {
        "id" : "zlib/3vq2jgzdjakdhpzvpvtrbzbcrtg6etrh",
        "ref" : "ZLIB"
      }
    ]
  },
  "name" : "hdf5",
  "sources" : [
    {
      "key" : "tar.bz2:l2q3vax4o42q5zriw6k243w6ax7ov4og",
```

Step 1: Hash the build

Internal protocol!

```
{
  "build" : {
    "commands" : [
      {
        "cmd" : [
          "$BASH",
          "_hashdist/build.sh"
        ]
      },
    ],
    "import" : [
      {
        "id" : "zlib/3vq2jgzdjakdhpzvpvtrbzbcrtg6etrh",
        "ref" : "ZLIB"
      }
    ]
  },
  "name" : "hdf5",
  "sources" : [
    {
      "key" : "tar.bz2:l2q3vax4o42q5zriw6k243w6ax7ov4og",
```

Step 2: Every build installs to separate location

Same as with the “module load” system:

```
$ echo bld/*/bld/adh/hwz2wmrcnbj7 bld/adh/lvpjelejrlldo  
bld/bzip2/zuo2tlurm7ez bld/cython/bidpqe4yx6gl bld/cython/pl  
bld/cython/xoju62amg7pm bld/daetk/dpoolktbk3si  
bld/docutils/ckp3lhso6vek bld/docutils/uv2667zawv7v  
bld/docutils/yekwczohjna7
```

```
$ ls bld/zmq/x7ogmtwtkola/lib  
pkgconfig libzmq.a libzmq.so libzmq.so.3 libzmq.so.3.0.0
```

Step 2: Every build installs to separate location

Unlike “module load” we don’t need LD_LIBRARY_PATH:

```
$ ldd bld/hdf5/tkiwsppxz3r/lib/libhdf5.so
linux-vdso.so.1 => (0x00007fffe21fe000)
libpthread.so.0 => /lib/x86_64-linux-gnu/libpthread.so.0 (0x00007f9d0cb8f000)
libz.so.1 => /home/cekees/.hashdist/bld/zlib/3vq2jgzdjakd/libz.so.1 (0x00007f9d0cb8f000)
libdl.so.2 => /lib/x86_64-linux-gnu/libdl.so.2 (0x00007f9d0cb8f000)
libm.so.6 => /lib/x86_64-linux-gnu/libm.so.6 (0x00007f9d0cb8f000)
libmpich.so.10 => /home/cekees/.hashdist/bld/mpich/4ztabf2u23u2/libmpich.so.10 (0x00007f9d0cb8f000)
libc.so.6 => /lib/x86_64-linux-gnu/libc.so.6 (0x00007f9d0cb8f000)
/lib64/ld-linux-x86-64.so.2 (0x00007f9d0d9dc000)
libmpl.so.1 => /home/cekees/.hashdist/bld/mpich/4ztabf2u23u2/libmpl.so.1 (0x00007f9d0cb8f000)
librt.so.1 => /lib/x86_64-linux-gnu/librt.so.1 (0x00007f9d0cb8f000)
libgcc_s.so.1 => /lib/x86_64-linux-gnu/libgcc_s.so.1 (0x00007f9d0cb8f000)
```

Step 3: Make a profile with links

```
$ ls -la bld/profile/ycz6e4bztfgd/bin
bunzip2 -> ../../../../bzip2/zuo2tlurm7ez/bin/bunzip2
bzipcat -> ../../../../bzip2/zuo2tlurm7ez/bin/bzipcat
bzipcmp -> ../../../../bzip2/zuo2tlurm7ez/bin/bzipcmp
...
```


Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit build # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit build # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`
- ▶ `~/mystack $ hit build # instant`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit build # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`
- ▶ `~/mystack $ hit build # instant`
- ▶ `~/mystack $ git fetch from-someone-else`
`~/mystack $ git checkout someone-elses-branch`
`~/mystack $ hit build # pause for extra builds`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.3`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit build # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`
- ▶ `~/mystack $ hit build # instant`
- ▶ `~/mystack $ git fetch from-someone-else`
`~/mystack $ git checkout someone-elses-branch`
`~/mystack $ hit build # pause for extra builds`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.3`
- ▶ `~/mystack $ git checkout paper-from-2010`
`~/mystack $ hit build # instant`
`~/mystack $ ~/local/bin/python --version`
`Python 2.6.3`

Consequences of hash-based installation

1. More dimensions! Even

`.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10`

is not exhaustive; “h5py/5ffg...” caters for everything

Consequences of hash-based installation

1. More dimensions! Even

`.../h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_debug_ubuntu12.10`
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit build
```

```
# ...then power shuts down, but you're good
```

Consequences of hash-based installation

1. More dimensions! Even

`.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10`
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit build
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (mark&sweep rather than file tracking)

Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit build  
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (mark&sweep rather than file tracking)
4. Jump around in software history (or between branches) in seconds!

Consequences of hash-based installation

1. More dimensions! Even

`.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10`
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit build  
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (mark&sweep rather than file tracking)
4. Jump around in software history (or between branches) in seconds!

Sophisticated features with simple implementation

Prior art: Eelco Dolstra's PhD thesis/the Nix project

Demo

- ▶ Show a stack/distribution profile spec
- ▶ Show package spec and modify source hash (to build new artifact)
- ▶ Show package spec and modify build options (to build new artifact)
- ▶ Revert package spec to show no rebuild occurs
- ▶ Show 'hit develop' to build a "virtual env"

Status

- ▶ Hashdist library and command line interface up and running

Status

- ▶ Hashdist library and command line interface up and running
- ▶ Multiple stacks (Proteus, SciPy Stack, Clawpack) across multiple platforms (HPC, Linux, OS X, Cygwin)

Status

- ▶ Hashdist library and command line interface up and running
- ▶ Multiple stacks (Proteus, SciPy Stack, Clawpack) across multiple platforms (HPC, Linux, OS X, Cygwin)
- ▶ Soon: relocatable builds, IPython Notebook integration, flexible constraints