

Hashdist – Yet Another Desperate Attempt at Fixing Scientific Software Distribution

Dag Sverre Seljebotn
Ondřej Čertík
Chris Kees

Simula, January 24, 2013

<http://github.com/hashdist>

Dag Sverre's work for Simula Innovation is funded by a grant from the International Research Office, US Army Engineer Research and Development Center (BAA contract W911NF-12-1-0604)

It's 2013, and most of the installation world is better off than 10 years ago

- ▶ Debian/RedHat

It's 2013, and most of the installation world is better off than 10 years ago

- ▶ Debian/RedHat
- ▶ App stores

It's 2013, and most of the installation world is better off than 10 years ago

- ▶ Debian/RedHat
- ▶ App stores
- ▶ Web apps

What makes scientific codes so special?

- ▶ No root access

What makes scientific codes so special?

- ▶ No root access
- ▶ Sometimes you **need** the very latest version

What makes scientific codes so special?

- ▶ No root access
- ▶ Sometimes you **need** the very latest version
- ▶ Fortran/C++ instead of C/Java/.NET

What makes scientific codes so special?


- ▶ No root access
- ▶ Sometimes you **need** the very latest version
- ▶ Fortran/C++ instead of C/Java/.NET
- ▶ Intersection of “need speed” and “do not pay dedicated application sysadmins”

Combinatorial explosion

```
/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so
```

Combinatorial explosion

```
/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so  
/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so
```



× LAPACK × FFT library × IDL/Python version...

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only
 - ▶ Deals “not good enough” with combinatorial explosion

Established options elsewhere

- ▶ Debian/Ubuntu/RedHat/Gentoo
 - ▶ Need root
 - ▶ Deals poorly with combinatorial explosion
- ▶ MacPorts, Fink
 - ▶ Mac only
 - ▶ Deals “not good enough” with combinatorial explosion
- ▶ HPC environment modules
 - ▶ The sysadmins hate them
 - ▶ The users need newer/their own libraries

Current solutions

- ▶ Build yourself from source

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work...

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work...
- ▶ Aha! Make a script to build from source...
 - ▶ Simula: dorsal
 - ▶ 5 different within DoD (incl. python-hpcmp)
 - ▶ Sage
 - ▶ Lots of others (“everybody” does it)

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work...
- ▶ Aha! Make a script to build from source...
 - ▶ Simula: dorsal
 - ▶ 5 different within DoD (incl. python-hpcmp)
 - ▶ Sage
 - ▶ Lots of others (“everybody” does it)
- ▶ Easy to do oneself \Rightarrow difficult for one to get momentum

Current solutions

- ▶ Build yourself from source
 - ▶ `./configure --prefix=$HOME/local; make; make install`
 - ▶ `export LD_LIBRARY_PATH=~sigurdkn/local/lib`
 - ▶ Fragile, duplication of work...
- ▶ Aha! Make a script to build from source...
 - ▶ Simula: dorsal
 - ▶ 5 different within DoD (incl. python-hpcmp)
 - ▶ Sage
 - ▶ Lots of others (“everybody” does it)
- ▶ Easy to do oneself \Rightarrow difficult for one to get momentum
- ▶ The details are different for everybody

Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal is all about curated software stacks

Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal is all about curated software stacks
- ▶ Perhaps you want 60% curated, 20% bleeding edge or manually tweaked, 20% your own code...

- ▶ Others have failed, we're trying yet again


- ▶ Others have failed, we're trying yet again
- ▶ Need to have new ideas

Theory


Hash function

$$h(k) : \mathbb{N} \rightarrow \mathbf{H}$$

Digression – $O(1)$ hash table lookups




Digression – $O(1)$ hash table lookups



If you know contents up front: Create *perfect* h

Digression – $O(1)$ hash table lookups



If you know contents up front: Create *perfect* h

h should be very fast; don't care so much about properties

Image: Hopgood (1968), Computer Bulletin

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3
- ▶ Mathematical research topic to make h such that no information about input is revealed

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3
- ▶ Mathematical research topic to make h such that no information about input is revealed

$h(\text{'The dark fox'}) = h(546865206461726b20666f78 \text{ hex})$
 $= b6589fc6ab0dc82cf12099d1c2d40ab994e8410c \text{ hex}$

Cryptographic/secure hashing

- ▶ Large key size (160, 256, or 512 bits)
 - ▶ NIST standards: SHA-1, SHA-2 (224, 256, 384, 512 bits), SHA-3
- ▶ Mathematical research topic to make h such that no information about input is revealed

$h(\text{'The dark fog'}) = h(546865206461726b20666f67 \text{ hex})$
 $= \text{da4b9237baccdf19c0760cab7aec4a8359010b0 hex}$


Example 1: Store passwords

Use the one-way nature

Example 2: git

```
$ (cd code/hashdist/.git/objects; find)
./59/5a2f8e3890d0ece24514f3e32ae874f1f03ac2
./2f/780151688e1f122a5b9072d42009c80c36140c
./2f/4b2eef40b51bc2d46027d1864653b37dd05f8f
./2f/237d74e3f81f498212629ac0b96bedac4b0b36
./2f/df799c54fed6fe96a91e1d5f1593996228ebc
./2f/27bd4efa5f8521fb98eb82181a67aae97b7f1a
./2f/3fedf882f1b28905199961356f4e00281ddf76
```

Example 2: git



Why hashes?

- ▶ Incremental database IDs don't work for distributed systems

Why hashes?

- ▶ Incremental database IDs don't work for distributed systems
- ▶ Random ID's would work...
 - ▶ E.g., UUID like 550e8400-e29b-41d4-a716-446655440000

Why hashes?

- ▶ Incremental database IDs don't work for distributed systems
- ▶ Random ID's would work...
 - ▶ E.g., UUID like 550e8400-e29b-41d4-a716-446655440000
- ▶ ...but a hash simultaneously verifies the content!


The cython network graph

Keyboard shortcuts available

All branches in the network using cython/cython as the reference point. Read our blog post about how it works.

Show Help

Last updated: 12 minutes ago



Chances of collision...

Types of attack (assume $k = 160$):

Chances of collision...

Types of attack (assume $k = 160$):

- ▶ Preimage attack: Chance $2^{-160} \sim 10^{-50}$

Chances of collision...

Types of attack (assume $k = 160$):

- ▶ Preimage attack: Chance $2^{-160} \sim 10^{-50}$
- ▶ Accidental collision: May happen in a collection of $2^{80} \sim 10^{25}$ keys due to “birthday paradox”
 - ▶ 6.5 billion programmers...
 - ▶ ...each produce one Linux kernel history every second...
 - ▶ ...and push to one enormous Git repository...
 - ▶ ...then after 5 years there's a 50% chance of collision

Chances of collision...

Types of attack (assume $k = 160$):

- ▶ Preimage attack: Chance $2^{-160} \sim 10^{-50}$
- ▶ Accidental collision: May happen in a collection of $2^{80} \sim 10^{25}$ keys due to “birthday paradox”
 - ▶ 6.5 billion programmers...
 - ▶ ...each produce one Linux kernel history every second...
 - ▶ ...and push to one enormous Git repository...
 - ▶ ...then after 5 years there's a 50% chance of collision
- ▶ Brute-force SHA-1 still needs only 2^{60} operations due to weaknesses in SHA-1
 - ▶ \$2.5M today, \$50K after 2020.

Hashdist

Hash-based installation

- ▶ Linux laptop:
`/usr/lib/libhdf5.so`

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Even

`h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_abel_debug`
`incomplete`

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Even

`h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_abel_debug`
incomplete

- ▶ Abel is new and small; US Army clusters have 20-30 versions of every package.

Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Even

`h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_abel_debug`
incomplete

- ▶ Abel is new and small; US Army clusters have 20-30 versions of every package.

- ▶ Hashdist:

`~/hit/opt/hdf5/efn3/lib/libhdf5.so`

`~/hit/opt/hdf5/i7ni/lib/libhdf5.so`

`~/hit/opt/hdf5/qgpd/lib/libhdf5.so`

(really `hdf5/efn3i7ni7lbtik4frlb5wcnqgpdmi3ql`)

Step 1: Hash the build

Internal protocol!

```
{
  "name": "hdf5",
  "import" : [{ "id" : "gcc/apycmxgafb564zz7rwhwvon7padvxdx"},
               { "id" : "unix/v-1"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "cmd": ["sh", "$in0"],
  "inputs": [
    "text": [
      ["/configure --prefix=${ARTIFACT} --with-pic \\"],
      [      --with-zlib=$ZLIB"],
      ["make"],
      ["make", "install"]
    ]
  ]
}
```

Step 1: Hash the build

Internal protocol!

```
{
  "name": "hdf5",
  "import" : [{ "id" : "gcc/apycmxgafb564zz7rwhwvon7padvxdx"},
               { "id" : "unix/v-1"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "cmd": ["sh", "$in0"],
  "inputs": [
    "text": [
      ["/configure --prefix=${ARTIFACT} --with-pic \\"],
      [      --with-zlib=$ZLIB"],
      ["make"],
      ["make", "install"]
    ]
  ]
}
```

Hash to create key → hdf5/u4vsabroylchvmwoxf5mdpxidd4lnrwl

Step 1: Hash the build

Internal protocol!

```
{
  "name": "hdf5",
  "import" : [{ "id" : "gcc/apycmxgafb564zz7rwhwvon7padvxdx"},
               { "id" : "unix/v-1"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "cmd": ["sh", "$in0"],
  "inputs": [
    "text": [
      ["/configure --prefix=${ARTIFACT} --with-pic \\"],
      [      --with-zlib=${ZLIB} CFLAGS=-O0"],
      ["make"],
      ["make", "install"]
    ]
  ]
}
```

Hash to create key → `hdf5/fjczhadqtxy6j1bnvzlthrzsex7wz7xb`

Step 2: Every build installs to separate location

Same as with the “module load” system:

```
$ echo opt/*/*  
opt/hdf5/avnj opt/hdf5/a5df opt/hdf5/a4sf opt/python/arxd  
opt/python/rvdo opt/readline/6vvu opt/readline/v7fw  
opt/zlib/fh7n opt/zlib/i7yr ...
```

```
$ ls opt/zlib/fh7n/lib  
libz.a libz.so libz.so.1 libz.so.1.2.5 pkgconfig
```

```
$ ls opt/hdf5/avnj/lib  
libhdf5.a libhdf5.so libhdf5.so.7 libhdf5.so.7.0.4
```

Step 3: Make a profile with links

```
$ ls -la opt/profile/ldhn/bin
h5dump -> ../../../../hdf5/avnj/bin/h5dump
h5import -> ../../../../hdf5/avnj/bin/h5import
h5ls -> ../../../../hdf5/avnj/bin/h5ls
...
```

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit update # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit update # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`
- ▶ `~/mystack $ hit update # instant`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit update # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`
- ▶ `~/mystack $ hit update # instant`
- ▶ `~/mystack $ git fetch from-someone-else`
`~/mystack $ git checkout someone-elses-branch`
`~/mystack $ hit update # pause for extra builds`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.3`

Branchable software stack

- ▶ `~/mystack $ ls`
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ hit update # takes some time`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.2`
- ▶ `~/mystack $ hit update # instant`
- ▶ `~/mystack $ git fetch from-someone-else`
`~/mystack $ git checkout someone-elses-branch`
`~/mystack $ hit update # pause for extra builds`
`~/mystack $ ~/local/bin/python --version`
`Python 2.7.3`
- ▶ `~/mystack $ git checkout paper-from-2010`
`~/mystack $ hit update # instant`
`~/mystack $ ~/local/bin/python --version`
`Python 2.6.3`

Consequences of hash-based installation

1. More dimensions! Even

`.../h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_debug-ubuntu12.10`
is not exhaustive; “h5py/5ffg...” caters for everything

Consequences of hash-based installation

1. More dimensions! Even

`.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10`
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit upgrade
```

```
# ...then power shuts down, but you're good
```

Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit upgrade
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (mark&sweep rather than file tracking)

Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_debug-ubuntu12.10
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit upgrade
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (mark&sweep rather than file tracking)
4. Jump around in software history (or between branches) in seconds!

Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hit upgrade
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (mark&sweep rather than file tracking)

4. Jump around in software history (or between branches) in seconds!

Sophisticated features with simple implementation

Prior art: Eelco Dolstra's PhD thesis/the Nix project

Ideas for autumn

- ▶ Specifying the entire software stack in minute detail is bothersome

Ideas for autumn

- ▶ Specifying the entire software stack in minute detail is bothersome
- ▶ Want a constraint solver
 - ▶ $A[\text{version} \geq 2]$ needs $B[\text{version} \geq 1.2]$
 - ▶ $B[\text{version} \geq 1.1]$ needs LAPACK=intel-mkl
 - ▶ Given constraints, which LAPACK and which version of A, B

Ideas for autumn

- ▶ Specifying the entire software stack in minute detail is bothersome
- ▶ Want a constraint solver
 - ▶ $A[\text{version} \geq 2]$ needs $B[\text{version} \geq 1.2]$
 - ▶ $B[\text{version} \geq 1.1]$ needs LAPACK=intel-mkl
 - ▶ Given constraints, which LAPACK and which version of A, B
- ▶ Debian does constraint solving between packages
 - ▶ But we have $\prod_{i \in \{\text{MPI, compiler, ...}\}} n_i$ possible “packages”

Ideas for autumn

- ▶ Specifying the entire software stack in minute detail is bothersome
- ▶ Want a constraint solver
 - ▶ $A[\text{version} \geq 2]$ needs $B[\text{version} \geq 1.2]$
 - ▶ $B[\text{version} \geq 1.1]$ needs $\text{LAPACK}=\text{intel-mkl}$
 - ▶ Given constraints, which LAPACK and which version of A, B
- ▶ Debian does constraint solving between packages
 - ▶ But we have $\prod_{i \in \{\text{MPI}, \text{compiler}, \dots\}} n_i$ possible “packages”
- ▶ We want to do constraint solving on input variables to the build

Ideas for autumn

- ▶ Specifying the entire software stack in minute detail is bothersome
- ▶ Want a constraint solver
 - ▶ $A[\text{version} \geq 2]$ needs $B[\text{version} \geq 1.2]$
 - ▶ $B[\text{version} \geq 1.1]$ needs LAPACK=intel-mkl
 - ▶ Given constraints, which LAPACK and which version of A, B
- ▶ Debian does constraint solving between packages
 - ▶ But we have $\prod_{i \in \{\text{MPI, compiler, ...}\}} n_i$ possible “packages”
- ▶ We want to do constraint solving on input variables to the build
- ▶ Objective function: Minimize build time or maximize package freshness?

Ideas for autumn

- ▶ Specifying the entire software stack in minute detail is bothersome
- ▶ Want a constraint solver
 - ▶ $A[\text{version} \geq 2]$ needs $B[\text{version} \geq 1.2]$
 - ▶ $B[\text{version} \geq 1.1]$ needs LAPACK=intel-mkl
 - ▶ Given constraints, which LAPACK and which version of A, B
- ▶ Debian does constraint solving between packages
 - ▶ But we have $\prod_{i \in \{\text{MPI, compiler, ...}\}} n_i$ possible “packages”
- ▶ We want to do constraint solving on input variables to the build
- ▶ Objective function: Minimize build time or maximize package freshness?
- ▶ NP-complete problem, e.g.:
 - ▶ Integer linear programming
 - ▶ Belief propagation (from Bayesian network theory)

Why bother?

- ▶ Leaving build input variables free (e.g., LAPACK) allows “re-seating” a software stack description from one system to another

Why bother?

- ▶ Leaving build input variables free (e.g., LAPACK) allows “re-seating” a software stack description from one system to another
- ▶ Small step towards the “reproducible paper”

The end

The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build

The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

Some help:

The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

Some help:

- ▶ Integrate with host system (Debian, environment modules, “generic”) to specify dependencies on package on host system

The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

Some help:

- ▶ Integrate with host system (Debian, environment modules, “generic”) to specify dependencies on package on host system
- ▶ “hdist-jail” can issue warnings if a build process accesses files it shouldn’t (or hide them)

User-facing software stack definitions

Declarative approach (because you can git it and share it):

```
include:
```

- sources # pull in ./sources.yml
- build
- when cluster == "abel":
 - abel-overrides

```
profiles:
```

- name: "default"
 - configuration:
 - lapack_type: "openblas"
 - cluster: "hexagon"

```
select:
```

- project: "hdf5"
 - version: 1.8.2
- project: "h5py"
- ...

User-facing software stack definitions

Declarative approach (because you can git it and share it):

```
include:
```

- sources # pull in ./sources.yml
- build
- when cluster == "abel":
 - abel-overrides

```
profiles:
```

- name: "default"
 - configuration:
 - lapack_type: "openblas"
 - cluster: "hexagon"

```
select:
```

- project: "hdf5"
 - version: 1.8.2 to 1.8.5 # with integer linear programming
- project: "h5py"
- ...

For stack developers: DSL focused on overrides

Manage the combinatorial explosion without creating packages for
hdf5_intel_mpich, hdf5_gcc_openmpi, ...:

rules:

```
...
CFLAGS: ["-g", "-O$optlevel"]
when recipe == "configure-make-install":
  optlevel: 2
when project == "hdf5":
  recipe: "configure-make-install"
  when version == 1.5.2:
    optlevel: 0
  build_deps:
    - project: "zlib"
      version: 1.2.5 to 1.2.7
...
```

Temporary internal representation in Hashdist

```
dict(  
    package='hdf5',  
    version='1.8.10',  
    recipe='configure-make-install',  
    downloads=['http://www.hdfgroup.org/ftp/HDF5/current/'  
               'src/hdf5-1.8.10.tar.bz2'],  
    sources=['tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2'],  
    configure=['--prefix=$ARTIFACT', '--with-pic'],  
    CFLAGS=['-O2'],  
    jail='warn',  
    build_deps=[zlib, unix, gcc]  
)
```

For Hashdist developers

Feed it through a Python pipeline:

```
@pipeline.add_recipe('configure-make-install')
def configure_make_install_recipe(ctx, cfg, build):
    build['build']['script'].extend([
        ["LDFLAGS=$(hdist", "build-ldflags", ")"],
        ["CFLAGS=$(hdist", "build-cflags", ")"],
        ["CFLAGS+= " + " ".join(cfg.CFLAGS)],
        ['./configure'] + cfg.configure,
        ['make'],
        ['make', 'install']
    ])
```

Generated, read by Hashdist developers while debugging

```
{ "import" : [{ "id" : "gcc/apyicmxgafb564zz7rwhwvon7padvvdx"},
               { "id" : "virtual:unix"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvsvdaomvypridodr35or2"}],
  "script" : [
    ["LDFLAGS=$(hdist", "build-ldflags", ")"],
    ["CFLAGS=$(hdist", "build-cflags", ")"],
    ["CFLAGS+= -O2"],
    ["/configure", "--prefix=${ARTIFACT}"],
    ["make"],
    ["make", "install"]]
}
```