

# Hashdist – Yet Another Desperate Attempt at Fixing Scientific Software Distribution

Dag Sverre Seljebotn  
Ondřej Čertík  
Chris Kees

Simula, January 24, 2013

<http://github.com/hashdist>

Dag Sverre's work for Simula Innovation is funded by a grant from the International Research Office, US Army Engineer Research and Development Center (BAA contract W911NF-12-1-0604)

# The Problem

# HPC software distribution

What makes HPC so special?

# HPC software distribution

What makes HPC so special?

- ▶ Only sysadmins have root (so no Debian/Ubuntu, RedHat)
  - ▶ others: virtualization

# HPC software distribution

What makes HPC so special?

- ▶ Only sysadmins have root (so no Debian/Ubuntu, RedHat)
  - ▶ others: virtualization
- ▶ Common to compile specifically for CPU for optimal speed
  - ▶ others: either performance isn't important, or own a datacenter

# HPC software distribution

What makes HPC so special?

- ▶ Only sysadmins have root (so no Debian/Ubuntu, RedHat)
  - ▶ others: virtualization
- ▶ Common to compile specifically for CPU for optimal speed
  - ▶ others: either performance isn't important, or own a datacenter
- ▶ Users lack computer skills (relative to what they do)
  - ▶ others: do what they're educated for...

# HPC software distribution

What makes HPC so special?

- ▶ Only sysadmins have root (so no Debian/Ubuntu, RedHat)
  - ▶ others: virtualization
- ▶ Common to compile specifically for CPU for optimal speed
  - ▶ others: either performance isn't important, or own a datacenter
- ▶ Users lack computer skills (relative to what they do)
  - ▶ others: do what they're educated for...
- ▶ Fortran compilers from multiple vendors with incompatible ABI
  - ▶ others: Fortran unheard of, only one compiler vendor anyway, C ABI standard

# HPC software distribution

What makes HPC so special?

- ▶ Only sysadmins have root (so no Debian/Ubuntu, RedHat)
  - ▶ others: virtualization
- ▶ Common to compile specifically for CPU for optimal speed
  - ▶ others: either performance isn't important, or own a datacenter
- ▶ Users lack computer skills (relative to what they do)
  - ▶ others: do what they're educated for...
- ▶ Fortran compilers from multiple vendors with incompatible ABI
  - ▶ others: Fortran unheard of, only one compiler vendor anyway, C ABI standard
- ▶ 

```
$ ls /usr/mpi/*  
/usr/mpi/gcc:  
mvapich-1.2.0  mvapich-1.2.0-qlc  mvapich2-1.7  
mvapich2-1.7-qlc  openmpi-1.4.3  openmpi-1.4.3-qlc  
/usr/mpi/intel:  
mvapich-1.2.0-qlc  mvapich2-1.7-qlc  openmpi-1.4.3-qlc  
/usr/mpi/pgi:  
mvapich-1.2.0-qlc  mvapich2-1.7-qlc  openmpi-1.4.3-qlc
```



# Scientific Python

- ▶ Python applications/scripts have large dependency trees
  - ▶ Really a result of *better* software engineering practices...

# Scientific Python

- ▶ Python applications/scripts have large dependency trees
  - ▶ Really a result of *better* software engineering practices...
- ▶ Scientists must sometimes live on bleeding edge

# Scientific Python


- ▶ Python applications/scripts have large dependency trees
  - ▶ Really a result of *better* software engineering practices...
- ▶ Scientists must sometimes live on bleeding edge
- ▶ Python packaging created by web developers who mostly write Python...

# Scientific Python

- ▶ Python applications/scripts have large dependency trees
  - ▶ Really a result of *better* software engineering practices...
- ▶ Scientists must sometimes live on bleeding edge
- ▶ Python packaging created by web developers who mostly write Python...
- ▶ ...while scientific Python really a shell around C, C++, Fortran codes

# Scientific Python

- ▶ Python applications/scripts have large dependency trees
  - ▶ Really a result of *better* software engineering practices...
- ▶ Scientists must sometimes live on bleeding edge
- ▶ Python packaging created by web developers who mostly write Python...
- ▶ ...while scientific Python really a shell around C, C++, Fortran codes



## Current options: Sophisticated

- ▶ Debian/Ubuntu/RedHat/Gentoo: Need root access

## Current options: Sophisticated

- ▶ Debian/Ubuntu/RedHat/Gentoo: Need root access
- ▶ MacPorts etc.: Mac only

## Current options: Sophisticated

- ▶ Debian/Ubuntu/RedHat/Gentoo: Need root access
- ▶ MacPorts etc.: Mac only
- ▶ Gentoo Prefix: Experimental



## Current options: Sophisticated

- ▶ Debian/Ubuntu/RedHat/Gentoo: Need root access
- ▶ MacPorts etc.: Mac only
- ▶ Gentoo Prefix: Experimental
- ▶ Grand Unified Builder, 0install: Lack scientific packages

## Current options: Sophisticated

- ▶ Debian/Ubuntu/RedHat/Gentoo: Need root access
- ▶ MacPorts etc.: Mac only
- ▶ Gentoo Prefix: Experimental
- ▶ Grand Unified Builder, 0install: Lack scientific packages
- ▶ Python environment provided by sysadmins: Outdated

## Current options: Simple user-space

Sage, python-hpcmp, dorsal, EasyBuild, Hans Petter's Python script:

- ▶ Simple (good)  $\Leftrightarrow$  lack features (minor inconvenience)

## Current options: Simple user-space

Sage, python-hpcmp, dorsal, EasyBuild, Hans Petter's Python script:

- ▶ Simple (good)  $\Leftrightarrow$  lack features (minor inconvenience)
- ▶ Easy to do oneself  $\Rightarrow$  difficult for one to get momentum

## Current options: Simple user-space

Sage, python-hpcmp, dorsal, EasyBuild, Hans Petter's Python script:

- ▶ Simple (good)  $\Leftrightarrow$  lack features (minor inconvenience)
- ▶ Easy to do oneself  $\Rightarrow$  difficult for one to get momentum
- ▶ The details are different for everybody
  - ▶ Best LAPACK for Sage is not best LAPACK for EPD/Anaconda

## Manual builds

- ▶ `./configure --prefix=$HOME/local; make; make install`

## Manual builds

- ▶ `./configure --prefix=$HOME/local; make; make install`
- ▶ Or in the case of my home institute,  
`export LD_LIBRARY_PATH=~oldstudent/local/lib`

# Manual builds

- ▶ `./configure --prefix=$HOME/local; make; make install`
- ▶ Or in the case of my home institute,  
`export LD_LIBRARY_PATH=~oldstudent/local/lib`

Some problems:



# Manual builds

- ▶ `./configure --prefix=$HOME/local; make; make install`
- ▶ Or in the case of my home institute,  
`export LD_LIBRARY_PATH=~oldstudent/local/lib`

Some problems:

- ▶ Steep learning curve (and hard-to-find bugs)

# Manual builds

- ▶ `./configure --prefix=$HOME/local; make; make install`
- ▶ Or in the case of my home institute,  
`export LD_LIBRARY_PATH=~oldstudent/local/lib`

Some problems:

- ▶ Steep learning curve (and hard-to-find bugs)
- ▶ Tedious to move between clusters

# Manual builds


- ▶ `./configure --prefix=$HOME/local; make; make install`
- ▶ Or in the case of my home institute,  
`export LD_LIBRARY_PATH=~oldstudent/local/lib`

Some problems:

- ▶ Steep learning curve (and hard-to-find bugs)
- ▶ Tedious to move between clusters
- ▶ Reproducibility

# The real knot

Combinatorial explosion:



× Python version × NumPy version × FFT library...

# Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal is all about curated software stacks

# Curation

- ▶ Debian, RedHat, cluster sysadmins, dorsal is all about curated software stacks
- ▶ Perhaps you want 60% curated, 20% bleeding edge or manually configured, 20% your own code...

# What to do?

- ▶ Ubuntu + root access: Make your own PPA

# What to do?

- ▶ Ubuntu + root access: Make your own PPA
- ▶ Build from source
  - ▶ Often on top of a scientific Python distribution



# What to do?

- ▶ Ubuntu + root access: Make your own PPA
- ▶ Build from source
  - ▶ Often on top of a scientific Python distribution
- ▶ dorsal, EasyBuild: Contribute your own configuration
  - ▶ `dolfin.package` vs. `dolfin-intel.package`

Hashdist

# Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

# Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

# Hash-based installation

- ▶ Linux laptop:

`/usr/lib/libhdf5.so`

- ▶ HPC environment modules:

`/cluster/software/VERSIONS/hdf5-1.6.1/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.6.1_pgi/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_intel/lib/libhdf5.so`

`/cluster/software/VERSIONS/hdf5-1.8.9_pgi/lib/libhdf5.so`

- ▶ Hashdist:

`~/hdist/opt/hdf5/efn3/lib/libhdf5.so`

`~/hdist/opt/hdf5/i7ni/lib/libhdf5.so`

`~/hdist/opt/hdf5/qgpd/lib/libhdf5.so`

(really hdf5/efn3i7ni7lbtik4frlb5wcnqgpdmi3ql)

(demo)

# Using a hash-based software store

## (1) Describe the build (**internal protocol!**)

```
{ "import" : [{ "id" : "gcc/apyicmxgafb564zz7rwhwvon7padvxdx"},
               { "id" : "virtual:unix"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "script" : [
    ["LDFLAGS=-L${ZLIB}/lib -Wl,-rpath,${ZLIB}/lib"],
    ["CFLAGS=-I${ZLIB}/include"],
    ["/configure", "--prefix=${ARTIFACT}", "--with-pic"],
    ["make"],
    ["make", "install"]]
}
```

# Using a hash-based software store

## (1) Describe the build (**internal protocol!**)

```
{ "import" : [{ "id" : "gcc/apyicmxgafb564zz7rwhwvon7padvxdx"},
                { "id" : "virtual:unix"},
                { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "script" : [
    ["LDFLAGS=-L${ZLIB}/lib -Wl,-rpath,${ZLIB}/lib"],
    ["CFLAGS=-I${ZLIB}/include"],
    ["/configure", "--prefix=${ARTIFACT}", "--with-pic"],
    ["make"],
    ["make", "install"]]
}
```

## (2) Hash the build spec → hdf5/u4vsabroylchvmwoxf5mdpxidd4lnrwl



# Using a hash-based software store

## (1) Describe the build (**internal protocol!**)

```
{ "import" : [{ "id" : "gcc/apyicmxgafb564zz7rwhwvon7padvxdx"},
               { "id" : "virtual:unix"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "script" : [
    ["LDFLAGS=-L${ZLIB}/lib -Wl,-rpath,${ZLIB}/lib"],
    ["CFLAGS=-I${ZLIB}/include -O0 -g"],
    ["/configure", "--prefix=${ARTIFACT}", "--with-pic"],
    ["make"],
    ["make", "install"]]
}
```

(2) Hash the build spec → `hdf5/fjczhadqtyx6jlbvz1thrzsex7wz7xb`

# Using a hash-based software store

## (1) Describe the build (**internal protocol!**)

```
{ "import" : [{ "id" : "gcc/apyicmxgafb564zz7rwhwvon7padvxdx"},
               { "id" : "virtual:unix"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "script" : [
    ["LDFLAGS=-L${ZLIB}/lib -Wl,-rpath,${ZLIB}/lib"],
    ["CFLAGS=-I${ZLIB}/include -O0 -g"],
    ["/configure", "--prefix=${ARTIFACT}", "--with-pic"],
    ["make"],
    ["make", "install"]]
}
```

(2) Hash the build spec → `hdf5/fjczhadqtyx6jlbvz1thrzsex7wz7xb`

(3) If not found, do an *isolated* build on the fly

## Using a hash-based software store

(4) When all packages are built create symbolic links to package contents in a *profile*:

```
$ ls -l ~/local
local -> /home/dagss/.hdist/opt/profile/w6gp

$ ls -l /home/dagss/.hdist/opt/profile/w6gp/bin
h5copy -> /home/dagss/.hdist/opt/hdf5/whfk/bin/h5copy
h5ls -> /home/dagss/.hdist/opt/hdf5/whfk/bin/h5ls
...

$ ldd /home/dagss/.hdist/opt/hdf5/whfk/lib/libhdf5.so
linux-vdso.so.1 => (0x00007ffffeb3ff000)
libsz.so.2 => /home/dagss/.hdist/opt/szip/5a5t/lib/libsz.so.2
libz.so.1 => /home/dagss/.hdist/opt/zlib/c116/lib/libz.so.1
libm.so.6 => /lib/x86_64-linux-gnu/libm.so.6
libc.so.6 => /lib/x86_64-linux-gnu/libc.so.6
/lib64/ld-linux-x86-64.so.2
```

# Consequences of hash-based installation

## 1. More dimensions! Even

`.../h5py-hdf5_1.8.9_pgi-python2.7-numpy1.6.3_debug-ubuntu12.10`  
is not exhaustive; “h5py/5ffg...” caters for everything

# Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5\_1.8.9\_pgi-python2.7-numpy1.6.3\_debug\_ubuntu12.10  
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hdist upgrade
```

```
# ...then power shuts down, but you're good
```

# Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10  
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hdist upgrade
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (GC rather than file tracking)

# Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5\_1.8.9\_pgi-python2.7-numpy1.6.3\_debug\_ubuntu12.10  
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hdist upgrade
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (GC rather than file tracking)
4. Jump around in software history (or between branches) in seconds!

# Consequences of hash-based installation

1. More dimensions! Even

.../h5py-hdf5-1.8.9-pgi-python2.7-numpy1.6.3-debug-ubuntu12.10  
is not exhaustive; “h5py/5ffg...” caters for everything

2. For free: Atomic upgrades

```
$ hdist upgrade
```

```
# ...then power shuts down, but you're good
```

3. Much easier: Uninstall (GC rather than file tracking)

4. Jump around in software history (or between branches) in seconds!

**Sophisticated features with simple implementation**

Prior art: Eelco Dolstra's PhD thesis/the Nix project



## Branchable software stack

- ▶ `~/mystack $ ls`  
`default.yml sources.yml build.yml abel-cluster.yml`

## Branchable software stack

- ▶ `~/mystack $ ls`  
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ git checkout cuttingedge`  
`~/mystack $ # make some modification`  
`~/mystack $ hdist shell . # slight pause`  
`~/mystack $ python --version`  
`Python 2.7.3`

## Branchable software stack

- ▶ `~/mystack $ ls`  
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ git checkout cuttingedge`  
`~/mystack $ # make some modification`  
`~/mystack $ hdist shell . # slight pause`  
`~/mystack $ python --version`  
`Python 2.7.3`
- ▶ `~/mystack $ ^D`  
`~/mystack $ git checkout paper-from-2010`  
`~/mystack $ hdist shell . # instant`  
`~/mystack $ python --version`  
`Python 2.6.3`

## Branchable software stack

- ▶ `~/mystack $ ls`  
`default.yml sources.yml build.yml abel-cluster.yml`
- ▶ `~/mystack $ git checkout cuttingedge`  
`~/mystack $ # make some modification`  
`~/mystack $ hdist shell . # slight pause`  
`~/mystack $ python --version`  
`Python 2.7.3`
- ▶ `~/mystack $ ^D`  
`~/mystack $ git checkout paper-from-2010`  
`~/mystack $ hdist shell . # instant`  
`~/mystack $ python --version`  
`Python 2.6.3`
- ▶ `~/mystack $ rm -rf ~/.hdist/opt/*`  
`~/mystack $ hdist shell . # takes quite some time`  
`~/mystack $ python --version`  
`Python 2.6.3`

## The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build

## The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

## The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

Some help:

## The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

Some help:

- ▶ Integrate with host system (Debian, environment modules, “generic”) to specify dependencies on package on host system



## The tradeoff: Builds must be “functional”

- ▶ All dependencies and all of the environment must be taken into account when describing the build
- ▶ More hassle, but very good for reproducibility

Some help:

- ▶ Integrate with host system (Debian, environment modules, “generic”) to specify dependencies on package on host system
- ▶ “hdist-jail” can issue warnings if a build process accesses files it shouldn’t (or hide them)

# User-facing software stack definitions

Declarative approach (because you can git it and share it):

```
include:
```

- sources # pull in ./sources.yml
- build
- when cluster == "abel":
  - abel-overrides

```
profiles:
```

- name: "default"
  - configuration:
    - lapack\_type: "openblas"
    - cluster: "hexagon"

```
select:
```

- project: "hdf5"
  - version: 1.8.2
- project: "h5py"
- ...

# User-facing software stack definitions

Declarative approach (because you can git it and share it):

```
include:
```

- sources # pull in ./sources.yml
- build
- when cluster == "abel":
  - abel-overrides

```
profiles:
```

- name: "default"
  - configuration:
    - lapack\_type: "openblas"
    - cluster: "hexagon"

```
select:
```

- project: "hdf5"
  - version: 1.8.2 to 1.8.5 # with integer linear programming
- project: "h5py"
- ...

## For stack developers: DSL focused on overrides

Manage the combinatorial explosion without creating packages for  
hdf5\_intel\_mpich, hdf5\_gcc\_openmpi, ...:

rules:

```
...
CFLAGS: ["-g", "-O$optlevel"]
when recipe == "configure-make-install":
  optlevel: 2
when project == "hdf5":
  recipe: "configure-make-install"
  when version == 1.5.2:
    optlevel: 0
  build_deps:
    - project: "zlib"
      version: 1.2.5 to 1.2.7
...
```

## Temporary internal representation in Hashdist

```
dict(  
    package='hdf5',  
    version='1.8.10',  
    recipe='configure-make-install',  
    downloads=['http://www.hdfgroup.org/ftp/HDF5/current/'  
               'src/hdf5-1.8.10.tar.bz2'],  
    sources=['tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2'],  
    configure=['--prefix=$ARTIFACT', '--with-pic'],  
    CFLAGS=['-O2'],  
    jail='warn',  
    build_deps=[zlib, unix, gcc]  
)
```

# For Hashdist developers

Feed it through a Python pipeline:

```
@pipeline.add_recipe('configure-make-install')
def configure_make_install_recipe(ctx, cfg, build):
    build['build']['script'].extend([
        ["LDFLAGS=$(hdist", "build-ldflags", ")"],
        ["CFLAGS=$(hdist", "build-cflags", ")"],
        ["CFLAGS+= " + " ".join(cfg.CFLAGS)],
        ['./configure'] + cfg.configure,
        ['make'],
        ['make', 'install']
    ])
```

## Generated, read by Hashdist developers while debugging

```
{ "import" : [{ "id" : "gcc/apyicmxgafb564zz7rwhwvon7padvvdx"},
               { "id" : "virtual:unix"},
               { "id" : "zlib/wbg27phinbgwjg4nasb4xzf3ypo72otn"}],
  "sources" : [{ "key" : "tar.bz2:7jxgwn5xs5xnvdaomvypridodr35or2"}],
  "script" : [
    ["LDFLAGS=$(hdist", "build-ldflags", ")"],
    ["CFLAGS=$(hdist", "build-cflags", ")"],
    ["CFLAGS+= -O2"],
    ["/configure", "--prefix=${ARTIFACT}"],
    ["make"],
    ["make", "install"]]
}
```