




Vault Governance



Vault Onboarding Program

A 7 week guided community environment

Assisting customers with onboarding and adoption



Agenda

Sentinel 01

Control Groups 02

Quotas 03

01

Sentinel

Overview

- Sentinel is an embeddable 'policy as code' framework to enable fine-grained, logic-based policy decisions that can be extended to source external information to make decisions
- Sentinel policies are used in combination with ACL policies and policy templates

Working with Sentinel policies

- Vault injects data into the Sentinel runtime environment, including properties for: requests, replication, tokens, Identity secrets engine, MFA, and Control Groups
- [Sentinel Properties List](#)
- Sentinel policies are written in a domain specific language
- Manage policies via HTTP API, CLI, or web UI
- The root token or tokens with the **root** policy attached are **exempt** from Sentinel policies!

Sentinel policy structure

```
import "<library>"  
  
<variable> = <value>  
  
<name> = rule { <condition_to_evaluate> }  
  
main = rule {  
    <condition_to_evaluate>  
}
```

Example Sentinel policy

```
import "sockaddr"
import "strings"

# Only evaluated for update operations against transit/ path
precond = rule {
    request.operation in [ "update" ] and
    strings.has_prefix(request.path, "transit/")
}

# Requests must originate from our private IP range
cidrcheck = rule {
    sockaddr.is_contained(request.connection.remote_addr,
"122.22.3.4/32")
}

# Check the precondition before executing the cidrcheck
main = rule when precond {
    cidrcheck
}
```


Policy types

- Sentinel allows you to write complex logic and use external information like client CIDR
- Two types **Endpoint Governing Policy** (EGP) & **Role Governing Policy** (RGP)
 - EGPs are applied to particular paths
 - RGPs are applied to tokens, Identity entities, or Identity groups
- [Enforcement levels](#): **advisory**, **soft-mandatory**, or **hard-mandatory**

Endpoint Governing Policies (EGPs)

- API: /sys/policies/egp/
- EGPs are tied to particular paths
- Access to as much information in the request as possible
- Can be tied to all authenticated and most unauthenticated paths
- Denote suffix with glob character (*) for example: **my-secret-path/***
- Path of just * affects all authenticated and login requests

EGP example

'Break Glass' policy
denies access when
token created prior to
specified time

```
import "time"

main = rule when not request.unauthenticated {

  time.load(token.creation_time).unix >

  time.load("2020-01-01T07:25:00Z").unix

}
```

Role Governing Policies (RGPs)


- API: `/sys/policies/rgp/`
- RGPs are tied to tokens, Identity entities, or Identity groups
- Access to a rich set of controls across many aspects of Vault

RGP example

Use available Identity
secrets engine
properties to make
decisions

```
main = rule {  
  identity.entity.name is "vincent" or  
  
  identity.entity.id is  
  "fe2a5bfd-c483-9263-b0d4-f9d345c0ffee" or  
  
  "sysops" in identity.groups.names or  
  
  "c0ffee0a-5c07-4b97-81ec-0d423accb8e0" in  
  keys(identity.groups.by-id)  
}
```

Policy evaluation workflow



Test policies with Sentinel CLI

[Download Sentinel](#)

Sentinel

Intro

Docs



Download

Download Sentinel

macOS

Windows

Linux

FreeBSD

NetBSD

OpenBSD

Solaris

MACOS BINARY DOWNLOAD

Sentinel 0.18.4

[64-bit](#)



Test cases

1/3

- Sentinel expects a **test/<policy_name>** folder with test case files in either HCL or JSON format
- Test case files contain data to test the policy

```
$ tree
├── cidr-check.sentinel
└── test
    ├── cidr-check
    │   ├── fail.hcl
    │   └── success.hcl
```


Test cases

2/3

Specify the data to test the policy against

Optional: Expected boolean value of the rules

In absence of the 'test' block, all rules are expected to return true

```
global "my_global_variable" {
```



```
value = <test_data>
```

```
},
```

```
test {
```

```
rules = {
```



```
<expected_result>
```

```
}
```

```
}
```

Test cases

3/3

Use **mock** instead of global to inject static value directly into the policy's scope

For example, if the **time** library is used in the policy, use **mock** to mock **time.now**

```
mock "time" {  
  
  data = {  
  
    now = {  
  
      weekday_name = "Monday"  
  
      hour          = 14  
  
    }  
  
  }  
  
}
```

```
import "sockaddr"
import "strings"

# Only evaluated for create, update, and delete operations against kv/ path

precond = rule {
    request.operation in ["create", "update", "delete"] and
    strings.has_prefix(request.path, "kv/")
}

# Requests must originate from our private IP range

cidrcheck = rule {
    sockaddr.is_contained(request.connection.remote_addr, "122.22.3.4/32")
}

# Check the precondition before executing the cidrcheck

main = rule when precond {
    cidrcheck
}
```

Passing test

The file
test/cidr-check/success.hcl
contains data for a passing
test

```
global "request" {  
  value = {  
    connection = {  
      remote_addr = "122.22.3.4"  
    }  
    operation = "create"  
    path = "kv/orders"  
  }  
}
```

Failing test

The file
test/cidr-check/fail.hcl
contains data for a
failing test

```
global "request" {  
  value = {  
    connection = {  
      remote_addr = "122.22.3.10"  
    }  
    operation = "create"  
    path = "kv/orders"  
  }  
}  
  
test {  
  rules = {  
    main      = false  
    precondition = true  
  }  
}
```

Run tests

Use the **sentinel test** command to invoke the simulator and test policy

TIP: Use **-verbose** flag to output additional traces and logs for failed tests

```
$ sentinel test
```

```
PASS - cidr-check.sentinel
```

```
PASS - test/cidr-check/success.hcl
```

```
PASS - test/cidr-check/fail.hcl
```

Use CLI to deploy policy

Use vault CLI to write the policy

When successfully written, Vault begins immediately enforcing the policy at the hard mandatory level

```
$ vault write sys/policies/egp/cidr-check \  
policy=@cidr-check.sentinel \  
enforcement_level="hard-mandatory" \  
paths="kv/"
```



Success! Data written to: sys/policies/egp/cidr-check

02

Control Groups

Vault Control Groups

Allow for additional authorizations to be required for access to a path in Vault

When a control group is defined, the following occurs:

1. The requestor receives a wrapping token in return
2. The authorizers required by the control group policy must approve the request
3. Once all authorizations are satisfied, the requester can unwrap the secrets

Factors


Control Group requirements on paths can be specified in:

- ACL policies
- Sentinel policies


The single currently supported Control Groups factor is Identity Groups

- An authorizer must belong to a specific Identity group (factor)

Control Groups Workflow (1/2)



Control Groups Workflow (2/2)



Control Groups in ACL policies

```
path "EU_GDPR_data/data/orders/*" {  
  capabilities = [ "read" ]  
  control_group = {  
    factor "acct_manager" {  
      identity {  
        group_names = [ "account" ]  
        approvals = 2  
      }  
    }  
  }  
}
```

Control Groups in Sentinel policies



```
import "controlgroup"
```

```
control_group = func() {  
    numAuthzs = 0  
    for controlgroup.authorizations as authz {  
        if "account" in authz.groups.by_name {  
            numAuthzs = numAuthzs + 1  
        }  
    }  
    if numAuthzs >= 2 {  
        return true  
    }  
    return false  
}
```

```
main = rule {  
    control_group()  
}
```

Multiple factor Control Groups

```
path "EU_GDPR_data/data/orders/*" {  
  capabilities = [ "create", "read", "update" ]  
  
  control_group = {  
    factor "acct_manager" {  
      ttl = "4h"  
      identity {  
        group_names = [ "account" ]  
        approvals = 2  
      }  
    }  
    factor "security" {  
      identity {  
        group_names = [ "eu-security" ]  
        approvals = 1  
      }  
    }  
  }  
}
```

Control Groups Workflow

Requester actions


```
$ vault login -method=userpass username=bob  
password=training
```

Key	Value
Token	s.5VvDmKAFZyxZ3tfBAhVntanm
Token_policies	["default"]
Identity_policies	["read-gdpr-order"]


```
$ vault kv get EU_GDPR_data/orders/acct1
```

Key	Value
wrapping_token:	s.JwkWZ1sWICHfNaZSwDuMeF0A
wrapping_accessor:	HpsbV9ANBnxVlvig9Kvsot0B
wrapping_token_ttl:	24h
wrapping_token_creation_time:	2019-05-17 12:20:06 -0700 PDT
wrapping_token_creation_path:	EU_GDPR_data/data/orders/acct1


Authorizer actions




Authorizer actions




Authorizer actions



Unwrap the secret



Unwrap the secret



03

Quotas

Overview

Protect system stability and network, storage resource consumption from runaway application behavior and Distributed Denial of Service (DDoS)

- **Rate Limit Quotas**

Limit maximum amount of requests per second (RPS) to a system or mount to protect network bandwidth

- **Lease Count Quotas**

Cap number of leases generated in a system or mount to protect system stability and storage performance at scale



Configuring Resource Quotas

Creating Resource Quotas:

To set rate limit or lease quotas, set `/sys/quotas/<type>` with possible types being:

- `rate-limit`: Rate limit quota
- `lease-count`: Maximum lease count (Enterprise only)

Configuring Resource Quotas:

- Set/list specific types of quotas from `/sys/quotas/<type>/<name>`
- Path parameter can be set to a mount, mount in the namespace, or omitted for a systemwide quota
- Different quotas have different parameters; see the documentation for more details

Logging

- If a request is rejected due to a 'Lease Count Quota' violation, Vault will record this in the audit log
- Violations of 'Rate Limit Quotas' are not logged to the audit log
- It is possible to enable traceability of 'Rate Limit Quotas' via the HTTP API endpoint: `sys/quotas/config`, changing the parameter: `'enable_rate_limit_audit_logging'` to **true** (by default it will be false)
- Enabling this can potentially impact performance if the request volume is large

Rate Limit Quotas Example

Protect Vault from
potential DDoS attack

```
# Create global quota rule and set rate at desired
requests per second
$ vault write sys/quotas/rate-limit/global-rate
rate=500

# Set rate limit on specific paths
$ vault write sys/quotas/rate-limit/db-creds rate=30
path="database"

# Set rate limit on specific namespace and path
$ vault write sys/quotas/rate-limit/orders \

path="us-west/kv-v2" \

rate=16.67 \

burst=100
```

Lease Count Quotas Example

Prevent the storage backend from becoming the point of failure


```
$ vault write sys/quotas/lease-count/global-count-limit \
    max_leases=500

$ vault write sys/quotas/lease-count/db-creds \
    max_leases=100
    path="us-west/postgres"
```

Next Steps

Tutorials

Step-by-step guides to accelerate deployment of Vault



The screenshot displays the HashiCorp Vault Developer Tutorials page. The top navigation bar includes links for Home, Documentation, Tutorials, Install, and Try Cloud. A search bar and user profile icon are also present. The left sidebar contains a 'Vault Home' link and a 'Tutorials' section with an 'Overview' tab. Below this, the sidebar lists 'Get Started' (CLI Quick Start, HCP Vault Quick Start, UI Quick Start), 'Use Cases' (ADP, Database Credentials, Data Encryption, Key Management, Secrets Management), 'Certification Prep' (Associate, Operations Pro), and 'Production' (Day One Preparation, Enterprise, HCP Vault Monitoring, Monitor & Troubleshoot, Recommended Patterns, Standard Procedures). The main content area is titled 'Developer / Vault / Tutorials' and features a yellow banner with the text 'Centrally store, access and deploy secrets' and a link to 'Explore HCP Vault'. Below the banner, the 'Get Started' section lists three tutorial cards: 'Getting Started' (13 tutorials), 'Getting Started with Vault UI' (8 tutorials), and 'Getting Started with HCP Vault' (9 tutorials). The 'Featured Tutorials' section lists 'Vault 1.12 Release Highlights' (7 tutorials), 'HCP Vault Operations' (12 tutorials), and 'Security' (5 tutorials). The 'New Tutorials' section lists 'Vault Installation to Minikube via Helm with TLS enabled' (13min) and 'Audit Device Logs and Incident Response with Elasticsearch' (27min).

Developer / Vault / Tutorials

Centrally store, access and deploy secrets

Explore HCP Vault →

Get Started

13 tutorials
Getting Started
Vault secures, stores, and tightly controls access to tokens, passwords, certificates, API keys,...

8 tutorials
Getting Started with Vault UI
Manage Vault environment as well as your secrets using Vault UI.

9 tutorials
Getting Started with HCP Vault
Quickly get hands-on with HashiCorp Cloud Platform (HCP) Vault using the HCP portal and setup your manage...

Featured Tutorials
Extend your knowledge of Vault features and use cases.

7 tutorials
Vault 1.12 Release Highlights
The listed tutorials were updated to showcase the new enhancements introduced in Vault 1.12.

12 tutorials
HCP Vault Operations
Learn how to provision and connect to HCP Vault clusters.

5 tutorials
Security
Implement security best practices to secure your applications, protect your network, manage sensitive data...

New Tutorials
Here are the most recently published tutorials.

13min
Vault Installation to Minikube via Helm with TLS enabled
Deploy Vault on Kubernetes locally with TLS using Minikube and the official Helm chart.

27min
Audit Device Logs and Incident Response with Elasticsearch
Learn how to use a Vault audit device with Elasticsearch for auditing specific critical Vault events as part of your incident response workflows.

<https://developer.hashicorp.com/vault/tutorials>

Resources

- [Sentinel Documentation](#)
- [Sentinel Properties](#)
- [Sentinel Policy Examples](#)
- [Standard Sentinel Imports](#)
- [List of Vault data available for Sentinel policies](#)
- [Sentinel Policy Tutorial](#)
- [Control Groups Tutorial](#)
- [Protecting Vault with Resource Quotas](#)

Need Additional Help?

Customer Success

Contact our Customer Success Management team with any questions. We will help coordinate the right resources for you to get your questions answered
customer.success@hashicorp.com

Technical Support

Something not working quite right? Engage with HashiCorp Technical Support by opening a ticket for your issue at
support.hashicorp.com


Discuss

Engage with the HashiCorp Cloud community including HashiCorp Architects and Engineers
discuss.hashicorp.com

Action Items


- Share to customer.success@hashicorp.com
 - Authorized technical contacts for support
 - Stakeholders contact information (name and email addresses)
- Review where Sentinel and/or Control Groups are appropriate for your environment(s)
- Implement quotas for active clusters

Upcoming Webinars



Program Closing

Asynchronous content that will be delivered to your Inbox



Please complete the Zoom survey when prompted at the end of today's webinar

Q&A



Thank you

customer.success@hashicorp.com

www.hashicorp.com/customer-success