



Vault Kubernetes Integration



Agenda

Helm Chart for Vault 01

Pod Secret Access 02

Vault Agent Injector 03

Container Storage Interface 04

Vault Secrets Operator 05

01




Helm Chart for Vault

Helm Chart for Vault

- Deployment via Helm is the recommended installation and configuration method for Vault on Kubernetes
- The Helm chart can be used to install a Vault server cluster and/or the Agent Injector
- Managing your Vault deployment using Helm can also simplify lifecycle management of your Vault Servers
- Vault's Helm chart is compatible with Helm 3.6+ and Kubernetes 1.16+

Vault in Kubernetes



- A dedicated Kubernetes cluster should be used for Vault
- Vault **should not** be deployed in the default namespace
- Vault is designed to run as an unprivileged user
- Vault is a stateful application that requires persistent storage

Vault Helm Chart

[hashicorp/vault-helm](https://github.com/hashicorp/vault-helm)

The screenshot shows the GitHub repository page for `hashicorp/vault-helm`. The repository is public and has 830 forks and 935 stars. The main branch is `main`, with 20 branches and 38 tags. The repository is described as a Helm chart to install Vault and other associated components.

Repository Details:

- hashicorp/vault-helm (Public)
- Notifications
- Fork 830
- Star 935

Navigation:

- Code
- Issues 125
- Pull requests 45
- Actions
- Projects
- Security
- Insights

Repository Information:

- main (20 branches, 38 tags)
- Go to file
- Code

Recent Commits:

| Commit | Author | Message | Time |
|---------|--------|-----------------------------------|------------|
| e2711a2 | tomhjp | Prepare for 0.25.0 release (#916) | 3 days ago |

Files:

| File | Commit | Time |
|-----------------|--|--------------|
| .github | ci: Fix yq command syntax (#881) | last week |
| templates | CSI configurable nodeSelector and affinity (#862) | last month |
| test | Prepare for 0.25.0 release (#916) | 3 days ago |
| .gitignore | feature: Support configuring various properties as ... | 2 years ago |
| .helmignore | Update .helmignore (#732) | last year |
| CHANGELOG.md | Prepare for 0.25.0 release (#916) | 3 days ago |
| CODEOWNERS | Convert hashicorp/vault-helm to GitHub Actions (...) | 2 months ago |
| CONTRIBUTING.md | update CONTRIBUTING.md (#677) | last year |
| Chart.yaml | Prepare for 0.25.0 release (#916) | 3 days ago |
| LICENSE | [COMPLIANCE] Add MPL 2.0 LICENSE (#800) | 8 months ago |
| Makefile | Updating GHA and default Vault version (#863) | 2 months ago |

About:

Helm chart to install Vault and other associated components.

- Readme
- MPL-2.0 license
- Code of conduct
- Security policy
- 935 stars
- 73 watching
- 830 forks

Report repository

Releases: 37

- v0.25.0 (Latest) 3 days ago
- + 36 releases

Helm Repository

```
...  
$ helm repo add hashicorp \ https://helm.releases.hashicorp.com  
"Hashicorp" has been added to your repositories  
  
$ helm search repo  
hashicorp/consul ...  
hashicorp/vault ...  
  
$ helm install vault hashicorp/vault  
NAME: vault  
...
```

Default Values

```
# ...  
  
server:  
  
    # Run Vault in "dev" mode. This requires no further setup, no ...  
    # and no initialization. This is useful for experimenting with ...  
    # needing to unseal, store keys, et. al. All data is lost on ...  
    # use dev mode for anything other than experimenting.  
    # See https://www.vaultproject.io/docs/concepts/dev-server.html ...  
  
dev:
```



enabled: false

--set "server.dev.enabled=true"

Create an Override File

[Configure Vault Helm Chart](#)

```
$ cat override-values.yaml

# Vault Helm Chart Value Overrides
global:
  enabled: true
  tlsDisable: false

server:
  # Use the Enterprise Image
  image:
    repository: "hashicorp/vault-enterprise"
    tag: "1.13.4_ent"

# Run Vault in "HA" mode
ha:
  enabled: true
  replicas: 5
  raft:
    enabled: true
    setNodeId: true
```

Licensing

```
$ secret=$(cat licensefile.hclic)

$ kubectl create secret generic vault-ent-license
--from-literal="license=${secret}"

$ helm install hashicorp hashicorp/vault -f config.yaml

$ kubectl exec -ti vault-0 -- vault license get
```

Licensing

```
# config.yaml
```

```
server:
```

```
  image:
```

```
    repository: "hashicorp/vault-enterprise"
```

```
    tag: "1.13.4_ent"
```



```
  enterpriseLicense:
```

```
    secretName: vault-ent-license
```

Primary HA Vault ENT Cluster Deployment

```
$ secret=$(cat licensefile.hcllic)

$ kubectl create secret generic vault-ent-license
--from-literal="license=${secret}"

$ helm install vault hashicorp/vault \
  --set='server.image.repository=hashicorp/vault-enterprise' \
  --set='server.image.tag=1.13.4_ent' \
  --set='server.ha.enabled=true' \
  --set='server.ha.raft.enabled=true' \
  --set='server.enterpriseLicense.secretName=vault-ent-license'
```

Primary HA Vault ENT Cluster Deployment

Initialize cluster and unseal first node

```
$ kubectl exec -ti vault-primary-0 -- vault operator init
```

```
$ kubectl exec -ti vault-primary-0 -- vault operator unseal
```

Join second pod to raft cluster and unseal

```
$ kubectl exec -ti vault-primary-1 -- vault operator raft join \  
http://vault-primary-0.vault-primary-internal:8200
```

```
$ kubectl exec -ti vault-primary-1 -- vault operator unseal
```

Join third pod to raft cluster and unseal

```
$ kubectl exec -ti vault-primary-2 -- vault operator raft join \  
http://vault-primary-0.vault-primary-internal:8200
```

```
$ kubectl exec -ti vault-primary-2 -- vault operator unseal
```

DR HA Vault ENT Cluster Deployment

```
$ secret=$(cat licensefile.hclic)

$ kubectl create secret generic vault-ent-license
--from-literal="license=${secret}"

$ helm install vault hashicorp/vault \
  --set='server.image.repository=hashicorp/vault-enterprise' \
  --set='server.image.tag=1.9.0_ent' \
  --set='server.ha.enabled=true' \
  --set='server.ha.raft.enabled=true' \
  --set='server.enterpriseLicense.secretName=vault-ent-license'
```

DR HA Vault ENT Cluster Deployment

Initialize cluster and unseal first node

```
$ kubectl exec -ti vault-primary-0 -- vault operator init
```

```
$ kubectl exec -ti vault-primary-0 -- vault operator unseal
```

Join second pod to raft cluster and unseal

```
$ kubectl exec -ti vault-primary-1 -- vault operator raft  
join \  
http://vault-primary-0.vault-primary-internal:8200
```

```
$ kubectl exec -ti vault-primary-1 -- vault operator unseal
```

Join third pod to raft cluster and unseal

```
$ kubectl exec -ti vault-primary-2 -- vault operator raft  
join \  
http://vault-primary-0.vault-primary-internal:8200
```

```
$ kubectl exec -ti vault-primary-2 -- vault operator unseal
```

Enable Disaster Recovery Replication

Primary Cluster

```
$ kubectl exec -ti vault-primary-0 -- vault write -f  
sys/replication/dr/primary/enable  
primary_cluster_addr=https://vault-primary-active:8201  
  
$ kubectl exec -ti vault/primary-0 -- vault write  
sys/replication/dr/primary/secondary-token id=secondary
```


Enable Disaster Recovery Replication

Secondary Cluster

```
$ kubectl exec -ti vault-secondary-0 -- vault write  
sys/replication/dr/secondary/enable token=<TOKEN FROM  
PRIMARY>
```

```
$ kubectl delete pod vault-secondary-1
```

```
$ kubectl exec -ti vault-secondary-1 -- vault operator  
unseal <PRIMARY UNSEAL TOKEN>
```

```
$ kubectl delete pod vault-secondary-2
```

```
$ kubectl exec -ti vault-secondary-2 -- vault operator  
unseal <PRIMARY UNSEAL TOKEN>
```

Upgrading Vault


- Always backup Vault data via snapshot before beginning any upgrade
- Follow general [Vault upgrade pattern](#) and use the Helm chart to update Vault server StatefulSet
- Vault StatefulSet uses *OnDelete* (instead of *RollingUpdate*) to ensure standby nodes are updated before the active primary node
- Helm will install the latest chart found in a repo by default, best practice is to specify the chart version when upgrading

02



Pod Secret Access

Kubernetes Auth Flow



Application Pod Definition

```
apiVersion: v1
kind: Pod
...
spec:
  serviceAccountName: k8s-service-acct
  containers:
    - name: app
      image: burtlo/exampleapp-ruby:k8s
      env:
        - name: VAULT_ADDR
          value: "http://vault.default.svc.cluster.local:8200"
        - name: VAULT_ROLE
          value: "internal-app"
```

Example App Code Changes

```
response = HTTP.put("#{vault_url}/v1/auth/kubernetes/login")  
do |req|
```

```
req.headers['Content-Type'] = 'application/json'
```

```
req.body = { "role" => vault_role, "jwt" => jwt }.to_json  
end
```

```
vault_token =  
JSON.parse(response.body)["auth"]["client_token"]
```

```
logger.info "Received Vault Token: [#{vault_token}]"
```


03



Vault Agent Injector


Sidecar Pattern Workflow

Vault Sidecar Secret Injection Workflow



Sidecar Pattern

- Vault Agent injector uses the Kubernetes Sidecar pattern to append a Vault Agent container to pods
- Vault Agent renders Vault secrets to a shared memory volume
- Agent injector is a Kubernetes mutating webhook controller
- Sidecar container needs:
 - Vault address
 - Vault authentication role
 - Vault secret path



Install Agent Injector

[Installation Guide](#)

```
$ helm repo add hashicorp
https://helm.releases.hashicorp.com

"hashicorp" has been added to your repositories

$ helm search repo hashicorp/vault
```

| NAME | CHART VERSION | APP VERSION | DESCRIPTION |
|-----------------|---------------|-------------|--------------------------------|
| hashicorp/vault | 0.25.0 | 1.13.4 | Official HashiCorp Vault Chart |

```
$ helm install vault hashicorp/vault \
--set="injector.enabled=true"
```

Agent Annotations

```
spec:
  template:
    metadata:
      annotations:
        vault.hashicorp.com/agent-inject: "true"
        vault.hashicorp.com/role: "internal-app"
        vault.hashicorp.com/agent-inject-secret-database-config.txt:
"internal/data/database/config"
```

View the Secret

```
$ kubectl exec orgchart --container orgchart \  
    -- cat /vault/secrets/database-config.txt
```


```
data: map[password:db-secret-password  
username:db-readonly-user]
```

```
metadata: map[created_time:2019-12-20T18:17:50.930264759Z  
deletion_time: destroyed:false version:2]
```

04

Container Storage Interface

CSI Driver Workflow



Vault CSI Driver

- Integrates secrets stores with Kubernetes via a Container Storage Interface (CSI) volume
- Is deployed as a daemonset on every node in the Kubernetes cluster
- Uses the Secret Provider Class specified and the pod's service account to retrieve secrets from Vault, and mount them into the pod's CSI volume
- Uses *hostPath* to mount ephemeral volumes into the pods (disabled by default in OpenShift)

Secrets Store CSI Driver

[CSI Driver](#)

The screenshot shows the GitHub repository page for `kubernetes-sigs/secrets-store-csi-driver`. The repository is public and has 17 watchers, 569 stars, and 136 forks. It has 48 issues, 4 pull requests, and 1 project. The main branch is `main`, with 6 branches and 28 tags. A recent pull request #814 by `k8s-ci-robot` is merged. The repository contains several directories: `.github`, `.local`, `apis`, `charts`, `cmd/secrets-store-csi-driver`, `config`, `controllers`, `deploy`, `docker`, and `docs`. The `cmd/secrets-store-csi-driver` directory is highlighted. The `About` section describes the driver as a Secrets Store CSI driver for Kubernetes secrets, integrating secrets stores with Kubernetes via a CSI volume. It lists related projects: `kubernetes`, `hashicorp-vault`, `csi`, `azure-keyvault`, `aws-secrets-manager`, `k8s-sig-auth`, `gcp-secret-manager`, `csi-secrets-store`, and `mount-multiple-secrets`. The repository also includes a `Readme`, `Apache-2.0 License`, and `Code of conduct`. The `Releases` section shows 20 releases.

kubernetes-sigs / secrets-store-csi-driver Public

Watch 17 Star 569 Fork 136

Code Issues 48 Pull requests 4 Actions Projects 1 Wiki Security Insights

main 6 branches 28 tags Go to file Add file Code

k8s-ci-robot Merge pull request #814 from spiffxp/use-k8s-infra-for-... 0f4ff7d 2 days ago 859 commits

| | | |
|------------------------------|--|--------------|
| .github | ci: add markdown-link-check workflow | 22 days ago |
| .local | chore: remove deprecated <code>--filtered-watch-secret</code> flag | 23 days ago |
| apis | feat: add SecretProviderClass and SecretProviderClassPodStatu... | 2 months ago |
| charts | release: update manifest and helm charts for v1.0.0 | 2 months ago |
| cmd/secrets-store-csi-driver | chore: remove deprecated <code>--filtered-watch-secret</code> flag | 23 days ago |
| config | feat: add SecretProviderClass and SecretProviderClassPodStatu... | 2 months ago |
| controllers | Issue#636 - add last lint check items | 2 months ago |
| deploy | release: update manifest and helm charts for v1.0.0 | 2 months ago |
| docker | images: use k8s-staging-test-infra/gcb-docker-gcloud | 2 days ago |
| docs | docs: fix dead links based on errors | 22 days ago |

About

Secrets Store CSI driver for Kubernetes secrets - Integrates secrets stores with Kubernetes via a CSI volume.

[secrets-store-csi-driver.sigs.k8s.io/](#)

kubernetes hashicorp-vault csi
azure-keyvault aws-secrets-manager
k8s-sig-auth gcp-secret-manager
csi-secrets-store mount-multiple-secrets

Readme
Apache-2.0 License
Code of conduct

Releases 20

Install Container Storage Interface

[Installation Guide](#)

```
$ helm repo add hashicorp
https://helm.releases.hashicorp.com
"hashicorp" has been added to your repositories

$ helm search repo hashicorp/vault
NAME                CHART VERSION    APP VERSION DESCRIPTION
hashicorp/vault     0.25.0           1.13.4          Official
HashiCorp Vault Chart

$ helm install vault hashicorp/vault \
--set "injector.enabled=false" \
--set "csi.enabled=true" \
--set "injector.externalVaultAddr=http://addr:8200"
```

Install Secrets Store CSI Driver

```
...  
$ helm repo add secrets-store-csi-driver \  
https://raw.githubusercontent.com/kubernetes-sigs/secrets-  
store-csi-driver/master/charts  
...  
  
$ helm install csi  
secrets-store-csi-driver/secrets-store-csi-driver  
...
```

Install Secrets Store CSI Driver

```
apiVersion: secrets-store.csi.x-k8s.io/v1alpha1
kind: SecretProviderClass
metadata:
  name: vault-database
spec:
  provider: vault
  parameters:
    vaultAddress:
      "http://vault.default.svc.cluster.local:8200"
    roleName: "internal-app"
    objects: |
      - objectName: "db-password"
        secretPath: "internal/data/database/config"
        secretKey: "password"
```

Define a Pod with a Volume

```
spec:
  containers:
    - image: nginx
      name: webapp
      volumeMounts:
        - name: secrets-store-inline
          mountPath: "/mnt/secrets-store"
          readOnly: true
  volumes:
    - name: secrets-store-inline
      csi:
        driver: secrets-store.csi.k8s.io
        readOnly: true
        volumeAttributes:
          secretProviderClass: "vault-database"
```


05



Vault Secrets Operator

VSO Overview

[Installation Guide](#)




- Vault Secrets Operator (VSO) uses Kubernetes custom resources (CRDs) to manage secrets for services
- Secrets are managed by Vault and orchestrated in Kubernetes using custom resources
- The Vault Secrets Operator reconciles the current state with the desired state specified in the CRDs using declarative patterns.
- The operator facilitates secrets rotation, dynamic secrets management, and auditing capabilities
- Secret rotation is supported for *Deployment*, *ReplicaSet*, and *StatefulSet* resource types
- Requires:
 - Kubernetes 1.22+
 - Vault 1.11.0+

Custom Resources Deployment

- VSO is dependent on custom resources, to set up secret sync, users first deploy the Operator through one of two supported methods:
 - Helm: Our Helm chart is available in the HashiCorp Helm repository, at <https://helm.releases.hashicorp.com>
 - Kustomize: The Operator's GitHub repo includes the artifacts necessary for deploying an instance of the Operator with Kustomize.
- Once sync is configured the Operator handles any of the supported Secret CRs
- VSO supports the following CRs:
 - VaultConnection
 - VaultAuth
 - VaultDynamicSecret
 - VaultPKISecret

VSO Workflow



Vault Server Connection

[API Reference](#)

```
apiVersion: secrets.hashicorp.com/v1beta1
kind: VaultConnection
metadata:
  namespace: vso-example
  name: example
spec:
  # address to the Vault server
  address:
    http://vault.vault.svc.cluster.local:8200
```

Vault Auth

[API Reference](#)

```
apiVersion: secrets.hashicorp.com/v1beta1
kind: VaultAuth
metadata:
  namespace: vso-example
  name: example
spec:
  vaultConnectionRef: example
  # Method to use when authenticating to Vault
  method: kubernetes
  # Mount to use when authenticating to auth method
  mount: kubernetes
  kubernetes:
    role: demo
    serviceAccount: default
```

Vault Secret

[API Reference](#)

```
apiVersion: secrets.hashicorp.com/v1beta1
kind: VaultDynamicSecret
metadata:
  namespace: vso-example
  name: example
spec:
  vaultAuthRef: example
  mount: db
  path: creds/postgres
  destination:
    create: true
    name: dynamic1
```

Required Permissions

VSO requires specific Kubernetes permissions to function correctly

| Object | Permission | Reason |
|-----------------------|-------------------------------------|-----------------------------|
| Secret | create, read, update, delete, watch | Sync operations, Vault auth |
| ServiceAccount | read token creation | Vault auth |
| Deployment | read, update, watch | Postsecret rotation actions |

Pattern Comparison

[Comparison Blog Article](#)

| | Agent Sidecar | CSI | Vault Operator |
|----------------------------|--|---|---|
| Secret projection | Shared Memory Volume Environment Variable | Ephemeral Disk Environment Variables Kubernetes Secrets | Kubernetes Secrets, Kubernetes Secret Volumes Environment Variables |
| Secret scope | Global | Global | Global |
| Secret types | All Secret Engines (Static & Dynamic) | All Secret Engines (Static & Dynamic) | All Vault Secret Engines (Static & Dynamic) |
| Secret templating | Yes | No | Yes |
| Secret size limit | No Limit (both storage types) | No Limit (both storage types) | No Limit (both storage types) |
| Secret definitions | CLI / API / UI | CLI / API / UI | Vault CLI / API |
| Encryption | Yes (at rest & in-transit) | Yes (at rest & in-transit) | In transit via TLS, at-rest ** only if 'etcd' storage is encrypted |
| Secret rotation | Yes | No | Yes |
| Secret caching | Yes | No | Yes |
| Auditability | Yes | Yes | Yes |
| Deployment method | 1 Shared K8s Cluster Service + 1 Sidecar Container Per Application Pod | Daemonset | Kubernetes Deployment |
| Vault agent support | Yes | No | No |
| Helm support | Yes | Yes | Yes |

Resources

Resources

- [Vault on Kubernetes Security Considerations](#)
- [Vault on Kubernetes Deployment Guide](#)
- [Vault Helm Chart](#)
- [Vault Enterprise License Management - Kubernetes](#)
- [Helm Chart Examples](#)
- [Upgrading Vault on Kubernetes](#)
- [Running Vault - OpenShift](#)
- Tutorials - Vault Installation to Managed Kubernetes Services
 - [Google GKE](#)
 - [Azure AKS](#)
 - [Amazon EKS](#)
- [Comparison of Vault Integration Methods](#)
- [Tutorial: Vault Agent Injector](#)
- [Documentation: Agent Sidecar Injector](#)
- [Tutorial: Container Storage Interface \(CSI\)](#)
- [Documentation: CSI Provider](#)
- [Tutorial: Vault Secrets Operator \(VSO\)](#)
- [Documentation: VSO](#)
- [Integrate a Kubernetes Cluster with an External Vault](#)

Q&A



Thank you

customer.success@hashicorp.com

www.hashicorp.com/customer-success