

CarryPin OpenAPI definition

Description:

Sand-Box environment

HOST:<http://118.178.120.57:9009>

prod environment

HOST:<https://api.carrypin.com>

Any change in the interface will add a description before the interface, please refer to Annex II for details.

- New: indicates that the interface is added
- Changed: indicates that the interface content is modified
- Deprecated: indicates that the interface is no longer recommended
- No-encrypt: indicates that the interface is not encrypted

Contacts: flysky_qzf@163.com

Version:v2.1.4

[TOC]

Summary (Important)

Request Body Description

In this article, appld, accountId, appKey are provided by CarryPin

In this paper, we provide the appld, accountId, appKey is the public information open to partners, is used in order to facilitate the caller for debugging, if you want to get their own appld, accountId, appKey, please contact CarryPin staff

All requests received by CarryPin must be objects of the following form

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

name	description	require	type
appld	provided by CarryPin	true	string
accountId	provided by CarryPin	true	string
msg	The content is obtained by encrypting the concrete object	true	string

The content of the interface in this article is the request body of the original request

Note: Only addresses in the ip whitelist can be successfully accessed

How To Encrypt

AES Algorithm Distribution

Our system uses the AES tool class provided by hutool as the encryption and decrypting scheme. The following is the test code of AES in hutool

- in github
[hutool/hutool-crypto/src/main/java/cn/hutool/crypto/symmetric/AES.java](#)
- in gitee
[hutool-crypto/src/test/java/cn/hutool/crypto/symmetric/AESTest.java](#)

You can use the Settings belo

Data format :hex

Encryption and decryption mode :ECB

Data filling mode :PKCS7

or

Data format :UTF-8

Encryption and decryption mode :**ECB**

Data filling mode :**PKCS7**

Please note that the results of the two encryption methods are different. The cases provided in this article are only reference examples, and the content after specific encryption may not be consistent

The encryption function can be detected through the following websites

[AES在线解密](#) [AES在线加密](#) [Aes online hex 十六进制密钥](#) - [The X 在线工具 \(the-x.cn\)](#)

In order to ensure the security of data, we use Aes encryption to encrypt the requested content

```
package com.roushan.api.common.util;

import cn.hutool.crypto.SecureUtil;
import cn.hutool.crypto.symmetric.SymmetricAlgorithm;
import cn.hutool.crypto.symmetric.SymmetricCrypto;

/**
 * aes util
 *
 * @author CarryPin
 */
public class AesUtil {

    /**
     * @param key      your appId
     * @param content  your request body , json format
     * @return
     */
    public static String encrypt(String key, String content) {
        byte[] byteKey = SecureUtil.generateKey(SymmetricAlgorithm.AES.getValue(), key.getBytes()).getEncoded();
        SymmetricCrypto aes = SecureUtil.aes(byteKey);
        return aes.encryptBase64(content);
    }

    /**
     * @param key      your appId
     * @param content  CarryPin response body , json format
     * @return
     */
    public static String decrypt(String key, String content) {
        byte[] byteKey = SecureUtil.generateKey(SymmetricAlgorithm.AES.getValue(), key.getBytes()).getEncoded();
        SymmetricCrypto aes = SecureUtil.aes(byteKey);
        return aes.decryptStr(content);
    }
}
```

encrypt demo

```
import com.alibaba.fastjson2.JSON;
import com.roushan.api.common.util.AesUtil;
import lombok.Data;

/**
 * @author CarryPin
 * @date 2023/9/5
 */
public class EncryptDemo {

    public static void main(String[] args) {
        String appId = "2023072638647825";
        String appKey = "5h6%DerF65K8oj0ElAmB#c9SgDDFLXPD";
        String accountId = "2023072638647824";

        GetTokenVo vo = new GetTokenVo();
        vo.setAppId(appId);
        vo.setAppKey(appKey);
        System.out.println("encrypt request body :" + AesUtil.encrypt(appId, JSON.toJSONString(vo)));

        /**
         * this is response example
         */
        String responseBody = "M0iJDsWB1G0I3uvWTQFy3G/xy1WKLflasBnYjpbVa7CXcA4tY+xujX1AQFdcKiFuznkwrt/IR27zrHWZtITLJ8y900jvIfuei";
        System.out.println("decrypt response body :" + AesUtil.decrypt(appId, responseBody));

    }

    @Data
    public static class GetTokenVo {

        private String appId;

        private String appKey;

    }
}
```

Authentication Check

introduce :

token authentication is requested. The token is valid for 2 hours and automatically becomes invalid after it expires

The token is obtained by the getToken interface and is required in all interfaces except getToken

realize :

Add the following parameters to the request header of the request

name	require	description
appld	true	appld
Authorization	true	"Bearer" and space before the temporary access token value

Request Body

introduce :

All request bodies are in the following format. The only difference is that msg is encrypted by different request contents. For specific request contents, refer to the description of request bodies in each interface

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

Interface V 1.x

Get Token

Basic info

- url: /api/getToken
- method: POST
- produces: application/x-www-form-urlencoded,application/json
- consumes: */*
- Request frequency limit: 5 times /60 seconds
- Note:

Request Body

RequestBody

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body , Refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "appKey": "5h6%DerF65K8oj0E1AmB#c9SgDDFLXPD"
}
```


Params:

name	description	require	type
appld	appld	true	string
appKey	appKey	true	string

Response body

Example

```
M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CXcA4tY+xujX1AQFdcKiFuznkwrt/IR27zrHWZtITLJ8y900jvIfueujJ2k9SouybRmMAASGC9EE/Z/+qYbue
```



According to the above return value, decrypt the content by appId: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": "1rbmuu130m0of1zmjajizl4qvqi9nh64",
  "msg": "success"
}
```

Response Params:

name	description	type

appld name	appld description	string type
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data	token	string

Get Account Info

Basic info

url: /api/getAccount

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Request frequency limit: 5 times /60 seconds

Note:

Request Body

RequestBody

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "2023072638647825"
}
```

Params:

name	description	require	type
userId	appld	true	string

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CkWqKmp+TuP5KH05ereiaS5v0GLY5B4ZZ1idiMP2PSmHm2TUiv/vhEoKHj00rv7ZBX2/KX99VK5jXaFLW4JOM



According to the above return value, decrypt the content by appld: 2023072638647825 refer to [encrypt demo](#)

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "accounts": [
      {
        "balance": 5706.35,
        "currency": "CNY",
        "effective": true,
        "walletId": "2023100853497077"
      },
      {
        "balance": 997121.67,
        "currency": "EUR",
        "effective": true,
        "walletId": "2023100853497076"
      },
      {
        "balance": 100006.00,
        "currency": "HKD",
        "effective": true,
        "walletId": "2023100853497079"
      },
      {
        "balance": 48208.07,
        "currency": "USD",
        "effective": true,
        "walletId": "2023100853497078"
      }
    ],
    "userId": "2023072638647825"
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer(int32)
msg	Response message success "success", Failure Others	string
data	account info	
userId	user id	string
accounts	account info ,Note that this is a collection object	array
walletId	Wallet id	string
currency	Wallet currency	string
balance	Wallet balance	number
effective	Is the wallet valid	boolean

(Changed)Get Product Info

Basic info

url: /api/getItem

method: POST

produces: application/x-www-form-urlencoded, application/json

consumes: */*

Request frequency limit: 5 times /60 seconds

Note:

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "appId": "2023072638647825",
  "currencyCode": "CNY",
  "language": "en",
  "current": 1,
  "itemId": "",
  "itemName": "",
  "size": 10
}
```

Params:

name	description	require	type
size	page size	true	integer(int32)
current	page number	true	integer(int32)
appld	appld	true	string
itemId	itemId	false	string
itemName	itemName	false	string
currencyCode	currency(Refer to Annex I)	false	string
language	zh:chinese,en:english; empty value or any other values will be treated as english	false	string

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CkwqKmp+TuP5KH05ereiaSvGRRM7cetnVxLte6rVr7ZZ25FtgupfJd6oQn+JFdyueUH7b39dF6pRU95e1yxrWK

According to the above return value, decrypt the content by appId: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "current": 1,
    "pages": 1,
    "records": [
      {
        "currencyCode": "HKD",
        "itemBrandName": "Nintendo",
        "itemId": "2023120137631311",
        "itemName": "Nintendo Hong Kong",
        "itemTitle": "Nintendo Hong Kong",
        "spuImage": "",
        "howExchange": "",
        "description": "",
        "spuType": 2,
        "skus": [
          {
            "maxFaceValue": 100.00,
            "maxPrice": 94.86,
            "minFaceValue": 100.00,
            "minPrice": 94.86,
            "skuId": "2023120137631312",
            "skuName": "Nintendo HK 100 HKD",
            "skuPrice": 94.86,
            "skuPriceCurrency": "HKD"
          }
        ]
      },
      {
        "currencyCode": "USD",
        "itemBrandName": "Nintendo",
        "itemId": "2024010471872891",
        "itemName": "Nintendo USD",
        "itemTitle": "",
        "spuImage": "",
        "howExchange": "",
        "spuType": 2,
        "skus": [
          {
            "maxFaceValue": 200.00,
            "maxPrice": 204.00,
            "minFaceValue": 1.00,
            "minPrice": 1.02,
            "skuId": "2024010471929913",
            "skuName": "Nintendo 1USD",
            "skuPriceCurrency": "USD"
          }
        ]
      }
    ],
    "size": 10,
    "total": 2
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer

name msg	description Response message success "success", Failure Others	type string
data		
current	For the current page, the default is 1	integer
size	page size	integer
total	item total size	integer
pages	page number	integer
records	item list .Note that this is a collection object	array
itemId	spu id	string
itemName	spu name	string
itemTitle	spu description	string
itemBrandName	spu brand name	string
currencyCode	transaction currency	string
description	spu detailed introduction	string
howExchange	how to exchange	string
spuType	spu type 1:game 2:giftcard 3:software 4:microsoft product	integer
skus	sku list. Note that this is a collection object	array
skuld	sku id	string
skuName	sku name	string
skuPrice	price (when purchase custom face value sku ,this param no value)	number
skuPriceCurrency	currency need to pay	string
maxFaceValue	max facevalue of sku	number
minFaceValue	min facevalue of sku	number
maxPrice	The price of the largest denomination sku	number
minPrice	The price of the smallest denomination sku	number

(Changed)Get ALL Product Info

Basic info

```
url: /api/getAllItem
method: POST
produces: application/x-www-form-urlencoded,application/json
consumes: */*
Request frequency limit: 2 times /1 hour
Note: get all product by one time
```

Request Body

```
Request Body
```

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body


```
{
  "appId": "2023072638647825",
  "currencyCode": "CNY",
  "language": "en",
  "itemId": "",
  "itemName": ""
}
```

Params:

name	description	require	type
appId	appId	true	string
itemId	itemId	false	string
itemName	itemName	false	string
currencyCode	currency(Refer to Annex I)	false	string
language	zh:chinese,en:english; empty value or any other values will be treated as english	false	string

Response body

Example



According to the above return value, decrypt the content by appId: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": [
    {
      "currencyCode": "JPY",
      "itemBrandName": "Nintendo",
      "itemId": "2023111340710725",
      "itemName": "Nintendo Japan",
      "spuType": 2,
      "skuList": [
        {
          "maxFaceValue": 200,
          "maxPrice": 1.33,
          "minFaceValue": 200,
          "minPrice": 1.33,
          "skuId": "2023111340882805",
          "skuName": "Nintendo Japan 200 JPY",
          "skuPriceCurrency": "USD"
        },
        {
          "maxFaceValue": 1000,
          "maxPrice": 7.6,
          "minFaceValue": 1000,
          "minPrice": 7.6,
          "skuId": "2024060456840458",
          "skuName": "Nintendo JP 1000 JPY",
          "skuPriceCurrency": "USD"
        },
        {
          "maxFaceValue": 500,
          "maxPrice": 3.95,
          "minFaceValue": 500,
          "minPrice": 3.95,
          "skuId": "2024060456840460",
          "skuName": "Nintendo JP 500 JPY",
          "skuPriceCurrency": "USD"
        }
      ]
    }
  ],
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
itemId	spu id	string
itemName	spu name	string
itemBrandName	spu brand name	string
currencyCode	transaction currency	string
spuType	spu type 1:game 2:giftcard 3:software 4:microsoft product	integer

name	description	type
skuList	sku list. Note that this is a collection object	array
skuld	sku id	string
skuName	sku name	string
skuPriceCurrency	currency need to pay	string
maxFaceValue	max facevalue of sku	number
minFaceValue	min facevalue of sku	number

Get Stock

Basic info

url: /api/getStock

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Request frequency limit: 5 times /60 seconds

Note:

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "skuIds": [ "2023062047862488", "2023062047816482" ]
}
```

Params:

name	description	require	type
skulds	skuld list	true	array

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7BQ2Gt1mPGipwxLbn+iAEF4KvZa2fsOvKv9k2gqz6Ex4IhVcd/jEGpPEzds2Gxo/B3vgmxzyAIkz2x1VV2I+tH

According to the above return value, decrypt the content by appId: 2023072638647825 refer to encrypt demo

```
{
  "appId": "2023080859462701",
  "code": 200,
  "data": [
    {
      "number": 0,
      "skuId": "2023062047752453"
    },
    {
      "number": 6,
      "skuId": "2023062047862488"
    }
  ],
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		stock info list
number	Inventory quantity (if return -1 ,means no limit)	integer
skuld	sku id	integer

(Changed)Get Product And Stock Info

Basic info

url: /api/getItemAndStock

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Request frequency limit: 5 times /60 seconds

Note:

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "appId": "2023072638647825",
  "currencyCode": "CNY",
  "current": 1,
  "itemId": "",
  "itemName": "",
  "size": 10
}
```

Params:

name	description	require	type
size	page size	true	integer(int32)
current	page number	true	integer(int32)
appId	appId	true	string
itemId	itemId	false	string
itemName	itemName	false	string
currencyCode	currency	false	string

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1wKLf1asBnYjpbVa7CkwQKmp+TuP5KH05ereiaSvGRRM7cetnVxLte6rVr7Z25FtgupfJd6oQn+JFdyueUH7b39dF6pRU9Se1yxrWK

According to the above return value, decrypt the content by appId: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "current": 1,
    "pages": 1,
    "records": [
      {
        "currencyCode": "HKD",
        "itemBrandName": "Nintendo",
        "itemId": "2023120137631311",
        "itemName": "Nintendo Hong Kong",
        "itemTitle": "Nintendo Hong Kong",
        "spuImage": "",
        "howExchange": "",
        "spuType": 2,
        "skuInfos": [
          {
            "maxFaceValue": 100.00,
            "maxPrice": 86.86,
            "minFaceValue": 100.00,
            "minPrice": 86.86,
            "skuId": "2023120137631312",
            "skuName": "Nintendo HK 100 HKD",
            "skuPrice": 86.86,
            "skuPriceCurrency": "CNY",
            "stock": -1
          }
        ]
      },
      {
        "currencyCode": "USD",
        "itemBrandName": "Nintendo",
        "itemId": "2024010471872891",
        "itemName": "Nintendo USD",
        "itemTitle": "",
        "spuImage": "",
        "howExchange": "",
        "spuType": 2,
        "skuInfos": [
          {
            "maxFaceValue": 200.00,
            "maxPrice": 1460.00,
            "minFaceValue": 1.00,
            "minPrice": 7.30,
            "skuId": "2024010471929913",
            "skuName": "Nintendo 1USD",
            "skuPriceCurrency": "CNY",
            "stock": -1
          }
        ]
      }
    ],
    "size": 10,
    "total": 2
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string

code name	Response status code success 200, failure other description	integer type
msg	Response message success "success", Failure Others	string
data		
current	For the current page, the default is 1	integer
size	page size	integer
total	item total size	integer
pages	page number	integer
records	item list .Note that this is a collection object	array
itemId	spu id	string
itemName	spu name	string
itemTitle	spu description	string
itemBrandName	spu brand name	string
currencyCode	transaction currency	string
skus	sku list. Note that this is a collection object	array
skuld	sku id	string
skuName	sku name	string
skuPrice	price (when purchase custom face value sku ,this param no value)	number
skuPriceCurrency	currency need to pay	number
maxFaceValue	max facevalue of sku	string
minFaceValue	min facevalue of sku	number
maxPrice	The price of the largest denomination sku	
minPrice	The price of the smallest denomination sku	
stock	sku stock number(-1 means no limit)	number

Place Order

Basic info

url: /api/placeOrder

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note: Card purchase service is available

Request Body

Request Body


```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "2023072638647825",
  "accountId": "2023072638647824",
  "currency": "USD",
  "serviceOrder": "1caf9f17-370e-112a-1e14-3c229sdfs99",
  "detailVos": [
    {
      "skuId": "2024010953617553",
      "faceValue": 12,
      "buyNum": 1
    }
  ]
}
```

Params:

name	description	require	type
userId	appld	true	string
accountId	account Id	true	string
currency	currency(The currency of payment)	true	string
serviceOrder	The service tracking number (provided by the caller)	true	string
detailVos	Goods to buy Note that this is a collection object	true	array
skuld	skuld	true	string
faceValue	sku facevalue (required ,when purchasing a custom par sku)	false	number
buyNum	buy number	true	integer

please ensure `serviceOrder` is unique, CarryPin will check this value, if repeated, you can not place the order

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CkWqKmp+TuP5KH05ereiaSBRtCTze5E/eppEin4WQp6FMoNVsruI5cT0M9D4FuXJ6x02swrDkrSlpBfCeJRGZ

Decrypt the content in the following format according to the return value above , Refer to [encrypt demo](#)

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "code": 200,
    "data": "2024011148886234",
    "message": "success"
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
data	order id	integer
message	Response message	integer

Get Order History

Basic info

url: /api/getOrderInfo

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note:

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "uesrId": "appId",
  "current": 1,
  "size": 10
}
```

Params:

name	description	require	type
uesrId	app Id	true	string
current	page number	true	integer
size	page size	true	integer

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1wKLf1asBnYjpbVa7CkWqKmp+TuP5KH05ereiaSvGRRM7cetnVxLte6rVr7Z25FtgupfJd6oQn+JFdyueXvwzrkb9KR8u6k0TY2PRH

According to the above return value, decrypt the content by appld: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "current": 1,
    "pages": 1,
    "records": [
      {
        "createTime": "2024-01-11 13:34:47",
        "cur": "USD",
        "deliveryStatus": 1,
        "orderId": "2024011148886234",
        "orderStatus": 0,
        "orderWay": 105,
        "totalAmount": 12.37,
        "orderDirectstatus": 0
      },
      {
        "createTime": "2024-01-09 15:53:08",
        "cur": "CNY",
        "deliveryStatus": 3,
        "orderId": "2024010957188439",
        "orderStatus": 1,
        "orderWay": 103,
        "totalAmount": 10.45,
        "orderDirectstatus": 0
      },
      {
        "createTime": "2024-01-09 15:48:28",
        "cur": "CNY",
        "deliveryStatus": 3,
        "orderId": "2024010956907157",
        "orderStatus": 1,
        "orderWay": 103,
        "totalAmount": 10.45,
        "orderDirectstatus": 0
      },
      {
        "createTime": "2024-01-09 15:28:11",
        "cur": "USD",
        "deliveryStatus": 3,
        "orderId": "2024010955690833",
        "orderStatus": 1,
        "orderWay": 105,
        "totalAmount": 126.39,
        "orderDirectstatus": 0
      },
      {
        "createTime": "2024-01-09 15:10:46",
        "cur": "USD",
        "deliveryStatus": 3,
        "orderId": "2024010954645785",
        "orderStatus": 1,
        "orderWay": 105,
        "totalAmount": 126.39,
        "orderDirectstatus": 0
      },
      {
        "createTime": "2024-01-09 15:09:11",
        "cur": "USD",
        "deliveryStatus": 3,
        "orderId": "2024010954550779",
        "orderStatus": 1,
        "orderWay": 105,
        "totalAmount": 126.39,

```

```
        "orderDirectstatus":0
    }
  ],
  "size": 10,
  "total": 6
},
"msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer(int32)
msg	Response message success "success" Failure Others	string
data		
current	Current page	integer(int64)
size	Gets the number of items displayed per page	integer(int64)
total	Total number of rows currently satisfying the condition	integer(int64)
pages	The total number of pages in the current paging	integer(int64)
records		array
orderId	orderId	string
orderStatus	Order status 0: Not completed, 1: Completed	integer
deliveryStatus	Status of shipment. 1: to be shipped, 2: partially shipped, 3: fully shipped	integer
orderWay	order Way	integer
createTime		string
totalAmount	total amount	number
totalAmount	total amount	number
orderDirectstatus	TOP-UP result(only used for TOP-UP products) 0:processing , 1:fail , 2:success	number

Get Order Detail Info

Basic info

url: /api/getOrderInfoAndDetail

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note:

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "appId",
  "orderId": "2024010955690833"
}
```

Params:

name	description	require	type
userId	appld	true	string
orderId	order Id	true	string

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1wKlf1asBnYjpbVa7CkWqKmp+TuP5KH05ereiaSo2Hyhah4C4aHiV90w18X91RitCFrwRIGKA/T41YRP10LY1ZNErnSuUhh+8T8mE

According to the above return value, decrypt the content by appld: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "firstTo": {
      "createTime": "2024-01-09 15:28:11",
      "deliveryStatus": 3,
      "orderId": "2024010955690833",
      "orderStatus": 1,
      "orderWay": 105,
      "totalAmount": 126.39,
      "orderDirectstatus": 0,
    },
    "secondTos": [
      {
        "actualPaidPrice": 126.39,
        "actualPaidPriceCur": "USD",
        "buyNum": 1,
        "discountRatioStr": "0.00%",
        "faceValue": 5.00,
        "isEnd": 1,
        "originalPrice": 126.39,
        "originalPriceCur": "EUR",
        "sendOutNum": 1,
        "skuId": "2024010953617553",
        "skuName": "Adidas Germany DE",
        "spuName": "Adidas Germany"
      }
    ]
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer(int32)
msg	Response message success "success" Failure Others	string
data		OrderInfoAndDetailOutTo
firstTo		
orderId	orderId	string
orderStatus	Order status 0: Not completed, 1: Completed	integer
deliveryStatus	Status of shipment 1: to be shipped, 2: partially shipped, 3: fully shipped	integer
orderWay	order way	integer
createTime	Time of order	string
totalAmount	Total price	number
cur	currency	string
orderDirectstatus	TOP-UP result(only used for TOP-UP products) 0:processing , 1:fail , 2:succes	number
secondTos		array
skuld	Sku id	string
skuName	sku name	string
spuName	item name	string
isEnd	Finished or not 0: Not finished, 1: finished	integer
buyNum	Quantity purchased	integer
faceValue	purchased sku facevalue	number
sendOutNum	The quantity shipped	integer
originalPrice	Original price	number
originalPriceCur	Original currency	string
actualPaidPrice	Actual price paid	number
actualPaidPriceCur	Actual payment currency	string
discountRatioStr	Percentage discount	string

Get Order Code

Basic info

```
url: /api/getBuyCard
method: POST
produces: application/x-www-form-urlencoded,application/json
consumes: */*
Note:
```

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body


```
{
  "userId": "appId",
  "orderId": "2024010955690833",
  "current": 1,
  "size": 10
}
```

Params:

name	description	require	type
userId	appld	true	string
orderId	order Id	true	string
current	page number	true	Integer
size	page size (max:2000)	true	Integer

Response body

Example



According to the above return value, decrypt the content by appId: 2023072638647825 refer to **encrypt demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "current": 1,
    "pages": 1,
    "records": [
      {
        "card": "db69179d-bbe1-457b-aeae-741adc62c07b",
        "skuId": "2024032040589254"
      },
      {
        "card": "db69179d-bbe1-457b-aeae-741adc62c07b",
        "pinCode": "db69179d-bbe1-457b",
        "skuId": "2024032040589254",
        "snCode": "aeae-741adc62c07b"
      }
    ],
    "size": 10,
    "total": 2
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
current	page number	integer
pages	The total number of pages in the current paging	integer
size	Gets the number of items displayed per page	integer
total	Total number of rows currently satisfying the condition	integer
records	code list	array
skuld	purchase skuld	string
card	code	string
pinCode	pinCode	string
snCode	snCode	string

Get direct top-up Param

Basic info

url: /api/getDirectParam

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note:

Request Body

Request Body:

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "2023072638647825",
  "skuId": "2024032040589254"
}
```


Params:

name	description	require	type
userId	appld	true	string
skuld	skuld	true	string

name	description	require	type
------	-------------	---------	------

Response body

Example



According to the above return value, decrypt the content by appld: 2023072638647825 refer to [encrypt demo](#)

```
{
  "appId": "",
  "code": 0,
  "msg": "",
  "data": {
    "code": 0,
    "msg": "",
    "paramInfos": [
      {
        "name": "",
        "type": "",
        "label": "",
        "placeholder": "",
        "values": [
          {
            "value": "",
            "label": ""
          }
        ]
      }
    ]
  }
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data	Response data	
code	Response status	integer
msg	Response message	string
paramInfos	Direct Top-up parameter list .Note that this is a collection object	array
name	parameter name	string
type	parameter type . input/select	string
label	parameter label	string
placeholder	placeholder	string
values	List of enumerated values if parameter type is select. Note that this is a collection object	array
value	The enum value	string
label	The enum label	string

Place Order (Direct Top-up)

Basic Info

url: /api/placeDirectOrder

method: POST

produces: application/x-www-form-urlencoded, application/json

consumes: */*

Note: Please obtain the direct top-up parameters before placing an order

Request Body

Request Body:

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "2023072638647825",
  "accountId": "2023072638647824",
  "currency": "EUR",
  "serviceOrder": "1caf9f17-370e-112a-1e14-3c229sdfs99",
  "skuId": "2023111340882805",
  "faceValue": 500,
  "attributeValues": [
    {
      "name": "player ID",
      "value": "1234",
      "label": "Player ID"
    }
  ]
}
```


Params:

name	description	require	type
userId	appld	true	string
accountId	account Id	true	string
currency	currency(The currency of payment)	true	string
serviceOrder	The service tracking number (provided by the caller)	true	string
skuld	skuld	true	string
faceValue	sku facevalue (required ,when purchasing a custom par sku)	false	number
attributeValues	parameter list	false	array
name	parameter name	true	string
value	parameter value	true	string
label	parameter label	false	string

please ensure serviceOrder is unique, CarryPin will check this value, if repeated, you can not place the order

Response Body

Example



Decrypt the content in the following format according to the return value above , Refer to [encrypt demo](#)

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "code": 200,
    "data": "2024011148886234",
    "message": "success"
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
data	order id	integer
message	Response message	integer

Interface V 2.x

Place Order V2

Basic info

url: /api/v2/placeOrder

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note: Provide card purchase service and card activation service

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "2023072638647825",
  "accountId": "2023072638647824",
  "currency": "USD",
  "serviceOrder": "{your serice order }",
  "chargeAccountType": 1,
  "chargeAccountName": "{your charge account}",
  "returnUr1": "{your return url}",
  "detailVos": [
    {
      "skuId": "2024032040589254",
      "faceValue": 30,
      "buyNum": 1
    }
  ]
}
```

Params:

name	description	require	type
userId	appld	true	string
accountId	account Id	true	string
currency	currency(The currency of payment)	true	string
serviceOrder	The service tracking number (provided by the caller)	true	string
chargeAccountType	Whether to activate the service. 1 indicates yes, 0 indicates no	true	integer
chargeAccountName	Activate the account with the recharge code. If chargeAccountType is 1, it is required	false	string
returnUrl	Recharge code Callback address of the activation result	false	string
detailVos	Goods to buy Note that this is a collection object	true	array
skuld	skuld	true	string
faceValue	sku facevalue (required ,when purchasing a custom par sku)	false	number
buyNum	buy number	true	integer

- 1. please ensure serviceOrder is unique, CarryPin will check this value, if repeated, you can not place the order
- 2. We will notify the caller immediately after the end of the recharge, and if the caller does not return the successful content, we will notify the caller at 1 second, 5 seconds, 20 seconds, 1 minute, 2 minutes, 5 minutes, 10 minutes after the result is obtained

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CkKwKmp+TuP5KH05ereiaSBRtCTze5E/eppEin4WQp6KaAQDIoImWeiHBmgA/Y5WPGMWhlbyCS4fhfLr9aPfr

Decrypt the content in the following format according to the return value above , Refer to [encrypt demo](#)

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "code": 200,
    "data": "2024032240914951",
    "message": "success"
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
data	order id (you can query charge service status by this)	string
message	Response message	string

Code Activate

Basic info

url: /api/v2/codeActivate

method: POST

produces: application/x-www-form-urlencoded, application/json

consumes: */*

Note: Provide card activation service

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body

```
{
  "userId": "2023072638647825",
  "carryPinCodes": [
    "{carryPin code}"
  ],
  "chargeAccount": "{your charge account}",
  "notifyUrl": "{your return url}"
}
```

Params:

name	description	require	type
userId	appld	true	string
carryPinCodes	carryPin codes	true	list
chargeAccountName	Activat account (like steam account name)	true	string
returnUrl	The return interface provided by the caller, if it exists, we will notify the caller after the recharge is finished	false	string

1. **We will do it at 1 second, 5 seconds, 20 seconds, 1 minute, 2 minutes, 5 minutes, 10 minutes after the end of the recharge

Response body

Example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CkWqKmp+TuP5KH05ereiaS5ZZxQD4GjaxsWpubXYZwt9bmBjIKswwsneCvZPyuo4E4LHF4490FUL0OuWbX41s

Decrypt the content in the following format according to the return value above , Refer to [encrypt demo](#)

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "code": 200,
    "msg": "Success",
    "orderServiceId": "2024032251303686"
  },
  "msg": "success"
}
```

Response Params:

name	description	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		
code	Response status	integer
orderServiceId	charge service order id , by this can check charge status	string
message	Response message	string

Query Activate status

Basic Info

url: /api/v2/queryCodeActivate

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note: query card activate status

Request Body

Request Body

```
{
  "appId": "provided by CarryPin",
  "accountId": "provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg is encrypted by the following request body


```
{
  "userId": "2023072638647825",
  "orderServiceId": "{CarryPinOrderId} or {orderServiceId}"
}
```

Params:

name	description	require	type
userId	appld	true	string
orderServiceId	Order number (palce order interface return) or service order number (code activate interface return)	true	string

Response body

Example



Decrypt the content in the following format according to the return value above , Refer to [encrypt demo](#)

```
{
  "code": 200,
  "msg": "成功",
  "stateCode": null,
  "data": {
    "orderServiceId": "2024032251303686",
    "rechargeMoney": 30,
    "finishMoney": 0,
    "serviceStatus": 1,
    "codesList": [
      {
        "carryPinCode": "920e9df7-*****-c16679b59071",
        "status": "PROCESSING",
        "failMessage": null
      }
    ]
  }
}
```

Response Params:

param	desc	type
appld	appld	string
code	Response status code success 200, failure other	integer
msg	Response message success "success", Failure Others	string
data		

orderServiceId param	charge service order id desc	string type
rechargeMoney	expecte recharge money	string
finishMoney	finish recharge money	string
serviceStatus	Recharge status (1 recharge 2 recharge completed 3 recharge abnormal (partially successful) 4 recharge failed)	string
codesList	carryPin codes	list
carryPinCode	carryPin code	string
status	code status	string
failMessage	error msg	string

(No-encrypt)Notify recharge result

Basic Info

```
url: {your callback url}

method: POST

produces: application/x-www-form-urlencoded,application/json

consumes: */*

Note: Notify the recharge result , ==encryption measures are not adopted on this interface==
```

Reuquest Body

Request Body

```
{
  "orderServiceId": "2024032251303686",
  "rechargeMoney": 30,
  "finishMoney": 0,
  "serviceStatus": 1,
  "codesList": [
    {
      "carryPinCode": "920e9df7-*****-c16679b59071",
      "status": "PROCESSING",
      "failMessage": null
    }
  ]
}
```

params:

param	desc	type
orderServiceId	charge service order id	string
rechargeMoney	expecte recharge money	string
finishMoney	finish recharge money	string
serviceStatus	Recharge status (1 recharge 2 recharge completed 3 recharge abnormal (partially successful) 4 recharge failed)	string
codesList	carryPin codes	list
carryPinCode	carryPin code	string

param	status	code	status	desc	string	type
failMessage				error msg		string

Response Body

response body

success

- success

Back to success, we assume you have received the notification and will not continue to notify you

- Any other string or content

We will do it at 1 second, 5 seconds, 20 seconds, 1 minute, 2 minutes, 5 minutes, 10 minutes after the end of the recharge until we get a success message from the caller

Interface V 3.x

Topup parameter fetching

Basic Info

url: /api/v3/getCodeParamInfo

method: POST

produces: application/x-www-form-urlencoded,application/json

consume: */*

Note :

Request body

Request body

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg:encrypted by the request body below

```
{
  "userId": "2023072638647825",
  "carryPinCodes": [
    "{carryPin code}"
  ]
}
```

parameter:

parameter	description	mandatory	type
userId	appId	true	string
carryPinCodes	activationcode	true	list

response body

example

f5x9jj+Qw19RqWJm5Epx+x0dGUL5RLHtAgkdQt3PfXmXt2Pmbrpb9WWliG8/I2a+ezRKs0D03hrf7ni4MuKYjdo0yrfpu9t30019WkUe1Kz0uBRiUXFJtoXE37jabH1

decrypt the response body by your Appld , refer to **encryption demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "code": 200,
    "msg": "成功",
    "codeParamInfos": [
      {
        "carryPinCode": "{carryPin code}",
        "paramInfos": [
          {
            "name": "{name}",
            "type": "{type}",
            "values": [
              {
                "value": "{value}",
                "label": "{label}"
              }
            ],
            "label": "{label}",
            "placeholder": "{placeholder}"
          }
        ]
      }
    ]
  },
  "msg": "success"
}
```

**response parameter.*

name	description	type
appld	appld	string
code	200 equals to success , else fail	integer
msg	success or others	string
data		
code	status	integer
msg	msg	string
codeParamInfos	topup parameter information	array
carryPinCode	topup code	string
paramInfos	topup parammeter	array
name	Attribute names	string
type	type	string
label	label	string
placeholder	placeholder	string
values	enumeration	array
value	value	string
label	label	string

name	description	type
Topup activation		

Basic Info

url: /api/v3/codeActivate
method: POST
produces: application/x-www-form-urlencoded,application/json
consume: */*
note :

Request body

Request body

```
{
  "appId": "provided by CarryPin",
  "accountId":"provided by CarryPin",
  "msg": "Encrypted request body"
}
```

msg:encrypted by the request body below

```
{
  "userId": "2023072638647825",
  "codeParams": [
    {
      "carryPinCode": "{carryPinCode}",
      "paramValues": [
        {
          "name": "{name}",
          "value": "{value}"
        }
      ]
    }
  ],
  "notifyUrl": "{notifyUrl}"
}
```

Parameter:

Parameter	description	Mandatory	type
userId	appId	true	string
codeParams	code list	true	list
carryPinCode	topup code	true	string
paramValues	topup parameters	true	list
name	name	true	string
value	value	true	string
notifyUrl	notification address	false	string

Response body

example

M0iJDsWB1G0I3uvWTQFy3G/xy1WKLf1asBnYjpbVa7CkWqKmp+TuP5KH05ereiaS5ZZxQD4GjxswpubXYZwt9bmBjIKswwsneCvZPyuo4E4LHF4490FUL00uWbX41s

decrypt the response body by your Appld , refer to **encryption demo**

```
{
  "appId": "2023072638647825",
  "code": 200,
  "data": {
    "code": 200,
    "msg": "Success",
    "orderServiceId": "2024032251303686"
  },
  "msg": "success"
}
```

Response parameter:

Parameter	Description	Type
appld	appld	string
code	200 equals to success , else fail	integer
msg	success or others	string
data		
code	status	integer
orderServiceId	topup orderId used to query topup status	string
message	message	string

Annex I 《CarryPin Currency Directory》

Country	Currency
Thailand	THB
China	CNY
Saudi Arabia	SAR
Hong Kong (China)	HKD
South Africa	ZAR
United States	USD
Indonesia	IDR
Vietnam	VND
Ukraine	UAH
European Union	EUR
India	INR
Malaysia	MYR
Turkey	TRY
Japan	JPY
Taiwan (China)	TWD

South Korea Country	KRW Currency
Brazil	BRL
Australia	AUD
Poland	PLN
Britain	GBP
The United Arab Emirates	AED
Qatar	QAR
Columbia	COP
New Zealand	NZD
Chile	CLP
Romania	RON
Sweden	SEK
Norway	NOK
Denmark	DKK
Kuwait	KWD
Canada	CAD
Mexico	MXN
Russia	RUB
Singapore	SGD
Argentina	ARS
Philippines	PHP
Switzerland	CHF
Czech Republic	CZK
Hungary	HUF
Peru	PEN
Morocco	MAD
Jordan	JOD

Annex II 《CarryPin Version Logs》

This section records the changes of all version updates since V1.2.0

V 1.2.1 2023-09-12

- Summary
 - 1. Request body add prod environment
- Place Order
 - 1. Request body add parameter **userId**
- Get Order History
 - 1. Request body change parameter from **accountId** to **userId**
 - 2. Request body change parameter from **pageSie** to **size**
 - 3. Request body change parameter from **pageNum** to **current**
- Get Order Detail Info

- 1. Request body add parameter **userId**
- Get Order Code
 1. Request body add parameter **userId**
 2. Response body modify **data** from an array object to an entity object

V 1.2.2 2023-09-13

- Place Order
 1. Delete the parameter **itemId** from the **detailVos** object
 2. Delete the parameter **itemName** from the **detailVos** object
 3. Delete the parameter **skuName** from the **detailVos** object

V 1.2.3 2023-09-14

- Get Stock
 1. Response body modify **data** from an entity object object to an array
 2. Request body change parameter from **skuld** to **skulds**
 3. Request body modify **skulds** from an string object object to an array
- Get Order Code
 1. Response body modify **records** , change from an array of strings to an array of objects

V 1.2.4 2023-09-21

- How To Encrypt
 1. add aes distribution

V 1.2.5 2023-10-16

- Added interfaces for obtaining commodity information and inventory information

V 1.2.6 2023-10-25

- Fix some documentation errors
- Increased call interface frequency limit

V 1.2.7 2023-12-03

- Add ip address whitelist

V 1.2.8 2024-01-11

- ==Increased supply of custom denominations==
- Modify the return parameter of the `getItemAndStock` interface
- Modify the return parameter of the `getItem` interface
- Modify the `placeOrder` interface request parameters
- Modify the return parameter of the `getOrderInfoAndDetail` interface
- Modify the Get Stock interface return. If -1 is returned, there is no limit
- Add annex `Supported Currency Catalog`

V 1.2.9 2024-01-16

- change dev ip

V 2.1.0 2024-03-21

- Provides a new ordering interface to support the code activation service for your account while placing an order for a card
- Provide code activation service
- Provides an interface for querying activation code results
- Provides an asynchronous notification activation result interface
- Change `getCode` interface , in response body ,add `pinCode` and `snCode`

V 2.1.1 2024-07-02

- change dev ip address

V 2.1.2 2024-07-23

- add new interfance `getAllItem`

V 2.1.3 2024-09-11

- `Get Product Info` add return param `spuImage` ,`howExchange`
- `Get Product And Stock Info` add return param `spuImage` ,`howExchange`

V 2.1.4 2024-11-15

- Get Product Info add return param spuType
- Get Product And Stock Info add return param spuType
- Get All Product add return param spuType

V 2.1.5 2025-03-19

- Topup parameter fetching
- Topup activation

V 2.1.6 2025-04-18

- add new interface getDirectParam
- add new interface placeDirectOrder

V 2.1.7 2025-04-28

- add TOP-UP status orderDirectStatus

V 2.1.8 2025-06-12

- Get Product Info add request param 'language'
- Get Product Info add return param description
- Get All Product add request param language