

Que-1.

Create a MySQL table called playlists to store Spotify-style music playlists, with columns: playlist_id (primary key), user_id (foreign key), name (varchar), and created_at (datetime). Write the CREATE TABLE statement.

Ans:-

```
CREATE TABLE playlists (  
    playlist_id INT AUTO_INCREMENT PRIMARY KEY,  
    user_id INT,  
    name VARCHAR(100),  
    created_at DATETIME DEFAULT CURRENT_TIMESTAMP,  
    FOREIGN KEY (user_id) REFERENCES SpotifyUser(user_id)  
);
```

Que-2.

Insert three sample records into the playlists table: one for a user with a 'Workout Mix', one with a 'Chill Vibes', and one with a 'Top Hits' playlist. Use realistic data for each field.

Ans:-

```
INSERT INTO playlists  
(user_id, name, created_at)  
VALUES  
(1, 'Workout Mix', '2026-06-10 08:30:00'),  
(2, 'Chill Vibes', '2026-06-10 10:15:00'),  
(3, 'Top Hits', '2026-06-10 12:00:00');
```

Que-3.

Write an SQL UPDATE statement to rename the 'Chill Vibes' playlist to 'Evening Chill' for a specific user_id.

Ans:-

```
UPDATE playlists  
SET name = 'Evening Chill'  
WHERE user_id = 2  
    AND name = 'Chill Vibes';
```

Que-4.

Write a DELETE statement to remove a playlist named 'Workout Mix' for a given user_id from the playlists table.
Hint: Make sure your WHERE clause targets only the intended row.

Ans:-

```
DELETE FROM playlists  
WHERE user_id = 1  
    AND name = 'Workout Mix';
```

Que-5.

Create a stored procedure named GetMonthlyPlaylistCount that takes a user_id and a month (as an integer) as input, and returns the total number of playlists the user created in that

month.

Hint: Use the MONTH() function in your WHERE clause.

Ans:-

```
DELIMITER //
```

```
CREATE PROCEDURE GetMonthlyPlaylistCount (  
    IN p_user_id INT,  
    IN p_month INT  
)  
BEGIN  
    SELECT COUNT(*) AS total_playlists  
    FROM playlists  
    WHERE user_id = p_user_id  
    AND MONTH(created_at) = p_month;  
END //
```

```
DELIMITER ;
```