

Que-1 Open MySQL Workbench or CLI and write a CREATE TABLE statement to create a table called 'restaurants' with columns: id (INT, primary key, auto-increment), name (VARCHAR(100)), location (VARCHAR(100)), and rating (DECIMAL(2,1)).

Ans-

```
CREATE TABLE restaurants (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(100),  
    location VARCHAR(100),  
    rating DECIMAL(2,1)  
);
```

Que-2. Use the ALTER TABLE command in MySQL to add a new column 'average_cost' (INT) to your 'restaurants' table.
Hint: Remember to specify the data type when adding a new column.

Ans-

```
ALTER TABLE restaurants  
ADD average_cost INT;
```

Que-3. Write a SQL statement to DROP the 'restaurants' table you created earlier. Double-check your command before running it to avoid accidental data loss.

Ans-

```
DROP TABLE restaurants;
```

Que-4. Create a new table called 'playlists' for a music app like Spotify, with columns: playlist_id (INT, primary key, auto-increment), title (VARCHAR(50)), created_by (VARCHAR(50)), and created_at (DATE).

Ans-

```
CREATE TABLE playlists (  
    playlist_id INT AUTO_INCREMENT PRIMARY KEY,  
    title VARCHAR(50),  
    created_by VARCHAR(50),  
    created_at DATE  
);
```