

Que-1 Create a SQL table called Restaurants with columns: id (INT, auto-increment), name (VARCHAR), cuisine (VARCHAR), rating (DECIMAL), and city (VARCHAR). Insert 5 sample restaurants into the table, each with a different cuisine and rating.

Ans:-

Create the Restaurants Table:-

```
CREATE TABLE Restaurants (  
    id INT AUTO_INCREMENT PRIMARY KEY,  
    name VARCHAR(100),  
    cuisine VARCHAR(50),  
    rating DECIMAL(2,1),  
    city VARCHAR(50)  
);
```

Insert 5 Record:-

```
INSERT INTO Restaurants (name, cuisine, rating, city)  
VALUES  
( 'Spice Garden', 'Indian', 4.5, 'Ahmedabad'),  
( 'Dragon Wok', 'Chinese', 4.2, 'Surat'),  
( 'Pizza Palace', 'Italian', 4.7, 'Mumbai'),  
( 'Taco Fiesta', 'Mexican', 4.1, 'Pune'),  
( 'Sushi World', 'Japanese', 4.8, 'Bangalore');
```

Que-2.

Write a SQL UPDATE statement to change the rating of the restaurant named 'Spice Villa' to 4.7 in the Restaurants table.

Ans-

```
UPDATE Restaurants  
SET rating = 4.7  
WHERE name = 'Spice Villa';
```

Que-3.

Delete all restaurants from the Restaurants table where the rating is less than 3.5 using a SQL DELETE statement.

Ans:-

```
DELETE FROM Restaurants  
WHERE rating < 3.5;
```

Que-4.

Use a SELECT query with WHERE and LIMIT to fetch the top 2 restaurants in the city 'Ahmedabad' with a rating above 4.0 from the Restaurants table.

Hint: Combine WHERE for city and rating, and LIMIT to restrict the number of results.

Ans:-

```
SELECT *  
FROM Restaurants  
WHERE city = 'Ahmedabad'  
      AND rating > 4.0  
LIMIT 2;
```