SIMATS ENGINEERING
ASSESSMENT TOOL 1

COURSE NAME: CSA07 COURSE CODE:Computer Networks

COURSE OUTCOME COVERED

CO1: *Apply the functions of OSI layer in enabling reliable data transmission across networks. (BL2, BL3)*

Assessment Tool Weightage: 40%

Annexure A

SHORT ANSWER TEST

Code of Conduct:

I R. Hashini / 192426035 2 *(Name / Reg No) certify that this submission is my original work and that I have adhered to the guidelines specified for this assessment.*
I understand that any violation of academic integrity rules will result in disciplinary action.

Signature of the student: R. Hashini

Criteria	Weightage	Q1 10marks	Q2 10marks	10marks	10marks
Understanding of Concepts	25%	2.00	2.00	2.00	2.00
Explanation	25%	2.00	2.00	2.00	2.00
Application	20%	1.60	1.60	1.60	1.60
Organization	15%	1.20	1.20	1.20	1.20
Accuracy	10%	0.80	0.80	0.80	0.80
Clarity	5%	0.40	0.40	0.40	0.40

Faculty

Short Answer Test

1. A company needs to transfer a **150 MB** design file from a client computer to a remote server over a network with a bandwidth of **50 Mbps**. The Transport Layer divides the file into **1500-byte segments**, while the Data Link Layer encapsulates each segment into frames by adding **40 bytes of header and trailer**. Calculate the total number of segments and frames transmitted, the total transmission overhead introduced by the Data Link Layer, and estimate the total transmission time (ignoring propagation delay). Explain how the Transport and Data Link layers ensure reliable communication.

2. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

3. A **12,000-byte** IP packet is transmitted through a router where the Maximum Transmission Unit (MTU) is **1500 bytes**. Assuming each fragment requires a **20-byte IP header**, calculate the total number of fragments created and the total header overhead introduced. Explain how the Network Layer ensures successful delivery of fragmented packets to the destination.

4. A Transport Layer protocol uses a **sliding window size of 6 frames**. Each frame carries **1024 bytes** of user data. If the sender transmits **48 frames**, calculate the number of transmission windows required. If one frame in every window is lost and must be retransmitted, determine the total number of retransmissions. Explain how flow control improves communication efficiency.

5. A multimedia application transfers a **600 MB** video file. The Session Layer inserts a synchronization checkpoint after every **60 MB** of transmitted data. During transmission, a failure occurs after **390 MB** has been transferred. Determine the number of checkpoints created before failure and calculate the amount of data that must be retransmitted after recovery. Explain the importance of synchronization in the Session Layer.

6. Before transmission, the Presentation Layer compresses a **900 MB** file by **40%**. The compressed data is encrypted, adding **5%** overhead to the compressed size. Calculate the compressed file size, the encrypted file size, and the total percentage reduction compared to the original file. Explain how the Presentation Layer improves transmission efficiency and security.

7.An FTP application transfers **3 GB** of data over a network with an effective throughput of **120 Mbps**. The Application Layer divides the data into requests

of **3 MB** each. Calculate the total number of requests generated and estimate the total transmission time in seconds. Discuss how the Application Layer provides reliable services to users.

8.A packet experiences the following processing delays at different OSI layers: Application Layer = **4 ms**, Transport Layer = **3 ms**, Network Layer = **5 ms**, Data Link Layer = **2 ms**, and Physical Layer = **1 ms**. The propagation delay is **18 ms**, and the transmission delay is **12 ms**. Calculate the total end-to-end delay experienced by the packet and explain how each layer contributes to the communication process.

9.A network transfers **80 MB** of useful data using frames of **1600 bytes**, where each frame contains **80 bytes** of protocol overhead added by different OSI layers. Calculate the total number of frames required, the total overhead transmitted, and the transmission efficiency as a percentage. Explain how protocol overhead affects network performance.

10.A hospital transfers a patient's medical record of **240 MB** through an IoT-enabled healthcare network. The Presentation Layer compresses the data by **30%**, the Transport Layer divides the compressed data into **1400-byte segments**, and the Data Link Layer adds **60 bytes** of overhead to each frame. Calculate the compressed file size, the total number of segments transmitted, the total protocol overhead introduced, and the final amount of data transmitted across the Physical Layer. Explain how multiple OSI layers work together to ensure secure and reliable communication.

RUBRICS FOR CALCULATION

Criteria	Weightage	Level 4 – Exemplary	Level 3 – Proficient	Level 2 – Developing	Level 1 – Beginning
Understanding of Concepts	25%	Demonstrates a thorough, accurate understanding of concepts	Good understanding with minor gaps	Basic understanding with some misconceptions	Poor understanding; major misconceptions
Explanation	25%	Detailed, well-explained answers with relevant examples	Clear explanation with adequate details	Limited explanation; lacks depth	Poor or unclear explanation

Application	20%	Effectively applies concepts with strong analytical ability	Applies concepts with minor errors	Limited application with weak analysis	No application or incorrect analysis
Organizatio n	15%	Well-structured answers with logical flow and coherence	Organized with minor issues in flow	Basic structure, lacks clarity	Poor organization, incoherent answers
Accuracy	10%	Completely accurate and covers all required points	Mostly accurate with minor omissions	Partially correct with missing points	Incorrect answers with major gaps
Clarity	5%	Clear, neat, professional presentatio n	Understanda ble with minor issues	Limited clarity, readability issues	Poorly written, difficult to understand

3. A 12,000 byte IP packet is transmitted thr a router where the maximum transmission unit 1500 bytes. Assuming each fragment requires a 20 byt header, calculate the total number of fragments created and the total header overhead introduced. Explain how the network layer ensures successful divery of fragmented packets to the destination.

4. A transport layer protocol uses a sliding window size of 6 frames. Each frame

Answers:

1. Given:

File size = 150MB

Bandwidth = 50Mbps

Segment size = 1500 bytes

Data link overhead = 50 bytes per head.

Step:1

Convert file size into bytes

Using 1MB = 10^6 bytes

e

Calculate the number of segments

$$\text{Segments} = \frac{\text{File size}}{\text{Segment size}}$$

$$= \frac{150,000,000}{1500}$$

$$= 100,00$$

Step : 3

Calculate the number of frames

Frames = Segments

= 100,000 frames

Step : 4

Calculate total ~~transmission~~ data link overhead

Overhead = Frames × 40

= 100,000 × 40

= 4,000,000 bytes

Step : 5

Total transmission time :

In bits, this is $154,000,000 \times 8 = 1,232,000,000$ bits

Transmission time:

Time = total bits ÷ bandwidth = $1,232,000,000 \div 50,000,000 = 24.64$ seconds (ignoring propagation delay)

Final answer:

100,000 segments, 100,000 frames; 4 MB overhead estimated transmission time = 24.64 seconds.

Explanation:

The transport layer divides data into segments and ensures reliable delivery using acknowledgements and retransmissions. The data link layer converts segments into frames and detects transmission errors.

2. Given:

Window size = 6 frames; total frames = 48; one lost frame per window.

Number of windows:

$48 \div 6 = 8$ windows

Transmissions :

One lost frame in each of the 8 windows means 8 retransmissions.

Data in each window : 6 x 1024 = 6,144 bytes of user data. Across 8 windows, the original user data is

48 x 1,024 = 49,152 bytes.

Final answer :

8 transmission windows and 8 retransmissions.

Explanation :

Flow control prevents a fast sender from overwhelming a slow receiver. Sliding windows allow multiple frame to be sent efficiently, while acknowledgements and retransmissions help recover lost frames.

(3) Given :

- IP packet size = 12,000 bytes
- MTU = 1,500 bytes
- IP header = 20 bytes

Maximum data per fragment

= MTU - Header

= 1,500 ~~bytes~~ - 20

= 1480 bytes

Step 2: Original payload

= 12,000 - 20 = 11,980 bytes

Step 3: Number of fragments

= 11,980 ÷ 1,480

~~= 12,00~~

= 8 full portions with 140 bytes remaining.

Therefore, 9 fragments are required.

Step 4.

Total header overhead

= Number of fragments × Header size

= 9 × 20 = 180 bytes

Final answer:

Number of fragments = 9

Header of overhead = 180 bytes

Explanation: The network layer divides large packets into smaller fragments,

Given:

- Total video = 600MB
- Checkpoint interval = 60MB
- Failure occurs at 390MB

Step : 1

No. of. checkpoints

Checkpoints : 60, 120, 180, 240, 300, 360 MB.

No. of. checkpoints = 6

Step 2:

Data to be retransmitted

= Data transferred - Last checkpoint

= 390 - 360 = 30MB

Final Answer:

Checkpoints created = 6

Data to be transmitted = 30MB