Name_	KEY	
Friday	, 10/25/2019	

Please circle the letter corresponding to the most correct answer. Each question is worth two points.

- 1. A COBOL MOVE CORRESPONDING will convert numeric elementary items when necessary.
  - a. True
  - b. False
- 2. In COBOL, which of these is to be found in the DATA DIVISION.?
  - a. WORKING-STORAGE SECTION.
  - b. INPUT-OUTPUT SECTION.
  - c. FILE SECTION.
  - d. FILE-CONTROL.
  - e. More than one of the above.
- 3. COBOL numeric fields that will be used as counters or for other arithmetic but never printed should be defined as BINARY SYNC.
  - a. True
  - b. False
- 4. Declared: 01 NUMBER-1 PIC 9(3)V9(3).

After executing: MOVE -3456.8997 TO NUMBER-1.

NUMBER-1 will hold the hexadecimal equivalent of \_\_\_\_\_

- a. 456.900
- b. 456899
- c. -456.900
- d. -345689
- e. None of above.
- 5. COBOL numeric literals may contain a decimal point.
  - a. True
  - b. False
- 6. To print either a floating plus sign ('+') if the sending field contains a positive value or a floating negative sign ('-') if the sending field contains a negative value, which PIC is correct?

```
a. PIC ----9.99DB.
```

- b. PIC ++++9.99CR.
- c. PIC ----9.99.
- d. PIC +++++9.99.
- e. None of the above.

7. Declared: 05 NUM1 PIC S9(5)V999 VALUE 36.788. PIC S9(5)V99 05 NUM2 PACKED-DECIMAL. After executing: COMPUTE NUM2 ROUNDED = NUM1  $\star$  1. NUM2 will hold the equivalent of a. 367.88 b. 36.78 c. 36.79 d. 36788.00 e. None of the above. 8. COBOL data names can be made up ONLY of letters, digits and hyphens. a. True b. False 9. A COBOL MOVE CORRESPONDING converts numeric data types. a. True b. False 10. Declared: 05 SHR-AMT PIC S9(3)V999 VALUE 123.456. 05 SHR-VALUE PIC S9(4)V99. 05 OUT-SHR-VALUE PIC \$\$,\$\$9.99. After executing: COMPUTE SHR-VALUE ROUNDED = SHR-AMT \* 1.03. MOVE SHR-VALUE TO OUT-SHR-VALUE. OUT-SHR-VALUE will contain bb\$127.16 where b represents a space. a. True b. False 11. A field defined as PIC S9(10) V9(3) PACKED-DECIMAL. will require \_\_\_\_\_\_ bytes of storage. a. 10 b. 4

12. A field defined as PIC S9(3) V99 BINARY. will require \_\_\_\_\_ bytes of storage.

c. 7 d. 13

a. 6 b. 8 c. 4 d. 7

e. None of the above.

e. None of the above.