

SQL Data Definition Language and Update Operations

© Department of Computer Science
Northern Illinois University
February 2002

1

Create Table - Syntax

- CREATE TABLE <table_name> (
 <attribute> <type>
 [not null][unique][primary key]
 {,<attribute> <type>
 [not null][unique][primary key] }
 [,<primary key constraint>]
 [{,<foreign key constraint> }]);

2

Create Table - Syntax

- where
 - <attribute> is the name of attribute in the table to be defined
 - <type> can be
 - INTEGER
 - FLOAT/REAL
 - DECIMAL(I,J)
 - CHAR(N)
 - VARCHAR(N)

3

Create Tables - Examples

- Create table person (
 ssn char(9) primary key,
 fname char(10) not null,
 lname char(10) not null,
 phone# char(10));

4

Create Tables - Examples

- Create table student (
 ssn char(9),
 classification char(6),
 gpa decimal(4,3),
 total_hours integer,
 primary key (ssn),
 foreign key (ssn) references
 person(ssn));

5

Alter Table - Syntax

- alter table <table_name> add (
 <attribute> <type>
 {, <attribute> <type>});
- alter table <table_name> modify (
 <attribute> <new_length>
 {, <attribute> <new_length>});

6

Alter Table - Examples

- alter table person add (
 birth_date char(8));
- alter table section modify (
 title char (25),
 description char (50));

7

Drop Tables - Syntax and Example

- drop table <table_name>
 [cascade constraints];
- drop table person
 cascade constraints;

8

Insert - Syntax

- insert into <table_name>
 values (<value-list>);
- insert into <table_name>
 (<attribute-list>
 values (<value-list>);
- insert into <table_name>
 select * from <another_table_name>;

9

Insert - Examples

- insert into student
 values('293844323','senior',3.294,110);
- insert into person
 (ssn, fname, lname)
 values ('384729479','Susie','Jones');
- insert into section
 select * from temp_section;

10

Delete - Syntax and Examples

- delete from <table_name>
 [where <condition>];
- delete from person
 where ssn = '394837497';
- delete from section;

11

To Change Data Type of an Attribute

- If a table contains data, the data type of an attribute cannot be directly changed
- To do so
 - a temporary table is created and populated with the tuples of the original table
 - the tuples of the original table are deleted and the table is modified
 - the data is copied from the temporary table back into the modified original table

12

To Change Data Type of an Attribute

- Example to change the data type of a character attribute to integer
 - create table temp_table as
select * from section;
 - delete section;
 - alter table section (
modify max_enroll integer);
 - insert into section
select * from temp_table;
 - drop temp_table cascade constraints;

13

Update tables

- Used to modify attribute values of one or more selected tuples.
- A WHERE-clause selects the tuples to be modified.
- An additional SET-clause specifies the attributes to be modified and their new values.
- Each command modifies tuples in the same relation.

14

Update - Syntax and Examples

- update <table_name>
set <attribute>=<value>
{,<attribute>=<value>}
[where <condition>];
- update student
set classification = 'senior'
where total_hours > 90;
- update section
set max_enroll = 0;


15

Views

- A view is a single virtual table that is derived from other tables
- The other tables could be base tables or previously defined views.
- A view does not exist in physical form, which limits the possible update operations that can be applied to views.
- There are no limitations on querying a view

16

Views



17

Create View - Syntax

- create view <view-name>
[(<view-col-name> [, <view-col-name>]...)]
as select <attr-name> [,<attr-name>] ...
from <table-or-view-name>
[,<table-or-view-name>] ...
where <condition>;

18

Create View - Examples

- create view dekalb_people
 (ssn, first_name, last_name)
as select ssn, fname, lname
 from person
 where zip = '60115';

19

Create View - Examples

- create view grade_count
 (grade, number_grade)
as select grade, count(*)
 from transcript
 group by grade;

20

Create View - Examples

- create view offered_sections
as select *
 from section, course
 where section.course# =
 course.course#;

21

Query on Views

- Views can be queried by using the same select operation as with tables just replace the table name with the view name
- There are some restrictions on insertion, deletion, and update function when used on views

22

Drop Views - Syntax and Example

- drop view <view_name> ;
- drop view dekalb_people;

23

Advantages of Views

- Views allow different users to see the data in different forms.
- Views can free users from complicated DML operations, especially in the case where the views involve joins.
- Views can enhance security

24

System Catalog Views

- To find out what tables you have created, type
 - select table_name from user_tables;
- To find out information about a particular table (person, for example) type:
 - describe person;

25

Some Built-in Functions

- lower(string)
 - converts string to lower case
- upper(string)
 - converts string to upper case
- Examples:

```
select *
  from c
 where lower(dept) = 'music';
```

26

Some Built-in Functions

- lpad(x, y[,z])
 - returns the column padded on the left side of the data in the column passed as x to a width passed as y.
 - The optional passed value z indicates the character(s) that lpad() will insert into the column.
 - If no character is specified, a space will be used.
- rpad(x,y[,z]) similar to lpad.

27

Some Built-in Functions

- Example
 - select ssn, course#, lpad(grade, 6), "GRADE" from transcript;

28

Some Built-in Functions

- The default input format for date type is DD-MON-YY.
 - insert '22-Mar-99' into a date attribute

29

Some Built-in Functions

- To insert a date value of different format into a date field, you need to use to_date function
 - insert into emp(empno, hiredate) values(8989, to_date('99-12-31', 'yy-mm-dd'));
 - insert into emp(empno, hiredate) values(8988, to_date('99-12-31 14:35:00', 'yy-mm-dd hh24:mi:ss'));

30