Laboratory Record

submitted as part of

Programming for Data Science Lab (MACSE502)

LAB ASSESSMENT-9

by



Reg No: 26MML0031

Name: Hasnain H. Makada

To



Dr M Rajasekhara Babu

Dr M Rajasekhara Babu

School of Computer Science and Engineering

VIT®

Vellore Institute of Technology

(Deemed to be University under section 3 of UGC Act, 1956)

October 2026

2026 FALL SEMESTER
Programming for Data Science Lab (MACSE502) Record
INDEX

Week No	Date	Sl. No.	Type	Topic	Title with download Link for document	Problem Statement	Page No.
1	09-07-2026	1	PP	Pandas	Basic Data Manipulation with Pandas	Create a DataFrame with columns Name, Age, and City containing data for five individuals. Perform the following operations: select only the Name and Age columns, filter rows where Age is greater than 25, add a new column Country with a default value, and sort the DataFrame by Age in descending order. Finally, calculate the average age of the individuals.	1
1	09-07-2026	2	EP	Pandas		An AI company maintains model performance records containing: • ModelID • Accuracy • Algorithm Perform: 1. Select ModelID and Accuracy. 2. Filter models with Accuracy greater than 90%. 3. Add Status with default value "Production Ready". 4. Sort models by Accuracy. 5. Calculate average model accuracy.	6
2	16-07-2026	3	PP	Pandas	Data Cleaning and Preprocessing with Pandas	Create a DataFrame with some missing values in columns Name, Age, and City. Perform the following operations: fill missing values in the Age column with the mean age, drop rows where Name or City is missing, and convert the Age column to integer type. Finally, normalize the Age column using min-max scaling	14
2	16-07-2026	4	EP	Pandas		A streaming platform maintains movie records containing: • MovieID • Rating • Genre Perform: 1. Create a dataset with missing values. 2. Fill missing Rating values using average rating. 3. Remove rows with missing MovieID or Genre. 4. Convert Rating into integer type. Normalize rating values.	18
3	23-07-2026	5	PP	NumPy	Creating and Manipulating Arrays Using NumPy	Create a 2D array of shape (3, 4) with random integers between 0 and 10. Perform the following operations: calculate the mean and standard deviation of the entire array, slice the array to get the first two rows and last two columns, reshape the array to shape (4, 3), and perform element-wise multiplication with another array of the same shape.	30
3	23-07-2026	6	EP	NumPy		A logistics company tracks shipments from 4 warehouses across 7 weeks. Create a 4 x 7 shipment matrix. Perform: (1) compute average shipments, (2) compute standard deviation, (3) slice the first two warehouses and last three weeks, (4) reshape the matrix into a 7 x 4 matrix, and (5) perform element-wise multiplication with a transportation-cost matrix of the same shape.	35
4	30-07-2026	7	PP	Pandas NumPy Matplotlib	Feature Engineering and Exploratory Data Analysis	Feature Engineering, Exploratory Data Analysis: Create a DataFrame with columns Feature1, Feature2, and Target containing random data. Perform the following operations: create a new feature that is the logarithm of Feature1, bin Feature2 into three categories (low, medium, high), and calculate the correlation matrix of the DataFrame. Finally, create a scatter plot of Feature1 vs. Feature2 colored by Target, and interpret any visible patterns	46
4	30-07-2026	8	EP	Pandas NumPy Matplotlib		A company wants to analyze workforce behavior and predict employee attrition. Create a DataFrame containing: OvertimeHours JobSatisfactionScore SalaryLevel TrainingHours WorkLifeBalance YearsAtCompany PromotionCount AttritionStatus Perform: 1. Create Log_OvertimeHours. 2. Categorize JobSatisfactionScore into: Disengaged, Satisfied, Highly Engaged. 3. Generate correlation matrix. 4. Create a Treemap Visualization of employee categories. 5. Analyze workforce trends.	54
5	06-08-2026	9	PP	Web Scraping	requests, BeautifulSouppandasjson	Scrape data from a webpage and store it in a structured format like CSV orJSON	63
5	06-08-2026	10	EP	Web Scraping	requests, BeautifulSoup pandas json	A recruitment agency wants to analyze job opportunities posted on a dynamic job portal. Develop a Python application using Selenium to scrape job listings, extract Job Title, Company Name, Location and Salary (if available), store the collected data in a Pandas DataFrame, save the dataset as a CSV file, and visualize job demand by location.	70

6	20-08-2026	11	PP	Plotly	Interactive Bar Chart with Plotly	Create an interactive bar chart showing the population of different cities	80
6	20-08-2026	12	PP	Plotly	Interactive Scatter Plot with Plotly	Create an interactive scatter plot showing the relationship between house size and price	88
7	27-08-2026	13	PP	Bokeh	Interactive Scatter Plot with Bokeh	Create an interactive scatter plot showing the relationship between petal length and petal width from the Iris dataset using Bokeh	101
7	27-08-2026	14	EP	Bokeh	Interactive Line Plot with Bokeh	Create an interactive line plot showing the daily temperatures over a week using Bokeh.	105
7	27-08-2026	15	EP	Bokeh	Interactive Bar Chart with Bokeh	Create an interactive bar chart showing the sales figures of different products using Bokeh	109
8	03-09-2026	16	PP	scikit-learn and Plotly	Visualizing Clusters with scikit-learn and Plotly	Perform Principal Component Analysis (PCA) on the Iris dataset and visualize the first two principal components using an interactive 2D scatter plot in Plotly	113
8	03-09-2026	17	EP	scikit-learn and Plotly	Visualizing Clusters with scikit-learn and Plotly	Perform K-means clustering on the Iris dataset and visualize the clusters using an interactive 3D scatter plot in Plotly	122
9	10-09-2026	18	EP	arrays in Scala	arrays in Scala	Create an array of integers with the values 2, 5, 9, 14, 20. Write a function that takes this array and returns the sum of its elements. Next, create an array of strings with the names of five different fruits. Write a function that concatenates all elements of this array, separated by commas. Finally, iterate over the array of integers and print each element to the console	131
10	17-09-2026	19	EP	lists, sets, and tuples in Scala	lists, sets, and tuples in Scala	Create a list of the first five prime numbers. Write a function that takes this list and returns a new list with each element squared. Then, create a set of unique characters from the string "hello world" and write a function that takes two sets and returns their intersection. Create a tuple with three elements: an integer, a string, and a boolean, then access and print each element	134
11	24-09-2026	20	EP	HashMap’s	Handling collisions and resolving conflicts in HashMap’s	Create a HashMap with keys representing student names and values representing their grades, then insert multiple entries including a duplicate key with a different grade. Write a function to merge two HashMap’s, resolving conflicts by taking the higher grade. Finally, write a function to handle collisions by chaining, using lists to store multiple values for a single key.	137
12	08-10-2026	21	EP	Exploring advanced functional combinators beyond the basic set	Exploring advanced functional combinators beyond the basic set	Create a list of integers from 1 to 10, then use filter to create a new list with only even numbers. Use map to create a new list where each element is multiplied by 3. Use flatMap to create a list of tuples where each integer is paired with its square. Finally, use foldLeft to calculate the product of all elements in the list.	140

PP: Practice Program; EP: Exercise Program; CP: Challenging Program

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Exercise Program

Date: 10/09/2026 Week No.: 9 Program S. No. 18

Title	Arrays in Scala
Problem Statement	Create an array of integers with the values 2, 5, 9, 14, 20. Write a function that takes this array and returns the sum of its elements. Next, create an array of strings with the names of five different fruits. Write a function that concatenates all elements of this array, separated by commas. Finally, iterate over the array of integers and print each element to the console.
Objectives	• To declare and initialize fixed-size arrays in Scala. • To write a user-defined function that aggregates an integer array. • To write a user-defined function that joins a string array. • To traverse an array with an index loop and print every element. • To verify a computed aggregate against an independent calculation.
Dataset URL Link / File	No external dataset is required. The inputs are declared inside the program: the integer array (2, 5, 9, 14, 20) and the string array (Apple, Banana, Mango, Grapes, Orange).

Functions Details

Sl. No.	Function	Package	Description of function
1	`Array()`	Scala	Creates a fixed-size array from the supplied elements.
2	`sum`	Scala	Returns the total of all elements of a numeric array.
3	`mkString()`	Scala	Joins every element into one string using a separator.
4	`length`	Scala	Returns the number of elements stored in the array.
5	`apply(index)`	Scala	Returns the element stored at the given index.
6	`Array[Int]`	Scala	Declares an array whose elements are integers.
7	`Array[String]`	Scala	Declares an array whose elements are strings.
8	`def`	Scala	Declares the user-defined functions used by the program.
9	`while`	Scala	Repeats the traversal while the index is below the length.
10	`println()`	Scala	Writes one formatted line of text to the console.
11	`==` `(equality)`	Scala	Compares the manual sum with the function result.
12	`main()`	Scala	Entry point that executes the program.

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model	1. Declare the integer array with the values 2, 5, 9, 14 and 20. 2. Define sumOfArray() that returns the total of the array elements. 3. Print the integer array, its length and the computed sum. 4. Declare the string array containing the names of five fruits. 5. Define concatenateStrings() that joins the elements using mkString. 6. Define printElements() that walks the array with an index loop. 7. Call printElements() so every integer is printed with its index. 8. Compute the sum manually and compare it with the function result. 9. Print the verification line and terminate the program.

Program

```
// Program 18 - Arrays in Scala
// Week 9 | 10-09-2026 | Exercise Program
object Program18 {

  // (a) Function that returns the sum of all elements of an integer array
  def sumOfArray(numbers: Array[Int]): Int = numbers.sum

  // (b) Function that concatenates all elements of a string array, separated by commas
  def concatenateStrings(names: Array[String]): String = names.mkString(", ")

  // (c) Function that prints every element of an integer array
  def printElements(numbers: Array[Int]): Unit = {
```

Student Reg. No: 26MML0031 Name: Hasnain Makada
Faculty: Dr Rajasekhara Babu M, Professor, School of CSE, Vellore Institute of Technology (VIT), Vellore

Date: 10/09/2026 Week No.: 9 Program S. No. 18

```
    var index = 0
    while (index < numbers.length) {
      println("  Element at index " + index + " = " + numbers(index))
      index += 1
    }
  }

  def main(args: Array[String]): Unit = {
    println("=" * 62)
    println("PROGRAM 18 : ARRAYS IN SCALA")
    println("=" * 62)

    val numbers = Array(2, 5, 9, 14, 20)
    println("\n1. Integer array         : " + numbers.mkString("[", ", ", "]"))
    println("   Length                : " + numbers.length)
    println("   Sum of all elements   : " + sumOfArray(numbers))

    val fruits = Array("Apple", "Banana", "Mango", "Grapes", "Orange")
    println("\n2. String array (fruits) : " + fruits.mkString("[", ", ", "]"))
    println("   Concatenated           : " + concatenateStrings(fruits))

    println("\n3. Iterating over the integer array:")
    printElements(numbers)

    val manualSum = 2 + 5 + 9 + 14 + 20
    println("\n4. Verification           : manual sum = " + manualSum +
            " , function sum = " + sumOfArray(numbers) +
            " , match = " + (manualSum == sumOfArray(numbers)))
    println("=" * 62)
  }
}
```

Output Snapshots With Explanation/ Observations




Fig. 1.1: Terminal execution showing creation of the integer array, its length and the sum returned by the user-defined function. The string array is concatenated using mkString().

The integer array is printed first with its length, and the user-defined function returns the sum 50, which the next line confirms against the manually calculated value. The string array is joined with mkString so the five fruit names appear as one comma-separated line.




Fig. 1.2: Index-based traversal printing every element of the integer array, followed by the verification line confirming that the function result matches the manual sum.

The index loop walks the array from position 0 to 4 and prints each element beside its index, which shows that a Scala array is addressable by position. The final verification line reports that the manual sum and the function result are equal.

Conclusions

The integer array (2, 5, 9, 14, 20) was created successfully and the user-defined function returned a total of 50, which matched the manually calculated value. The string array of five fruits was concatenated into a single comma-separated string using mkString(). The index-based traversal printed every element of the integer array together with its position. The experiment demonstrated that Scala arrays are fixed-size, index-addressable collections and that aggregation and string joining can be expressed concisely through built-in collection methods.

References

1. Scala Array documentation: https://www.scala-lang.org/api/current/scala/Array.html
2. Scala Collections overview:

Date: 10/09/2026 Week No.: 9 Program S. No. 18

	https://docs.scala-lang.org/overviews/collections/overview.html 3. Class lecture: Arrays and array operations in Scala. 4. Python program (GitHub link): https://github.com/hasnainmakada-99/Data-Science-Codes/blob/main/WEEK%209/programs/Program18_Arrays.scala

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Exercise Program

Date: 17/09/2026 Week No.: 10 Program S. No. 19

Title	Lists, Sets and Tuples in Scala
Problem Statement	Create a list of the first five prime numbers. Write a function that takes this list and returns a new list with each element squared. Then, create a set of unique characters from the string hello world and write a function that takes two sets and returns their intersection. Create a tuple with three elements: an integer, a string and a boolean, then access and print each element.
Objectives	• To create immutable lists and transform their elements with a function. • To build a set of unique characters from a string. • To compute the intersection of two sets. • To construct a tuple holding three different types and access its components. • To compare immutable collections with the arrays used earlier.
Dataset URL Link / File	No external dataset is required. The inputs are the first five prime numbers (2, 3, 5, 7, 11), the literal string hello world and the tuple (101, Hasnain Makada, true).

Functions Details

Sl. No.	Function	Package	Description of function
1	`List()`	Scala	Creates an immutable linked list of elements.
2	`map()`	Scala	Applies a function to every element, returning a new list.
3	`sum`	Scala	Returns the total of all elements of a numeric list.
4	`toSet`	Scala	Converts a string or collection into a set of unique values.
5	`Set()`	Scala	Creates an immutable set that rejects duplicates.
6	`intersect()`	Scala	Returns the elements common to two sets.
7	`size`	Scala	Returns the number of elements in a set or list.
8	`toList`	Scala	Converts a set into a list so that it can be sorted.
9	`sorted`	Scala	Orders the elements of a collection in ascending order.
10	`Tuple3 / ( )`	Scala	Creates a tuple grouping three values of mixed types.
11	`_1, _2, _3`	Scala	Accesses the first, second and third tuple components.
12	`println()`	Scala	Writes one formatted line of text to the console.

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model

1. Create the list of the first five prime numbers 2, 3, 5, 7 and 11.
2. Define squareList() that maps every element of the list to its square.
3. Print the original list, the squared list and the sum of the squares.
4. Convert the string hello world into a set of unique characters.
5. Print the unique characters and their count.
6. Define intersectSets() that returns the common elements of two sets.
7. Intersect the character set with the vowel set and print the result.
8. Create the tuple (101, Hasnain Makada, true).
9. Access and print each tuple component using _1, _2 and _3.

Program

```
// Program 19 - Lists, Sets and Tuples in Scala
// Week 10 | 17-09-2026 | Exercise Program
object Program19 {

  // (a) Function that squares every element of a list
  def squareList(numbers: List[Int]): List[Int] = numbers.map(n => n * n)

  // (b) Function that returns the intersection of two sets
  def intersectSets(first: Set[Char], second: Set[Char]): Set[Char] =
first.intersect(second)

  // (c) Function that prints each element of a tuple
  def printTuple(record: (Int, String, Boolean)): Unit = {
    println("  First  element (Int)     : " + record._1)
    println("  Second element (String)  : " + record._2)
    println("  Third  element (Boolean) : " + record._3)
  }
```

Date: 17/09/2026 Week No.: 10 Program S. No. 19

```
  def main(args: Array[String]): Unit = {
    println("=" * 62)
    println("PROGRAM 19 : LISTS, SETS AND TUPLES IN SCALA")
    println("=" * 62)

    val primes = List(2, 3, 5, 7, 11)
    println("\n1. List of first five primes : " + primes)
    println("   Squares of each element    : " + squareList(primes))
    println("   Sum of squares             : " + squareList(primes).sum)

    val text = "hello world"
    val uniqueChars = text.toSet
    println("\n2. Source string             : " + text)
    println("   Unique characters (Set)    : " + uniqueChars.toList.sorted.mkString("[", ",
", "]"))
    println("   Number of unique chars     : " + uniqueChars.size)

    val vowels = Set('a', 'e', 'i', 'o', 'u')
    println("   Vowel set                  : " + vowels.toList.sorted.mkString("[", ", ",
"]"))
    println("   Intersection (vowels)      : " + intersectSets(uniqueChars,
vowels).toList.sorted.mkString("[", ", ", "]"))

    val record = (101, "Hasnain Makada", true)
    println("\n3. Tuple                     : " + record)
    printTuple(record)
    println("=" * 62)
  }
}
```

Output Snapshots With Explanation/ Observations

```
Program19.scala

hasnain@vit:~/WEEK 9/programs$
scala Program19
==============================================================
PROGRAM 19 : LISTS, SETS AND TUPLES IN SCALA
==============================================================

1. List of first five primes : List(2, 3, 5, 7, 11)
   Squares of each element    : List(4, 9, 25, 49, 121)
   Sum of squares             : 208
```

Fig. 2.1: Terminal execution showing the list of prime numbers, the squared list produced by the user-defined function and the sum of the squares.

The list of five primes is printed, followed by the squared list produced by the mapping function and the sum of those squares, so the transformation applied to every element is visible in one place.

```
Program19.scala

hasnain@vit:~/WEEK 9/programs$
scala Program19
2. Source string             : hello world
   Unique characters (Set)    : [ , d, e, h, l, o, r, w]
   Number of unique chars     : 8
   Vowel set                  : [a, e, i, o, u]
   Intersection (vowels)      : [e, o]

3. Tuple                     : (101,Hasnain Makada,true)
  First  element (Int)     : 101
  Second element (String)  : Hasnain Makada
  Third  element (Boolean) : true
==============================================================
```

Fig. 2.2: Unique characters extracted from the string, the vowel intersection and the three components of the tuple printed individually.

Converting the string to a set removes the repeated letters and leaves eight unique characters. Intersecting that set with the vowel set returns only e and o, and the tuple is then printed whole before each of its three components is echoed individually.

Conclusions

A list of the first five prime numbers was created and the mapping function returned the squared list (4, 9, 25, 49, 121) with a total of 208. Converting the string hello world into a set removed all duplicate letters and left eight unique characters, and the intersection with the vowel set produced {e, o}. The three-element tuple was created and each component was accessed and printed individually. The experiment showed that Scala lists preserve order, sets guarantee uniqueness and tuples group heterogeneous values without a dedicated class.

References

1. Scala List documentation: https://www.scala-lang.org/api/current/scala/collection/immutable/List.html
2. Scala Set documentation: https://www.scala-lang.org/api/current/scala/collection/immutable/Set.html
3. Scala Tuples guide: https://docs.scala-lang.org/tour/tuples.html

Date: 17/09/2026 Week No.: 10 Program S. No. 19

	4. Python program (GitHub link): https://github.com/hasnainmakada-99/Data-Science-Codes/blob/main/WEEK%209/programs/Program19_ListsSetsTuples.scala

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Exercise Program

Date: 24/09/2026 Week No.: 11 Program S. No. 20

Title	HashMaps: Handling Collisions and Resolving Conflicts
Problem Statement	Create a HashMap with keys representing student names and values representing their grades, then insert multiple entries including a duplicate key with a different grade. Write a function to merge two HashMaps, resolving conflicts by taking the higher grade. Finally, write a function to handle collisions by chaining, using lists to store multiple values for a single key.
Objectives	• To create and update a mutable HashMap of student names and grades. • To observe how a duplicate key overwrites the previously stored value. • To merge two HashMaps while resolving key conflicts deterministically. • To implement separate chaining so colliding keys share a bucket. • To explain the role of the hash function in distributing keys.
Dataset URL Link / File	No external dataset is required. All records are declared inside the program: student names paired with integer grades, plus a second set of six names used to force collisions across four buckets.

Functions Details

Sl. No.	Function	Package	Description of function
1	`mutable.HashMap()`	Scala	Creates a mutable hash table keyed by student name.
2	`+= (key -> value)`	Scala	Inserts a new entry or overwrites an existing key.
3	`get()`	Scala	Returns the value for a key wrapped in an Option.
4	`match / Some / None`	Scala	Selects the conflict-resolution branch for a key.
5	`++= (collection)`	Scala	Copies all entries of one map into another.
6	`toSeq.sorted`	Scala	Orders entries so the map prints deterministically.
7	`hashCode`	Scala	Produces the integer hash used to choose a bucket.
8	`abs / % (modulus)`	Scala	Maps the hash onto a valid bucket index.
9	`Array.fill()`	Scala	Creates the fixed array of bucket chains.
10	`List / :: (cons)`	Scala	Stores several colliding entries in one bucket chain.
11	`collect()`	Scala	Extracts all values that match a key inside a chain.
12	`foreach / for`	Scala	Traverses the bucket array to print occupied buckets.

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model	1. Create a mutable HashMap with three student names and their grades. 2. Insert two more students, then insert an existing key with a different grade. 3. Observe that the duplicate key replaces the earlier grade. 4. Define mergeTakingHigher() that copies the first map into a new map. 5. For every key of the second map keep the larger of the two grades. 6. Print both input maps and the merged map to show resolved conflicts. 7. Define a ChainedHashMap class with a fixed number of buckets. 8. Compute the bucket index as |key.hashCode| % bucketCount. 9. Insert six names so several of them land in the same bucket. 10. Print the non-empty buckets to show the chains built by separate chaining.

Program	`// Program 20 - HashMaps: collisions and conflict resolution`
	`// Week 11 | 24-09-2026 | Exercise Program`
	`import scala.collection.mutable`

Student Reg. No: 26MML0031 Name: Hasnain Makada
Faculty: Dr Rajasekhara Babu M, Professor, School of CSE, Vellore Institute of Technology (VIT), Vellore

Date: 24/09/2026 Week No.: 11 Program S. No. 20

```
// A HashMap that resolves collisions by separate chaining with lists
class ChainedHashMap(bucketCount: Int) {

  private val table: Array[List[(String, Int)]] = Array.fill(bucketCount)
(List.empty[(String, Int)])

  // Hash function that maps a key to a bucket index
  private def bucketIndex(key: String): Int = math.abs(key.hashCode) % bucketCount

  // Insert a key-value pair, prepending it to the bucket chain
  def put(key: String, grade: Int): Unit = {
    val index = bucketIndex(key)
    table(index) = (key, grade) :: table(index)
  }

  // Look up every value stored under a key (a chain may hold several)
  def get(key: String): List[Int] =
    table(bucketIndex(key)).collect { case (k, v) if k == key => v }

  // Show the non-empty buckets, proving that chaining holds the collisions
  def display(): Unit = {
    println("   Bucket | Chain (key -> grade)")
    println("   -------+---------------------")
    for (index <- table.indices; if table(index).nonEmpty) {
      val chain = table(index).reverse.map { case (k, v) => k + " -> " + v }.mkString(" , ")
      println("   " + index + "       | " + chain)
    }
  }
}

object Program20 {

  // (a) Merge two HashMaps, resolving conflicts by keeping the higher grade
  def mergeTakingHigher(first: mutable.HashMap[String, Int],
                        second: mutable.HashMap[String, Int]): mutable.HashMap[String, Int]
= {
    val merged = mutable.HashMap[String, Int]()
    merged ++= first
    for ((name, grade) <- second) {
      merged.get(name) match {
        case Some(existing) => if (grade > existing) merged(name) = grade
        case None           => merged(name) = grade
      }
    }
    merged
  }

  // (b) Handle collisions by chaining when many keys land in one bucket
  def demonstrateChaining(): Unit = {
    val chained = new ChainedHashMap(4)
    val entries = List("Amit" -> 78, "Neha" -> 85, "Rahul" -> 66, "Sara" -> 92,
                       "Vikram" -> 74, "Zoya" -> 88)
    for ((name, grade) <- entries) chained.put(name, grade)
    println("   Hash function      : index = |key.hashCode| % 4")
    for ((name, _) <- entries) {
      println("   " + name + " -> bucket " + (math.abs(name.hashCode) % 4))
    }
    println()
    chained.display()
  }

  def main(args: Array[String]): Unit = {
    println("=" * 62)
    println("PROGRAM 20 : HASHMAPS - COLLISIONS AND CONFLICT RESOLUTION")
    println("=" * 62)

    // 1. Create a HashMap of student names and grades
    val grades = mutable.HashMap(
      "Hasnain" -> 88,
      "Amit"    -> 76,
      "Neha"    -> 91
    )
    println("\n1. Initial HashMap           : " + grades.toSeq.sorted.mkString("{", ", ",
"}"))

    // 2. Insert multiple entries, including a duplicate key with a different grade
    grades += ("Rahul" -> 69)
    grades += ("Sara"  -> 95)
    grades += ("Hasnain" -> 93)
    println("   After inserts + duplicate : " + grades.toSeq.sorted.mkString("{", ", ",
"}"))
    println("   Note: the duplicate key Hasnain replaced 88 with " + grades("Hasnain"))

    // 3. Merge two HashMaps, resolving conflicts by taking the higher grade
    val sectionA = mutable.HashMap("Hasnain" -> 93, "Amit" -> 76, "Zoya" -> 81)
    val sectionB = mutable.HashMap("Hasnain" -> 85, "Zoya" -> 90, "Vikram" -> 74)
    val merged   = mergeTakingHigher(sectionA, sectionB)
    println("\n2. Section A                 : " + sectionA.toSeq.sorted.mkString("{", ", ",
"}"))
```

Date: 24/09/2026 Week No.: 11 Program S. No. 20

```
    println("   Section B                : " + sectionB.toSeq.sorted.mkString("{", ", ",
"}"))
    println("   Merged (higher grade wins): " + merged.toSeq.sorted.mkString("{", ", ",
"}"))
    println("   Hasnain 93 vs 85 -> " + merged("Hasnain") + " | Zoya 81 vs 90 -> " +
merged("Zoya"))

    // 4. Collision handling by chaining
    println("\n3. Collision handling by separate chaining:")
    demonstrateChaining()
    println("=" * 62)
  }
}
```

Output Snapshots With Explanation/ Observations




Fig. 3.1: Terminal execution showing the initial HashMap, insertion of new entries, the duplicate-key overwrite and the merge of two HashMaps taking the higher grade.

The initial map holds three students. After the inserts the duplicate key Hasnain replaces the earlier grade of 88 with 93, which shows that a HashMap keeps one value per key. The merged map then resolves the overlapping names by keeping the higher grade.




Fig. 3.2: Bucket assignment produced by the hash function and the non-empty buckets showing separate chaining for colliding keys.

The hash function assigns every name to one of four buckets, and two pairs of names land in the same bucket. The bucket table printed underneath lists both entries in each of those chains, so no record is lost even though two keys share an index.

Conclusions

The initial HashMap stored three students and the duplicate insertion for Hasnain replaced the earlier grade of 88 with 93, confirming that a HashMap allows only one value per key. Merging two HashMaps with the higher-grade rule produced a combined map in which Hasnain kept 93 and Zoya was upgraded from 81 to 90. The chained implementation placed six keys into four buckets, with bucket 0 holding Neha and Rahul and bucket 1 holding Sara and Zoya, so no entry was lost even though the hash function assigned two keys to the same index.

References

1. Scala HashMap documentation: https://www.scala-lang.org/api/current/scala/collection/mutable/HashMap.html
2. Hash table collision resolution: https://en.wikipedia.org/wiki/Hash_table#Collision_resolution
3. Class lecture: Maps and HashMaps in Scala.
4. Python program (GitHub link): https://github.com/hasnainmakada-99/Data-Science-Codes/blob/main/WEEK%209/programs/Program20_HashMapCollisions.scala

2026 FALL SEMESTER
Programming for Data Science (MACSE502) Lab Record
Exercise Program

Date: 08/10/2026 Week No.: 12 Program S. No. 21

Title	Advanced Functional Combinators in Scala
Problem Statement	Create a list of integers from 1 to 10, then use filter to create a new list with only even numbers. Use map to create a new list where each element is multiplied by 3. Use flatMap to create a list of tuples where each integer is paired with its square. Finally, use foldLeft to calculate the product of all elements in the list.
Objectives	• To apply filter, map and flatMap to an immutable list of integers. • To distinguish flatMap from map by the shape of the returned collection. • To reduce a collection to a single value with foldLeft. • To chain several combinators into one readable transformation pipeline. • To compare each combinator result against known values.
Dataset URL Link / File	No external dataset is required. The source collection is the list of integers from 1 to 10 generated with (1 to 10).toList.

Functions Details

Sl. No.	Function	Package	Description of function
1	`(1 to 10).toList`	Scala	Builds the source list of ten integers.
2	`filter()`	Scala	Keeps only the elements that satisfy a predicate.
3	`map()`	Scala	Transforms every element, preserving the collection length.
4	`flatMap()`	Scala	Transforms each element and flattens results into one list.
5	`foldLeft()`	Scala	Reduces the list left to right using an accumulator.
6	`product`	Scala	Multiplies all elements, used to verify foldLeft.
7	`sum`	Scala	Adds all elements, used to total the mapped list.
8	`length`	Scala	Counts the elements produced by a combinator.
9	`mkString()`	Scala	Joins the resulting elements into one display string.
10	`List((n, n*n))`	Scala	Wraps each pair so flatMap can flatten it.
11	`println()`	Scala	Writes one formatted line of text to the console.
12	`main()`	Scala	Entry point that executes the program.

Steps/ Process/ Procedure/ Algorithm/ Flowchart/ Model

1. Build the source list of the integers 1 to 10.
2. Apply filter with the predicate n % 2 == 0 to keep the even numbers.
3. Apply map with the function n * 3 to triple every element.
4. Apply flatMap so each integer is paired with its square.
5. Apply foldLeft with seed 1 and multiplication to obtain 10 factorial.
6. Verify the foldLeft result against the built-in product of the list.
7. Chain filter, map and foldLeft into a single transformation pipeline.
8. Print a summary of how many elements each combinator produced.

Program

```
// Program 21 - Advanced functional combinators
// Week 12 | 08-10-2026 | Exercise Program
object Program21 {

  def main(args: Array[String]): Unit = {
    println("=" * 62)
    println("PROGRAM 21 : ADVANCED FUNCTIONAL COMBINATORS")
    println("=" * 62)

    val numbers = (1 to 10).toList
    println("\n1. Source list (1 to 10)     : " + numbers.mkString("[", ", ", "]"))

    // 2. filter - keep only the even numbers
    val evens = numbers.filter(n => n % 2 == 0)
    println("\n2. filter(n % 2 == 0)        : " + evens.mkString("[", ", ", "]"))
    println("   Count of even numbers     : " + evens.length)

    // 3. map - multiply every element by 3
    val tripled = numbers.map(n => n * 3)
    println("\n3. map(n => n * 3)           : " + tripled.mkString("[", ", ", "]"))
    println("   Sum after mapping         : " + tripled.sum)
```

Student Reg. No: 26MML0031 Name: Hasnain Makada

Faculty: Dr Rajasekhara Babu M, Professor, School of CSE, Vellore Institute of Technology (VIT), Vellore

Date: 08/10/2026 Week No.: 12 Program S. No. 21

```
    // 4. flatMap - pair every integer with its square
    val pairs = numbers.flatMap(n => List((n, n * n)))
    println("\n4. flatMap(n => (n, n*n))    :")
    println("   " + pairs.mkString("[", ", ", "]"))
    println("   Number of pairs produced  : " + pairs.length)

    // 5. foldLeft - product of all elements
    val product = numbers.foldLeft(1)((accumulator, n) => accumulator * n)
    println("\n5. foldLeft(1)(_ * _)        : " + product)
    println("   Verification (10!)         : " + (1 to 10).product +
            " , match = " + (product == (1 to 10).product))

    // 6. Combined pipeline using several combinators together
    val pipeline = numbers
      .filter(n => n % 2 == 0)
      .map(n => n * 3)
      .foldLeft(0)((accumulator, n) => accumulator + n)
    println("\n6. Combined pipeline")
    println("   evens -> x3 -> sum        : " + pipeline)

    println("\n7. Summary of combinator results")
    println("   filter   -> " + evens.length + " elements")
    println("   map      -> " + tripled.length + " elements")
    println("   flatMap  -> " + pairs.length + " elements")
    println("   foldLeft -> single value " + product)
    println("=" * 62)
  }
}
```

Output Snapshots With Explanation/ Observations




Fig. 4.1: Terminal execution showing the source list, the filtered even numbers, the tripled list and the flatMap pairs generated from the input list.

The source list 1 to 10 is shown, followed by the five even numbers returned by filter and the ten tripled values returned by map. The flatMap block pairs every integer with its square and flattens the pairs into a single list.




Fig. 4.2: foldLeft product with its verification against the built-in product, the combined pipeline result and the summary of combinator outputs.

foldLeft reduces the list to 3628800, and the verification line confirms that this equals the built-in product of 1 to 10. The combined pipeline then applies filter, map and foldLeft in one expression to give 90, and the summary counts how many elements each combinator produced.

Conclusions

Applying filter to the list 1 to 10 returned the five even numbers (2, 4, 6, 8, 10), while map with multiplication by three produced a list of the same length containing (3, 6, 9, ..., 30). flatMap paired every integer with its square and flattened the pairs into a single list of ten tuples, and foldLeft returned 3628800, which matches the built-in product and confirms 10 factorial. The combined pipeline of filter, map and foldLeft produced 90 in a single expression, showing that functional combinators can replace explicit loops with shorter and more declarative code.

Date: 08/10/2026 Week No.: 12 Program S. No. 21

References	1. Scala collections operations: https://docs.scala-lang.org/overviews/collections/operations.html 2. Scala tour: anonymous function syntax: https://docs.scala-lang.org/tour/anonymous-function-syntax.html 3. Class lecture: Functional combinators in Scala. 4. Python program (GitHub link): https://github.com/hasnainmakada-99/Data-Science-Codes/blob/main/WEEK%209/programs/Program21_FunctionalCombinators.scala