UNICORN
GENERATOR

PRODUCT CATALOGUE

Reliable Power • Built to Perform



CUMMINS

DIESEL GENERATOR SETS

50 Hz DCEC CUMMINS
DIESEL GENERATOR SETS

Genset Model	Rated Power		Standby Power		Engine Model	Engine Power (kW)		Asp	Cyl	Bore×Stroke (mm×mm)	Displace-ment (L)	Compr-ession Ratio	Fuel Cons. (g/kw.h)	Alternator Model
	kW	kVA	kW	kVA		Rated Power	Standby Power							
CP-C22.5	18.0	22.5	19.8	24.8	4B3.9-G11	20	22	N/A	4	102*120	3.9	17.3:1	229	CP-184E
CP-C27.5	22.0	27.5	24.2	30.3	4B3.9-G1	24	27	N/A	4	102*120	3.9	17.3:1	245	CP-184F
CP-C27.5	22.0	27.5	24.2	30.3	4B3.9-G2	24	27	N/A	4	102*120	3.9	17.3:1	245	CP-184F
CP-C31.3	25.0	31.3	27.5	34.4	4BT3.9-G1	36	40	TC	4	102*120	3.9	17.3:1	229	CP-184G
CP-C37.5	30.0	37.5	33.0	41.3	4BT3.9-G1	36	40	TC	4	102*120	3.9	17.3:1	229	CP-184H
CP-C40	32.0	40.0	35.2	44.0	4BT3.9-G2	36	40	TC	4	102*120	3.9	17.3:1	229	CP-184J
CP-C42.5	34.0	42.5	37.4	46.8	4BT3.9-G2	36	40	TC	4	102*120	3.9	17.3:1	214	CP-224C
CP-C50	40.0	50.0	44.0	55.0	4BTA3.9-G2	50	55	TC	4	102*120	3.9	17.3:1	213	CP-224D
CP-C60	48.0	60.0	52.8	66.0	4BTA3.9-G2	50	55	TC	4	102*120	3.9	17.3:1	213	CP-224E
CP-C62.5	50.0	62.5	55.0	68.8	4BTA3.9-G2	58	64	TC	4	102*120	3.9	17.3:1	214	CP-224E
CP-C72.5	58.0	72.5	63.8	79.8	4BTA3.9-G11	70	80	TC	4	102*120	3.9	17.3:1	208	CP-224F
CP-C80	64.0	80.0	70.4	88.0	4BTA3.9-G11	70	80	TC	4	102*120	3.9	17.3:1	208	CP-224G
CP-C85	68.0	85.0	74.8	93.5	6BT5.9-G1	86	92	TC	6	102*120	5.9	17.3:1	208	CP-224G
CP-C100	80.0	100.0	88.0	110.0	6BT5.9-G2	86	92	TC	6	102*120	5.9	17.3:1	214	CP-274C
CP-C112.5	90.0	112.5	100.0	125.0	6BT5.9-G2	96	106	TC	6	102*120	5.9	17.3:1	208	CP-274D
CP-C125	100.0	125.0	110.0	137.5	6BTA5.9-G2	106	116	TC	6	102*120	5.9	17.3:1	211	CP-274D
CP-C140	112.0	140.0	123.2	154.0	6BTAA5.9-G2	120	130	TC	6	102*120	5.9	17.3:1	208	CP-274E
CP-C150	120.0	150.0	132.0	165.0	6BTAA5.9-G12	140	155	TC	6	102*120	5.9	17.3:1	203	CP-274F
CP-C187.5	150.0	187.5	160.0	200.0	6CTA8.3-G1	163	180	TC	6	114*135	8.3	17.3:1	215	CP-274G
CP-C187.5	150.0	187.5	160.0	200.0	6CTA8.3-G2	163	180	TC	6	114*135	8.3	17.3:1	212	CP-274G
CP-C200	160.0	200.0	176.0	220.0	6CTAA8.3-G2	183	203	TC	6	114*135	8.3	18.0:1	205	CP-274H
CP-C225	180.0	225.0	198.0	247.5	6LTAA8.9-G2	220	240	TC	6	114*135	8.9	16.6:1	197.0	CP-274J
CP-C250	200.0	250.0	220.0	275.0	6LTAA8.9-G2	220	240	TC	6	114*135	8.9	16.6:1	197.0	CP-274K
CP-C275	220.0	275.0	242.0	302.5	6LTAA9.5-G3	250	280	TC	6	114*135	9.5	16.6:1	198	CP-444D
CP-C300	240.0	300.0	264.0	330.0	6LTAA9.5-G1	290	320	TC	6	114*135	9.5	16.6:1	198	CP-444D
CP-C375	300.0	375.0	330.0	412.5	6ZTAA13-G3	340	380	TC	6	130*163	13.0	17:01	189	CP-444F
CP-C450	360.0	450.0	396.0	495.0	6ZTAA13-G4	400	415	TC	6	130*163	13.0	17:01	191	CP-544C
CP-C500	400.0	500.0	440.0	550.0	QSZ13-G3	450	470	TC	6	130*163	13.0	17:01	193	CP-544D

50 Hz CCEC CUMMINS
DIESEL GENERATOR SETS

Genset Model	Rated Power		Standby Power		Engine Model	Engine Power (kW)		Asp	Cyl	Bore×Stroke (mm×mm)	Displace-ment (L)	Compr-ession Ratio	Fuel Cons. (g/kw.h)	Alternator Model
	kW	kVA	kW	kVA		Rated Power	Standby Power							
CP-C250	200.0	250.0	220.0	275.0	NT855G-A	231	254	TC	6	140*152	14	14:1	192	CP-274K
CP-C300	240.0	300.0	264.0	330.0	NTA855-G1A	264	291	TC	6	140*152	14	14:1	195	CP-444D
CP-C325	260.0	325.0	286.0	357.5	NTA855-G1B	284	321	TC	6	140*152	14	14:1	209	CP-444E
CP-C350	280.0	350.0	308.0	385.0	NTA855-G2A	312	343	TC	6	140*152	14	14:1	193	CP-444F
CP-C375	300.0	375.0	330.0	412.5	NTAA855-G7	343	377	TC	6	140*152	14	14:1	199	CP-444ES
CP-C450	360.0	450.0	396.0	495.0	KTA19-G3	403	448	TC	6	159*159	19	13.9:1	203	CP-544C
CP-C500	400.0	500.0	440.0	550.0	KTA19-G3A	448	504	TC	6	159*159	19	13.9:1	203	CP-544D
CP-C500	400.0	500.0	440.0	550.0	KTA19-G4	448	504	TC	6	159*159	19	13.9:1	203	CP-544D
CP-C562.5	450.0	562.5	495.0	618.8	KTAA19-G5	470	555	TC	6	159*159	19	13.9:1	204	CP-544ES
CP-C600	480.0	600.0	528.0	660.0	KTAA19-G6	520	570	TC	6	159*159	19	13.9:1	215	CP-544E
CP-C750	600.0	750.0	660.0	825.0	KT38-GA	647	711	TC	12	159*159	38	14.5:1	221	CP-634C
CP-C750	600.0	750.0	660.0	825.0	KTA38-G2	664	731	TC	12	159*159	38	14.5:1	214	CP-634C
CP-C800	640.0	800.0	704.0	880.0	KTA38G-2B	711	790	TC	12	159*159	38	14.5:1	200	CP-634D
CP-C900	720.0	900.0	792.0	990.0	KTA38-G2A	813	896	TC	12	159*159	38	14.5:1	203	CP-634E
CP-C1000	800.0	1000.0	880.0	1100.0	KTA38-G5	881	970	TC	12	159*159	38	13.9:1	202	CP-634E
CP-C1250	1000.0	1250.0	1100.0	1375.0	KTA50-G3	1097	1227	TC	16	159*159	50	13.9:1	210	CP-634H
CP-C1375	1100.0	1375.0	1210.0	1512.5	KTA50-G8	1200	1429	TC	16	159*159	50	14.9:1	215	CP-734B
CP-C1500	1200.0	1500.0	1320.0	1650.0	KTA50-GS8	1287	1429	TC	16	159*159	50	14.9:1	204	CP-734C

Note: 1. Optional alternator brand: Leroy somer, Stamford, Mecc alte or CASPER POWER
2. In line with our policy of continuous product development, we reserve the right to change specification without notice.



CUMMINS

DIESEL GENERATOR SETS

60 Hz DCEC CUMMINS
DIESEL GENERATOR SETS

Genset Model	Rated Power		Standby Power		Engine Model	Engine Power (kW)		Asp	Cyl	Bore×Stroke (mm×mm)	Displace-ment (L)	Compr-ession Ratio	Fuel Cons. (g/kw.h)	Alternator Model
	kW	kVA	kW	kVA		Rated Power	Standby Power							
CP-C25	20.0	25.0	22.0	27.5	4B3.9-G11	23	26	N/A	4	102*120	3.9	17.3:1	229	CP-184E
CP-C27.5	22.0	27.5	24.2	30.3	4B3.9-G2	30	33	N/A	4	102*120	3.9	17.3:1	238	CP-184E
CP-C32.5	26.0	32.5	28.6	35.8	4B3.9-G2	30	33	N/A	4	102*120	3.9	17.3:1	238	CP-184F
CP-C37.5	30.0	37.5	33.0	41.3	4B3.9-G12	33	36	N/A	4	102*120	3.9	17.3:1	245	CP-184G
CP-C45	36.0	45.0	39.6	49.5	4BT3.9-G2	40	44	TC	4	102*120	3.9	17.3:1	221	CP-184H
CP-C62.5	50.0	62.5	55.0	68.8	4BTA3.9-G2	60	66	TC	4	102*120	3.9	17.3:1	213	CP-224D
CP-C68.8	55.0	68.8	60.5	75.6	4BTA3.9-G2	60	66	TC	4	102*120	3.9	17.3:1	213	CP-224E
CP-C75	60.0	75.0	66.0	82.5	4BTA3.9-G2	67	74	TC	4	102*120	3.9	17.3:1	214	CP-224E
CP-C87.5	70.0	87.5	77.0	96.3	4BTA3.9-G11	80	90	TC	4	102*120	3.9	17.3:1	207	CP-224F
CP-C100	80.0	100.0	88.0	110.0	6BT5.9-G2	100	110	TC	6	102*120	5.9	17.3:1	235	CP-224G
CP-C112.5	90.0	112.5	99.0	123.8	6BT5.9-G2	100	110	TC	6	102*120	5.9	17.3:1	235	CP-274C
CP-C135	108.0	135.0	118.8	148.5	6BT5.9-G2	115	127	TC	6	102*120	5.9	17.3:1	208	CP-274D
CP-C137.5	110.0	137.5	121.0	151.3	6BTA5.9-G2	120	132	TC	6	102*120	5.9	17.3:1	211	CP-274D
CP-C150	120.0	150.0	132.0	165.0	6BTAA5.9-G2	132	145	TC	6	102*120	5.9	17.3:1	212	CP-274E
CP-C170	136.0	170.0	149.6	187.0	6BTAA5.9-G12	150	165	TC	6	102*120	5.9	17.3:1	208	CP-274E
CP-C187.5	150.0	187.5	165.0	206.3	6CTA8.3-G2	170	187	TC	6	114*135	8.3	17.3:1	213	CP-274F
CP-C225	180.0	225.0	198.0	247.5	6CTAA8.3-G2	190	210	TC	6	114*135	8.3	18.0:1	214	CP-274G
CP-C250	200.0	250.0	220.0	275.0	6LTAA8.9-G2	235	258	TC	6	114*135	8.9	16.6:1	208	CP-274H
CP-C275	220.0	275.0	242.0	302.5	6LTAA8.9-G3	255	282	TC	6	114*135	8.9	16.6:1	201	CP-274J
CP-C300	240.0	300.0	264.0	330.0	6LTAA9.5-G3	265	290	TC	6	114*135	9.5	16.6:1	201	CP-274K
CP-C325	260.0	325.0	286.0	357.5	6LTAA9.5-G1	280	310	TC	6	114*135	9.5	16.6:1	201	CP-444D
CP-C375	300.0	375.0	330.0	412.5	6ZTAA13-G3	340	380	TC	6	130*163	13.0	17:01	200	CP-444E
CP-C450	360.0	450.0	396.0	495.0	6ZTAA13-G4	400	415	TC	6	130*163	13.0	17:01	206	CP-444F
CP-C500	400.0	500.0	440.0	550.0	QSZ13-G3	450	470	TC	6	130*163	13.0	17:01	199	CP-544C

60 Hz CCEC CUMMINS
DIESEL GENERATOR SETS

Genset Model	Rated Power		Standby Power		Engine Model	Engine Power (kW)		Asp	Cyl	Bore×Stroke (mm×mm)	Displace-ment (L)	Compr-ession Ratio	Fuel Cons. (g/kw.h)	Alternator Model
	kW	kVA	kW	kVA		Rated Power	Standby Power							
CP-C300	240.0	300.0	264.0	330.0	NTA855-G1	287	317	TC	6	140*152	14.0	14.5:1	212.3	CP-274K
CP-C350	280.0	350.0	308.0	385.0	NTA855-G1B	313	347	TC	6	140*152	14.0	14:1	208.8	CP-444D
CP-C375	300.0	375.0	330.0	412.5	NTA855-G3	358	399	TC	6	140*152	14.0	14:1	207.0	CP-444E
CP-C400	320.0	400.0	352.0	440.0	NTA855-G3	358	399	TC	6	140*152	14.0	14:1	207.0	CP-444E
CP-C450	360.0	450.0	396.0	495.0	KTA19-G2	392	448	TC	6	159*159	18.9	14.5:1	213.0	CP-444FS
CP-C500	400.0	500.0	440.0	550.0	KTA19-G3	463	511	TC	6	159*159	18.9	13.9:1	203.0	CP-444F
CP-C562.5	450.0	562.5	495.0	618.8	KTA19-G3A	507	563	TC	6	159*159	18.9	13.9:1	203.0	CP-544C
CP-C600	480.0	600.0	528.0	660.0	KTAA19-G5	533	605	TC	6	159*159	18.9	13.5:1	213.0	CP-544D
CP-C750	600.0	750.0	660.0	825.0	KT38-G	679	747	TC	12	159*159	37.8	15.5:1	193.0	CP-544F
CP-C875	700.0	875.0	770.0	962.5	KTA38-G1	768	847	TC	12	159*159	37.8	14.5:1	216.0	CP-634C
CP-C910	728.0	910.0	800.8	1001.0	KTA38-G2	809	895	TC	12	159*159	37.8	14.5:1	214.0	CP-634C
CP-C937.5	750.0	937.5	825.0	1031.3	KTA38-G2B	830	913	TC	12	159*159	37.8	14.5:1	209.0	CP-634D
CP-C1000	800.0	1000.0	880.0	1100.0	KTA38-G2A	915	1007	TC	12	159*159	37.8	14.5:1	209.0	CP-634E
CP-C1125	900.0	1125.0	990.0	1237.5	KTA38-G4	1007	1112	TC	12	159*159	37.8	13.9:1	207.0	CP-634F
CP-C1375	1100.0	1375.0	1210.0	1512.5	KTA50-G3	1220	1380	TC	16	159*159	50.3	13.9:1	203.0	CP-634G
CP-C1575	1260.0	1575.0	1386.0	1732.5	KTA50-G9	1386	1657	TC	16	159*159	50.3	13.9:1	203.0	CP-634H

Note: 1. Optional alternator brand: Leroy somer, Stamford, Mecc alte or CASPER POWER
2. In line with our policy of continuous product development, we reserve the right to change specification without notice.