Attenda®
2 Shelf Storage Unit



Model	ATN320
Weight	31 lbs / 14.1 kg

Dimensions	in	cm
Width	18"	45.7
Depth	17"	14.2
Height	36"	91.5
Cubby Volume	**cu ft**	**m^3**
Single Cubby	1.3	0.03
Total Cubby Volume	2.6	0.07

**Note: Dimensional tolerances are +1% due to manufacturing process.*

Finishes
See Design Guide for finish options.

Assembly
None required.

**Intended for indoor use only*

Fabrication & Material
Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, ligature resistant, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Anti-ligature design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Made in the U.S.A.

Warranty
10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.

Maintenance
For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation
Anchors required for permanently attaching to solid wall. Anchors not supplied by Norix. Groove along mounting surface for caulk application (caulk not supplied by Norix). Two Shelf unit can be hung horizontal or vertical.

Environmental Test Standards
- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards
- State of California, Technical Bulletin No. 133, Flammability Test Procedurefor Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

One Innovation Drive, West Chicago, IL 60185 | Phone: 630-231-1331 | Toll Free: 800-234-4900 | E-mail: furniture@norix.com
Specifications subject to change without notice. | ©2024 Norix Group, Inc. | All Rights Reserved. | Printed in U.S.A. 9/24