# Attenda®
Stool



| | |
|---|---|
| **Model** | ATN500 |
| **Weight** | 9.5 lbs / 9.5 kg |

| Dimensions | in | cm |
|---|---|---|
| Seat Diameter | 12" | 30.5 |
| Base Diameter | 16.5" | 41.9 |
| Height | 16" | 40.6 |

**Note: Dimensional tolerances are +1% due to manufacturing process.*

## Finishes
See Design Guide for finish options.

## Assembly
None required.

**Intended for indoor use only*

## Fabrication & Material
Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, anti-ligature, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Ligature resistant design with no internal openings. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

## Warranty
10 year limited replacement warranty.

*Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.*

## Maintenance
For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

## Installation
Anchors required for permanently attaching to floor. Anchors not supplied by Norix. Groove along mounting surface for caulk application (caulk not supplied by Norix).

## Patents
This product may be covered by US Patent No. US 8,007,059 B2.

## Performance Test Standards
- Product tested to 1,000 lbs (453.6 kg) static load.

## Environmental Test Standards
- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

## Flammability Test Standards
- State of California, Technical Bulletin No. 133, Flammability Test Procedurefor Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

GREENGUARD GOLD | TruColor COLOR COMPOUNDING TECHNOLOGY | MADE IN THE USA

One Innovation Drive, West Chicago, IL 60185 | Phone: 630-231-1331 | Toll Free: 800-234-4900 | E-mail: furniture@norix.com
Specifications subject to change without notice. | ©2024 Norix Group, Inc. | All Rights Reserved. | Printed in U.S.A. 9/24