Attenda®
Wardrobe



Model	ATN801
Weight	75-80 lbs / 34-36.3 kg

Dimensions	in	cm
Width	26"	66
Depth *(No Door)*	24"	61
Depth *(Door)*	25.5"	64.8
Height	78.4"	199.1

**Note: Dimensional tolerances are +1% due to manufacturing process.*

Finishes
See Design Guide for finish options.

Options
- **ATN801LK, ATN801RK**: Left or Right hinge. Wing Key Lock.
- **ATN801LL, ATN801RL**: Left or Right hinge. Wing Latch.
- **ATN800**: No Door

Assembly
Door field reversible.

**Intended for indoor use only*

Fabrication & Material
Slightly textured maintenance free surface allows for easy cleaning. Rotationally molded, specially formulated, high-impact polyethylene with ultraviolet light stabilizers (to reduce fading). Chemically resistant to blood, vinegar, urine, feces, salt solution and chlorine solution. Premium TruColor™ material is fully compounded for superior color consistency and durability. Unit is filled with rigid polyurethane foam for increased durability and sound absorption. Made in the U.S.A.

Warranty
10 year limited replacement warranty.

Norix recommends products placed in storage prior to installation should be held in a climate controlled area similar to the room where the product will be used. Norix also recommends that any Attenda® products shipped via ocean container maintain a temperature of 70-75°F (21.1-23.9°C) with a Relative Humidity of 35%.

Maintenance
For routine and regular cleaning maintenance, Norix recommends the use of Simple Green® or an equivalent cleaning product. Attenda® products are bleach/water solution cleanable and suitable for use with hospital-grade disinfectants (such as Virex®, Wexcide® or Oxivir Five 16®) per manufacturers' instructions.

Installation
Anchors required for permanently attaching to solid wall. Anchors not supplied by Norix. Bottom and back surfaces have a channel to accommodate security caulk. (Caulk not supplied by Norix).

Patents
This product may be covered by US Patent No. US 8,007,059 B2.

Environmental Test Standards
- GREENGUARD and GREENGUARD Gold Certified by UL Environment. Product certified for low chemical emissions to UL 2818. UL.COM/GG.

Flammability Test Standards
- State of California, Technical Bulletin No. 133, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- State of California, Technical Bulletin No. 117, Flammability Test Procedure for Seating Furniture for Use in Public Occupancies
- UL1056 Fire Test of Upholstered Furniture
- ASTM E1537 Test Method for Fire Testing of Real Scale Upholstered Furniture Items
- NFPA 261 Cigarette Ignition Resistance of Upholstered Furniture

GREENGUARD GOLD | TruColor COLOR COMPOUNDING TECHNOLOGY | MADE IN THE USA

One Innovation Drive, West Chicago, IL 60185 | Phone: 630-231-1331 | Toll Free: 800-234-4900 | E-mail: furniture@norix.com
Specifications subject to change without notice. | ©2024 Norix Group, Inc. | All Rights Reserved. | Printed in U.S.A. 9/24