

KRONES VARIOPAC PRO FS120HR PREVENTIVE MAINTENANCE			
Asset Activity:	Krones Variopac Pro FS 120hr PM	Work Order #:	WO-AUDIT
Machine ID:	VARIOPAC-PRO-L3	Actual Start Date:	_____
Interval:	120 Operating Hours	Actual End Date:	_____
Team Member(s):	Audit Test	Machine Hours:	_____
Generated:	07 May 2026 19:00 UTC	Comments:	_____

STOPPED TASKS					
TASK #	AREA	ACTION	DESCRIPTION	INITIAL	DONE ■
10	SAFETY	LOCKOUT	STOP MACHINE â€” INITIATE CONTROLLED SHUTDOWN â€” PRESS E-STOP â€” ISOLATE MAIN ELECTRICAL SUPPLY â€” APPLY FULL LOCKOUT/TAGOUT TO ALL ISOLATORS â€” DEPRESSURISE PNEUMATIC CIRCUITS		■
20	INSPECT	CHECK	INSPECT FILM WRAPPING ORBITING RODS FOR BENDING, WEAR OR EXCESSIVE PLAY IN BEARINGS â€” MANUALLY OPERATE THROUGH FULL ROTATION â€” CHECK ORBITAL MOTION IS SMOOTH AND CORRECT		■
30	INSPECT	CHECK	CHECK FILM MANDREL 1 SPINDLE BEARINGS FOR WEAR OR PLAY â€” MANUALLY ROTATE AND FEEL FOR ROUGHNESS, BINDING OR UNEVEN RESISTANCE â€” REPLACE BEARING IF WORN		■
40	INSPECT	CHECK	CHECK FILM MANDREL 2 SPINDLE BEARINGS FOR WEAR OR PLAY â€” MANUALLY ROTATE AND FEEL FOR ROUGHNESS, BINDING OR UNEVEN RESISTANCE â€” REPLACE BEARING IF WORN		■
50	CLEAN	CLEAN	CLEAN FILM SPLICING UNIT THOROUGHLY â€” REMOVE ALL ADHESIVE TAPE RESIDUE, FILM STRIPS AND DUST FROM SPLICE TABLE SURFACE â€” USE APPROVED SOLVENT AND LINT-FREE CLOTH		■
60	INSPECT	CHECK	CHECK FILM TENSIONING DEVICE â€” VERIFY SPRING TENSION IS CORRECT AND HAS NOT RELAXED â€” VERIFY ALL TENSION ROLLERS ROTATE FREELY WITHOUT BINDING â€” ADJUST TENSION IF OUTSIDE SPECIFICATION		■
70	CLEAN	CLEAN	CLEAN FILM CUTTING BLADE STATION â€” REMOVE ALL FILM SCRAPS AND DEBRIS â€” INSPECT BLADE EDGE FOR SHARPNESS AND CHIPS â€” WEAR CUT-RESISTANT GLOVES â€” REPLACE BLADE IF EDGE IS DULL OR NICKED		■
80	CLEAN	CLEAN	CLEAN ALL CONTAINER SPACER LUGS â€” REMOVE PRODUCT RESIDUE AND FILM DEBRIS â€” CHECK SPACER LUGS FOR CRACKS OR WEAR â€” REPLACE ANY DAMAGED LUGS BEFORE RETURNING TO SERVICE		■
90	INSPECT	CHECK	INSPECT PUSHER CHAIN TENSION AND CONDITION â€” CHECK CHAIN IS NOT OVER-STRETCHED â€” INSPECT ALL CHAIN LINKS AND ATTACHMENT PLATES FOR WEAR, CRACKS OR DEFORMATION â€” ADJUST TENSION IF REQUIRED		■
100	LUBRICATE	LUBRICATE	APPLY SPECIFIED KRONES CHAIN LUBRICANT TO PUSHER CHAIN PER LUBRICATION SCHEDULE â€” APPLY TO INNER CHAIN LINKS â€” WIPE OFF EXCESS â€” RECORD LUBRICANT TYPE AND QUANTITY IN LUBE LOG		■
110	SAFETY	CHECK	CAUTION: COMPENSATING CONVEYOR CONTINUES OPERATING SLOWLY IN SET-UP MODE â€” KEEP HANDS CLEAR OF CONVEYOR AT ALL TIMES â€” VERIFY CONVEYOR BELT CONDITION AND TRACKING FROM OUTSIDE GUARD		■
120	GENERAL	CONFIRM	REMOVE ALL LOTO DEVICES â€” REINSTATE MACHINE â€” PERFORM E-STOP TEST â€” RUN MACHINE WITH SAMPLE PACKS â€” VERIFY PACKING QUALITY AND FILM WRAP BEFORE RETURNING TO FULL PRODUCTION		■

Technician Name:	_____	Supervisor Approval:	_____	Date:	_____
------------------	-------	----------------------	-------	-------	-------

**** END OF REPORT ****
GENERAL — PRIOR TO RETURNING TO SERVICE FOLLOW ALL GMP PROCEDURES
■ Remove all LOTO (Lockout/Tagout) devices before returning to service
■ Re-check all E-STOP (Emergency Stop) and control switches
■ This document must be signed and retained as a maintenance record

Document hash: (see system) | Generated: 2026-05-07 19:00 UTC | System: PM Automation v1.0