

Automatic Booster Pump AUTO CM



● AUTO CM4/3

● Product Photo :-



● Automatic booster pump

● Features :-

- Wetted parts completely SS304
- Bearing-NSK
- 100% Copper winding motor
- Impeller-AISI304 Stainless Steel
- Motor housing :- Aluminium
- Ambient temperature: -10-50 °C
- Liquid temperature: -10-120 °C
- Single Phase
- 220V
- 60HZ

● Description :-

- Fully intelligent, ultra quiet stainless steel multi-stage pump, dual automatic control function of pressure and water flow,PCB dry running protection, timing memory function, free you from the trouble of installation and debugging, quiet operation below 50 dB, refuse noise pollution, flow passage components adopt sanitary stainless steel, eliminate water rust, high-end electric pump, high-end quality, leading you comfortable life.

● Proformance Table :-

Model	Inlet/Outlet	Power		Q (m³/h)	0.9	1.5	2.1	2.4	3.0	3.6	3.9	4.5	5.1	5.4	8.1
Single phase	inch	KW	HP	(L/min)	15	25	35	40	50	60	65	75	85	90	135
AUTO CM4/3	1"X1"	0.55	0.75	H (meters)	32	30.5	30	29	28.5	27.5	27	25	24	22	20

● Application :-

- Rotor & Spray Irrigation
- Domestic water pressure boosting
- Groundwater transfer
- Domestic ground water intake
- Commercial water pressure boosting
- Community water supply

● Working conditions :-

- PH value : 5-9
- Ambient temperature: -10-50 °C
- Liquid temperature: -10-120 °C
- Relative humidity: max.85% (RH)
- Inlet pressure: must be lower than the starting value of pressure switch

Peroformance curve :

AUTO CM 4/3

