SUZUKI

Way of Life!

Jimny

Smart in city, tough in nature.



PAK SUZUKI MOTOR CO. LTD.



Major Equipment		
Engine		JIMNY
		M13A
Drive system		Part-time 4WD
Grade		JLDX
Transmission		5MT
S=Number of doors		3
CHASSIS		
Tyres and wheels	205/70R15 + steel wheels	S
Spare tyre and wheel	205/70R15 + steel wheel	S
EXTERIOR		
Front grille	Horizontal design + Gunmetal coloured	S
Wheel arch extensions	Black	S
Side splash panels	Black	S
Outside door handles	Unpainted	S
VISIBILITY		
Headlamps	Halogen multireflector	S
Wipers	Front: 2-speed (low, high) + intermittent + washer	S
	Rear: 1-speed + intermittent + washer	S
Rear window demister		S
Outside door mirrors	Black	S
Day / night rearview mirror		S
STEERING AND INSTRUMENT PANEL		
3-spoke steering wheel	Urethane	S
Power steering	Hydraulic	S
Tachometer		S
Light-off and key reminder	Alarm	S
Door ajar reminder	Alarm	S
Low fuel warning	Lamp	S
Instrument panel centre garnishes	Silver coloured	S
INTERIOR		
Air conditioner	Manual	S
Heater		S
Cabin lights	Front cabin light (3-position)	S
Driver's sun visor	With ticket holder & vanity mirror	S
Passenger's sun visor		S
Assist grips	Passenger's side	S
	Rear x 2	S
Cup holders	Front x 2 (MT)	S
	Rear x 2	S
12V interior accessory socket	Instrument panel x 1	S
Ashtray		S
Remote fuel lid opener		S
SEATS		
Front seats	Walk-in mechanism (passenger's side)	S
Rear seat	50:50-split single-folding	S
Seat upholstery material	Fabric	S
LUGGAGE AREA		
Luggage area behind rear seats		S
SAFETY AND SECURITY		
Seatbelts	Front: 3-point ELR seatbelts with height adjusters	S
	Rear: 3-point ELR seatbelts x 2	S
Side impact door beams		S

Specifications			
			JIMNY
			4WD
			5MT
DIMENSIONS			
Overall length	Front bumper to spare tyre	mm	3,695
Overall width		mm	1,600
Overall height		mm	1,670
Wheelbase		mm	2,250
Tread	Front	mm	1,355
	Rear	mm	1,365
MInimum turning radius		m	4.9
MInimum ground clearance		mm	190
CAPACITIES			
Seating capacity		persons	4
Luggage capacity	Max. Volume (Manufacturer data)	litre	816
	Rear seat back tumble-folded (VDA method)	litre	324
	Rear seat back raised (VDA method)	litre	113
Fuel tank capacity		litre	40
ENGINE			
Type			M13A
Number of cylinders			4
Number of valves			16
Piston displacement		cm^3	1,328
Bore x stroke		mm	78.0 x 69.5
Compression ratio			9.5:1
Maximum output		kW/rpm	60/5,500
Maximum torque		N·m/rpm	110/4,500
Fuel distribution			Multipoint injection
TRANSMISSION			
Type			5MT
Gear ratio	1st		4.425
	2nd		2.304
	3rd		1.674
	4th		1.190
	5th		1.000
	Reverse		5.151
Final gear ratio			4.300
Transfer gear ratio	High		1.000
	Low		2.002
CHASSIS			
Steering			Recirculating ball
Brakes	Front		Solid Disc
	Rear		Drum, leading & trailing
Suspension	Front		3-link rigid axle with coil spring
	Rear		3-link rigid axle with coil spring
Tyres			205/70R15
WEIGHT			
Kerb weight (min./with full option)		kg	1,060
Gross vehicle weight		kg	1,420

Pak Suzuki Motor Co. Ltd. reserves the right to change, without notice, prices, colours, materials, equipments, specification and models and also to discontinue models.

Please visit nearest Suzuki Authorized Dealership for colour and vehicle availability.

ORIENTmMcCANN

PAK SUZUKI MOTOR CO. LTD.

Suzuki Pakistan @SuzukiPakistan Suzuki Pakistan

Head Office Karachi:
DSU-13, Pak Steel Industrial Estate, Bin Qasim, Karachi.
Call Centre: 111-SUZUKI (021-111-789-854)
Tel: 34723551-58 Fax: 34723521-3
E-mail: customercentre@paksuzuki.com.pk
Website: www.paksuzuki.com.pk

Region Office Lahore:
7-A, Aziz Avenue, Canal Bank Road,
Gulberg-5, Lahore.
Tel: 042-35775456-7
Fax: 042-35775467

Region Office Rawalpindi:
3rd Floor Malhi Plaza, Opp. Ministry of Defence,
Production Building, Murree Road, Rawalpindi, Cantt.
Tel: 051-5130229-31 Fax: 051-5130232

Region Office Multan:
Office No. 402, 4th Floor
United Mall, Abdali Road, Multan.
Tel: 061-4586489, 4516491
Fax: 061-4581353