

techniques-for-cross-validation

October 29, 2023

1 Cross-Validation implementation

2 There are different Cross-Validation techniques

- Hold-out cross-validation
- K-folds cross-validation
- Leave-one-out cross-validation
- Leave-p-out cross-validation
- Stratified K-folds cross-validation
- Repeated K-folds cross-validation
- Group K-Fold Cross-Validation
- Time series CV cross-validation

Hold-Out based Validation

```
[4]: import numpy as np
from sklearn.model_selection import train_test_split
X, y = np.arange(10).reshape((5, 2)), range(5)
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.
↪2, random_state=111)
```

K-folds cross-validation

```
[5]: import numpy as np
from sklearn.model_selection import KFold

X = np.array([[1, 2], [3, 4], [1, 2], [3, 4]])
y = np.array([1, 2, 3, 4])
kf = KFold(n_splits=2)

for train_index, test_index in kf.split(X):
    print("TRAIN:", train_index, "TEST:", test_index)
    X_train, X_test = X[train_index], X[test_index]
    y_train, y_test = y[train_index], y[test_index]
```

TRAIN: [2 3] TEST: [0 1]

TRAIN: [0 1] TEST: [2 3]

- Leave-one-out cross-validation

```
[6]: import numpy as np
from sklearn.model_selection import LeaveOneOut

X = np.array([[1, 2], [3, 4]])
y = np.array([1, 2])
loo = LeaveOneOut()

for train_index, test_index in loo.split(X):
    print("TRAIN:", train_index, "TEST:", test_index)
    X_train, X_test = X[train_index], X[test_index]
    y_train, y_test = y[train_index], y[test_index]
```

TRAIN: [1] TEST: [0]

TRAIN: [0] TEST: [1]

- Leave-p-out cross-validation

```
[7]: import numpy as np
from sklearn.model_selection import LeavePOut

X = np.array([[1, 2], [3, 4], [5, 6], [7, 8]])
y = np.array([1, 2, 3, 4])
lpo = LeavePOut(2)

for train_index, test_index in lpo.split(X):
    print("TRAIN:", train_index, "TEST:", test_index)
    X_train, X_test = X[train_index], X[test_index]
    y_train, y_test = y[train_index], y[test_index]
```

TRAIN: [2 3] TEST: [0 1]

TRAIN: [1 3] TEST: [0 2]

TRAIN: [1 2] TEST: [0 3]

TRAIN: [0 3] TEST: [1 2]

TRAIN: [0 2] TEST: [1 3]

TRAIN: [0 1] TEST: [2 3]

- Stratified k-Fold cross-validation

```
[8]: import numpy as np
from sklearn.model_selection import StratifiedKFold

X = np.array([[1, 2], [3, 4], [1, 2], [3, 4]])
y = np.array([0, 0, 1, 1])
skf = StratifiedKFold(n_splits=2)

for train_index, test_index in skf.split(X, y):
    print("TRAIN:", train_index, "TEST:", test_index)
    X_train, X_test = X[train_index], X[test_index]
    y_train, y_test = y[train_index], y[test_index]
```

TRAIN: [1 3] TEST: [0 2]
TRAIN: [0 2] TEST: [1 3]

- Repeated k-Fold cross-validation

```
[9]: import numpy as np
      from sklearn.model_selection import RepeatedKFold

      X = np.array([[1, 2], [3, 4], [1, 2], [3, 4]])
      y = np.array([0, 0, 1, 1])
      rkf = RepeatedKFold(n_splits=2, n_repeats=2, random_state=42)

      for train_index, test_index in rkf.split(X):
          print("TRAIN:", train_index, "TEST:", test_index)
          X_train, X_test = X[train_index], X[test_index]
          y_train, y_test = y[train_index], y[test_index]
```

TRAIN: [0 2] TEST: [1 3]
TRAIN: [1 3] TEST: [0 2]
TRAIN: [0 2] TEST: [1 3]
TRAIN: [1 3] TEST: [0 2]

- Group K-Fold Cross-Validation

```
[ ]:
```