SOFTWARE ENGINEERING · LECTURE 5

Scan to follow along

Open today's slides on your own phone or laptop — then you can run real code yourself.

`hassanmiir.github.io/cpp-course/lecture5/`



📱 Point your camera here

👁 0 opened today

Dr. Mir Hassan

Associate Professor in Artificial Intelligence and Trustworthy Digital Systems

LECTURE 5 · LOOPS

Never write the same line twice

Grade 200 students by copy-pasting `cout` 200 times? Never.

A **loop** does the same work again and again — 5 times or 5 million — from **three lines**.

A 2-hour hands-on session · you'll build a multiplication table

WHERE WE LEFT OFF

Last time your program chose a path *once*

An `if` runs its block **zero or one** time. But a gradebook has 30 students, a table has 12 rows, a game runs every frame...

You need to do something **many** times. That's a `loop` — and it's three ideas: **start**, **keep going while...**, **step**.



1 → 2 → 3 → ... → done

PART 1

The while loop

Keep repeating as long as a condition stays true.

- Check, run, repeat
- The infinite-loop trap
- Run a countdown — live




THE SHAPE

Check the condition, run the body, repeat

```cpp
int i = 1;                  // start
while (i <= 3) {            // keep going while true
    cout << i << " ";
    i = i + 1;              // step — or it never ends!
}
```

Prints `1 2 3`. When `i` becomes 4, the test is false and the loop exits.



YOUR TURN · LIVE CODE RUN IT!

A countdown

Run it. Then change the start number. What happens if you delete the `n = n - 1` line? (Don't — that's the infinite loop!) (Input: 5)

main.cpp ▶ Run ↺ Open in OnlineGDB ▸

```
#include <iostream>
using namespace std;

int main() {
    int n;
    cin >> n;

    while (n > 0) {
        cout << n << "... ";
        n = n - 1;          // the step that ends the loop
    }
    cout << "Liftoff!" << endl;
```

OUTPUT Ready

Click ▶ Run to see the output here.

YOU BE THE COMPUTER ON PAPER · 3 MIN

Trace it — what does it print?

Run this loop **in your head**. Write every value of `i` that gets printed, in order.

```
int i = 2;
while (i < 10) {
    cout << i << " ";
    i = i + 3;
}
```

Output: ? ? ? ?

How many numbers print? ?

✏️ **Track i each time: 2, then +3, then +3... stop when i < 10 is false.**

THE ANSWER

Three numbers: `2 5 8`

`i = 2 ✓ print` `i = 5 ✓ print` `i = 8 ✓ print` **`i = 11 ✗ stop`**

The off-by-one trap

After printing 8, `i` becomes 11. The check `11 < 10` is false, so 11 never prints. Always ask: *what's the last value that passes the test?*

PART 2

The for loop

The same three ideas — start, test, step — on one tidy line.



- Count a known number of times
- Build a multiplication table

THREE PARTS, ONE LINE

`for` — start, test, step together

```
for (int i = 1; i <= 5; i++) {
    cout << i << " ";
}
// prints 1 2 3 4 5
```

`i++` is shorthand for `i = i + 1`.

`int i = 1` — start
Runs once, before the loop begins.

`i <= 5` — test
Checked before every pass. True → run; false → stop.

`i++` — step
Runs after each pass. Moves you toward the end.

while vs for
Same three ideas. Use `for` when you know *how many times*; `while` when you loop *until something happens*.

YOUR TURN · LIVE CODE RUN IT!

A multiplication table

The 7× table, built by a loop. Change `7` to your favourite number and run. (Input: none)

main.cpp ▶ Run ↺ Open in OnlineGDB ▸

```cpp
#include <iostream>
using namespace std;

int main() {
    int table = 7;
    for (int i = 1; i <= 10; i++) {
        cout << table << " x " << i << " = " << table * i << endl;
    }
    return 0;
}
```

OUTPUT Ready

```
Click ▶ Run to see the output here.
```

QUICK CHECK THINK!

How many times does this loop run?

```
for (int i = 0; i < 5; i++) {
    cout << "*";
}
```

Careful with the start value and the `<`.

A 4 times

B 5 times


C 6 times

PART 3

break, continue & traps

Escape early, skip a turn — and dodge the loops that never end.

- break — leave now
- continue — skip to next
- the infinite loop



TWO ESCAPE HATCHES

`break` leaves · `continue` skips

```
for (int i = 1; i <= 10; i++) {
    if (i == 5) break;      // stop the whole loop at 5
    cout << i;              // prints 1234
}

for (int i = 1; i <= 5; i++) {
    if (i == 3) continue;   // skip just this turn
    cout << i;              // prints 1245
}
```



`break`

Exits the loop entirely — found what you wanted, stop looking.



`continue`

Skips the rest of *this* pass, jumps to the next one.

DANGER ZONE

The loop that never ends

```cpp
int i = 1;
while (i <= 5) {
    cout << i;
    // forgot i++  →  i is ALWAYS 1
}   // prints 1 1 1 1 1 1 ... forever
```

Why it hangs

If the condition never becomes false, the loop runs forever and your program freezes.

The rule

Every loop must **change something** that moves the condition toward false.

If it ever hangs

Press `Ctrl + C` (or close the tab) to stop it — then find the missing step.

QUICK CHECK THINK!

What does this print?

```
for (int i = 1; i <= 6; i++) {
    if (i == 4) break;
    cout << i;
}
```

A 123

B 1235 6

C 12356

PART 4

Build it: sum & table

Add up 1…N, then print a full times-table — pure loop power.

- Sum 1 + 2 + … + N
- The full multiplication table
- Work with a partner



PAIR CHALLENGE · USE YOUR BRAIN 15 MIN

Sum, then the table

Read a number `N`, then:

1. Sum: use a loop to add `1 + 2 + … + N` and print the total.
2. Table: print the full `N × table` (N×1 up to N×10), one line each.
3. Stretch: print only the even numbers from 1 to N (hint: `i % 2 == 0`).

15:00

❚❚ Pause ↺ +1 min

Watch the bounds

For the sum, loop `i <= N` (not `< N`) so N itself is included. Start your running total at 0.

PAIR CHALLENGE · BUILD HERE RUN IT!

Your sum & table

Starter reads N. **You add** the sum loop and the table loop. (Input: 5)

main.cpp ▶ Run ↺ Open in OnlineGDB ▸

```
#include <iostream>
using namespace std;

int main() {
    int N;
    cin >> N;

    // TODO 1 — SUM: start total = 0, loop i from 1 to N, total += i
    int total = 0;
    for (int i = 1; i <= N; i++) {
        total = total + i;
    }
```

OUTPUT Ready

```
Click ▶ Run to see the output here.
```

ONE SOLUTION COMPARE YOURS

How it works

```cpp
int total = 0;
for (int i = 1; i <= N; i++)   // 1..N inclusive
    total += i;                // running sum
cout << "Sum = " << total << endl;

for (int i = 1; i <= 10; i++)  // the table
    cout << N << " x " << i << " = " << N * i << endl;

// stretch: even numbers
for (int i = 1; i <= N; i++)
    if (i % 2 == 0) cout << i << " ";
```

Running total

Start at 0, add `i` each pass. `+=` is "add to".

One loop, ten lines

The loop variable `i` becomes the multiplier.

Even filter

`i % 2 == 0` inside the loop — last lecture's trick, reused.

RECAP

What you can do now

Repeat

`while` loops until a condition turns false; `for` counts a known number of times — same three ideas.

Control

`break` leaves early, `continue` skips a turn — and every loop must move toward its end.

Milestone

Your programs now scale — the same few lines handle 5 students or 5 million. That's the power of a loop.

KEEP THESE WORDS

Today's keywords — click any one for a reminder

`while` Loop while true	**`for`** Counting loop	**`i++`** Add one	**`break`** Exit the loop
`continue` Skip a turn	**`infinite loop`** Never ends	**`off-by-one`** The ±1 bug	**`i`** Loop counter

BEFORE NEXT TIME

Practice (15–20 min)

Factorial

Read N, compute `N! = 1×2×…×N` with a loop (start the product at 1, not 0!).

A triangle of stars

Print a right triangle: row 1 has one `*`, row 2 has two… up to N. (A loop inside a loop!)

Loop your gradebook

Read 5 scores in a loop and print the average — Group B needs this for a whole class.

NEXT LECTURE

Lecture 6 — Functions

Loops repeat lines in *one* place. Next you'll wrap code in a **function** — name it once, call it anywhere, as many times as you like.



- Write your own functions
- Pass in values, get a result back
- Turn your calculator into reusable tools



Three lines, a million times.

Loops are how a short program does enormous work. You just unlocked scale. Next: naming and reusing your code.

Dr. Mir Hassan · Associate Professor in AI & Trustworthy Digital Systems