CSS Pseudo cheat sheet

Simple selectors

Selector	Syntax	Example
Element	element	`div {` `}`
Class	.class	`.alpha {` `}`
ID	#id	`#alpha {` `}`
Universal	*	`* {` `}`

Variations of simple selectors

Elements	Syntax	Example	Description
Two classes	.first-class.second-class	`.alpha.beta {` `}`	All elements with classes alpha and beta
Element and class	element.class	`p.alpha {` `}`	All alpha class elements inside <p>
Two elements	element, element	`p, div {` `}`	All <p> and <div> elements
Two elements	element element	`p div {` `}`	All <div> elements inside <p>

Descendant selectors/combinators

Selector	Syntax	Example	Description
Descendant	element element	`div p {` `}`	All <p> descendants of <div>
Child	element>element	`div > p {` `}`	All <p> direct descendants of <div>
Adjacent Sibling	element+element	`div + p {` `}`	<p> element directly after <div>
General Sibling	element~element	`div ~ p {` `}`	All <p> element iterations after <div>

Attribute selectors

Selector	Syntax	Example
[attribute]	`[href] {` `}`	Selects all elements with a href attribute
[attribute=value]	`[lang="fr"] {` `}`	Selects all elements with lang attribute that has a value of "fr"
[attribute~=value]	`[input~=hello] {` `}`	Elements with input attribute containing the whitespace separated substring "hello"
[attribute|=value]	`[lang|=en] {` `}`	Elements with lang attribute value equal to "en" or "en-"(en hyphen)
[attribute^=value]	`a[href^="https"] {` `}`	Every <a> element with href attribute value begins with "https"
[attribute$=value]	`a[href$=".docx"] {` `}`	Every <a> element with href attribute value ends with ".docx"
[attribute*=value]	`a[href*="meta"] {` `}`	Every <a> element with href attribute value has substring "meta"

Pseudo-class	Example	Description of selection
:active	`a:active {` `}`	All active links
:checked	`input:checked {` `}`	All the checked <input> elements
:default	`input:default {` `}`	All default <input> elements
:disabled	`input:disabled {` `}`	All disabled <input> elements
:empty	`div:empty {` `}`	All the <div> elements with no children
:enabled	`input:enabled {` `}`	All the enabled <input> elements
:first-child	`p:first-child {` `}`	All the <p> elements who are the first child of a parent element
:first-of-type	`p:first-of-type {` `}`	All the <p> element who are the first <p> element of a parent element
:focus	`input:focus {` `}`	Input element under focus
:fullscreen	`:fullscreen {` `}`	The element in full-screen mode
:hover	`p:hover {` `}`	Action effect on mouse hover
:invalid	`input:invalid {` `}`	Input elements with an invalid value
:last-child	`p:last-child {` `}`	All the <p> elements who are the last child of a parent element
:last-of-type	`p:last-of-type {` `}`	All the <p> elements who are the last <p> element of a parent element
:link	`a:link {` `}`	All unvisited links
:not(*selector*)	`:not(div) {` `}`	All the elements that are not a <div> element
:nth-child(*n*)	`div:nth-child(3) {` `}`	All the <p> elements that are the third child of a parent element
:nth-last-child(*n*)	`div:nth-last-child(3) {` `}`	All the <div> elements which are the third child of a parent element, counting from last child element
:nth-last-of-type(*n*)	`p:nth-last-of-type(2) {` `}`	The second sibling from the last child of a parent element.
:nth-of-type(*n*)	`p:nth-of-type(2) {` `}`	The second sibling of a parent element.
:only-of-type	`p:only-of-type {` `}`	All the <p> elements which are only <p> elements inside its parent
:only-child	`p:only-child {` `}`	All the <p> elements which are only child of a parent element
:optional	`input:optional {` `}`	The input elements with no "required" attribute
:required	`input:required {` `}`	Selects input elements with the "required" attribute specified
:root	`:root {` `}`	The Root element of document
::selection	`::selection {` `}`	The portion of an element that is selected by a user
:valid	`input:valid {` `}`	All the input elements with a valid value
:visited	`a:visited {` `}`	Selects all visited links

Pseudo-element selectors

Syntax	Example	Description
::after	`p::after {` `}`	Inserts content after content of <p> element
::before	`p::before {` `}`	Inserts content before content of <p> element
::first-letter	`p::first-letter {` `}`	Selects first letter of every <p> element
::first-line	`p::first-line {` `}`	Selects first line of every <p> element
::placeholder	`input::placeholder {` `}`	Selects input elements with "placeholder" attribute specified
::marker	`::marker {` `}`	Selects markers in a list