

<ul style="list-style-type: none"> SetIpv6ProbeFalse Forces the result of the browser's IPv6 probing (i.e. IPv6 connectivity test) to be unsuccessful. This causes IPv4 addresses to be prioritized over IPv6 addresses. Without this flag, the probing result is set to be successful, which causes IPv6 to be used over IPv4 when possible. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #set-ipv6-probe-false 	Enabled ▼
<ul style="list-style-type: none"> Handling of extension MIME type requests Used when deciding how to handle a request for a CRX or User Script MIME type. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #extension-mime-request-handling 	Always prompt for ins ▼
<ul style="list-style-type: none"> Disable search engine collection Prevents search engines from being added automatically. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #disable-search-engine-collection 	Enabled ▼
<ul style="list-style-type: none"> Show avatar/people/profile button Show avatar/people/profile button in the browser toolbar. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS #show-avatar-button 	Never ▼
<ul style="list-style-type: none"> Omnibox Autocomplete Filtering Restrict omnibox autocomplete results to a combination of search suggestions (if enabled), bookmarks, and internal chrome pages. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #omnibox-autocomplete-filtering 	Search suggestions c ▼
<ul style="list-style-type: none"> Popups to tabs Makes popups open in new tabs. ungoogled-chromium flag – Mac, Windows, Linux, ChromeOS, Android #popups-to-tabs 	Enabled ▼
<ul style="list-style-type: none"> Clear data on exit Clears all browsing data on exit. ungoogled-chromium flag – Mac, Windows, Linux, ChromeOS #clear-data-on-exit 	Disabled ▼
<ul style="list-style-type: none"> Remove Tabsearch Button Removes the tabsearch button from the tabstrip. ungoogled-chromium flag – Mac, Windows, Linux, ChromeOS #remove-tabsearch-button 	Enabled ▼
<ul style="list-style-type: none"> Disable QR Generator Disables the QR generator for sharing page links. ungoogled-chromium flag – Mac, Windows, Linux, ChromeOS #disable-qr-generator 	Enabled ▼
<ul style="list-style-type: none"> Tab Hover Cards Allows removing the tab hover cards or using a tooltip as a replacement. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS #tab-hover-cards 	Tooltip ▼
<ul style="list-style-type: none"> Disable Sharing Hub Disables the sharing hub button. ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS #disable-sharing-hub 	Enabled ▼
<ul style="list-style-type: none"> Enable get*ClientRects() fingerprint deception Scale the output values of Range::getClientRects() and Element::getBoundingClientRect() with a randomly selected factor in the range -0.0003% to 0.0003%, which are recomputed on every document initialization. ungoogled-chromium flag, Bromite feature. – Mac, Windows, Linux, ChromeOS, Android 	Enabled ▼

<ul style="list-style-type: none"> Enable Canvas::measureText() fingerprint deception Scale the output values of Canvas::measureText() with a randomly selected factor in the range -0.0003% to 0.0003%, which are recomputed on every document initialization. ungoogled-chromium flag, Bromite feature. – Mac, Windows, Linux, ChromeOS, Android #fingerprinting-canvas-measuretext-noise 	Enabled ▾
<ul style="list-style-type: none"> Enable Canvas image data fingerprint deception Slightly modifies at most 10 pixels in Canvas image data extracted via JS APIs. ungoogled-chromium flag, Bromite feature. – Mac, Windows, Linux, ChromeOS, Android #fingerprinting-canvas-image-data-noise 	Enabled ▾
<ul style="list-style-type: none"> Disable Top Sites Disables the top sites and most visited entries on the new tab page. Chromium feature, ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #disable-top-sites 	Enabled ▾
<ul style="list-style-type: none"> No default browser check Disables the default browser check. Chromium feature, ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS #no-default-browser-check 	Enabled ▾
<ul style="list-style-type: none"> No Pings Don't send hyperlink auditing pings. Chromium feature, ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #no-pings 	Enabled ▾
<ul style="list-style-type: none"> WebRTC IP policy Restrict which IP addresses and interfaces WebRTC uses. Chromium feature, ungoogled-chromium flag. – Mac, Windows, Linux, ChromeOS, Android #webrtc-ip-handling-policy 	Default public interfa ▾
<ul style="list-style-type: none"> Allow WebRTC to adjust the input volume. Allow the Audio Processing Module in WebRTC to adjust the input volume during a real-time call. Disable if microphone muting or clipping issues are observed when the browser is running and used for a real-time call. This flag is experimental and may be removed at any time. – Mac, Windows, Linux #enable-webrtc-allow-input-volume-adjustment 	Disabled ▾
<ul style="list-style-type: none"> Smooth Scrolling Animate smoothly when scrolling page content. – Windows, Linux, ChromeOS, Android #smooth-scrolling 	Enabled ▾
<ul style="list-style-type: none"> Connect to Cast devices on all IP addresses Have the Media Router connect to Cast devices on all IP addresses, not just RFC1918/RFC4193 private addresses. – Mac, Windows, Linux, ChromeOS #media-router-cast-allow-all-ips 	Disabled ▾
<ul style="list-style-type: none"> Parallel downloading Enable parallel downloading to accelerate download speed. – Mac, Windows, Linux, ChromeOS, Android #enable-parallel-downloading 	Enabled ▾