



INF 551

Wensheng Wu

Installation on EC2

- Create a new yum repository file for MongoDB
 - `cd /etc/yum.repos.d`
 - Create a file called: `mongodb-org-4.0.repo`
- Add the following content to the file:
 - `[mongodb-org-4.0]`
 - `name=MongoDB Repository`
 - `baseurl=https://repo.mongodb.org/yum/amazon/2013.03/mongodb-org/4.0/x86_64/`
 - `gpgcheck=1`
 - `enabled=1`
 - `gpgkey=https://www.mongodb.org/static/pgp/server-4.0.asc`

Installation on EC2

- `sudo yum -y install mongodb-org`
- `sudo service mongod start`
 - Start the server
- `sudo service mongod stop`
 - Stop it

Document store

- MongoDB is a document database
- A document is similar to a JSON object
 - Consists of field-value pairs
 - Value may be another document, array, string, number, etc.
- Document = record/row in RDBMS

Collections

- Documents are stored in a collection
- Collection = table in RDBMS
- But documents may have different structures
 - In contrast, records in RDBMS have the same schema

Primary key

- Every document has a unique `_id` field
 - That acts as a primary key

MongoDB shell

- mongo

```
[ec2-user@ip-172-31-18-182 yum.repos.d]$ mongo
MongoDB shell version v3.4.9
connecting to: mongodb://127.0.0.1:27017
MongoDB server version: 3.4.9
Welcome to the MongoDB shell.
For interactive help, type "help".
For more comprehensive documentation, see
  http://docs.mongodb.org/
Questions? Try the support group
  http://groups.google.com/group/mongodb-user
Server has startup warnings:
2017-10-17T04:54:38.148+0000 I STORAGE [initandlisten]
2017-10-17T04:54:38.148+0000 I STORAGE [initandlisten] ** WARNING: Using
the XFS filesystem is strongly recommended with the wiredTiger storage
engine
2017-10-17T04:54:38.148+0000 I STORAGE [initandlisten] **           See
http://dochub.mongodb.org/core/prodnotes-filesystem
2017-10-17T04:54:38.225+0000 I CONTROL [initandlisten]
2017-10-17T04:54:38.225+0000 I CONTROL [initandlisten] ** WARNING: Access
control is not enabled for the database.
2017-10-17T04:54:38.225+0000 I CONTROL [initandlisten] **           Read
and write access to data and configuration is unrestricted.
2017-10-17T04:54:38.225+0000 I CONTROL [initandlisten]
> |
```

Create a new database

- No need to explicitly create it, just use it
 - It will be automatically created once you add a collection (i.e., table) to it

```
> show databases;
local  0.000GB
> use inf551
switched to db inf551
> show databases;
local  0.000GB
> use inf551
switched to db inf551
> db.createCollection('person')
{ "ok" : 1 }
> show databases;
inf551  0.000GB
local  0.000GB
```

```
> use inf551
switched to db inf551
> show collections
person
> show tables
person
> |
```


Databases

- use inf551
 - Switch to database "inf551"
- show databases
 - List all databases
- show tables/show collections
 - List all tables/collections in the current db
 - Can also say "show collections"

Database

- Dropping a database
 - `db.dropDatabase();`

Create/drop a collection

- `db.createCollection('person')`
 - `db` is a shell variable representing the current db
- `db.person.drop()`
 - Dropping a collection

Adding documents

- `db.person.insert({"_id": 1, "name": "john smith"})`
 - May omit `""` in keys when doing insert
 - May also use single quotes (**unlike JSON**)
- `db.person.insert({"_id": 1, "name": "david smith"})`
 - Error: duplicate key!

ObjectId()

- ObjectId() function creates an ID
- `db.person.insert({"_id": ObjectId(), "name": "john smith"})`

```
writeResult({ "nInserted" : 1 })
> db.person.find()
{ "_id" : 1, "name" : "john smith" }
{ "_id" : ObjectId("58250aec7c61126eba98db48"), "name" : "john smith" }
```

ObjectId()

- `db.person.insert({"name": "john smith"})`
 - Here no specification of `"_id"` field
 - But an id will be automatically created

```
> db.person.find()
{ "_id" : 1, "name" : "john smith" }
{ "_id" : ObjectId("58250aec7c61126eba98db48"), "name" : "john smith" }
{ "_id" : ObjectId("58250d56249e740a9ddfbacc"), "name" : "john smith" }
> |
```

ObjectId()

- A 12-byte hexademical value
 - E.g., 58250aec7c61126eba98db48
- Among 12 bytes:
 - 4-byte: the seconds since 1970/1/1
 - 3-byte: machine identifier
 - 2-byte: process id
 - 3-byte: a counter, starting with a random value

Embedded sub-document

- `db.person.insert(
 {
 "name": "david johnson",
 "address": {"street": "123 maple",
 "city": "LA",
 "zip": 91989},
 "phone": ["323-123-0000", "626-124-0999"],
 "scores": [25, 35]
 })`

Array

Insert multiple documents at once

- `db.person.insertMany([{"name": "kevin small", "age": 35, "scores": [5, 6, 3]}, {"name": "mary lou", "age": 25, "scores": [5, 8, 2]}])`

Query

- `db.person.find()`
 - Return all documents in person
- `db.person.find({"name": "kevin small"})`
 - Return all documents with specified name
- `db.person.find().pretty()`
 - Pretty print the output

Query operators

- Introduced by \$
- \$lt, \$gt, \$lte, \$gte, \$ne, \$in, \$all
 - Comparison operators
- \$or, \$and, \$not
 - Logical operators

Query operators

- `db.person.find({"age": {$gt: 25}})`
- `db.person.find({"name": "kevin small", "age": {$gt: 25}})`
 - Specify "and" condition
- `db.person.find({ $or: [{"name": "kevin small"}, {"age": {$gt: 25}}] })`
 - Specify "or" condition

Query operator

- `db.person.find({name: {$not: {$eq: "john"}}})`
 - May omit "" in keys when doing find


Same as:

- `db.person.find({name: {$ne: "john"}})`

\$in

- `db.person.find({age: {$in: [25, 35]}})`
 - Find persons whose age are either 25 or 35
- \$in matches any of the values in the array

Pattern matching

- `db.person.find({"name":/Kevin/i})`
 - This finds person whose name contains "kevin"
 - "i" means case-insensitive
 - Above is equivalent to:
 - `db.person.find({"name":{"$regex": /Kevin/, $options: 'i'}})`
 - In general, `/pattern/` where pattern is a regular expression
- \$regex is a query operator**
- 

Query operator

- What does each of these queries find?
 - `db.person.find({$or: [{"name":/kevin/i}, {"age":25}]})`
 - `db.person.find({$or: [{"name":/kevin/i, "age":25}]})`
 - `db.person.find({$and: [{"name":/kevin/i}, {"age":25}]})`

Matching elements in array

- `db.person.find({"scores": {$gt: 20}})`
 - Note the "scores" field is an array and at least one value of the array should satisfy the specified condition (i.e., > 20)
- `db.person.find({scores: {$all: [2, 5]}})`
 - Find persons whose scores contain both 2 and 5 (all elements in the given array)
 - Compared to: `db.person.find({scores: {$in: [2, 5]}})`

Sorting

- `db.person.find().sort({age:-1})`
 - 1 for ascending; -1 descending
- Equivalent to:
 - Select *
 - From person
 - Order by age desc

Skip & limit

- `db.person.find().limit(1)`
 - Returns the first person
- `db.person.skip(1).limit(1)`


Distinct

- `db.person.distinct("age")`
- `db.person.distinct("age", {age: {$gt: 20}})`
 - distinct ages (for ages > 20)

Count()

- `db.person.count()`
 - Return # of documents in the person collection
- `db.person.count({age: {$gt: 25}})`
 - What does this do?
- `db.person.find({age: {$gt: 25}}).count()`

Projection

- `db.person.find(`
 `{"age": {$ne: 25} },`
 `{"name":1, "age": 1}`
 `)`


Specify query condition

Specify projection
1: included in result; 0: do not
- This will return name and age (plus `_id`)
 - i.e., similar to 'select `_id`, name, age from users where age `!= 25`'

Projection

- This does not work:
 - `db.person.find(
 {"age": {$ne: 25} },
 {"name":1, "age": 0}
)`
 - Can not mix 1 and 0 conditions (unless it is "_id")

Projection

- `db.person.find(
 {"age": {$ne: 25} },
 {"name":1, "age": 1, "_id": 0}
)`
- This does not return id, e.g.,
 { "name" : "john smith" }
 { "name" : "david johnson" }
 { "name" : "kevin small", "age" : 35 }

Example

- Without projection

```
> db.person.find({"age": 25})
{ "_id" : ObjectId("582559b19f185cd8ccf23ff6"), "name" : "mary lou", "age" : 25 }
```

- With projection

```
> db.person.find({"age": 25}, {"name": 1, _id: 0})
{ "name" : "mary lou" }
```

Update/upsert documents

- `db.person.update(`
 `{ "age": { $gt: 25 } },`
 `{ $set: { "status": "C" } },`
 `{ multi: true }`
)
- Existing documents may not have status field; if not, insert it instead
- Update one or all documents


Similar to:

Update users set status = 'C' where age > 25

Another example

- `db.person.update({}, {$set: {"status":'C'}}, {multi:true})`
 - Note the empty query `{}`
- Add "status" field to all documents

Remove fields

- `db.person.update({}, {$unset: {"status": ""}}, {multi: true})`

Can put any value here
- Remove the "status" field from all documents

Remove documents

- `db.person.remove({})`
 - Remove all documents/records of person
- `db.person.remove({ "age": {$gt: 30} })`
 - Remove documents which satisfy a condition

Remove a collection/table

- `db.person.drop()`
 - This will remove the person collection/table

Query a embedded document

- Using **dot notation** to identify field in the embedded document
- `db.person.find({"address.city": "LA"})`
 - Return all documents whose city sub-field of address field = "LA"
 - Note "" is required here for key

Example for aggregation

- `db.product.insert({category: "cell", store:1, qty: 10})`
- `db.product.insert({category: "cell", store:2, qty: 20})`
- `db.product.insert({category: "laptop", store:1, qty: 10})`
- `db.product.insert({category: "laptop", store:2, qty: 30})`
- `db.product.insert({category: "laptop", store:2, qty: 40})`

Aggregation: sum

- `db.product.aggregate({$group: {_id: "$category", total: {$sum: "$qty"}}})`
 - `{ "_id" : "laptop", "total" : 80 }`
 - `{ "_id" : "cell", "total" : 30 }`
- Similar to: `"select category, sum(qty) from product group by category"`

Aggregation: count

- `db.product.aggregate({"$group": {_id: "$category", total: {$sum: 1}}})`
`{ "_id" : "laptop", "total" : 2 }`
`{ "_id" : "cell", "total" : 2 }`
- Similar to: "select category, count(*) from product group by category"

Aggregation with "having ..."

- `db.product.aggregate({$group: {_id: "$category", total:{$sum:"$qty"}}}, {$match: {total: {$gt: 50}}})`
 - `{ "_id" : "laptop", "total" : 80 }`
- In SQL:
Select category, sum(qty) total
from product
group by category
having total > 50

Aggregation on more than one field

- `db.product.aggregate({$group: {_id: {cat: "$category", st: "$store"}, total: {$sum: "$qty"}}})`

```
{ "_id" : { "cat" : "laptop", "st" : 1 }, "total" : 10 }
```

```
{ "_id" : { "cat" : "laptop", "st" : 2 }, "total" : 70 }
```

```
{ "_id" : { "cat" : "cell", "st" : 2 }, "total" : 20 }
```

```
{ "_id" : { "cat" : "cell", "st" : 1 }, "total" : 10 }
```

Aggregation

- Other operators
 - \$avg
 - \$min
 - \$max

Aggregation pipeline

- `db.product.aggregate({$match: {store: 2}},
{$group: {_id: "$category", total: {$sum:
"$qty"}}}, {$match: {total: {$gt: 10}}}, {$limit:
2}, {$sort: {total: 1}})`
- `$match -> $group -> $match -> $limit -> $sort`

```
{ "_id" : "cell", "total" : 20 }  
{ "_id" : "laptop", "total" : 70 }
```

Sharding in MongoDB

- Distribute documents/records in a large collection/table over multiple machines
- User can specify a sharding key
 - i.e., a field in a document
- Support sharding by key range or hashing

Hash function...

- $h(\text{"abc"}) = ?$

Dec	Hex	Name	Char	Ctrl-char	Dec	Hex	Char	Dec	Hex	Char	Dec	Hex	Char
0	0	Null	NUL	CTRL-@	32	20	Space	64	40	@	96	60	`
1	1	Start of heading	SOH	CTRL-A	33	21	!	65	41	A	97	61	a
2	2	Start of text	STX	CTRL-B	34	22	"	66	42	B	98	62	b
3	3	End of text	ETX	CTRL-C	35	23	#	67	43	C	99	63	c
4	4	End of xmit	EOT	CTRL-D	36	24	\$	68	44	D	100	64	d
5	5	Enquiry	ENQ	CTRL-E	37	25	%	69	45	E	101	65	e
6	6	Acknowledge	ACK	CTRL-F	38	26	&	70	46	F	102	66	f
7	7	Bell	BEL	CTRL-G	39	27	'	71	47	G	103	67	g
8	8	Backspace	BS	CTRL-H	40	28	(72	48	H	104	68	h
9	9	Horizontal tab	HT	CTRL-I	41	29)	73	49	I	105	69	i
10	0A	Line feed	LF	CTRL-J	42	2A	*	74	4A	J	106	6A	j
11	0B	Vertical tab	VT	CTRL-K	43	2B	+	75	4B	K	107	6B	k
12	0C	Form feed	FF	CTRL-L	44	2C	,	76	4C	L	108	6C	l
13	0D	Carriage feed	CR	CTRL-M	45	2D	-	77	4D	M	109	6D	m
14	0E	Shift out	SO	CTRL-N	46	2E	.	78	4E	N	110	6E	n
15	0F	Shift in	SI	CTRL-O	47	2F	/	79	4F	O	111	6F	o
16	10	Data line escape	DLE	CTRL-P	48	30	0	80	50	P	112	70	p
17	11	Device control 1	DC1	CTRL-Q	49	31	1	81	51	Q	113	71	q
18	12	Device control 2	DC2	CTRL-R	50	32	2	82	52	R	114	72	r
19	13	Device control 3	DC3	CTRL-S	51	33	3	83	53	S	115	73	s
20	14	Device control 4	DC4	CTRL-T	52	34	4	84	54	T	116	74	t
21	15	Neg acknowledge	NAK	CTRL-U	53	35	5	85	55	U	117	75	u
22	16	Synchronous idle	SYN	CTRL-V	54	36	6	86	56	V	118	76	v
23	17	End of xmit block	ETB	CTRL-W	55	37	7	87	57	W	119	77	w
24	18	Cancel	CAN	CTRL-X	56	38	8	88	58	X	120	78	x
25	19	End of medium	EM	CTRL-Y	57	39	9	89	59	Y	121	79	y
26	1A	Substitute	SUB	CTRL-Z	58	3A	:	90	5A	Z	122	7A	z
27	1B	Escape	ESC	CTRL-[59	3B	;	91	5B	[123	7B	{
28	1C	File separator	FS	CTRL-\	60	3C	<	92	5C	\	124	7C	
29	1D	Group separator	GS	CTRL-]	61	3D	=	93	5D]	125	7D	}
30	1E	Record separator	RS	CTRL-^	62	3E	>	94	5E	^	126	7E	~
31	1F	Unit separator	US	CTRL-~	63	3F	?	95	5F	~	127	7F	DEL

Sample data set

- Restaurants data
 - <https://raw.githubusercontent.com/mongodb/docs-assets/primer-dataset/primer-dataset.json>

Import sample dataset

- `mongoimport --db inf551 --collection restaurants --file primer-dataset.json`
 - No need to pre-create inf551 and restaurants if they do not exist yet
- More details:
 - <https://docs.mongodb.com/getting-started/shell/import-data/>

Resources

- Install MongoDB Community Edition on Amazon Linux
 - <https://docs.mongodb.com/manual/tutorial/install-mongodb-on-amazon/>