

Lesson 4

Numerical Solution of PDE

4.2 Parabolic PDE

- *Semi-discretization*
- *Full finite difference discretization*
- *Fourier Analysis*
- ***Unconditional Stability***



Numerical Methods for PDE: Parabolic PDE



Can we design a scheme that is unconditionally stable?

Numerical Methods for PDE: Parabolic PDE



Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

Numerical Methods for PDE: Parabolic PDE

Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

The backward-centered difference method for the heat equation leads to

$$\frac{u_n^{j+1} - u_n^j}{k} = c \frac{u_{n+1}^{j+1} - 2u_n^{j+1} + u_{n-1}^{j+1}}{h^2} + f_n^{j+1}, \quad 0 < n < N, j = 0, 1, \dots, M-1,$$
$$u_0^j = u_N^j = 0, \quad j = 0, 1, \dots, M,$$
$$u_n^0 = u_0(nh), \quad 0 < n < N.$$

Numerical Methods for PDE: Parabolic PDE

Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

The backward-centered difference method for the heat equation leads to

$$\frac{u_n^{j+1} - u_n^j}{k} = c \frac{u_{n+1}^{j+1} - 2u_n^{j+1} + u_{n-1}^{j+1}}{h^2} + f_n^{j+1}, \quad 0 < n < N, j = 0, 1, \dots, M-1,$$

$$u_0^j = u_N^j = 0, \quad j = 0, 1, \dots, M,$$

$$u_n^0 = u_0(nh), \quad 0 < n < N.$$

Thus, u_n^{j+1} can be obtained by solving a tridiagonal system

$$-\lambda u_{n+1}^{j+1} + (1 + 2\lambda)u_n^{j+1} - \lambda u_{n-1}^{j+1} = u_n^j + k f_n^{j+1}, \quad u_0^{j+1} = u_N^{j+1} = 0.$$

Numerical Methods for PDE: Parabolic PDE

Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

The backward-centered difference method for the heat equation leads to

$$\frac{u_n^{j+1} - u_n^j}{k} = c \frac{u_{n+1}^{j+1} - 2u_n^{j+1} + u_{n-1}^{j+1}}{h^2} + f_n^{j+1}, \quad 0 < n < N, j = 0, 1, \dots, M-1,$$

$$u_0^j = u_N^j = 0, \quad j = 0, 1, \dots, M,$$

$$u_n^0 = u_0(nh), \quad 0 < n < N.$$

Thus, u_n^{j+1} can be obtained by solving a tridiagonal system

$$-\lambda u_{n+1}^{j+1} + (1 + 2\lambda)u_n^{j+1} - \lambda u_{n-1}^{j+1} = u_n^j + k f_n^{j+1}, \quad u_0^{j+1} = u_N^{j+1} = 0.$$

It is easy to see that the local truncation error for the scheme is again $O(k + h^2)$.

Numerical Methods for PDE: Parabolic PDE

Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

The backward-centered difference method for the heat equation leads to

$$\frac{u_n^{j+1} - u_n^j}{k} = c \frac{u_{n+1}^{j+1} - 2u_n^{j+1} + u_{n-1}^{j+1}}{h^2} + f_n^{j+1}, \quad 0 < n < N, j = 0, 1, \dots, M-1,$$

$$u_0^j = u_N^j = 0, \quad j = 0, 1, \dots, M,$$

$$u_n^0 = u_0(nh), \quad 0 < n < N.$$

Thus, u_n^{j+1} can be obtained by solving a tridiagonal system

$$-\lambda u_{n+1}^{j+1} + (1 + 2\lambda)u_n^{j+1} - \lambda u_{n-1}^{j+1} = u_n^j + k f_n^{j+1}, \quad u_0^{j+1} = u_N^{j+1} = 0.$$

It is easy to see that the local truncation error for the scheme is again $O(k + h^2)$.

We again use the Fourier analysis to determine the stability of the scheme. In operator form, the method reads

$$\frac{u^{j+1} - u^j}{k} = c D_h^2 u^{j+1} + f^{j+1},$$

Numerical Methods for PDE: Parabolic PDE

Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

The backward-centered difference method for the heat equation leads to

$$\frac{u_n^{j+1} - u_n^j}{k} = c \frac{u_{n+1}^{j+1} - 2u_n^{j+1} + u_{n-1}^{j+1}}{h^2} + f_n^{j+1}, \quad 0 < n < N, j = 0, 1, \dots, M-1,$$

$$u_0^j = u_N^j = 0, \quad j = 0, 1, \dots, M,$$

$$u_n^0 = u_0(nh), \quad 0 < n < N.$$

Thus, u_n^{j+1} can be obtained by solving a tridiagonal system

$$-\lambda u_{n+1}^{j+1} + (1 + 2\lambda)u_n^{j+1} - \lambda u_{n-1}^{j+1} = u_n^j + k f_n^{j+1}, \quad u_0^{j+1} = u_N^{j+1} = 0.$$

It is easy to see that the local truncation error for the scheme is again $O(k + h^2)$.

We again use the Fourier analysis to determine the stability of the scheme. In operator form, the method reads

$$\frac{u^{j+1} - u^j}{k} = c D_h^2 u^{j+1} + f^{j+1},$$

that is,

$$u^{j+1} = (I - ck D_h^2)^{-1} (u^j + k f^{j+1}).$$

Numerical Methods for PDE: Parabolic PDE

Can we design a scheme that is unconditionally stable?

Try backward Euler method in time!

The backward-centered difference method for the heat equation leads to

$$\frac{u_n^{j+1} - u_n^j}{k} = c \frac{u_{n+1}^{j+1} - 2u_n^{j+1} + u_{n-1}^{j+1}}{h^2} + f_n^{j+1}, \quad 0 < n < N, j = 0, 1, \dots, M-1,$$

$$u_0^j = u_N^j = 0, \quad j = 0, 1, \dots, M,$$

$$u_n^0 = u_0(nh), \quad 0 < n < N.$$

Thus, u_n^{j+1} can be obtained by solving a tridiagonal system

$$-\lambda u_{n+1}^{j+1} + (1 + 2\lambda)u_n^{j+1} - \lambda u_{n-1}^{j+1} = u_n^j + k f_n^{j+1}, \quad u_0^{j+1} = u_N^{j+1} = 0.$$

It is easy to see that the local truncation error for the scheme is again $O(k + h^2)$.

We again use the Fourier analysis to determine the stability of the scheme. In operator form, the method reads

$$\frac{u^{j+1} - u^j}{k} = c D_h^2 u^{j+1} + f^{j+1},$$

that is,

$$u^{j+1} = (I - ck D_h^2)^{-1} (u^j + k f^{j+1}).$$

The operator $I - ck D_h^2$ has eigenvalues $1 + ck\lambda_m$ which are all greater than one, so $\|(I - ck D_h^2)^{-1} v\|_h \leq \|v\|_h$.



We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$



We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$

Hence, we have

$$\|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h$$



We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$

Hence, we have

$$\|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h$$

and the stability result

$$\max_{1 \leq j \leq M} \|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h.$$

We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$

Hence, we have

$$\|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h$$

and the stability result

$$\max_{1 \leq j \leq M} \|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h.$$

As we did not have to make any assumption on the relation between k and h , the backward-centered difference scheme is **unconditionally stable**.

Numerical Methods for PDE: Parabolic PDE

We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$

Hence, we have

$$\|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h$$

and the stability result

$$\max_{1 \leq j \leq M} \|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h.$$

As we did not have to make any assumption on the relation between k and h , the backward-centered difference scheme is **unconditionally stable**.

Combining the stability estimate with the local truncation error, we obtain the error estimate

$$\max_{1 \leq j \leq M} \|e^j\|_h = O(k + h^2)$$

for the method.

Numerical Methods for PDE: Parabolic PDE

We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$

Hence, we have

$$\|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h$$

and the stability result

$$\max_{1 \leq j \leq M} \|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h.$$

As we did not have to make any assumption on the relation between k and h , the backward-centered difference scheme is **unconditionally stable**.

Combining the stability estimate with the local truncation error, we obtain the error estimate

$$\max_{1 \leq j \leq M} \|e^j\|_h = O(k + h^2)$$

for the method.

If we use trapezoidal rule to discretize in time, we get the **Crank-Nicolson method**:

$$\frac{u^{j+1} - u^j}{k} = \frac{c}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{1}{2} (f^j + f^{j+1}).$$

Numerical Methods for PDE: Parabolic PDE

We, therefore, have

$$\|u^{j+1}\|_h = \|(I - ckD_h^2)^{-1}(u^j + kf^{j+1})\|_h \leq \|u^j\|_h + k\|f^j\|_h, \quad j = 0, 1, \dots, M-1.$$

Hence, we have

$$\|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h$$

and the stability result

$$\max_{1 \leq j \leq M} \|u^j\|_h \leq \|u^0\|_h + T \max_{1 \leq j \leq M} \|f^j\|_h.$$

As we did not have to make any assumption on the relation between k and h , the backward-centered difference scheme is **unconditionally stable**.

Combining the stability estimate with the local truncation error, we obtain the error estimate

$$\max_{1 \leq j \leq M} \|e^j\|_h = O(k + h^2)$$

for the method.

If we use trapezoidal rule to discretize in time, we get the **Crank-Nicolson method**:

$$\frac{u^{j+1} - u^j}{k} = \frac{c}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{1}{2} (f^j + f^{j+1}).$$

Using the Taylor expansion about the point $(nh, (j + 1/2)k)$, it is straightforward to show that the local truncation error is $O(k^2 + h^2)$, so the Crank-Nicolson method is second order in both space and time.

Numerical Methods for PDE: Parabolic PDE

If we use trapezoidal rule to discretize in time, we get the **Crank-Nicolson method**:

$$\frac{u^{j+1} - u^j}{k} = \frac{c}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{1}{2} (f^j + f^{j+1}).$$

Using the Taylor expansion about the point $(nh, (j + 1/2)k)$, it is straightforward to show that the local truncation error is $O(k^2 + h^2)$, so the Crank-Nicolson method is second order in both space and time.

To get the operator equation for the method, we write

$$u^{j+1} = u^j + \frac{ck}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{k}{2} (f^j + f^{j+1}),$$

that is

$$u^{j+1} - \frac{ck}{2} D_h^2 u^{j+1} = u^j + \frac{ck}{2} D_h^2 u^j + \frac{k}{2} (f^j + f^{j+1}).$$

Numerical Methods for PDE: Parabolic PDE

If we use trapezoidal rule to discretize in time, we get the **Crank-Nicolson method**:

$$\frac{u^{j+1} - u^j}{k} = \frac{c}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{1}{2} (f^j + f^{j+1}).$$

Using the Taylor expansion about the point $(nh, (j + 1/2)k)$, it is straightforward to show that the local truncation error is $O(k^2 + h^2)$, so the Crank-Nicolson method is second order in both space and time.

To get the operator equation for the method, we write

$$u^{j+1} = u^j + \frac{ck}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{k}{2} (f^j + f^{j+1}),$$

that is

$$u^{j+1} - \frac{ck}{2} D_h^2 u^{j+1} = u^j + \frac{ck}{2} D_h^2 u^j + \frac{k}{2} (f^j + f^{j+1}).$$

Thus

$$u^{j+1} = \left(I - \frac{1}{2} ck D_h^2 \right)^{-1} \left(I + \frac{1}{2} ck D_h^2 \right) u^j + \frac{k}{2} \left(I - \frac{1}{2} ck D_h^2 \right)^{-1} (f^j + f^{j+1}).$$

Numerical Methods for PDE: Parabolic PDE

If we use trapezoidal rule to discretize in time, we get the **Crank-Nicolson method**:

$$\frac{u^{j+1} - u^j}{k} = \frac{c}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{1}{2} (f^j + f^{j+1}).$$

Using the Taylor expansion about the point $(nh, (j + 1/2)k)$, it is straightforward to show that the local truncation error is $O(k^2 + h^2)$, so the Crank-Nicolson method is second order in both space and time.

To get the operator equation for the method, we write

$$u^{j+1} = u^j + \frac{ck}{2} (D_h^2 u^j + D_h^2 u^{j+1}) + \frac{k}{2} (f^j + f^{j+1}),$$

that is

$$u^{j+1} - \frac{ck}{2} D_h^2 u^{j+1} = u^j + \frac{ck}{2} D_h^2 u^j + \frac{k}{2} (f^j + f^{j+1}).$$

Thus

$$u^{j+1} = \left(I - \frac{1}{2} ck D_h^2 \right)^{-1} \left(I + \frac{1}{2} ck D_h^2 \right) u^j + \frac{k}{2} \left(I - \frac{1}{2} ck D_h^2 \right)^{-1} (f^j + f^{j+1}).$$

The eigenvalues of $\left(I - \frac{1}{2} ck D_h^2 \right)^{-1} \left(I + \frac{1}{2} ck D_h^2 \right)$ is $(1 - ck\lambda_m/2)/(1 + ck\lambda_m/2)$ which is less than 1. Therefore, we get unconditional stability. The Crank-Nicolson method converges with $O(k^2 + h^2)$.