You Cannot See Grip Without Using It: Active Probing for Rapid Motor Adaptation in Autonomous Racing

Nathan Chong
University of Hawai'i at Mānoa
NSF REU, University of Nevada, Las Vegas

Venkata Prashant Modekurthy
University of Nevada, Las Vegas

***Abstract*—Tire–road friction sets a race car's safe envelope, changes with surface and wear, and is not measured by any onboard sensor. Rapid Motor Adaptation (RMA) infers such hidden conditions from a robot's recent motion. Applied to grip on the F1TENTH platform, it cannot work as usually trained: with the car's actions decoupled from grip, its motion history carries no grip information ($R^2 \approx 0$ for three tire models), because the car is near neutral steer and drives inside the friction circle. Adaptation modules that appear to work instead read grip off the expert's own driving or simply drive slowly; a speed-capped non-adaptive car matches them. We add an *active probe*, a brief speed pulse on straights that asks the tires for more than low grip can give. Grip becomes readable (R^2 0.89–0.93), the car drives within 0.1 m/s of an oracle at every grip, and at $\mu = 0.4$ it crashes in 2–8% of episodes versus 33–47% for a non-adaptive car matched to its speed, on three training seeds; no fixed speed limit matches it on both speed and safety. Retrained with the car's real sensing (wheel odometry with slip, kinematic yaw rate, 40 Hz LiDAR), a braking probe and a racing expert, the controller still reads grip (R^2 0.84–0.87) and, at equal average speed, cuts crashes at $\mu = 0.6$ from 33–56% to 0–5%. All hypotheses were pre-registered, including those that failed.**

I. Introduction

Grip limits safe control, and it changes with rain, dust, tire wear and payload. A controller tuned for nominal grip is conservative everywhere or unsafe when grip falls. RMA [1] trains a base policy with privileged physics and an adaptation module that recovers those physics from recent states and actions; it works for legged robots and quadcopters [2], whose dynamics expose the hidden parameters continually.

A car's grip is different. Below the limit the tires deliver whatever force is asked, at any grip; grip shows only near the limit, which a cautious controller never visits. This is the familiar excitation requirement of tire–road friction estimation [3], [4]. We ask whether an RMA controller on F1TENTH can infer grip from its own motion, and whether adapting to it beats simply driving slower.

Contributions. (1) A *leakage-free observability test*: rolling out the policy with a random grip belief, independent of the true grip, removes the information the controller's own actions carry. Under it, the motion history contains no grip information, which explains why standard RMA fails here and why apparent successes are leakage. (2) *Active grip probing* for RMA: a short speed pulse on straights, applied identically to all controllers, makes grip readable and yields oracle-like speed modulation. (3) A *speed-matched control* that separates adaptation from slowness: without the probe, slowness explains all of the safety gain; with it, it does not. (4) Transfer to realistic car sensing, including a closed-loop check of the deployment node, and a robustness analysis of the wheel-slip assumption. (5) Pre-registered hypotheses with dated amendments, paired episodes, three training seeds and held-out tracks.

II. Related Work

RMA regresses an adaptation module onto privileged encodings and trains it on its own rollouts [1]; the quadcopter variant adds joint PPO and imitation [2]. We show a second reason on-policy training matters: action leakage. **Learning on F1TENTH** includes LiDAR-only deep RL [5], [6], imitation benchmarks [7] and a survey [8]; none estimates physics online. RL racing policies have been deployed zero-shot on F1TENTH cars with domain randomization and actuator modeling [9] and with disturbances and observation preprocessing [10]. History-dependent policies help domain-randomized transfer [11], [12]. The same group estimates velocity on F1TENTH with a learned dynamics model and an online friction estimate [13], and proposes long-horizon memory beyond RMA's short reactive window [14]. **Friction estimation** needs excitation: slip-based estimators need high tire utilization (up to 80–90% on low-μ surfaces [3]; 54–94% for a brush-model estimator [15]) and fail in steady driving [4]. We bring this requirement to learned adaptation and meet it with a deliberate excitation.

III. Method

Simulator. f1tenth_gym [16] single-track model at 100 Hz. Its tire is linear and never saturates, so we add a friction-circle tire: each axle's lateral force is capped at $\sqrt{(\mu F_z)^2 - F_x^2}$ and acceleration at μg. **Observation and action.** $x_t \in \mathbb{R}^{113}$: speed, steering, the previous speed and steering commands, yaw rate, and 108 LiDAR beams; action: steering and speed command (0–3 m/s). No map or pose. **Randomization.** Per episode, grip $\in [0.4, 1]$ ($\mu = 1.0489 \cdot$grip); mass, inertia, steering and drive gains $\pm 20\%$; actuator delays 0–50 ms; mid-episode grip drops in 30% of episodes; LiDAR noise and

TABLE I
CONFIGURATION Q (IDEAL SENSORS + PROBE), PER TRAINING SEED. N = 100 PAIRED EPISODES PER CELL.

	seed 0	seed 1	seed 2
ϕ speed, μ 1.0→0.4 (m/s)	2.02→1.28	2.06→1.29	2.00→1.28
Oracle speed, μ 1.0→0.4	2.12→1.27	2.11→1.27	2.11→1.26
Crash μ 0.4: ϕ / Blind	0.07 / 0.46	0.02 / 0.47	0.08 / 0.43
Speed-matched Blind, μ 0.4	0.37	0.47	0.33
McNemar p vs ϕ	2×10^{-9}	6×10^{-14}	6×10^{-8}
E5 grip R^2	0.90	0.93	0.89

dropout. **Phase 1.** Policy $\pi(x, z)$ (MLP 3×256) and encoder $z = \mu(e) \in \mathbb{R}^8$, trained by DAgger from a grip-aware Pure Pursuit expert [17] on 13 scaled circuits [18]. **Phase 2.** ϕ: a 1-D CNN mapping the last 50 steps (0.5 s) to $\hat{z}$, trained by regression on oracle-driven data and then three on-policy rounds [1]. **Controllers.** One frozen π with three sources of z: *Oracle* $\mu(e_{\text{true}})$, ϕ (estimated), *Blind* $\mu(e_{\text{nominal}})$; plus Blind with a speed limit matched to ϕ's measured speed. **Active probe.** Every 0.5 s on straights ($|\delta| < 0.15$ rad), the speed command is offset for 0.1 s (+2 m/s in configuration Q, −1 m/s braking in R). The speed controller then requests more than μg at low grip, so the response measures grip. The probe runs for every controller, in training and evaluation. **Leakage-free test.** Roll out π with a grip belief drawn independently of the true grip, so actions carry no grip information, and fit (i) a ridge probe on physical window features and (ii) ϕ's network, cross-validated by episode. **Evaluation.** $\mu \in \{1.0, 0.8, 0.6, 0.4\}$, 100 episodes per cell from seeded random starts shared by all controllers (paired); exact McNemar tests on paired crashes, Holm-corrected; E5: grip R^2 of $\hat{z}$ over 200 episodes.

IV. RESULTS

A. Without excitation, grip is not observable

With grip-independent driving, physical features of 0.5 s windows predict grip with $R^2 = -0.02$ (friction-circle tire) and -0.03 (Fiala brush tire); with oracle or ϕ-driven data they reach 0.97 and 0.68, all of it leakage. Below the limit, grip barely changes the yaw response (-3% to -5% at 1.5–2 m/s, μ 0.4 vs 1.0), and the policy's 99th-percentile accelerations (3–3.7 m/s^2 longitudinal, ∼2 m/s^2 lateral) stay under even low-grip μg. With the probe, the same test gives $R^2 = 0.84$; ϕ's network learns it from proprioception (0.67) but not from all 115 channels (0.15).

Standard RMA fails accordingly. Trained on oracle-driven data, ϕ drives faster than the oracle at every grip and crashes more than Blind at $\mu = 0.4$ (0.39 vs 0.32). Trained on its own rollouts with the friction-circle tire, ϕ is far safer than Blind (0.04 vs 0.44) but slows only 0.10–0.19 m/s with grip (R^2 0.28), and Blind capped at ϕ's speed is as safe on every seed.

B. With the probe, adaptation beats a speed limit

Table I and Fig. 1 (left) show configuration Q. ϕ reads grip (R^2 0.89–0.93), drives within 0.1 m/s of the Oracle at every grip, and is as safe as the Oracle. Because the probe adds speed on top of a limit, the matched Blind is capped so its




Fig. 1. Crash rate vs. grip for the same base policy with the true grip (Oracle), ϕ's estimate, or none (Blind). Mean of 3 training seeds (band: min–max), N = 100 paired episodes per point. Left: ideal sensors; right: car sensors, braking probe and racing expert.




Fig. 2. Speed on full grip vs. crash rate at $\mu = 0.4$ (seed 0, Q). A fixed speed limit trades one for the other; ϕ gets both. Lower right is better.

measured speed equals ϕ's; it still crashes 5–20 times as often at $\mu = 0.4$. A sweep of fixed limits (Fig. 2) shows that matching ϕ's safety costs 19–29% speed on full grip. With the probe switched off at test time, the same ϕ falls back to a constant ∼1.2 m/s (R^2 0.24); on three held-out tracks a model that never saw them closes 80% of the Oracle gap (87% for one trained on them); after a grip drop the estimate settles in 0.77 s. The probe changes Blind's and the Oracle's crash rates by at most 0.02.

C. Realistic car sensing and racing speed (R)

Configuration R builds the observation the way the car's node builds it from the standard F1TENTH stack: speed from VESC wheel odometry (the wheel spins up or locks when traction-limited; ±5% gain error; 50 Hz), yaw rate computed as $v \tan \delta_{\text{cmd}}/L$ (no gyro), commanded steering, and 40 Hz LiDAR. The probe is a braking pulse (an accelerating one asked for 5 m/s before corners), ϕ also sees ten front LiDAR beams, and the expert races: full speed on straights, corners at $\sqrt{0.6\mu g R}$. Base policies are faster and safer (2/117 validation crashes at ∼2.5 m/s, vs 3/39 at 1.2–2.0 m/s).

ϕ still reads grip (R^2 0.84–0.87). All three controllers drive at about the same average speed; adaptation is *where* to slow




Fig. 3. Crash rate at $\mu = 0.4$ under five wheel-slip models at test time (seed 0, R). ϕ trained on one slip model is blind without slip; randomizing the slip model in training removes this.




Fig. 4. Grip R^2 of ϕ's estimate (E5) by configuration; mean over training seeds where available.

(Fig. 1, right). At $\mu = 0.6$, ϕ crashes 0–5% vs 33–56% for Blind (Oracle 0%); at $\mu = 0.4$, 28–39% vs 84–86% (Oracle 0–9%), and Blind matched to ϕ's measured speed crashes 84–86% ($p < 10^{-13}$, every seed). The pre-registered checks pass on every seed, except a ratio of cross-grip variance that even the Oracle fails with the probe.

D. Robustness to the wheel-slip model

The wheel-slip model is an assumption. Evaluated under four alternatives, ϕ degraded and, with no slip at all, was blind (Fig. 3; $\mu = 0.4$: 0.86 vs 0.86 for Blind), although the true deceleration and the front LiDAR still carry the information. Retraining ϕ with the slip model randomized per episode costs nothing under the default model and beats Blind in all 30 slip-model $\times$ seed $\times$ grip comparisons ($\mu = 0.6$: $\leq$0.07 vs 0.29–0.56); with no slip it reads grip at R^2 0.59–0.63 (Fig. 4). The pre-registered margin at $\mu = 0.4$ (0.30) is missed on one seed for the two weakest-signal models (0.19, 0.22).

E. Real-car pilot

In July, an F1TENTH car (Traxxas Slash 4$\times$4) ran an earlier checkpoint (linear tire, no probe, and a 50 Hz node against 100 Hz training) through one 90° corner with four tire wraps (81 trials); its steering and yaw rate differed between bare and electrical-tape tires (uncorrected $p = 0.0001$ and 0.009; over the nine comparisons the analysis runs, steering survives a Bonferroni–Holm correction and yaw does not; effects of -3.8% and -2.5%). This shows the policy responds to a real tire change, not that the probe works on the car.

V. Discussion and Limitations

The probe changes the method: the controller spends a small, fixed amount of driving on measurement; a learned, risk-aware probing policy is future work. **The wheel-slip model is assumed**, and the controller is strongest when its signature is present. A one-session test measures it: braking pulses on three surfaces, logging odometry, IMU and front-LiDAR range; a simulated version of the test predicts that odometry alone separates grip 1.0/0.7/0.4 ($p < 10^{-7}$). **At $\mu = 0.4$ a gap remains** under realistic sensing (49–58% of the Oracle gap closed vs 82–87% with ideal sensors), plausibly because the estimate depends on probes on straights. **Regime:** speeds $\leq$3 m/s on narrow scaled tracks, uniform grip, simulation only for every probe result.

VI. Conclusion

On F1TENTH, RMA cannot infer grip from passive driving: the information is not in the motion, and adaptation modules that appear to succeed are reading their own actions or driving slowly. A brief, deliberate probe makes grip observable; with it, an RMA controller matches an oracle's speed at every grip and beats any fixed speed limit at low grip, across seeds, held-out tracks and realistic car sensing. Whether the real car's wheels reveal grip under a braking pulse as the model assumes is the next, one-session experiment.

Acknowledgment

Supported by NSF REU Site Award #2349616 (UNLV Smart Cities). Thanks to Ederic Oytas for hardware support.

References

[1] A. Kumar, Z. Fu, D. Pathak, and J. Malik, "RMA: Rapid motor adaptation for legged robots," in *Robotics: Science and Systems (RSS)*, 2021, arXiv:2107.04034.

[2] D. Zhang, A. Loquercio, J. Tang, T.-H. Wang, J. Malik, and M. W. Mueller, "A learning-based quadcopter controller with extreme adaptation," *IEEE Transactions on Robotics*, vol. 41, pp. 3948–3964, 2025, arXiv:2409.12949.

[3] M. Acosta, S. Kanarachos, and M. Blundell, "Road friction virtual sensing: A review of estimation techniques with emphasis on low excitation approaches," *Applied Sciences*, vol. 7, no. 12, p. 1230, 2017.

[4] S. Khaleghian, A. Emami, and S. Taheri, "A technical survey on tire-road friction estimation," *Friction*, vol. 5, no. 2, pp. 123–146, 2017.

[5] M. Hell, G. Hajgató *et al.*, "A LiDAR-based approach to autonomous racing with model-free reinforcement learning," in *IEEE Intelligent Vehicles Symposium (IV)*, 2024, pp. 258–263.

[6] B. D. Evans, H. A. Engelbrecht, and H. W. Jordaan, "High-speed autonomous racing using trajectory-aided deep reinforcement learning," *IEEE Robotics and Automation Letters*, 2023, arXiv:2306.07003.

[7] X. Sun, M. Zhou, Z. Zhuang, S. Yang, J. Betz, and R. Mangharam, "A benchmark comparison of imitation learning-based control policies for autonomous racing," in *IEEE Intelligent Vehicles Symposium (IV)*, 2023, arXiv:2209.15073.

[8] B. D. Evans, R. Trumpp, M. Caccamo, F. Jahncke, J. Betz, H. W. Jordaan, and H. A. Engelbrecht, "Unifying F1TENTH autonomous racing: Survey, methods and benchmarks," 2024.

[9] G. Czechmanowski, J. Węgrzynowski, P. Kicki, and K. Walas, "On learning racing policies with reinforcement learning," 2025, arXiv:2504.02420.
[10] C. Budai, T. Széles, B. Németh, and P. Gáspár, "End-to-end reinforcement learning for autonomous racing: Bridging the sim-to-real gap," in *American Control Conference (ACC)*, 2025, pp. 200–205.
[11] X. Chen, J. Hu, C. Jin, L. Li, and L. Wang, "Understanding domain randomization for sim-to-real transfer," in *International Conference on Learning Representations (ICLR)*, 2022.
[12] J. Tobin, R. Fong, A. Ray, J. Schneider, W. Zaremba, and P. Abbeel, "Domain randomization for transferring deep neural networks from simulation to the real world," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2017.
[13] J. Węgrzynowski, G. Czechmanowski, P. Kicki, and K. Walas, "Learning dynamics models for velocity estimation in autonomous racing," in *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2024, arXiv:2408.15610.
[14] G. Czechmanowski, J. Węgrzynowski, P. Kicki, and K. Walas, "Beyond reactive adaptation: Long-horizon memory for autonomous racing via state space models," extended abstract.
[15] J. Prokes, A. Albinsson, and L. Laine, "Quantification of excitation required for accurate friction estimation," in *IEEE International Conference on Intelligent Transportation Systems (ITSC)*, 2016, pp. 2551–2558.
[16] M. O'Kelly, H. Zheng, D. Karthik, and R. Mangharam, "F1TENTH: An open-source evaluation environment for continuous control and reinforcement learning," in *Proceedings of the NeurIPS 2019 Competition and Demonstration Track*, ser. Proceedings of Machine Learning Research, vol. 123, 2020, pp. 77–89.
[17] R. C. Coulter, "Implementation of the pure pursuit path tracking algorithm," Carnegie Mellon University, Tech. Rep. CMU-RI-TR-92-01, 1992.
[18] J. Betz, H. Zheng, A. Liniger, U. Rosolia, P. Karle, M. Behl, V. Krovi, and R. Mangharam, "Autonomous vehicles on the edge: A survey on autonomous vehicle racing," *IEEE Open Journal of Intelligent Transportation Systems*, vol. 3, pp. 458–488, 2022.