

Practical-2:

Write and Perform the SQL queries for the below:

SQL Where

=====

1. Select all records where the Ciry column has the value "Ahmedabad".
2. Use the NOT keyword to select all records where Ciry is NOT "Ahmedabad".
3. Select all records where the comm column has the value 11.11.
4. Select all records where the Ciry column has the value 'Ahmedabad' and the comm column has the value 25.52.
5. Select all records where the Ciry column has the value 'Ahmedabad' or 'Kosamba'.

SQL Order By

=====

1. Select all records from the salespeople table, sort the result alphabetically by the column Ciry.
2. Select all records from the salespeople table, sort the result reversed alphabetically by the column Ciry.
3. Select all records from the salespeople table, sort the result alphabetically, first by the column Ciry, then by the column comm.

SQL Null

=====

1. Select all records from the salespeople where the Ciry column is empty.
2. Select all records from the salespeople where the salespeople where the Ciry column is NOT empty.

SQL Update

=====

1. Update the Ciry column of all records in the salespeople table.
2. Set the value of the Ciry columns to 'Surat', but only the ones where the Comm column has the value 88.99.
3. Update the salesperson name value and the Ciry value for the particular salesperson.

SQL Delete

=====

1. Delete all the records from the orders table where the onum value is 305.
2. Delete all the records from the orders table.

SQL> select * from salespeople;

SNUM SNAME	CIRY	COMM
-----	-----	-----
101 Devendra Vashi	Kosamba	25.52
102 Yogini Vashi	Boridatr	12.21
103 Ada Lawrence	Belgaum	11.11
104 Yesha Rana	Deli	33.33
105 Maggi Vashi	Ahmedabad	88.99
1 A	Ahmedabad	1.1

=====

SQL Where

=====

1. Select all records where the Ciry column has the value "Ahmedabad".

SQL> SELECT * FROM salespeople WHERE Ciry = 'Ahmedabad';

SNUM SNAME	CIRY	COMM
-----	-----	-----
105 Maggi Vashi	Ahmedabad	88.99
1 A	Ahmedabad	1.1

2. Use the NOT keyword to select all records where Ciry is NOT "Ahmedabad".

SQL> SELECT * FROM salespeople WHERE NOT Ciry = 'Ahmedabad';

SQL> SELECT * FROM salespeople WHERE City <> 'Ahmedabad';

SQL> SELECT * FROM salespeople WHERE City != 'Ahmedabad';

SNUM	SNAME	CIRY	COMM
101	Devendra Vashi	Kosamba	25.52
102	Yogini Vashi	Boridatr	12.21
103	Ada Lawrence	Belgaum	11.11
104	Yesha Rana	Deli	33.33

3. Select all records where the comm column has the value 11.11.

SQL> SELECT * FROM salespeople WHERE comm = 11.11;

SNUM	SNAME	CIRY	COMM
103	Ada Lawrence	Belgaum	11.11

4. Select all records where the Ciry column has the value 'Ahmedabad' and the comm column has the value 25.52.

SQL> SELECT * FROM salespeople WHERE Ciry = 'Ahmedabad' AND comm = 25.52;

no rows selected

SQL> SELECT * FROM salespeople WHERE Ciry = 'Ahmedabad' AND comm = 88.99;

SNUM	SNAME	CIRY	COMM
105	Maggi Vashi	Ahmedabad	88.99

5. Select all records where the Ciry column has the value 'Ahmedabad' or 'Kosamba'.

SQL> SELECT * FROM salespeople WHERE Ciry = 'Ahmedabad' OR Ciry = 'Kosamba';

SNUM	SNAME	CIRY	COMM
101	Devendra Vashi	Kosamba	25.52
105	Maggi Vashi	Ahmedabad	88.99
1	A	Ahmedabad	1.1

SQL Order By

=====

1 Select all records from the salespeople table, sort the result alphabetically by the column Ciry.

SQL> SELECT * FROM salespeople **ORDER BY** Ciry ;

SNUM	SNAME	CIRY	COMM
105	Maggi Vashi	Ahmedabad	88.99
1	A	Ahmedabad	1.1
103	Ada Lawrence	Belgaum	11.11
102	Yogini Vashi	Boridatr	12.21
104	Yesha Rana	Deli	33.33
101	Devendra Vashi	Kosamba	25.52

2 Select all records from the salespeople table, sort the result reversed alphabetically by the column Ciry.

SQL> SELECT * FROM salespeople **ORDER BY** Ciry **DESC**;

SNUM	SNAME	CIRY	COMM
101	Devendra Vashi	Kosamba	25.52
104	Yesha Rana	Deli	33.33
102	Yogini Vashi	Boridatr	12.21
103	Ada Lawrence	Belgaum	11.11
105	Maggi Vashi	Ahmedabad	88.99

1.1

3 Select all records from the salespeople table, sort the result alphabetically, first by the column CIRD, then, by the column comm.

```
SQL> SELECT * FROM salespeople ORDER BY CITY, comm;
```

SNUM	SNAME	CIRY	COMM
1	A	Ahmedabad	1.1
105	Maggi Vashi	Ahmedabad	88.99
103	Ada Lawrence	Belgaum	11.11
102	Yogini Vashi	Boridatr	12.21
104	Yesha Rana	Deli	33.33
101	Devendra Vashi	Kosamba	25.52

```
SQL> insert into salespeople values(&snum,&sname,&city,&comm);
```

Enter value for snum: 107

Enter value for sname: Viha

Enter value for city: Chennur

Enter value for comm: 0.1

```
old 1: insert into salespeople values(&snm,'&sname','&city',&comm)
```

```
new 1: insert into salespeople values(107,'Viha','Chennur',0.1)
```

1 row created.

SQL> SELECT * FROM salespeople ORDER BY Ciry, comm;

SNUM	SNAME	Ciry	COMM
1	A	Ahmedabad	1.1
105	Maggi Vashi	Ahmedabad	88.99
103	Ada Lawrence	Belgaum	11.11
102	Yogini Vashi	Boridatr	12.21
107	Viha	Chennur	.1
104	Yesha Rana	Deli	33.33
101	Devendra Vashi	Kosamba	25.52

SQL Null

=====

1 Select all records from the salespeople where the Ciry column is empty.

SQL> SELECT * FROM salespeople WHERE Ciry IS NULL;

no rows selected

2 Select all records from the salespeople where the salespeople where the Ciry column is NOT empty.

SQL> SELECT * FROM salespeople WHERE Ciry IS NOT NULL;

SNUM	SNAME	Ciry	COMM
101	Devendra Vashi	Kosamba	25.52
102	Yogini Vashi	Boridatr	12.21
103	Ada Lawrence	Belgaum	11.11
104	Yesha Rana	Deli	33.33
105	Maggi Vashi	Ahmedabad	88.99
1	A	Ahmedabad	1.1

.1

=====

```
SQL> select * from salespeople;
```

7 rows selected.

7 rows updated.

```
SQL> select * from salespeople;
```

SNUM	SNAME	CIRY	COMM
101	Devendra Vashi	Oslo	25.52
102	Yogini Vashi	Oslo	12.21

103	Ada Lawrence	Oslo	11.11
104	Yesha Rana	Oslo	33.33
105	Maggi Vashi	Oslo	88.99
1	A	Oslo	1.1
107	Viha	Oslo	.1

7 rows selected.

2 Set the value of the Ciry columns to 'Surat', but only the ones where the Comm column has the value 88.99.

```
SQL> UPDATE salespeople SET Ciry = 'Surat' WHERE Comm = 88.99;
```

1 row updated.

```
SQL> select * from salespeople;
```

SNUM	SNAME	CIRY	COMM
101	Devendra Vashi	Oslo	25.52
102	Yogini Vashi	Oslo	12.21
103	Ada Lawrence	Oslo	11.11
104	Yesha Rana	Oslo	33.33
105	Maggi Vashi	Surat	88.99
1	A	Oslo	1.1
107	Viha	Oslo	.1

7 rows selected.

3 Update the salesperson name value and the Ciry value for the particular salesperson.

```
SQL> UPDATE salespeople SET sname = 'Devendra' , ciry = 'Ahmedabad' WHERE snum= 101;
```

1 row updated.

```
SQL> select * from salespeople;
```

SNUM	SNAME	CIRY	COMM
101	Devendra	Ahmedabad	25.52
102	Yogini Vashi	Oslo	12.21
103	Ada Lawrence	Oslo	11.11
104	Yesha Rana	Oslo	33.33
105	Maggi Vashi	Surat	88.99
1	A	Oslo	1.1
107	Viha	Oslo	.1

7 rows selected.

SQL Delete

=====

1 Delete all the records from the orders table where the onum value is 305.

```
SQL> select * from orders;
```

ONUM	AMT ODATE	CNUM	SNUM
301	100 01-JAN-06	201	101
302	120 15-FEB-10	202	102
303	130 14-FEB-04	203	103
304	90 15-FEB-03	204	104
305	89 16-APR-00	205	105

```
SQL> desc orders;
```

Name	Null?	Type
ONUM		NOT NULL NUMBER(4)

AMT	NUMBER(6,2)
ODATE	DATE
CNUM	NUMBER(4)
SNUM	NUMBER(4)

SQL> **DELETE** FROM orders **WHERE** onum = 305;

1 row deleted.

SQL> select * from orders;

ONUM	AMT ODATE	CNUM	SNUM
-----	-----	-----	-----
301	100 01-JAN-06	201	101
302	120 15-FEB-10	202	102
303	130 14-FEB-04	203	103
304	90 15-FEB-03	204	104

2 Delete all the records from the orders table.

SQL> **DELETE** FROM orders;

4 rows deleted.

SQL> select * from orders;

no rows selected