```c
typedef struct _IMAGE_DOS_HEADER {      // DOS .EXE header
    WORD   e_magic;                     // Magic number
    WORD   e_cblp;                      // Bytes on last page of file
    WORD   e_cp;                        // Pages in file
    WORD   e_crlc;                      // Relocations
    WORD   e_cparhdr;                   // Size of header in paragraphs
    WORD   e_minalloc;                  // Minimum extra paragraphs needed
    WORD   e_maxalloc;                  // Maximum extra paragraphs needed
    WORD   e_ss;                        // Initial (relative) SS value
    WORD   e_sp;                        // Initial SP value
    WORD   e_csum;                      // Checksum
    WORD   e_ip;                        // Initial IP value
    WORD   e_cs;                        // Initial (relative) CS value
    WORD   e_lfarlc;                    // File address of relocation table
    WORD   e_ovno;                      // Overlay number
    WORD   e_res[4];                    // Reserved words
    WORD   e_oemid;                     // OEM identifier (for e_oeminfo)
    WORD   e_oeminfo;                   // OEM information; e_oemid specific
    WORD   e_res2[10];                  // Reserved words
    LONG   e_lfanew;                    // File address of new exe header
  } IMAGE_DOS_HEADER, *PIMAGE_DOS_HEADER;
//
// File header format.
//

typedef struct _IMAGE_FILE_HEADER {
    WORD    Machine;
    WORD    NumberOfSections;
    DWORD   TimeDateStamp;
    DWORD   PointerToSymbolTable;
    DWORD   NumberOfSymbols;
    WORD    SizeOfOptionalHeader;
    WORD    Characteristics;
} IMAGE_FILE_HEADER, *PIMAGE_FILE_HEADER;

```

```c
#define IMAGE_SIZEOF_FILE_HEADER             20
//
// Directory format.
//

typedef struct _IMAGE_DATA_DIRECTORY {
    DWORD   VirtualAddress;
    DWORD   Size;
} IMAGE_DATA_DIRECTORY, *PIMAGE_DATA_DIRECTORY;

#define IMAGE_NUMBEROF_DIRECTORY_ENTRIES    16

//
// Optional header format.
//

typedef struct _IMAGE_OPTIONAL_HEADER {
    //
    // Standard fields.
    //

    WORD    Magic;
    BYTE    MajorLinkerVersion;
    BYTE    MinorLinkerVersion;
    DWORD   SizeOfCode;
    DWORD   SizeOfInitializedData;
    DWORD   SizeOfUninitializedData;
    DWORD   AddressOfEntryPoint;
    DWORD   BaseOfCode;
    DWORD   BaseOfData;

    //
    // NT additional fields.
    //

    DWORD   ImageBase;
    DWORD   SectionAlignment;
    DWORD   FileAlignment;
    WORD    MajorOperatingSystemVersion;
    WORD    MinorOperatingSystemVersion;
    WORD    MajorImageVersion;
    WORD    MinorImageVersion;
    WORD    MajorSubsystemVersion;
    WORD    MinorSubsystemVersion;
    DWORD   Win32VersionValue;
    DWORD   SizeOfImage;
    DWORD   SizeOfHeaders;
    DWORD   CheckSum;
    WORD    Subsystem;
    WORD    DllCharacteristics;
    DWORD   SizeOfStackReserve;
    DWORD   SizeOfStackCommit;
    DWORD   SizeOfHeapReserve;
    DWORD   SizeOfHeapCommit;
    DWORD   LoaderFlags;
    DWORD   NumberOfRvaAndSizes;
    IMAGE_DATA_DIRECTORY DataDirectory[IMAGE_NUMBEROF_DIRECTORY_ENTRIES];
} IMAGE_OPTIONAL_HEADER32, *PIMAGE_OPTIONAL_HEADER32;

#define IMAGE_NT_OPTIONAL_HDR32_MAGIC      0x10b
#define IMAGE_NT_OPTIONAL_HDR64_MAGIC      0x20b
#define IMAGE_ROM_OPTIONAL_HDR_MAGIC       0x107

typedef IMAGE_OPTIONAL_HEADER32             IMAGE_OPTIONAL_HEADER;
typedef PIMAGE_OPTIONAL_HEADER32            PIMAGE_OPTIONAL_HEADER;
#define IMAGE_NT_OPTIONAL_HDR_MAGIC         IMAGE_NT_OPTIONAL_HDR32_MAGIC

typedef struct _IMAGE_NT_HEADERS {
    DWORD Signature;
    IMAGE_FILE_HEADER FileHeader;
    IMAGE_OPTIONAL_HEADER32 OptionalHeader;
} IMAGE_NT_HEADERS32, *PIMAGE_NT_HEADERS32;

typedef IMAGE_NT_HEADERS32                  IMAGE_NT_HEADERS;
typedef PIMAGE_NT_HEADERS32                 PIMAGE_NT_HEADERS;

// Directory Entries

#define IMAGE_DIRECTORY_ENTRY_EXPORT          0   // Export Directory
#define IMAGE_DIRECTORY_ENTRY_IMPORT          1   // Import Directory
#define IMAGE_DIRECTORY_ENTRY_RESOURCE        2   // Resource Directory
#define IMAGE_DIRECTORY_ENTRY_EXCEPTION       3   // Exception Directory
#define IMAGE_DIRECTORY_ENTRY_SECURITY        4   // Security Directory
#define IMAGE_DIRECTORY_ENTRY_BASERELOC       5   // Base Relocation Table
#define IMAGE_DIRECTORY_ENTRY_DEBUG           6   // Debug Directory
//      IMAGE_DIRECTORY_ENTRY_COPYRIGHT       7   // (X86 usage)
#define IMAGE_DIRECTORY_ENTRY_ARCHITECTURE    7   // Architecture Specific Data
#define IMAGE_DIRECTORY_ENTRY_GLOBALPTR       8   // RVA of GP
#define IMAGE_DIRECTORY_ENTRY_TLS             9   // TLS Directory
#define IMAGE_DIRECTORY_ENTRY_LOAD_CONFIG    10   // Load Configuration Directory
#define IMAGE_DIRECTORY_ENTRY_BOUND_IMPORT   11   // Bound Import Directory in headers
#define IMAGE_DIRECTORY_ENTRY_IAT            12   // Import Address Table
#define IMAGE_DIRECTORY_ENTRY_DELAY_IMPORT   13   // Delay Load Import Descriptors
#define IMAGE_DIRECTORY_ENTRY_COM_DESCRIPTOR 14   // COM Runtime descriptor

//
// Section header format.
//

#define IMAGE_SIZEOF_SHORT_NAME              8

typedef struct _IMAGE_SECTION_HEADER {
    BYTE    Name[IMAGE_SIZEOF_SHORT_NAME];
    union {
            DWORD   PhysicalAddress;
```

```
                DWORD   VirtualSize;
        } Misc;
        DWORD   VirtualAddress;
        DWORD   SizeOfRawData;
        DWORD   PointerToRawData;
        DWORD   PointerToRelocations;
        DWORD   PointerToLinenumbers;
        WORD    NumberOfRelocations;
        WORD    NumberOfLinenumbers;
        DWORD   Characteristics;
} IMAGE_SECTION_HEADER, *PIMAGE_SECTION_HEADER;

#define IMAGE_SIZEOF_SECTION_HEADER          40

typedef struct _IMAGE_IMPORT_DESCRIPTOR {
    union {
        DWORD   Characteristics;            // 0 for terminating null import descriptor
        DWORD   OriginalFirstThunk;         // RVA to original unbound IAT (PIMAGE_THUNK_DATA)
    } DUMMYUNIONNAME;
    DWORD   TimeDateStamp;                  // 0 if not bound,
                                            // -1 if bound, and real date\time stamp
                                            //     in IMAGE_DIRECTORY_ENTRY_BOUND_IMPORT (new BIND)
                                            // O.W. date/time stamp of DLL bound to (Old BIND)

    DWORD   ForwarderChain;                 // -1 if no forwarders
    DWORD   Name;
    DWORD   FirstThunk;                     // RVA to IAT (if bound this IAT has actual addresses)
} IMAGE_IMPORT_DESCRIPTOR;
typedef IMAGE_IMPORT_DESCRIPTOR UNALIGNED *PIMAGE_IMPORT_DESCRIPTOR;

typedef struct _IMAGE_THUNK_DATA32 {
    union {
        DWORD ForwarderString;      // PBYTE
        DWORD Function;             // PDWORD
        DWORD Ordinal;
        DWORD AddressOfData;        // PIMAGE_IMPORT_BY_NAME
    } u1;
} IMAGE_THUNK_DATA32;
typedef IMAGE_THUNK_DATA32 * PIMAGE_THUNK_DATA32;


```