SQL Assignment: LLM Agent Platform Database

Create a simple relational database for a platform where users build AI agents. The goal is to practice creating tables, primary keys, foreign keys, a many-to-many link table, basic constraints and simple SQL queries.

> **Background.** An *LLM agent* is a program that uses a large language model (LLM) to do tasks. Each agent belongs to a **user** and runs on one **model**. An agent is allowed to use some **tools** (web search, running code). Each task an agent does is a **run**, and during a run the agent makes **tool calls**. Models charge money per token (a token is a small piece of text).

1. Database Tables

users

Column	Meaning
`user_id`	Unique number of the user
`name`	User's full name
`email`	User's email

models

Column	Meaning
`model_id`	Unique number of the model
`model_name`	Name of the model
`price`	Price in USD per 1 million tokens

agents

Column	Meaning
`agent_id`	Unique number of the agent
`agent_name`	Name of the agent
`user_id`	The user who owns the agent
`model_id`	The model the agent uses

tools

Column	Meaning
`tool_id`	Unique number of the tool
`tool_name`	Name of the tool

agent_tools

Column	Meaning
`agent_id`	The agent
`tool_id`	A tool this agent is allowed to use

runs

Column	Meaning
`run_id`	Unique number of the run
`agent_id`	The agent that did the task
`task`	What the agent was asked to do
`tokens`	How many tokens the run used
`status`	Result of the run

tool_calls

Column	Meaning
`call_id`	Unique number of the tool call
`run_id`	The run during which the call happened
`tool_id`	The tool that was called
`status`	Result of the call

2. Relationships

- A user can own many agents. Each agent belongs to one user.
- A model can be used by many agents. Each agent uses one model.
- An agent can use many tools, and a tool can be used by many agents (many-to-many through `agent_tools`).
- An agent can have many runs. Each run belongs to one agent.
- A run can have many tool calls. Each tool call belongs to one run and is for one tool.
- The relationships must be implemented using foreign keys.

3. Required Constraints

- Every table must have a PRIMARY KEY. In `agent_tools` the primary key is the pair (agent_id, tool_id).
- All foreign keys must reference the appropriate tables.
- User email must be UNIQUE and NOT NULL. User name must be NOT NULL.
- Model name and tool name must be UNIQUE and NOT NULL.
- Agent name and run task must be NOT NULL.
- Model price and run tokens must be greater than or equal to 0.

- Run status must be `'COMPLETED'` or `'FAILED'`.
- Tool call status must be `'SUCCESS'` or `'ERROR'`.

4. Sample Data

- 2 users
- 2 models
- 2 agents
- 2 tools
- 3 agent–tool assignments
- 3 runs (at least one failed)
- 3 tool calls (at least one error)

5. Required SQL Queries

1. Display all users.
2. Display models that cost less than 10 USD per 1 million tokens.
3. Display all failed runs.
4. Display the number of runs and the total tokens for each agent.
5. Display all tool calls that ended with an error.

6. What to Submit

- One `.sql` file that creates the tables, inserts the sample data and contains all the queries. It must run from top to bottom without errors.
- An ER diagram of the database (for example made in drawSQL or dbdiagram.io).