

Şerit Tipi Nozullar

Corner Strip Nozzles



Sabit açılı nozullar, sulama sistemlerinde hassas ve etkili sulama sağlamak için tasarlanmış önemli bir unsurdur. Bu nozullar, suyun belirli bir açıda ve sabit bir basınçla püskürtülmesini sağlayarak sulama işlemini optimize eder. Genellikle dar çim ve bitki alanlarında kullanılan bu nozullar, suyun düzgün bir şekilde dağılmasını ve alanın tamamının homojen bir şekilde sulanmasını sağlar. Ayrıca, sabit açılı nozulların kullanımıyla su israfı önlenir ve sulama verimliliği artar. Dayanıklı yapıları sayesinde uzun süreli kullanım için idealdirler ve değişik hava koşullarına uyum sağlayacak şekilde tasarlanmışlardır.

Fixed angle nozzles are an important element in irrigation systems designed to provide precise and effective irrigation. These nozzles optimize the irrigation process by ensuring that water is sprayed at a certain angle and with a constant pressure. These nozzles, which are generally used in narrow grass and plant areas, ensure even distribution of water and homogeneous irrigation of the entire area. Additionally, with the use of fixed angle nozzles, water waste is prevented and irrigation efficiency increases. Thanks to their durable structure, they are ideal for long-term use and are designed to adapt to different weather conditions.

POELSANARC
Automated Rain Control

Özellikler

Specifications

- ✦ Şerit alanlarını doğru şekilde kapsama amacıyla özel olarak geliştirilmiştir.

It was specially developed for the purpose of accurate coverage of lane areas.

- ✦ Farklı dikdörtgen alanlara uyacak şekilde çeşitli modeller sunulmaktadır.

A variety of models are offered to fit different rectangular spaces.

- ✦ Zorlu koşullara dayanıklı yapıya sahiptir.

It has a structure that is resistant to harsh conditions.


Çalışma Özellikleri

Operating Features

Önerilen çalışma basıncı 2.1 bar olarak belirlenmiştir.

The recommended operating pressure is set to 2.1 bar.



KOD CODE	BASINÇ (bar) PRESSURE	BASINÇ (kPa) PRESSURE	Genişlik x Uzunluk (m) WIDTH x LENGTH	DEBİ (m³/h) FLOW	DEBİ (L/dak) FLOW
LCSN515 	1,0	100	1,2 x 4,2	0,10	1,7
	1,5	150	1,2 x 4,3	0,13	2,1
	2,1	210	1,5 x 4,5	0,15	2,5
	2,5	250	1,5 x 4,5	0,16	2,7
	3,0	300	1,5 x 4,5	0,17	2,8
RCSN515 	1,0	100	1,2 x 4,2	0,10	1,7
	1,5	150	1,2 x 4,3	0,13	2,1
	2,1	210	1,5 x 4,5	0,15	2,5
	2,5	250	1,5 x 4,5	0,16	2,7
	3,0	300	1,5 x 4,5	0,17	2,8
SSN530 	1,0	100	1,2 x 8,5	0,21	3,5
	1,5	150	1,2 x 9,0	0,25	4,2
	2,1	210	1,5 x 9,1	0,30	5,0
	2,5	250	1,5 x 9,1	0,33	5,5
	3,0	300	1,5 x 9,1	0,34	5,7
SSN918 	1,0	100	2,4 x 5,2	0,27	4,5
	1,5	150	2,7 x 5,5	0,33	5,5
	2,1	210	2,7 x 5,5	0,39	6,5
	2,5	250	2,7 x 5,5	0,43	7,1
	3,0	300	2,7 x 5,5	0,47	7,9
CNS530 	1,0	100	1,2 x 8,5	0,21	3,5
	1,5	150	1,2 x 9,0	0,25	4,2
	2,1	210	1,5 x 9,1	0,30	5,0
	2,5	250	1,5 x 9,1	0,33	5,5
	3,0	300	1,5 x 9,1	0,34	5,7
CNS515 	1,0	100	1,1 x 4,2	0,10	1,7
	1,5	150	1,2 x 4,3	0,13	2,1
	2,1	210	1,5 x 4,5	0,15	2,5
	2,5	250	1,5 x 4,5	0,16	2,7
	3,0	300	1,5 x 4,5	0,17	2,8

LCSN515
Sol Köşe
Şerit Tipi Nozul
Left corner strip
type nozzle



RCSN515
Sağ Köşe
Şerit Tipi Nozul
Right corner strip
type nozzle



SSN530
Şerit Tipi Nozul
Strip type nozzle



SSN918
Orta
Şerit Tipi Nozul
Center corner strip
nozzle



CNS530
Merkez
Şerit Tipi Nozul
Center corner strip
nozzle



CNS515
Son
Şerit Tipi Nozul
End corner strip
nozzle



SSN918



SSN530



RCSN515



LCSN515



CNS530



CNS515

KOD CODE	NOZUL RENGİ NOZZLE COLOR	TANIM DEFINITION	ATIŞ MESAFESİ (m) THROW DISTANCE (m)	AMBALAJ ADEDİ PACKING QUANTITY	KUTU ADEDİ BOX QUANTITY
SSN530	● Black	Şerit tipi nozul Corner strip nozzles	1.5 x 9.1	25	250
LCSN515		Sol köşe şerit tipi nozul Left corner strip type nozzle	1.50 x 4.50	25	250
RCSN515		Sağ köşe şerit tipi nozul Right corner strip type nozzle	1.50 x 4.50	25	250
SSN918		Orta şerit köşe nozulu Central strip corner nozzle	2.70 x 5.50	25	250
CNS530		Merkez şerit tipi nozul Center strip type nozzle	1.50 x 9.10	25	250
CNS515		Son şerit tipi nozul End strip type nozzle	1.50 x 4.50	25	250