

Item 17

git_comments:

git_commits:

1. **summary:** HBASE-805 Remove unnecessary getRow overloads in HRS (Jonathan Gray via Jim Kellerman)
message: HBASE-805 Remove unnecessary getRow overloads in HRS (Jonathan Gray via Jim Kellerman) git-svn-id: <https://svn.apache.org/repos/asf/hadoop/hbase/branches/0.2@684060> 13f79535-47bb-0310-9956-ffa450edef68

github_issues:

github_issues_comments:

github_pulls:

github_pulls_comments:

github_pulls_reviews:

jira_issues:

1. **summary:** Remove unnecessary getRow overloads in HRS
description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.
2. **summary:** Remove unnecessary getRow overloads in HRS
description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.
3. **summary:** Remove unnecessary getRow overloads in HRS
description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.
4. **summary:** Remove unnecessary getRow overloads in HRS
description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.
5. **summary:** Remove unnecessary getRow overloads in HRS
description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.
label: code-design
6. **summary:** Remove unnecessary getRow overloads in HRS
description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.

final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.

7. **summary:** Remove unnecessary getRow overloads in HRS

description: HRS currently contains: public RowResult getRow(final byte [] regionName, final byte [] row, final long ts) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns) public RowResult getRow(final byte [] regionName, final byte [] row, final byte [][] columns, final long ts) The first two call the last one which calls HR.getFull. Changes will be made to HTable to map all getRow calls to a single getRow HRS method.

label: code-design

jira_issues_comments:

1. Reviewed patch. +1. Cannot commit until 0.2 branch is created.
2. Committed to 0.2 branch and trunk. Thanks for the patch Jonathan!
3. -1 This patch changed all lines of HRegionServer. (appears to be whitespace change) This makes maintaining other patches a PITA...
4. Hmm. The patch doesn't change all lines. Was it when you did the application Jim that all lines changed?
5. **body:** Fixed whitespace diffs in HRegionServer
label: code-design