DESMOR

Cement descaler

DESCRIPTION

For removing cement, glue, plaster, paint and cement-based stucco when cleaning claddings and ceramic floorings.

TECHNICAL CARACTERISTICS

Product made of strong acids diluted at the appropriate concentration.

APPLICATION PROCEDURE

- It can be applied directly or diluted in water.
- Wet throughly the surface to be treated, specialy the joints.
- Pour the product and rub strongly with a brush or scouring pad.
- After removing the stains, clean with plenty of clean water to remove any rests of the product.
- Isolated stains can be removed by soaking them and rubbing with a cloth or scouring pad drenched with the detergent remover.
- Before applying, always check whether the surface to be treated is acid resistant.
- For cleaning joints, use it diluted in water if the flooring material is not attacked by acids.

RECOMMENDATIONS

- Toxic product. Handle with due precaution at all times and avoid contact with eyes, skin or clothing.
- Do not swallow.
- In case of contact with eyes or skin, wash immediately with plenty of water.

PACKAGING AND STORAGE

1.5 and 25 l bags.
Shelf live: 2 years in sealed original packaging.

TECHNICAL DATA

(Statistical data obtained under standard conditions)	
Aspect	Colourless liquid
Density	1,3 gr / cm³
PH	Strong acid
Solubility	Completely soluble in water

LEGAL DISCLAIMER

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the

Rev. 24_04 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40

grupopuma

work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

NOTAS

The instructions for use are given according to our tests and knowledge and do not imply any commitment by GRUPO PUMA nor free the consumer from the examination and verification of the products for their correct use. Claims must be accompanied by the original packaging to allow a proper traceability.

GRUPO PUMA is not responsible, in any case, for the application of its products or constructive solutions carried out by the application company or other parties involved in the process and / or execution of the work, limiting the responsibility of GRUPO PUMA exclusively to the damages directly attributable to the supplied products, individually or integrated in systems, due to failures in their manufacturing process.

In any case, the drafter of the work project, the technical management or the person responsible for the work, or collaterally the application company or other parties involved in the process and / or execution of the work, must ensure the suitability of the products addressing the characteristics of them, as well as the conditions, support and possible pathologies of the work in question.

The values obtained by GRUPO PUMAS's products or its constructive solutions that, as the case may be, are determined by the EN standards or any other regulation that applies to it in each case refers exclusively to the conditions specifically stipulated in said regulation and that are referred to, among others, to certain characteristics of the support, humidity and temperature conditions, etc. without being them required in the tests obtained under different conditions, all in accordance with the relevant regulation.

Rev. 24_04 · This revision cancels all previous ones. Please, obtain the latest version from our web site · www.grupopuma.com · (+34) 957 76 40 40

grupopuma