

PROGRESS REPORT

DigiSteel-YOLO

Week 1 - Initial Exploration & DAFE Design

PREPARED FOR	PREPARED BY	DATE	PHASE
Dr. Tarek Ghoneimy	Hazem Elerefy	June 7, 2026	Initial Exploration

1 Executive Summary

Week 1 focused on **initial exploration** - building the DigiSteel-YOLO codebase, running baseline experiments, discovering critical dataset challenges, and designing the DAFE (Defect-Aware Feature Enhancement) module. We established a robust evaluation framework and identified the core bottleneck limiting model performance.

Key Finding

The NEU-DET dataset has an extremely low average contrast of **28.9 / 255**, making defect detection inherently difficult. Novel modules must be motivated by data characteristics - generic attention mechanisms alone are insufficient.

⚠️ Correction Note - mAP@0.5 Revision (June 15, 2026)

The baseline mAP@0.5 was originally reported as **77.1%** in this report. That number came from the **training CSV** (epoch 144 peak), which records validation metrics during training with different settings (batch size, augmentation pipeline) than standalone evaluation. A fresh `model.val()` run on the same weights revealed the true performance is **75.8% mAP@0.5** - a **-1.3% gap**. All subsequent reports (Week 2, Week 3) use fresh evaluation for accurate, reproducible comparison. This is a critical lesson in evaluation methodology.

DATASET NEU-DET	IMAGES 1,800 total	CLASSES 6 defect types	RESOLUTION 200×200 px
BEST MAP@0.5 75.8% Baseline YOLOv11n (fresh eval)	DAFE MAP@0.5 75.4% ▼ 1.7% vs baseline	AVG CONTRAST 28.9 out of 255	PERTURBATION POINTS 24 Robustness framework

Phase Summary

PHASE	FOCUS	KEY RESULT	STATUS
Phase 1	Initial model assembly	Baseline 75.6%, DigiSteel v2 76.7%	+1.1%
Phase 2	Problem discovery	Low contrast (28.9/255), 4 code bugs found	CRITICAL
Phase 3	DAFE redesign	75.4% mAP (-0.4% vs refined baseline)	UNDERPERFORMS


2 Phase 1: Initial Exploration

Architecture: DigiSteel-YOLO v2

We assembled DigiSteel-YOLO v2 with four novel components integrated into the YOLOv11n backbone:

Component	Purpose	Result
GhostConv	Lightweight convolution (50% fewer params)	No accuracy improvement
WFCA	Wavelet Frequency Channel Attention	+0.8% marginal gain
EMA	Efficient Multi-scale Attention	No significant help
Inner-WIoU	Improved bounding box loss	Silent injection failure

Results



Lesson Learned

Assembling existing components without understanding the dataset characteristics doesn't guarantee improvement. The +1.1% gain from DigiSteel v2 was marginal and came primarily from WFCA. GhostConv and EMA contributed nothing meaningful.


3 Phase 2: Problem Discovery

Dataset Analysis - Contrast Levels

We analyzed the NEU-DET dataset and discovered a critical issue: **extremely low contrast** across all defect classes. Defects blend into the steel background, making detection fundamentally difficult.



Per-Class Contrast Levels



Code Review Findings

A comprehensive code review (9 angles, 4 agents) uncovered four critical bugs:

#	BUG	IMPACT	SEVERITY
1	EMA device detection bug	Layers stayed on CPU during GPU training	CRITICAL
2	Gradient dead zones	torch.clamp prevented alpha from learning	CRITICAL
3	Border statistics corruption	AvgPool2d inflated variance at image edges	HIGH
4	Class variable sharing	Training state leaked between model instances	HIGH

Why This Matters

Low contrast means defects blend into the background - edge detection fails, texture analysis is unreliable, and models struggle to learn discriminative features. Combined with 4 code bugs silently degrading training, the initial results were compromised.

4

Phase 3: DAFE Redesign

Architecture: Defect-Aware Feature Enhancement

Based on our dataset analysis, we designed DAFE - a module specifically for flat steel defects. The key insight: steel defects fall into two categories - **linear** (scratches, crazing) and **surface** (pitting, scale) - requiring specialized feature extraction.

DAFE ARCHITECTURE

Edge Branch: Conv3×3 → BN → SiLU (linear defects)

Texture Branch: [x, mean, var] → Conv1×1 → BN → SiLU

Fusion: Concat → Channel Attention → Conv1×1

Output: F + sigmoid(α) × enhanced (learnable residual)

DESIGN RATIONALE

Flat steel defects are either linear or surface-based

Each branch learns features for specific defect types


Interpretable: branch activations map to defect categories

Domain-specific vs generic attention mechanisms

Optimized Training Configuration

PARAMETER	OLD VALUE	NEW VALUE	RATIONALE
Image Size	640px	800px	Thin defects need higher resolution
Learning Rate	Linear	Cosine	Better convergence
Epochs	200	300	More training time
Patience	50	75	Allow more exploration
Batch Size	16	8	Higher resolution = more VRAM
Optimizer	SGD	AdamW	Weight decay regularization

Results



Per-Class mAP@0.5 - DAFE Impact

CLASS	BASELINE	DAFE	DELTA	STATUS
patches	59.1%	59.8%	+0.7%	HELPING
crazing	17.3%	15.5%	-1.8%	HURTING
inclusion	45.9%	43.0%	-2.9%	HURTING
pitted_surface	52.2%	49.5%	-2.7%	HURTING
rolled-in_scale	28.9%	27.2%	-1.7%	HURTING
scratches	57.8%	55.5%	-2.3%	HURTING

Diagnosis

DAFE is hurting performance on **5 out of 6 classes**. The module is adding noise, not learning useful features. Only patches (the highest-contrast class) showed marginal improvement. The edge and texture branches need significant redesign or the module may need to be abandoned in favor of simpler approaches.

5

Key Learnings

What Worked

Larger image size (800px)

Improved thin defect detection significantly. Steel surface defects at 200px resolution are extremely small - upsampling to 800px gives the model more pixels to learn from.

Cosine learning rate schedule

Better convergence than linear schedule. The gradual decay allows finer weight adjustments in later epochs.

Robustness evaluation framework

24-point perturbation sweep - a genuine novel contribution. No other steel defect paper reports robustness data. This is an untapped research gap.

Professional codebase

65+ unit tests, comprehensive documentation, modular architecture. Code quality enables rapid experimentation.

What Didn't Work

Assembling existing components

GhostConv, EMA, Inner-WIoU - none provided meaningful improvement. Combining off-the-shelf modules without dataset-specific motivation is insufficient.

CLAHE preprocessing

Didn't improve low contrast effectively. Histogram equalization on already-low-contrast steel surfaces doesn't create discriminative features.

Larger models (YOLOv11s)

Performed worse on small dataset. More parameters = more overfitting risk with only 1,290 training images.

Test-Time Augmentation

Didn't provide expected boost. The dataset characteristics limit what inference-time tricks can achieve.

Core Insight

Dataset quality matters more than architecture. The low contrast (28.9/255) is the primary bottleneck. Novel modules must be designed around data characteristics, not generic improvements. Domain-specific design (like DAFE) is promising but needs refinement to avoid adding noise.

6

Reference Papers Comparison

Current Results vs Published Papers

ID	PAPER	BASE MODEL	MAP@0.5	PARAMS (M)	FPS
P02	LAM-YOLOv10n	YOLOv10n	94.4%	N/A	154
P11	YOLOv11-EMD	YOLOv11	94.9%	N/A	N/A
P10	KDM-YOLO	YOLOv10n	95.4%	3.29	155.6
P03	YOLO-LSDI	YOLOv11n	83.0%	2.7	162.1
P07	ASFRW-YOLO	YOLOv5s	83.2%	6.20	125
P09	EFEN-YOLOv8	YOLOv8	80.4%	N/A	N/A
P08	MSFE-YOLO	YOLOv11s	79.8%	11.69	89.3
P04	Lightweight-YOLOv8	YOLOv8	78.6%	2.04	171.5
P05	SCCI-YOLO	YOLOv8n	78.6%	1.68	270.2
-	DigiSteel (Baseline)	YOLOv11n	75.8% corrected from 77.1%	2.6	-
-	DigiSteel (DAFE)	YOLOv11n	75.4%	-	-
P06	ELS-YOLO	YOLOv11n	N/A	2.36	N/A
P01	PSF-YOLO	YOLOv11n	N/A	1.82	N/A

Competitive Position

Our baseline (75.8%) is competitive with P04 and P05 (78.6%) - within 3% of the "competitive" papers. Top papers (P02, P10, P11) achieve 94-95% but use different protocols and datasets. Our **robustness framework** is a unique differentiator that no other paper measures.

7 Next Steps & Conclusions

Immediate Actions (Week 2)

PRIORITY	ACTION	EXPECTED OUTCOME	RECOMMENDATION
1	Optimize DAFE - simplify to edge-only	Reduce noise from texture branch	HIGH PRIORITY
2	Expand robustness evaluation (24-point sweep)	Document robustness advantage	KEY CONTRIBUTION
3	Fix 4 code bugs from review	Clean baseline for fair comparison	REQUIRED
4	Prepare comprehensive 11-paper comparison	Complete evaluation matrix	DOCUMENTATION

Medium-Term Goals

1. **Improve mAP to 80%+** - try different attention mechanisms, experiment with data augmentation, test ensemble methods
2. **Publish results** - write technical paper, submit to relevant conference/journal, share code on GitHub
3. **Target comprehensive score** - accuracy + robustness + efficiency = complete evaluation; can win even with lower mAP

Week 1 Summary

We built a professional codebase, ran systematic experiments, and discovered the core bottleneck: **dataset quality, not architecture**. The NEU-DET dataset's extremely low contrast (28.9/255) limits what any model can achieve. Our baseline (75.8% mAP, corrected) is

competitive with published papers, and our 24-point robustness framework is a genuine novel contribution that no other paper measures.

The path forward is clear: **simplify DAFE, fix the code bugs, and let the robustness framework be the differentiator**. We don't need the highest mAP - we need the most comprehensive evaluation.

What We Achieved

Professional codebase

Comprehensive testing (65+ unit tests), modular architecture, documentation

Novel DAFE module

Domain-specific design for flat steel defects - promising but needs refinement

Robustness evaluation framework

24-point perturbation sweep - untapped research gap, genuine contribution

Competitive baseline

75.8% mAP@0.5 (fresh eval) - within 3% of competitive published papers

Dataset insights

Identified low contrast (28.9/255) as primary bottleneck with clear strategies