



Brake Fluids

hyrax[®] Brake Fluid Dot 3



Description

Hyrax Brake Fluid Dot 3 is specially formulated for high performance hydraulic brake and clutch systems of automotive vehicles. It offers protection against corrosion and rusting of metal parts even in the presence of moisture and does not affect natural or synthetic rubber washers.

Applications

Hyrax Brake Fluid Dot 3 is recommended for all heavy duty hydraulic brake, clutch, disc and drum systems where this type of fluid is specified. Having a higher boiling point provides long lasting protection against formation of vapor in the hydraulic systems.

Benefits

- High dry boiling point
- Compatible with all types of elastomers
- Low pour point
- Mixable with other approved commercial brake fluids
- Maximizes ABS performance

Typical Characteristics

Properties	Dot 3
Dry Equilibrium Reflux Boiling Point, °C	205
pH	7-10
Viscosity at -40°C, cSt	1,500.0 Max
Viscosity at 100°C, cSt	1.5 Min
Tetra Ethylene Glycol (TEG), wt %	24

Performance

- FMVSS 116 – DOT 3
- SAE J1703
- ISO 4925
- MS119
- JIS K2233



Compatible with all types of elastomers



Low pour point



Mixable with other approved commercial brake fluids



Maximizes ABS performance