



Brake Fluids

hyrax® Brake Fluid Dot 4



Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable. Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.



Compatible with all types of elastomers



Low pour point



Mixable with other approved commercial brake fluids



Maximizes ABS performance

Description

Hyrax Brake Fluid Dot 4 is specially formulated for high performance hydraulic brake and clutch systems of automotive vehicles. It offers protection against corrosion and rusting of metal parts even in the presence of moisture and does not affect natural or synthetic rubber washers.

Applications

Hyrax Brake Fluid Dot 4 is recommended for all heavy duty hydraulic brake, clutch, disc and drum systems where this type of fluid is specified. It is suitable for use in all models of cars, motorcycles and scooters requiring DOT 4 performance.

Benefits

- High dry boiling point
- Compatible with all types of elastomers
- Low pour point
- Mixable with other approved commercial brake fluids
- Maximizes ABS performance

Typical Characteristics

Properties	Dot 4
Dry Equilibrium Reflux Boiling Point, °C	230
pH	7.0 – 10.0
Viscosity at -40°C, cSt	1,350.0
Viscosity at 100°C, cSt	2.2
Tetra Ethylene Glycol (TEG), wt %	25

Performance

- FMVSS 116 – DOT 4
- SAE J17034 / J1703
- ISO 4925
- MS119
- JIS K2233