



Description

Hyrax Superguard is a super high performance multigrade diesel motor oil formulated to meet the highest performance required by high speed turbo-charged diesel engines running on low sulphur diesel or conventional high sulphur diesel fuel. Formulated with premium quality base oils and advanced detergent / dispersants, combined with anti-oxidant and anti-wear additive system provide maximum performance protection to the engines operating at high temperature and extreme conditions.

Applications

Hyrax Superguard is recommended for the lubrication of all types of diesel engines, including turbo-charged models installed in trucks, buses, earthmoving equipment and other diesel engines applications. Also suitable for gasoline engine requiring API SG and below performance level.

Benefits

- Prevents harmful crankcase deposits and excellent wear protection to prolong engine life
- Provides greater engine cleanliness, shear stable and resistance to oil thickening
- Excellent TBN retention to effectively neutralizing the acidic by-products of combustion

Typical Characteristics

Properties	Method	SAE 10W-30	SAE 15W-40	SAE 20W-50
Density at 15°C, Kg/L	ASTM D4052	0.868	0.873	0.873
Flash Point, °C	ASTM D92	>210	>210	>210
Pour Point, °C	ASTM D97	-36	-30	-27
Viscosity at 40°C, cSt	ASTM D445	72.9	107.4	149.6
Viscosity at 100°C, cSt	ASTM D445	10.9	14.2	18.8
Viscosity Index	ASTM D2270	140	135	142
Total Base Number, mgKOH/g	ASTM D2896	10	10	10

Performance

API CF-4 / SG



Excellent wear protection to prolong engine life



cleanliness



Excellent TBN retention



ormulated with premium