



Greases hyrax® EP Grease



Note:

All information supplied by or on behalf of Hyrax Oil in relation to its products, whether in the nature of data, recommendations or otherwise, is supported by rigorous laboratory work and research and believed to be reliable. Typical test data are average values only. Minor variations to typical properties not affecting the performance of the product are to be expected in normal manufacturing circumstances.



Multipurpose EP grease for wide range of applications



Excellent protection against rust and corrosion



Minimize wear under heavy and shock loading vibration



High resistance to water wash-out

Description

Hyrax EP Grease is premium quality extreme pressure multipurpose lithium hydroxyl-stearate grease developed for use in applications which require extreme pressure. It contains extreme pressure, anti-corrosion and anti-oxidant additives to provide excellent performance for heavy duty and shock loads application in the areas of corrosion protection, low temperature pumpability, high temperature service and load carrying capability as well as good water wash-out resistance.

Applications

Hyrax EP Grease is suitable for high load, shock load and vibration in variety of automotive, industrial, construction, mining and marine applications. It is highly recommended for a wide range of bearing operations with temperature of -15°C to 145°C. The product complies with Timken specification.

Benefits

- Multipurpose EP grease for wide range of applications
- Excellent protection against rust and corrosion
- Minimize wear under heavy and shock loading vibration application
- High resistance to water wash-out
- Excellent mechanical and storage stability

Typical Characteristics

Properties	NLGI 2	NLGI 3
Appearance	Smooth Amber	
Color	Brown	
Soap	Lithium 12-hydroxyl-stearate	
Dropping Point, °C	180	185
Worked Penetration at 25°C, dmm	280	235
Timken OK Load, lbs	45	45