1-Number of Zeros in a Given Array

Started on	Monday, 28 September 2026, 3:29 PM
State	Finished
Completed on	Monday, 28 September 2026, 4:03 PM
Time taken	33 mins 55 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 Correct Mark 1.00 out of 1.00 Flag question

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int countzero(int arr[], int low, int high, int n) {
    if (high >= low) {
        int mid = low + (high - low) / 2;

        if ((mid==0 || arr[mid - 1] == 1) && arr[mid] == 0)
            return n - mid;

        if (arr[mid] == 0)
            return countzero(arr, low, mid - 1, n);

        return countzero(arr, mid + 1, high, n);
    }
    return 0;
}

int main() {
    int m;
    scanf("%d",&m);

    int arr[m];

    for (int i = 0; i < m; i++) {
        scanf("%d", &arr[i]);
    }

    int zeroes = countzero(arr, 0, m - 1, m);
    printf("%d\n", zeroes);

    return 0;
}
```

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔
✔	10 1 1 1 1 1 1 1 1 1 1	0	0	✔
✔	8 0 0 0 0 0 0 0 0	8	8	✔
✔	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review

Back to Course

2-Majority Element

Started on	Monday, 28 September 2026, 3:33 PM
State	Finished
Completed on	Monday, 28 September 2026, 4:14 PM
Time taken	41 mins 11 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int main() {
    int n;
    scanf("%d",&n);

    int nums[n];
    for (int i = 0; i < n; i++) {
        scanf("%d", &nums[i]);
    }

    int candidate = 0;
    int count = 0;

    for (int i = 0; i < n; i++) {
        if (count == 0) {
            candidate = nums[i];
            count = 1;
        } else if (nums[i] == candidate) {
            count++;
        } else {
            count--;
        }
    }
    printf("%d\n", candidate);

    return 0;
}
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review

Back to Course

CS23331-Design and Analysis of Algorithms-2025 Batch-CSD

Started on	Wednesday, 30 September 2026, 9:22 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:44 PM
Time taken	21 mins 58 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100%**)

Quiz navigation

1

Finish review

Question 1 Correct Mark 1.00 out of 1.00 Flag question

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int findfloor(int arr[], int low, int high, int x, int ans){
    if(low>high) return ans;

    int mid = (low+high)/2;

    if (arr[mid]==x) return arr[mid];

    if (arr[mid]<x) {
        ans =arr[mid];
        return findfloor(arr,mid+1,high,x,ans);
    }
    else
        return findfloor(arr,low,mid-1,x,ans);
}

int main(){
    int n,x;
    scanf("%d",&n);

    int arr[n];

    for(int i=0;i<n;i++) scanf("%d",&arr[i]);

    scanf("%d",&x);

    printf("%d",findfloor(arr,0,n-1,x,-1));

    return 0;
}
```

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔
✔	5 10 22 85 108 129 100	85	85	✔
✔	7 3 5 7 9 11 13 15 10	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review

CS23331-Design and Analysis of Algorithms-2025 Batch-CSD

Started on	Wednesday, 30 September 2026, 9:45 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:53 PM
Time taken	7 mins 42 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Quiz navigation

1

Finish review

Question 1 | Correct Mark 1.00 out of 1.00 Flag question

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int binsearch(int arr[], int low,int high, int key){
    if(low>high) return -1;

    int mid = (low+high)/2;

    if(arr[mid]==key) return mid;
    if(arr[mid]<key) return binsearch(arr,mid+1,high,key);
    else return binsearch(arr,low,mid-1,key);
}

int main(){
    int n,x;
    scanf("%d",&n);

    int arr[n];
    for(int i=0;i<n;i++) scanf("%d",&arr[i]);

    scanf("%d",&x);

    for(int i=0;i<n-1;i++){
        int k = x-arr[i];
        int pos=binsearch(arr,i+1,n-1,k);

        if (pos !=-1){
            printf("%d\n",arr[i]);
            printf("%d\n",arr[pos]);
            return 0;
        }
    }

    printf("No\n");
    return 0;
}
```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review

CS23331-Design and Analysis of Algorithms-2025 Batch-CSD

Started on	Wednesday, 30 September 2026, 9:55 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 10:00 PM
Time taken	5 mins 33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100%**)

Quiz navigation

1

Finish review

Question 1 | Correct | Mark 1.00 out of 1.00 | Flag question

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```c
#include <stdio.h>

void quicksort(int arr[],int low,int high){
    if (low< high){
        int pivot = arr[high];
        int i=low-1;

        for(int j=low;j<high;j++){
            if (arr[j]<pivot){
                i++;
                int temp=arr[i];
                arr[i]=arr[j];
                arr[j]=temp;
            }
        }

        int temp=arr[i+1];
        arr[i+1]=arr[high];
        arr[high]=temp;

        int p=i+1;

        quicksort(arr,low,p-1);
        quicksort(arr,p+1,high);
    }
}

int main(){
    int n;
    scanf("%d",&n);

    int a[n];

    for(int i=0;i<n;i++) scanf("%d",&a[i]);

    quicksort(a,0,n-1);

    for(int i=0;i<n;i++) printf("%d ",a[i]);

    return 0;
}
```

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Finish review