Started on	Thursday, 8 October 2026, 6:28 PM
State	Finished
Completed on	Thursday, 8 October 2026, 6:32 PM
Time taken	3 mins 45 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main(){
    int n , i , j;
    scanf("%d",&n);

    int a[n];
    for(i=0;i<n;i++){
        scanf("%d",&a[i]);
    }
    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if (a[i]==a[j]){
                printf("%d",a[i]);
            }
        }
    }
    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 6:34 PM
State	Finished
Completed on	Thursday, 8 October 2026, 6:55 PM
Time taken	20 mins 52 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main(){
    int n,i,j;
    scanf("%d",&n);

    int a[n];
    for(int i=0;i<n;i++){
        scanf("%d",&a[i]);
    }
    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if (a[i]==a[j]){
                printf("%d",a[i]);

                return 0;
            }
        }
    }
    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 6:44 PM
State	Finished
Completed on	Thursday, 8 October 2026, 6:51 PM
Time taken	7 mins 5 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array

2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main(){
    int t,n1,n2,i,j;
    scanf("%d",&t);

    while(t--){
        scanf("%d",&n1);

        int a[n1];
        for(i=0;i<n1;i++)
        scanf("%d",&a[i]);

        scanf("%d",&n2);
```

```
        int b[n2];
        for(i=0;i<n2;i++)
        scanf("%d",&b[i]);

        for(i=0;i<n1;i++){
            for(j=0;j<n2;j++){
                if (a[i]==b[j]){
                    printf("%d ",a[i]);
                    break;
                }
            }
        }
        printf("\n");
    }
    return 0;
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 6:36 PM
State	Finished
Completed on	Thursday, 8 October 2026, 6:42 PM
Time taken	5 mins 27 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main(){
    int t,n1,n2,i,j;
    scanf("%d",&t);

    while(t--){
        scanf("%d",&n1);

        int a[n1];
        for(int i=0;i<n1;i++)
        scanf("%d",&a[i]);
        scanf("%d",&n2);

        int b[n2];
```

```
        for(i=0;i<n2;i++)
        scanf("%d",&b[i]);

        for(i=0;i<n1;i++){
            for(j=0;j<n2;j++){
                if (a[i]==b[j]){
                    printf("%d ",a[i]);
                }
            }
        }
        printf("\n");
    }
    return 0;
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 6:57 PM
State	Finished
Completed on	Thursday, 8 October 2026, 7:01 PM
Time taken	3 mins 31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main(){
    int n,k,i,j;
    scanf("%d",&n);

    int a[n];

    for(i=0;i<n;i++)
    scanf("%d",&a[i]);

    scanf("%d",&k);

    for(i=0;i<n;i++){
        for(j=i+1;j<n;j++){
            if (a[j]-a[i]==k){
                printf("1");
                return 0;
            }
        }
    }
    printf("0");
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.