

The Future of PRAYCG

Public-Safe Roadmap for Individual, Four-Day, and Group Studies

Version 1.1 - GitHub/OSF public-safe release draft

Document status: Forward-looking research-design roadmap. Not a preregistration, not IRB approval, not medical guidance, not a clinical protocol, and not a claim that exploratory PRAYCG self-runs have confirmed narrative meaning, memory formation, OSM biology, consciousness, or any biological mechanism. Public-safe for GitHub/OSF: no raw data, no copyrighted media, no private local paths.

Table of contents

- 1. Executive summary
- 2. Analysis of the institutional-deployment critique
- 3. Department placement: where PRAYCG belongs
- 4. Stable protocol core
- 5. Current discovery map and what it does not prove
- 6. Confirmation-grade gate logic
- 7. Individual N-of-1 development program
- 8. Four-day individual study design
- 9. Future group study roadmap
- 10. Future protocol variants
- 11. Variant 4 deep dive: High-Order Visual Control / Structural Defense
- 12. Statistical and computational roadmap
- 13. Hardware and software roadmap
- 14. Ethics, disclosure, and data governance
- 15. Recommended next steps
- Appendix A: Claim labels
- Appendix B: Public-safe repository checklist

1. Executive summary

The next stage of PRAYCG should not be more grandiose; it should be more discriminating. The project is strongest when framed as a rigorous open workbench for naturalistic psychophysiology, not as a proof of consciousness or speculative cellular memory. Its future value lies in turning story-driven experience into a structured causal-inference problem: What remains after sensory entrainment, high-order visual structure, gaze allocation, task load, order effects, respiration, artifact, and self-report confounds have been modeled?

Recommended future posture: PRAYCG should be presented as an open-source methods platform for testing state-locked narrative psychophysiology under explicit confound gates. The future claim is not 'meaning has been proven.' The future claim is 'this architecture makes stronger tests of meaning-vs-sensory/task explanations possible.'

A university or research lab could reasonably consider PRAYCG, but only if it adopts the project's own quarantine doctrine: the human EEG protocol is not evidence of microtubules, biophotons, quantum biology, OSM-CELL, or metaphysical mechanism. The university-grade object is the protocol, software, timing/QC workflow, counterbalanced study design, and analysis methodology.

2. Analysis of the institutional-deployment critique

The outside critique argues that PRAYCG may have strategic value for university labs if biological-mechanism claims are quarantined, and that its engineering value lies in timing/QC, naturalistic stimulus controls, and a software platform that graduate students could extend. That critique is directionally useful, but several phrases need correction before the idea is safe for GitHub, OSF, IRB, or grant-facing use.

Gemini-style claim	Rigorous assessment	Public-safe correction
A university lab should absolutely consider running PRAYCG.	Conditionally correct. A lab may consider PRAYCG as exploratory methods development, not as confirmed theory.	A lab could evaluate PRAYCG as an open naturalistic-EEG workbench after ethics review, pilot validation, and strict claim boundaries.
The protocol is a masterclass in causal inference and artifact control.	Too strong. The architecture is causal-inference-aware, but current fixed-order self-runs still have unresolved face/object, gaze, order, carryover, and gamma-artifact confounds.	PRAYCG is an unusually explicit artifact/confound-aware workbench. Future variants should test whether its controls are sufficient.
Cost-effective rigor with millisecond-accurate event-related timing using OpenBCI and PT19.	Partly correct but needs precision. A photodiode/ALS channel can validate physical display onset. It does not make consumer EEG a high-density clinical EEG system, and it does not solve all timing issues.	Runner-side ALS barcode pulses can improve physical display-timing validation, but every run still needs a timing-grade label.
CET-R mathematically strips away low-level audiovisual entrainment.	Overstated. CET-R residualizes measured exogenous regressors; it does not remove every unmeasured stimulus property.	CET-R tests whether observed physiology is explainable by recorded stimulus regressors such as luminance, audio envelope, cuts, motion, cue timing, and related features.
Manual heuristics are a goldmine for machine learning.	Reasonable as a future engineering direction, but current N is too small for high-capacity models.	Use PRAYCG heuristics as transparent baselines; move to contrastive/latent models only after multi-subject data, frozen endpoints, and strong leakage controls.
OSM/microtubules must be severed for institutional survival.	Mostly correct for the public human protocol. Cellular OSM belongs in a separate speculative or cellular-methods track.	Keep PRAYCG human EEG papers about timing, controls, physiology, and state trajectories. Keep OSM-CELL quarantined until direct cellular evidence exists.
The strict QC gauntlet creates low-yield threat.	Correct. But low positive yield is not a failure if invalid data are clearly rejected.	Define yield as valid interpretable runs, not positive results. Negative and vetoed runs are part of the method.
Gamma contamination is a major risk.	Correct and central. Scalp lower-gamma/high-frequency features are vulnerable to EMG, ocular, jaw, forehead, and motion artifacts.	Gamma-derived features remain candidate work-signal proxies only; they require EOG/EMG/artifact veto and cannot stand alone.
A lab should bypass the standard three-arm pilot and immediately build PRAYCG2.1 upgrades.	Not recommended. A lab should not bypass feasibility. It should run a staged program: usability, timing validation, standard core, then confound-expanded variants.	Begin with a standard PRAYCG2.1 feasibility run, then add high-order visual controls, eye tracking, counterbalancing, and long-washout variants.

Corrected institutional verdict: A research lab should consider PRAYCG only as a bounded open-methods platform. The protocol is promising because it makes confounds explicit, not because it has already defeated them.

3. Department placement: where PRAYCG belongs

PRAYCG should not be owned by only one academic silo. Its natural home is a cross-disciplinary team. The scientific lead should ideally come from cognitive neuroscience, affective neuroscience, neuroaesthetics, media psychology, or psychophysiology. The technical co-lead should come from signal processing, biomedical engineering, computer science, or applied machine learning. The reason is structural: the protocol combines naturalistic stimulus design, human-subjects psychophysiology, OpenBCI/LSL acquisition, artifact control, video preprocessing, autonomic physiology, and statistical modeling.

Possible home	Strength	Risk if isolated
Psychology / media cognition / affective science	Best fit for story, affect, task stance, self-report, and participant design.	May under-resource timing, acquisition engineering, and ML/latent model work.
Cognitive neuroscience / neuroaesthetics	Best conceptual fit for naturalistic viewing, EEG, and narrative cognition.	May still need engineering support for open hardware and software deployment.
Biomedical engineering / signal processing	Best fit for LSL, OpenBCI, ALS timing, artifact control, and reproducible pipelines.	May under-theorize narrative, self-report, and stimulus selection.
Computer science / machine learning	Useful for contrastive learning, latent dynamics, automatic QC, and open-source tooling.	High risk of overfitting or treating subjective meaning as a generic label without experimental nuance.
Human-computer interaction / media technology	Useful for applied interface, immersion, and public software usability.	Could drift toward product demos before scientific validation.

The best configuration is a co-supervised program: psychophysiology/neuroaesthetics for the experimental question, engineering/computer science for metrology, and statistics/methodology for preregistered model comparison.

4. Stable protocol core

The future PRAYCG architecture should preserve the current stable spine while adding controls around it. The core remains: a meaning-damaged sensory control, an intact target narrative, and the same intact narrative under analytic or extraction-oriented task stance. The key design rule is that Target and Contextual Override should use the same cue-embedded stimulus, with only the participant instructions differing. The phase-scrambled Control is generated from the cue-embedded Target so cue timing and low-level cue energy are represented in the control branch.

Stable element	Future rule	Reason
Phase-scrambled Control	Keep it for serious studies.	Without it, PRAYCG cannot answer the sensory-entrainment critique.
Same-stimulus Target/Override	Target and Override must be bit-identical or equivalently documented.	This supports a task-stance contrast rather than a stimulus-file contrast.
Cue schedule provenance	Log seed, interval, duration, position, expected sum, and file hashes.	Cue properties can become confounds if undocumented.
Frame-locked anchors	Use LOCKED anchors for confirmatory	A-MRED is timing-dependent.

	attempts; estimated anchors remain pilot-only.	
Runner-side ALS barcode	Use PRAYCG2.1 barcode overlay before each branch.	Physical display timing should not depend only on an MP4-internal square that may shift under safe-fit playback.
Final reflection baseline	Keep Baseline2, but interpret it as cumulative after-state, not pure Target recovery.	Baseline2 follows the whole protocol, including task completion and reflection.
Self-report boundary	Use first-person reports as covariates and constraints, not proof.	Experience and physiology are separate evidence streams.

5. Current discovery map and what it does not prove

The current self-run series should be treated as design discovery rather than confirmation. It is useful because it exposed multiple archetypes and failure modes. It does not justify population claims, clinical claims, mechanism claims, or the removal of controls.

Current archetype	Working interpretation	Boundary
Arrival	Recognition-dominant: meaning-recognition proxies may appear without a clean new-integration endpoint.	Older run; limited by older protocol structure and channel/ROI caution.
Contact	MRED-Peak candidate: strongest acute peak-like case in current self-run set.	Conceptually predeclared but not fully runner-registered confirmation.
Field of Dreams	MRED-Resolution candidate: reflective afterglow and closure-like profile rather than acute peak only.	Runner-registered estimated blind-anchor pilot; not strict frame-verified confirmation.
Eternal Sunshine	Decoder-gate dissociation: semantic access and emotional/afterglow impact separated under real-world audio confound.	Audio-confounded and ALS-cautioned; useful for theory, not confirmation.

- Meaning recognition and integration can plausibly dissociate.
- Peak-like meaning and resolution-like meaning may have different physiological shapes.
- Analytic extraction may reroute, attenuate, or reorganize meaning rather than simply erasing it.
- Sensory clarity and emotional impact can separate.
- Phase-scrambled Control is not zero; it is a meaning-damaged sensory-control branch that can still produce physiology.
- Baseline2 is cumulative and may reflect narrative afterglow, task-completion relief, fatigue, respiration, or their mixture.

What the current data do not prove: consciousness, OSM biology, memory formation, microtubules, biophotons, clinical effect, universal validity, or a population-level narrative-meaning biomarker.

6. Confirmation-grade gate logic

A future result should be called confirmation-grade only if it passes a predeclared chain of gates. A failed gate does not make the run worthless; it changes the label to pilot, exploratory, confound-discovery, or calibration data.

```

A_MRED_confirmable =
  AnchorLocked
* TimingPass
* MediaQC
* AudioQC
* ArtifactPass
* CETRPass
* HOCTPass
* OSAPass
* OHCTPass
* AAMPass
* RespDualPathPass
* EndpointPass

```

- AnchorLocked: frame-verified LOCKED anchor JSON loaded before acquisition and hash-logged.
- TimingPass: runner-side ALS barcode detected in Control, Target, and Override, or timing grade explicitly labeled.
- MediaQC: Target/Override bit identity verified; Control generated from cue-embedded Target.
- AudioQC: Control audio unintelligible by manual review; branch audibility acceptable and balanced.
- ArtifactPass: EOG/EMG or strong artifact sentinels do not explain the event.
- CETRPass: low-level stimulus regressors do not explain the endpoint.
- HOCTPass: high-order face/body/object/social-visual variables do not explain the endpoint.
- OSAPass: cue/gaze/spatial-attention burden does not explain Target/Override contrast.
- OHCTPass: order, habituation, and prior-branch carryover do not explain the endpoint.
- AAMPass: afterglow attribution favors narrative after-state over task-completion relief when Baseline2 is invoked.
- RespDualPathPass: respiration is modeled as both artifact and valid autonomic state signal.

7. Individual N-of-1 development program

Individual PRAYCG runs remain valuable if their purpose is explicit. They are best used to harden the apparatus, test stimulus suitability, debug anchor timing, and map within-person archetypes. They should not be used as population evidence.

Stage	Purpose	Permitted interpretation
A. Engineering pilots	Control Center, streams, LabRecorder, ALS mount, MediaPrep, runner, analysis, offline interpreter.	No scientific endpoint claim.
B. Estimated-anchor pilots	Runner-registered estimated anchors to test stimulus timing and subjective suitability.	Pilot-only; useful for refining anchors and confounds.
C. Frame-locked confirmability attempts	LOCKED anchors, quiet audio, ALS barcode, EOG/EMG if possible.	N-of-1 confirmation-grade only if every gate passes.
D. Repeated N-of-1 series	Multiple stimuli, repeated sessions, counterbalanced variants across days.	Within-person reliability and archetype mapping, still not population inference.

8. Four-day individual study design

The four-day structure separates acclimation, calibration, hypothesis-critical perturbation, and delayed after-state/debrief. It prevents one morning session from carrying all burdens at once.

Day	Procedure	Purpose
Day 1 - Acclimation and gear comfort	Fit cap; practice stillness; test OpenBCI, Polar, Vernier, ALS, LSL, LabRecorder; practice override cues on neutral media.	Reduce equipment novelty and identify setup failures before hypothesis testing.
Day 2 - Calibration and neutral controls	Run resting baselines, paced/natural breathing, neutral media, cue-monitor practice, signal-quality and ALS barcode tests.	Estimate baseline physiology, respiratory/common-drive behavior, cue burden, and artifact profile.
Day 3 - Main PRAYCG perturbation	Run predeclared stimulus with PhaseScrambled, ShotOrderScramble when available, Target, CueMonitor/Override as designed, and final Baseline2.	Test the primary PRAYCG endpoint under the strongest feasible within-person controls.
Day 4 - Delayed after-state and debrief	Repeat baseline, collect delayed self-report, optional memory/recognition check, disclose any temporary concealment, confirm withdrawal/public-sharing choices.	Distinguish immediate state from delayed after-state; respect participant agency and data governance.

If incomplete disclosure is used to preserve novelty or reduce expectancy, it must be minimal-risk, disclosed in advance as incomplete disclosure, reviewed ethically where required, followed by debrief, and paired with withdrawal options. No participant should be misled about physiological recording, emotional content category, or data use.

9. Future group study roadmap

The group program should proceed as staged methods validation, not an immediate maximal theory test. Numbers below are planning ranges only; actual power depends on pilot variance, attrition, artifact rate, and endpoint stability.

Study stage	Scale	Primary purpose	Interpretive status
Group 0 - Usability	N=3-6	Can naive users operate Control Center, streams, LabRecorder, runner, and analysis?	Software/hardware feasibility only.
Group 1 - Endpoint feasibility	N=8-12	Estimate artifact rates, ALS pass rates, self-report distributions, endpoint variance.	Feasibility; not confirmatory.
Group 2 - Counterbalanced core test	N=24-40	Target/Override order counterbalanced across stimuli and participants.	First serious group test of task-stance effect.
Group 3 - High-order control test	N=30-60	Add ShotOrderScramble and HOC-R to test narrative-order beyond faces/social structure.	Strong structural-defense study.
Group 4 - Multisite/open replication	Powered from prior variance	Frozen software, frozen endpoints, independent site/team.	External validity and reproducibility.

Endpoint_score ~ Condition * Variant

+ Familiarity + AudioAccess + TaskLoad + CueBurden
+ FaceArea + BiologicalMotion + Luminance + AudioEnvelope
+ Respiration + Artifact
+ ExposureIndex + PreviousBranch
+ (1 | Subject) + (1 | Stimulus) + (1 | Anchor)

10. Future protocol variants

Variant	Structure	Purpose	Cost / limitation
Variant 1: Standard PRAYCG2.1	PhaseScrambled -> Target -> Override	Core public workflow and feasibility comparison.	Fixed order and phase-scramble limitations remain.
Variant 2: Counterbalanced Target/Override	Different participants or days receive Target before Override or Override before Target.	Separates task stance from third-watch habituation.	May spoil natural Target novelty for some participants.
Variant 3: Cue-Monitor Control	Target -> CueMonitor -> Override	Separates upper-right cue spatial attention from arithmetic/extraction.	Adds time and repetition burden.
Variant 4: High-Order Visual Control	PhaseScrambled -> ShotOrderScramble -> Target -> Override	Tests whether Target survives a control that preserves faces/bodies/local social structure but breaks narrative order.	Editing and QC burden; requires shot maps and manual verification.
Variant 5: Long-washout / day-separated	Branches separated by long intervals or different days.	Tests endocrine/autonomic carryover concerns.	Fatigue, scheduling, and stimulus familiarity tradeoffs.
Variant 6: Eye-tracked PRAYCG	Add dedicated eye tracker or webcam gaze proxy.	Directly tests OSA/gaze/AOI confounds.	Additional hardware and calibration.
Variant 7: EOG/EMG-enhanced PRAYCG	Add vertical/horizontal EOG and jaw/temple/forehead EMG.	Best gamma-artifact defense.	Setup complexity and participant burden.
Variant 8: Subtitle Override	Muted subtitle extraction condition.	Tests semantic access vs sensory modality and extraction load.	Requires gaze-locked subtitle timing for best metrology.
Variant 9: Group/hyperscanning	Multiple participants with shared stimuli and counterbalanced variants.	Tests intersubject structure and generalizability.	Requires larger sample and stronger ethics/logistics.

11. Variant 4 deep dive: High-Order Visual Control / Structural Defense

Variant 4 is the strongest future defense against the critique that Target > PhaseScrambled merely reflects faces, bodies, object structure, edges, or biological motion. It is not definitive proof of narrative meaning, but it substantially narrows the alternative-explanation space.

The proposed structure is: PhaseScrambled -> ShotOrderScramble -> Target -> Override. The ShotOrderScramble branch preserves local high-order visual/social structure while damaging the temporal order that creates narrative arc. The participant still sees faces, bodies, gestures, closeups, and

local action; what is disrupted is the sequence by which expectation, reversal, recognition, and release are built.

The critique's strongest phrase is that Variant 4 is the 'crown jewel.' That is directionally fair, but it must not be phrased as definitive proof. If Target survives ShotOrderScramble, the result is more consistent with narrative-order or temporal-meaning structure than with face processing alone. It still requires artifact, gaze, order, familiarity, audio, and self-report controls.

Step	Procedure	QC requirement
1. Shot detection	Use automated cut detection as draft, then manually verify every shot boundary.	No accidental micro-cuts, subtitles, logos, or source-stamps that carry meaning.
2. Shot annotation	For each shot, mark duration, face count/area, body motion, speaker/dialogue, local emotional intensity, luminance, audio level, and anchor relevance.	Creates HOC-R regressors and makes the scramble auditable.
3. Scramble construction	Shuffle shot order while preserving shot integrity, broad duration distribution, local faces/bodies/motion, and cue schedule compatibility.	Avoid creating a coherent alternative story or introducing gross discontinuity artifacts.
4. Audio strategy	Choose shot-linked audio scramble, speech-shaped noise envelope, or envelope-preserved unintelligible audio.	Human audio QC remains mandatory; no recognizable narrative sentence fragments.
5. Cue schedule	Apply the same cue timing if the branch includes cues.	Cue timing and low-level cue energy represented across branches.
6. StimulusFingerprint + HOC-R	Compute luminance, audio envelope, cuts, optical flow, face metrics, object/edge density, biological-motion proxies, and shot-order entropy.	HOC-R must be available before claiming structural defense.
7. Endpoint analysis	Compare Target to PhaseScrambled, ShotOrderScramble, CueMonitor, and Override where available.	A-MRED/MRED-Peak/Resolution should survive all relevant controls.

```

Y_w = beta0
+ beta_T * I(Target_w)
+ beta_H * I(ShotOrderScramble_w)
+ beta_C * I(PhaseScrambled_w)
+ beta_F * FaceArea_w
+ beta_B * BiologicalMotion_w
+ beta_O * ObjectStructure_w
+ beta_L * Luminance_w
+ beta_A * AudioEnvelope_w
+ beta_K * CutRate_w
+ beta_R * Respiration_w
+ beta_G * GazeOrCueBurden_w
+ error_w

```

Candidate narrative-order evidence requires beta_T to remain positive and stable after HOC-R/CET-R/artifact/gaze/order terms.

Observed pattern	Conservative interpretation
Target > PhaseScrambled but Target ~ ShotOrderScramble	High-order social visual structure or local emotional content may explain the effect; narrative-order claim

	weakened.
Target > PhaseScrambled and Target > ShotOrderScramble	More consistent with temporal narrative structure or integrated story meaning, pending artifact/gaze/order controls.
ShotOrderScramble > Target	Could reflect novelty, confusion, arousal, or artifact; narrative interpretation fails for that anchor.
Override ~= Target	Task did not attenuate reception, task failed, meaning broke through task, or task and target effects are not separable for this stimulus.
Override < Target but CueMonitor < Target	Could be spatial attention/AOI burden, not arithmetic extraction; OSA/eye tracking required.
No branch differences after HOC-R/CET-R	Stimulus-side features explain the candidate effect; endpoint should not pass.

12. Statistical and computational roadmap

The present handcrafted module system should be preserved as a transparent baseline. Machine learning can be added later, but not as a black box that replaces the experimental logic. ML should be used to test whether latent dynamics improve prediction under cross-validation, not to relabel pilot effects as proof.

Contrastive representation proposal:

$z_t = f_{\theta}(\text{EEG}_t, \text{HRV}_t, \text{Resp}_t)$

Objective:

maximize prediction of locked condition/anchor state,
minimize prediction of nuisance variables such as subject identity,
luminance, audio envelope, face area, cue burden, motion, and artifact.

Never use random window splits that leak adjacent temporal or subject-specific information.

Prefer blocked time splits, leave-one-subject-out splits, and leave-one-stimulus-out tests.

Computational upgrade	Use	Guardrail
Latent dynamical systems	Model continuous hidden state trajectories across branches.	Needs enough subjects/trials; must include stimulus and artifact inputs.
Contrastive learning	Learn features that distinguish Target from controls while penalizing nuisance variables.	High overfitting risk; require held-out subjects/stimuli.
State-space causal models	Test carryover and directionality under time-lagged assumptions.	No causal claim without non-overlapping windows and negative controls.
Automated shot maps	Support Variant 4 and HOC-R.	Manual QC remains required.
Offline interpreter	Make output legible to non-experts.	Must clearly label pilot/exploratory/confirmable status.

13. Hardware and software roadmap

Item	Implementation	Why it matters
PRAYCG2.1 runner-side ALS barcode	Black 0.5 s -> white 2.0 s -> black 0.5 s -> white 0.75 s -> black 1.0 s before each branch.	More robust physical display-timing validation than a single MP4-embedded pulse.
ALS/PT19 holder	Opaque shroud, foam gasket, cable	Reduces false missing pulse due to

	strain relief, stable screen coordinate.	placement or room light.
EOG/EMG	Vertical/horizontal EOG; jaw/temple/forehead EMG.	Makes gamma/high-frequency claims less vulnerable.
Eye tracking	Dedicated eye tracker or webcam proxy.	Tests whether Override effects are due to cue gaze/AOI burden.
MediaPrep HOC branch	ShotOrderScramble generation plus shot-map templates and face/body metrics.	Required for high-order visual structural defense.
Control Center	Keep as orchestrator, not monolithic mega-app.	Public usability and reproducibility.
Master Suite v1.5.8+	Barcode detector, confound expansion modules, HOC-R, OSA, OHC, AAM, RespDualPath.	Moves the suite toward confirmation-grade confound accounting.

Respiration should remain part of the acquisition stack. The correct doctrine is dual-path: a breath/sigh can be a physiological state event and an EEG/HRV confound. It should be preserved as a possible autonomic release marker while being penalized or modeled when interpreting clean EEG endpoints.

14. Ethics, disclosure, and data governance

- For self-runs, label data as self-experimentation and do not generalize to population effects.
- For any other participant, obtain informed consent and pursue appropriate ethics/IRB review where applicable.
- Do not redistribute copyrighted stimulus media. Public repos should store code, templates, hashes, manifests, public-safe derived examples, and instructions for local stimulus procurement.
- Incomplete disclosure, if used to preserve novelty or reduce expectancy, should be minimal-risk, pre-disclosed as incomplete disclosure, reviewed where required, followed by debrief, and paired with withdrawal options.
- Emotionally intense stimuli should be screened and disclosed appropriately. Participants should be able to stop without penalty.
- Do not claim clinical benefit, diagnosis, treatment, trauma resolution, or mechanistic healing from PRAYCG data.
- Raw biosignal data and free-text self-reports may be identifiable; public sharing requires deidentification and consent.

15. Recommended next steps

Priority	Action	Outcome
1	Stabilize PRAYCG2.1 ALS barcode and sensor mount.	Timing-grade data becomes more plausible.
2	Run clean standard PRAYCG2.1 feasibility with quiet audio and locked anchors.	Baseline confirmation attempt without new variants.
3	Add EOG/EMG before relying on gamma-heavy endpoints.	Stronger artifact defense.
4	Add CueMonitor or eye tracking.	Separates task arithmetic from spatial attention.
5	Build ShotOrderScramble tooling and templates.	Enables Variant 4 high-order structural defense.
6	Run small Group 0/1 usability and	Detects whether public/lab users can

	endpoint feasibility.	reproduce workflow.
7	Freeze a preregistered group test with mixed-effects model and defined claim labels.	Moves from exploratory workbench to scientific test.

Appendix A: Claim labels

Label	Meaning
Engineering test	Software/hardware workflow only. No physiological interpretation.
Pilot	Useful run with at least one important missing confirmation gate.
Confound-discovery	A run that reveals why a design fails or splits; valuable but not endpoint-positive.
N-of-1 confirmable	All gates pass for a single participant; not population evidence.
Group feasibility	Group run estimates variance/artifact rates but is not powered for final claims.
Confirmation-grade group result	Predeclared, adequately powered, counterbalanced, independently reproducible, and passed the full gate chain.

Appendix B: Public-safe repository checklist

- No copyrighted movie clips.
- No raw private XDF/EEG/HRV/respiration data unless explicit consent and deidentification procedures are in place.
- No unredacted free-text self-report from other participants.
- No local file paths or personal folder names in public examples when avoidable.
- No medical or clinical claims.
- No proof-of-consciousness or proof-of-OSM claims.
- Every example result labeled pilot/exploratory/confirmable according to gate status.
- Public-safe demo media should be CC0/public-domain/open-license or synthetic, with license documented.