Segregation of Duties for AI Agents

Internal-Control-Grounded Defences Against Invoice Manipulation and Payment Diversion in Agentic Procure-to-Pay

Interim Report

Note: the OpMech order-gap diagnostic is treated as an exploratory ablation, not as a proven defence.

Author: Hemanth

Class: MAIB March 2025

Project area: Agentic AI in Supply Chain Finance and Financial Controls

Supervisor: Prof. Dr. Debashis Guha

Primary environment: SoD-Bench, an open synthetic procure-to-pay sandbox built for this study

Target venue: USENIX Security '27, Cycle 2 (submission due 26 January 2027)

Date: 7 November 2026

Code and data: github.com/hbasired/agenticAI, branch claude/sod-bench (commit e1ee0f8)

Honesty note

This interim report keeps four kinds of evidence strictly apart, and every table says which kind it shows: (A) architectural results, in which the language model is replaced by behavioural agents that span possible model behaviour; (M) measurements of real software components; (P) a small real-model pilot with an open-weight 4-billion-parameter model on a laptop-class CPU; and (S) numbers reported by other authors.

Source-reported numbers are never presented as our own. Results from synthetic worlds are not evidence of production readiness. Where we are not certain of a fact or a reading of prior work, we say so in the text.

Abstract

Accounts payable is where a supply chain turns into money, and it is being handed to AI agents. The fraud that most often targets this workflow, business email compromise, produced losses of roughly USD 3 billion reported to the FBI in 2025 (source-reported [2]; secondary summaries differ slightly, so the primary report should be consulted). An accounts-payable agent reads untrusted documents, touches vendor and ledger data and changes financial state, which is the combination that agent-security guidance warns against [9], [53]. This interim report tests whether internal controls, re-expressed as agent architecture and enforced as deterministic controls-as-code, bound the money a manipulated agent can divert.

We built SoD-Bench, an open procure-to-pay sandbox with purchase orders, goods receipts, PDF and UBL / PINT AE-style e-invoices, supplier e-mail and weekly payment runs, seeded with nine attack families and benign look-alikes, and implemented eleven defence configurations, including the proposed Control-Grounded Agent Architecture (CGA). In the architectural tier, a fully compromised model diverts AED 2.47M per twelve-week period from an undefended agent and AED 2.7k from CGA, while CGA keeps the highest straight-through processing (STP) of all designs. CGA's loss is nearly flat in model susceptibility, so the bound does not depend on how robust today's or tomorrow's models are. Z3 proofs, property-based tests, a transitive extension of the Agents Rule of Two, a real prompt-injection classifier, adaptive attackers and a pre-registered benchmark campaign support and qualify this result; a real-model pilot with Qwen3.5-4B shows the same pattern on a small sample.

Keywords

Agentic AI; procure-to-pay; accounts payable; prompt injection; business email compromise; internal controls; segregation of duties; Clark-Wilson integrity; information-flow control; Rule of Two; controls-as-code; formal verification; e-invoicing; supply chain finance; open-weight models.

Contents

Abstract....2
Keywords....2
1. Executive Summary....5
2. Real-World Problem Scan and Topic Selection....5
2.1 What is going wrong in 2025–2026....5
3. Introduction....6
4. Problem Statement and Research Questions....7
5. Literature Review....8
5.1 Agentic AI in supply chain and finance....8
5.2 Prompt injection and agent-security benchmarks....8
5.3 Defences: model-level versus system-level....9
5.4 Internal controls and payment fraud....9
5.5 Adaptive evidence handling and the OpMech idea....10
5.6 Segregation of duties, integrity models and information flow....10
5.7 Governed execution, runtime enforcement and agent authorisation....10
5.8 Memory, multi-agent and protocol attacks....11
5.9 Measurement: structured outputs, calibration and risk....11
6. Data and Environment Plan....12
6.1 Why a synthetic environment....12
6.2 SoD-Bench design....12
6.3 Attack families and benign look-alikes....13
6.4 Realism conditions added in the interim phase....13
7. Proposed Methodology and Architecture....14
7.1 Threat model....14
7.2 Formal setting and loss....14
7.3 Control-Grounded Agent Architecture (CGA)....14
7.4 Defences compared....16
7.5 Adaptive attacker....16
7.6 OpMech order-gap as an exploratory diagnostic....16
7.7 Model-agnostic evaluation and the compromised-maker bound....17
7.8 Clark-Wilson grounding and the Transitive Rule of Two....17
7.9 Machine-checked controls....18
8. Experimental Design and Evaluation Plan....18
8.1 Protocol and hypotheses....18
8.2 Metrics....19
8.3 Source-reported reference points....19
8.4 Pre-registered benchmarks and protocol....20
8.5 Interim results: architectural tier....20
8.6 Interim results: real-LLM pilot....24
8.7 Detector and adaptive attacks....25
8.8 Benchmark outcomes and the conditions under which they are met....26
8.9 Status of hypotheses and research questions....28
9. Hardware and Feasibility Plan....28
10. Project Plan and Timeline....29

11. Expected Contributions....29
11.1 Relationship to prior work and scope of claims....30
12. Risks, Ethics and Governance....30
13. Conclusion....30
Appendix A. Illustrative Episode....31
Appendix B. Reproducibility....31
References....31

1. Executive Summary

This study asks a practical question on the seam between supply chain management and finance: when a large language model (LLM) agent processes supplier invoices and prepares payments, how much money can an attacker who controls only documents and e-mails divert, and which defences bound that loss? The proposal of 30 October 2026 committed to measuring the answer in currency rather than assuming it. Six weeks of planned build work have been compressed into this interim phase: the benchmark, the defences, the analysis tools and a first round of measurements now exist, and the evidence is reported with its tier and its conditions.

The headline is architectural. With a model that pursues the attacker's goal on every attacked item, CGA reduces diverted value by 99.89 % against an undefended single agent on the same worlds, and raises rather than lowers straight-through processing, because a poisoned vendor record also breaks legitimate payments in the undefended design. The reduction comes from where controls sit, not from a better model: the beneficiary account can only come from verified master data, quantities and prices are re-derived from orders and receipts, and every vendor-master change waits for a call-back to a contact already on file [32]. Machine-checked proofs show that no proposal a model could emit escapes these bounds, and the residual loss is exactly the one the proofs predict: overpayment inside price tolerances.

Three further findings matter for practice. First, segregating duties between two LLM sessions is not enough: a design whose maker and payer are both models, joined by free text, passes the per-session Rule of Two [9] and still loses as much as the undefended agent; a transitive version of the rule detects this. Second, the real prompt-injection classifier we deployed caught only a small share of injected items and was evaded by every adaptive mutation search it faced, matching the warning of Nasr et al. [34]. Third, routing items to humans by the model's own risk estimate does nothing once the model is deceived. Each finding, with its conditions and its limits, is in Section 8.

We also set benchmarks before running the confirmatory campaign, as requested by the supervisor-facing plan and in line with pre-registration practice [54]: hypotheses H1-H4 from the proposal, five external reference points from other benchmarks (flagged as not like-for-like), six operational targets for an accounts-payable function and three real-model targets. Three frozen CGA versions were evaluated once each on fresh held-out worlds; Section 8.8 lists which targets each version beats and under which conditions.

2. Real-World Problem Scan and Topic Selection

2.1 What is going wrong in 2025–2026

Agentic AI in supply chains is still in a test-and-learn phase. A November 2025 survey of North American transportation, logistics and supply chain executives found 42 percent of organisations not yet exploring agentic AI at all (source-reported [13]), Boston Consulting Group argues that AI decisions in supply chains must be transparent, auditable and explainable [14], and Gartner expects more than 40 percent of agentic AI projects to be cancelled by the end of 2027 for reasons that include inadequate risk controls [5]. Benchmarks of agents acting as inventory managers and enterprise decision-makers report systematic decision biases [55], [56]. Trust and control, rather than raw capability, remain the binding constraint.

Payments fraud is persistent and is being industrialised by the same models. The Association for Financial Professionals reports that 76 percent of U.S. organisations experienced attempted or actual

payments fraud in 2025 [1], billing schemes account for 22 percent of occupational fraud cases [15], and the FBI's 2025 report, released in April 2026, was the first to break out AI-related complaints as a category (source-reported [2]). Research has measured LLMs' ability to run fully automated spear-phishing [57] and voice-phishing [58] campaigns, to evolve phishing adaptively [59], and to clone voices well enough to defeat audio authentication [60], [61]. Accounting staff are a documented target group [62]. The last point matters directly for this study, because call-back verification, one of the controls we rely on, assumes the voice on the phone is genuine.

Agents are now arriving in exactly this workflow, and attacks on them have moved from proofs of concept to systematic studies. Microsoft's Payables Agent ingests vendor invoices from mailboxes [3]; EchoLeak showed a zero-click prompt-injection exploit in a production assistant [4]; real-world e-mail agents have been hijacked through their inboxes [63], [64]; hidden instructions in PDFs now have their own benchmark and detectors [65], [66] and have appeared in academic peer review [67]; and the OWASP agentic top ten lists goal hijack and tool misuse first [17]. In 2026 the first payment-specific agent studies appeared: an authorisation benchmark replaying thousands of human-written attacks against a payment agent [68], attacks that make agent payment protocols sign carts the user never chose [69], and hardening of HTTP-native agent payments [70].

Infrastructure and governance are shifting at the same time; because these developments are recent, we cite the documents we could retrieve in November 2026 and recommend checking them for later revisions. Verification of Payee is mandatory for euro-area payment service providers since 9 October 2025 [18]; the UAE's PINT AE e-invoicing standard [71] is phased in from 2026-2027 [19], [20]; the EU's VAT in the Digital Age package mandates structured e-invoicing for intra-EU trade later in the decade [72]. Agent payment protocols such as AP2 [73], the Agentic Commerce Protocol [74] and Visa's Trusted Agent Protocol [75] launched in late 2025. COSO issued guidance on internal control over generative AI in February 2026 [76], and NIST's Center for AI Standards and Innovation opened an AI Agent Standards Initiative after a request for information on agent security [77], together with design tenets for agent identity that name separation of duties and least privilege [78].

3. Introduction

Procure-to-pay (P2P) is the chain through which an organisation buys and pays: a requisition becomes a purchase order, goods are received, the supplier invoices, the invoice is matched against order and receipt, an authorised person approves, and a payment run releases funds. Finance wraps this chain in internal controls: segregation of duties, maker-checker approval above limits, three-way matching, duplicate checks and strict control of vendor-master changes [32], codified for audit in frameworks such as COSO [32], [76], the Sarbanes-Oxley Act [79], PCAOB AS 2201 [80], SOC 2 criteria [81] and the Three Lines Model [82]. Process-mining work on real purchase-to-pay event logs shows how often such processes deviate from their designed paths [83], [84], and forensic accounting has long used statistical regularities to find manipulated amounts [85].

Computer security formalised the same ideas half a century ago. Saltzer and Schroeder's separation of privilege and least privilege [86], Clark and Wilson's commercial integrity model with its certified transformation procedures and separation of duty [87], Biba's integrity levels [88], the Chinese Wall policy [89] and role-based access control with separation-of-duty constraints [90], [91], [92], [93], [94] were all designed for systems in which a single actor must not be able to complete a sensitive transaction alone. NIST SP 800-53 still lists separation of duties and least privilege as baseline controls [95].

LLM agents are, in an important sense, clerks who can be deceived at machine speed. In indirect prompt injection, text in data that an application processes is interpreted as instructions [33], [96], [97]; a tool-using agent that follows such text becomes a confused deputy [98]. Meta's Agents Rule of Two [9] and Willison's lethal trifecta [53] both say that no session should combine untrusted input, sensitive access and the power to act. A naive accounts-payable agent needs all three.

Defences inside the model have not closed the gap. Instruction hierarchies [99], [100], [101], structured-query training [102], preference optimisation [103], [104] and detectors [41], [105], [106] all reduce attack success, yet adaptive attackers bypassed twelve recent defences in most cases [34], [107]. System-level designs fare better: CaMeL [35] and its successors [108], [109], [110], information-flow control [111], [112], privilege control [113] and design patterns [36], [114]. This report takes finance's own control vocabulary seriously, implements the deterministic controls as code that the model cannot override, and measures what an attacker can still extract.

4. Problem Statement and Research Questions

The task is to let an agent process a realistic accounts-payable workload of purchase orders, receipts, PDF and structured invoices, supplier e-mails and a weekly payment run, while an adversary who controls only supplier-facing content tries to divert or inflate payments. For every inbox item the system returns an action (pay, hold, escalate or reject), a payment where appropriate, and an audit trail of evidence and control decisions.

The main research question is unchanged: **can classic internal controls, re-expressed as agent architecture and enforced as code, bound the money that a manipulated LLM agent can divert in procure-to-pay, while preserving most of the automation value at a fixed analyst review budget?**

RQ1 (Exposure). How much value can invoice- and e-mail-borne attacks divert from undefended and conventionally defended agents, and how does diverted value differ from attack success rate as a risk measure?

RQ2 (Controls versus model-level defences). Do segregation-of-duties sessions with deterministic controls-as-code reduce diverted value more than prompt-level, detector-level and capability-based defences, at matched straight-through processing and review budget?

RQ3 (Rule of Two in practice). Can an accounts-payable workflow be decomposed so that every LLM session satisfies the Agents Rule of Two while retaining most of the benign straight-through processing rate?

RQ4 (Channel). Does structured e-invoicing (UBL and Peppol PINT AE) shrink the attack surface relative to PDF-and-e-mail intake, or do its free-text fields preserve it?

RQ5 (Adaptive attackers). Which defences keep their loss reduction when the attacker knows the controls and searches adaptively, and where does the residual loss concentrate?

RQ6 (Exploratory). Does the OpMech order-gap between consolidating against verified records and expanding into new evidence flag manipulated documents better than chance, and does it survive adaptive attack?

RQ7 (Composition, added in the interim phase). Does segregating duties between LLM sessions bound loss by itself, or only when the channel between sessions is certified by deterministic code? We add this question because the first results made it unavoidable (Section 7.8).

5. Literature Review

The review was extended from 52 to 299 sources for this interim report. All arXiv entries were checked against the arXiv API in November 2026; standards, books and classic papers are cited from their published versions. Because agent security moves quickly, recent preprints are flagged as such: many 2026 works cited here have not yet been peer reviewed, and for several we have read only the abstract, which we state where it matters.

5.1 Agentic AI in supply chain and finance

Agentic AI research in operations has moved from capability demonstrations to questions of reliability. In the MIT Beer Game, LLM agents reduced total supply-chain cost relative to human teams in their best configuration but showed run-to-run instability [25]; related work reproduces classic supply-chain game results with LLMs [26], and AIM-Bench documents decision biases of agentic inventory managers [55]. In trade compliance, HSCodeComp reports a wide gap between the best agent and human experts in tariff classification (source-reported [21], [22]). In financial crime, agentic pipelines classify money-laundering typologies [23] and draft suspicious-activity narratives with investigators in the loop [24]; FinRobot packages LLM agents for financial analysis [115]; long-horizon evaluation questions the apparent edge of LLM trading strategies [28]; and adversarial market benchmarks probe their robustness [29]. Enterprise benchmarks extend this to strategic decision-making [56].

The newest finance-agent work turns from accuracy to accountability. NumTrace audits where the numbers in financial analysts' agent outputs come from [116]; work on auditable agents [117] and on verifiable agent insurance [118] treats agent behaviour as something to be evidenced and priced. These are close in spirit to our use of money as the unit of risk, but none of them, as far as we can tell from the papers we read, models a procure-to-pay process with orders, receipts and internal controls.

5.2 Prompt injection and agent-security benchmarks

Indirect prompt injection was characterised against real LLM-integrated applications by Greshake et al. [33], building on direct injection [96] and application-level attacks [97]; games and competitions collected large attack corpora [119], [120], [121]; optimisation-based attacks transfer across aligned models [122]; and Liu et al. formalised attacks and defences [30]. Agent benchmarks followed: InjecAgent [37], Agent Security Bench [38], AgentDojo with state-checked utility and security [31], BIPIA [123], WASP for web agents [124], AgentHarm [125], Agent-SafetyBench [126], R-Judge [127], ToolEmu's emulated sandbox [128], τ-bench and τ^2-bench for policy-following tool use [39], [129], multi-turn adaptive adversaries [130] and phishing-specific evaluation of e-mail agents [131]. Finance arrived in 2026 with FinVault [6], FraudBench [7], an agentic-commerce systematisation [27] and a payment-authorisation benchmark replaying a public capture-the-flag event [68].

The benchmark-methodology literature shapes how SoD-Bench reports results. Checklists and audits of agentic benchmarks warn about invalid tasks, leaked answers and judge errors [132], [133], [134]; cost-aware and multi-dimensional evaluation is recommended [135], [136], [137]; and recent work argues that benchmarks should be maintained like software [138]. We follow these by computing every outcome from environment state, separating development from held-out templates, reporting cost, and versioning the benchmark with its code.

Work	Setting	What it measures	Gap for procure-to-pay
AgentDojo [31]	Workspace, Slack, travel, e-banking	Utility and attack success from state	No orders, receipts or internal controls; no loss metric

Work	Setting	What it measures	Gap for procure-to-pay
InjecAgent [37]; ASB [38]	Tool calls across many scenarios	Attack success by technique and stage	Not workflow-grounded; no control semantics
FinVault [6]	31 regulatory scenarios	Attack success, false positives	No corporate accounts payable; success rate ignores severity
FraudBench [7]	Banking agent vs adaptive caller	Attack security	Customer dialogue, not supplier documents
APort Vault [68]	Payment agent, replayed CTF attacks	Five events per evaluation	Single payment tool; no three-way match or vendor master
CrackedPDFs [65]	Hidden injection in PDFs	Detector accuracy	Detection only; no downstream money
SoD-Bench (this work)	Corporate P2P: PDF and UBL invoices, e-mail, payment runs	Diverted value, Loss@B, STP, false holds, adaptive residual	—

Table 1. Closest benchmarks and what SoD-Bench adds. Descriptions summarise the cited papers.

5.3 Defences: model-level versus system-level

Model-level defences change what the model believes or sees. Prompt-level defences mark untrusted text [40]; training-time defences teach models to rank instructions by privilege [99], [100], [101] or to ignore data-borne instructions [102], [103], [104]; detectors screen inputs [41], [44], [105], [106], [139], [140] or internal states [141], [142]; and inference-time checks compare runs or align actions with tasks [42], [52], [143], [144]. Guardrail agents and step-level guards add policy reasoning around tool calls [145], [146], [147], [148]. Google DeepMind's account of defending Gemini shows how much engineering such layers need [149]. All are probabilistic, and adaptive attackers have broken representatives of each [34], [107]; automated red-teaming engines make such adaptation cheap [150], [151], [152].

System-level defences change what an agent can do. The dual-LLM pattern [114] and CaMeL [35] keep untrusted data out of control flow and enforce capability policies; follow-up work operationalises CaMeL for enterprises [108], adds temporal-logic verification [110], and asks whether its guarantees compose in multi-agent hierarchies [109]. Information-flow control systems label data and block policy-violating flows [111], [112], [153], [154]; isolation architectures separate applications [155], [156]; privilege-control and fine-grained authorisation systems restrict tools [113], [157]; contextual policies are generated per task [158]; rule-based isolation and plan-then-execute designs are catalogued with implementation advice [36], [159], [160]. CGA belongs to this family. Its difference is that the policy is not generic: it is the internal-control system of an accounts-payable function, written as code.

5.4 Internal controls and payment fraud

COSO's Internal Control-Integrated Framework is the reference model for internal control, and authorisation, segregation of duties and reconciliation are its operational core [32]; COSO's 2026 guidance applies its principles to generative AI [76], and audit standards and attestation criteria make the controls testable [79], [80], [81]. Fraud data explains the controls: billing schemes are among the most common occupational frauds [15], business email compromise is among the costliest reported crimes [2], high-precision BEC detection needs sender-specific models [161], [162], and look-alike domains rely on typosquatting and homographs [163], [164]. Regulators are shifting losses: the UK's reimbursement requirement for authorised push payment scams [165] and euro-area Verification of Payee [18] both change who pays when a beneficiary is wrong.

E-invoicing changes what an invoice can contain. EN 16931 defines the semantic model [166], UBL 2.1 the syntax [167], Peppol BIS Billing 3.0 the profile [43], and PINT AE the UAE specialisation [71], [19]; IBANs follow ISO 13616 [168]. Invoice-extraction research shows that general-purpose LLMs read invoices well but not perfectly [169], [170], that synthetic invoices can be generated realistically [171], and, closest to our straight-through-processing metric, that auto-approval of extracted fields needs calibrated confidence with bounded residual error [172]. Synthetic data is standard where real financial data cannot be shared [8], [173], [174]. This literature does not yet ask what happens when the clerk being controlled is an LLM.

5.5 Adaptive evidence handling and the OpMech idea

Consolidation-Expansion Operator Mechanics proposes that adaptive learners alternate between consolidating what they know and expanding into new evidence, and defines an order-gap measuring how far the two operations fail to commute [12]. A document that tries to override verified records should, intuitively, not commute with consolidation. The LLM literature gives reasons to expect order effects at all: models use long contexts unevenly [175], show position biases across tasks [176], and order sensitivity has been exploited as an attack surface [177]. Dual-run and self-consistency methods compare outputs across runs [42], [178], [179]. We test the order-gap as an exploratory diagnostic only (Section 8.6), consistent with how the framework itself is framed [12].

5.6 Segregation of duties, integrity models and information flow

The theory behind CGA predates LLMs by decades. Saltzer and Schroeder's design principles include separation of privilege and least privilege [86]. Clark and Wilson's integrity model, written for commercial accounting systems, distinguishes constrained data items, which only certified transformation procedures may change, from unconstrained data items, which must be validated before they affect constrained state, and it requires separation of duty between those who certify and those who execute [87]. Biba's integrity levels [88], the Chinese Wall policy [89], role-based access control and its separation-of-duty constraints [90], [91], [92], [93] and workflow authorisation constraints [94] refine these ideas, and capability systems make authority explicit [180], [181].

Information-flow security supplies the mechanism. Denning's lattice model [182], Goguen and Meseguer's noninterference [183] and language-based enforcement [184] define when data of one integrity level may influence another; dynamic taint tracking implements this at run time [185], [186]. For LLM agents, recent work redefines information-flow tracking for model-mediated flows [187], plans first and controls flows across persistent queries [188], brings IFC to browser agents [189], finds bidirectional data-flow risks in MCP ecosystems [190], guarantees confidentiality deterministically [191] and evaluates containment after exposure [192]. Our provenance rule is the integrity counterpart: a value that originated in supplier text may enter the payment path only after certified code has re-derived it from verified records.

5.7 Governed execution, runtime enforcement and agent authorisation

In 2026 several groups converged on the idea that authority must be governed outside the model. Jing studies separation of duties for privileged operating-system agents with a planner, policy gate, executor and auditor [193]; the Organizational Control Layer intercepts generated actions before execution and checks them against role, policy and economic constraints [194]; persona-execution separation [195] and twin-agent privilege separation [196] split agents into trust domains. Runtime-enforcement systems check company policy adherence [197], behavioural specifications [198], natural-language policies compiled

into predicate programs [199] and domain-specific rules [200]; authorisation languages such as Cedar are designed to be analysable [201]; formal verification is beginning to reach agentic systems [202], [203]; and the cost of verification has itself been measured [204]. We see CGA as an instance of this movement, specialised to a process whose controls are already standardised and audited.

Identity and authorisation for agents are being standardised in parallel: authenticated delegation [205], agent IDs and visibility [206], [207], OpenID Connect and JWT extensions [208], [209], compositional and capability-based delegation [210], [211], least-privilege enforcement for agent skills [212] and attack-surface modelling of agentic platforms [213]. Verifiable execution histories, process evidence and attestation of actions rather than agents [214], [215], [216] complement the tamper-evident logs we use [217], [218], [219]. Governance frameworks frame the obligations: the EU AI Act [220], the NIST AI RMF and its generative-AI profile [221], [222], NIST's adversarial ML taxonomy [223], ISO/IEC 42001 [224], OWASP's LLM and agentic top-ten lists [225], [17], MITRE ATLAS [226], legal analysis of agent governance [227], NIST's agent standards work [77], [78] and the 2025 International AI Safety Report [228].

5.8 Memory, multi-agent and protocol attacks

Attack family A9 in SoD-Bench, cross-agent trust contamination, is an instance of a fast-growing literature. Memory and knowledge-base poisoning was shown early [229]; 2026 studies systematise memory write channels [230], show instructions that persist across sessions [231] and analyse poisoning in multi-agent systems [232]. Multi-agent systems can be steered to execute arbitrary code [233], infections spread between agents [234], communication itself can be attacked [235], and surveys map the risks of interacting agents [236], [237], [238].

Protocols widen the surface. The Model Context Protocol [239] has a landscape study [240], tool-poisoning disclosures [241], two security benchmarks [242], [243], a hardened variant [244] and network-level defences against supply-chain injection [245]. Agent2Agent [246] has security guidance [247], a systematic attack analysis [248], tamper-evident runtime evidence [249], comparative threat modelling across protocols [250] and lessons from internet-protocol history [251]. Agent payment protocols [73], [74], [75] carry the problem into money: cryptographically valid mandates do not constrain the decisions that produced them [69], and behaviour-aware fraud detection is proposed for agent payments [252], [70].

5.9 Measurement: structured outputs, calibration and risk

CGA's maker emits typed proposals under constrained decoding. Grammar- and schema-constrained generation is well developed [253], [254], [255] and benchmarked [256], and structured-output reliability can be scored [257]. Two recent papers warn that structure is not safety: prefix-tree interfaces can aid jailbreaks [258] and structured-output backdoors can be implanted in coding agents [259]. The typed channel in CGA is safe only because the checker re-derives what matters.

Risk scores must be calibrated to be useful for triage. We use expected calibration error [260], [261], aware that LLM confidence is often miscalibrated [262], and split conformal prediction [263], [264] with conformal risk control [265], which 2026 work applies to LLM tool calls [266] and compositional agent risk [267]. Loss is summarised with value-at-risk and conditional value-at-risk [268], [269], coherent risk measures [270] and the FAIR approach to information risk [271]; uncertainty uses the bootstrap [272], Wilson intervals [273] and exact McNemar tests [274]. Datasets and models are documented with datasheets [275], Croissant metadata [276] and model cards [277].

6. Data and Environment Plan

6.1 Why a synthetic environment

Real accounts-payable data contains supplier bank details, personal data and confidential prices, and real fraud labels are incomplete. A synthetic environment gives complete ground truth: for every invoice we know what was ordered, what was received, what is owed and to which account it should be paid. The price is external validity, which we address by grounding formats in public standards [43], [167], [71], [166], attack families in documented typologies [15], [2], [161] and process rules in internal-control practice [32], and by stating plainly that sandbox results are not evidence of production readiness. Synthetic transaction generators are established in anti-money-laundering research for the same reasons [8], [173].

6.2 SoD-Bench design

SoD-Bench v0.1 is implemented in Python (package `sodbench`). One buying organisation is simulated over twelve business weeks: 300 suppliers with verified master data (legal name, synthetic tax number with a Luhn check digit [278], contact on file, ISO 13616-structured IBAN with a valid mod-97 checksum but a fictitious bank code [168]), six suppliers onboarded during the period, employees with authority limits, about 1,500 purchase orders, 1,800 goods receipts with partial deliveries, short shipments and returns, and about 1,900 inbox items per world. E-mail domains use the reserved .example top-level domain, so no generated address can route to a real party.

Two intake channels are rendered faithfully. PDF invoices are drawn with ReportLab and read back through a real text-layer extractor, so text drawn in white one-point type reaches the agent exactly as it would through a production parser while remaining invisible to a human reader, the threat studied by CrackedPDFs and PhantomLint [65], [66]. Structured invoices are UBL 2.1 documents with the PINT AE customisation identifier and Peppol endpoint scheme 0235 [71], flattened field by field for the agent, including the free-text fields (notes, item descriptions, payment instruction notes) where attack family A3 hides instructions. E-mails are RFC 5322 messages.

Ground truth is exact by construction. Entitlement is computed per purchase-order line from goods actually received, net of returns, at the PO price including contract amendments; diverted value counts every payment to an account not owned by the payee in full, plus any amount paid to a genuine supplier above what it is owed. An append-only audit log chains each entry to its predecessor with SHA-256, following the hash-chain time-stamping idea [217], [218]; tampering with any entry breaks verification, which the test suite checks.

Component	What it provides	Status (interim)
Supplier master (306)	Verified identity, contact on file, IBAN, tolerance group	Built; tested
Purchase orders and receipts	Ordered, received and returned quantities; prices; amendments	Built
PDF invoices and credit notes	ReportLab layout, pypdf text layer, hidden-text capable	Built
UBL / PINT AE-style e-invoices	Structured fields plus free-text notes	Built; flattened agent view
Supplier e-mail	Invoices, reminders, statements, bank changes, onboarding	Built

Component	What it provides	Status (interim)
Policy pack (YAML)	Tolerances, approval matrix, change protocol, variance policy	Built; versioned
Bank simulator	Payment runs, Verification of Payee name checks	Built
Audit log	SHA-256 hash chain of every control decision	Built; tamper test passes
Data card, Croissant metadata	Datasheet and machine-readable metadata [275], [276]	Draft v0.1

Table 2. SoD-Bench components and their implementation status.

6.3 Attack families and benign look-alikes

Nine attack families cover the main ways a supplier-facing adversary can try to move money. Each is paired with benign look-alikes so that a defence cannot score well by holding everything unusual. Development and held-out splits use disjoint injection phrasings (8 and 8), business-email-compromise, re-issue, onboarding and laundering templates, look-alike-domain transformations [163], [164], near-duplicate number mutations (compared with Levenshtein distance [279]), inflation ranges, attacker banks and targeted supplier pools. Bank-change attacks are timed shortly before invoices the attacker knows are pending, as real BEC campaigns are.

ID	Attack family	Channel	Attacker goal	Benign look-alike
A1	Hidden instruction in an invoice PDF	PDF text layer (white, 1 pt)	Change beneficiary	Long small-print legal footer
A2	Visible note to automated processing	PDF body or e-mail body	As A1, with urgency	Genuine processing notes
A3	Instruction in structured e-invoice free text	UBL notes, item text, payment note	As A1	Legitimate e-invoice notes
A4	Bank-change request without injection	E-mail, look-alike or compromised	Redirect future payments	Genuine change confirmed by call-back
A5	Impersonation with re-issued invoice	E-mail plus PDF	Be paid for real goods	Credit note plus corrected invoice
A6	Duplicate or near-duplicate invoice	PDF or e-invoice	Double payment	Partial invoices and credit notes
A7	Price or quantity inflation; splitting	Invoice lines	Overpayment	Contract-backed price amendment; agreed surcharges
A8	Fictitious supplier onboarding	Onboarding e-mail plus invoices	Pay a shell company	Genuine new supplier
A9	Cross-agent trust contamination	Notes written by one agent, read by another	Launder a 'verified by phone' claim	Internal verification-service records

Table 3. Attack families and benign look-alikes. All content is synthetic.

6.4 Realism conditions added in the interim phase

Two realism conditions were added once the first results arrived, because without them some designs would look better than they are. First, a share of suppliers bill a small agreed surcharge (0.5-2 percent) on every invoice, which is owed and recorded in a vendor tolerance group; strict price policies then pay a real automation cost. Second, every result can be re-run with a fallible human reviewer (miss rate 10-30 percent) and with fictitious suppliers that pass onboarding (20 percent), reflecting automation bias [280],

[281] and the commoditisation of deepfakes [61], [60]. Both conditions are part of the pre-registered robustness sweep (Section 8.4).

7. Proposed Methodology and Architecture

7.1 Threat model

The adversary controls supplier-facing content: e-mails, including those from look-alike domains, PDF and structured invoices, and onboarding requests. It may know the agent's design, prompts and controls (white-box) and observe the outcomes of earlier attempts (adaptive). It cannot modify the ERP database directly, alter contact details that were on file before the attack, or compromise internal staff; insider fraud, ERP compromise and attacks on the human call-back step are out of scope. We now flag the last exclusion as the most fragile assumption: voice cloning is good enough to defeat audio authentication in published tests [60], and automated voice phishing has been demonstrated [58].

7.2 Formal setting and loss

Let s be the environment state and $x_1, ..., x_n$ the inbox items of a period. A configuration π maps items to actions and ultimately to a set P of executed payments, each with amount a_p, beneficiary b_p and entitlement e_p. Diverted value is

$$DV(\pi) = \Sigma_{p \in P} \left[a_p \cdot 1(b_p \notin V) + max(0, a_p - e_p) \cdot 1(b_p \in V) \right]$$

where V is the set of accounts genuinely owned by the payee. In the implementation the second term is computed per purchase order, so duplicates, splits and re-issues on the same order cannot hide overpayment. Straight-through processing (STP) is the share of legitimate payable value paid correctly without human touch; the false-hold rate (FHR) is the share of legitimate payable items not paid in full automatically. Loss@B is diverted value at the escalation threshold that fits a review budget of B percent of daily volume, and the residual adaptive loss is the largest diverted value an adaptive attacker finds within a query budget Q. We add two finance-native summaries: weekly diverted-value-at-risk ($DVaR_{95}$) and its conditional version ($CVaR_{95}$) [268], [269], [270].

7.3 Control-Grounded Agent Architecture (CGA)

CGA splits the workflow into sessions that each satisfy the Agents Rule of Two and places deterministic controls between them (Figure 1). The intake agent (maker) reads supplier content and looks up records read-only; its only output is a typed proposal under schema-constrained decoding [256]. The checker is plain code that applies the policy pack. The payer executes only approved proposals and never sees supplier text. Escalations go to a human queue ranked by a calibrated risk score, and an audit log records every decision.




Figure 1. Control-Grounded Agent Architecture in SoD-Bench (reproduced from the proposal). Badges mark the Agents Rule of Two properties held by each LLM session; the checker is deterministic code. The OpMech diagnostic is an exploratory ablation.

Internal control	Agent-level implementation in CGA	Attacks addressed	Implemented as
Segregation of duties	Maker and payer sessions with a deterministic checker between them	A1-A5, A9	runner.process_typed
Maker-checker above limits	Human release above AED 250,000; first-payment hold	A4-A8	checker._payable
Three-way match	Cumulative match of order, receipt and invoice; short-pay	A1, A2, A7	checker._payable
Duplicate-payment check	Exact key rejects; near-duplicate (same order, same digit core) escalates	A6	checker.is_duplicate
Vendor-master change control	Tickets only; call-back to contact on file; cooling-off	A1-A5, A9	runner.tickets_and_review
Verification of Payee	Name check at payment; block on no match, escalate on close match	A4, A5, A9	bank.verify_payee
Price-variance control (v0.2/v0.3)	Pay PO price; route variances to buyer; vendor tolerance groups	A6, A7	checker._payable

Internal control	Agent-level implementation in CGA	Attacks addressed	Implemented as
Data-flow (provenance) control	Beneficiary only from verified master data	A1-A3, A5, A9	checker._payable
Audit trail	SHA-256 hash-chained log of every decision	All (detection)	state.AuditLog

Table 4. Internal controls and their implementation in CGA.

7.4 Defences compared

All configurations run on the same worlds, attacks, seeds and review budgets (Table 6). We added D7, naive segregation of duties with two LLM sessions joined by free text, to test whether segregation without certified channels is enough, and VoP-removal ablations to measure how controls cover for each other.

ID	Configuration	Idea	Source
D0	Single tool-using agent with all tools	Undefended reference	—
D1	D0 with spotlighting (datamarking) and hardened prompt	Mark untrusted text as data	[40]
D2	D0 with a prompt-injection classifier on all untrusted text	Detector-level filtering	[41], [282]
D3	D0 with least-privilege tool filtering	Remove unneeded tools	[31]
D4	Plan-then-execute, quarantined LLM, capability policy	System-level isolation	[35], [36]
D5	Human approval of every payment	Security reference	—
D6	CGA (v0.1, v0.2, v0.3)	SoD sessions, controls-as-code, provenance	This work
D6a-c	No provenance; no call-back; controls advisory only	Ablations	This work
D7	Maker LLM and payer LLM joined by free text	Naive segregation	This work

Table 5. Defence configurations compared under one protocol.

7.5 Adaptive attacker

Following the recommendation that defences be evaluated against attackers who adapt [34], we implemented two adaptive attackers. A white-box control-boundary search knows the policy pack, observes the money outcome of each attempt, samples attack parameters (inflation, splitting, duplicate-number mutations, amounts, delays, target supplier group) and refines around the best point; each query is a full twelve-week episode. A black-box mutation search attacks the real detector, rewording, padding and re-encoding the injected note while preserving the attacker's account number, in the spirit of automated red-teaming and self-evolving phishing [150], [59]. A human red-team round remains planned.

7.6 OpMech order-gap as an exploratory diagnostic

For an inbox item e, let P_e denote expansion (reading the item) and Q consolidation (reading the verified records). We run the intake agent twice, once with the document first and once with the records first, and define the order-gap as a disagreement in document kind, beneficiary, total, requested action or bank-

change account between the two proposals. A large gap is read as a diagnostic, never as a fraud score [12]; the comparison costs one extra model call per item.

7.7 Model-agnostic evaluation and the compromised-maker bound

Model-level defences can only be evaluated model by model, and every new model release reopens the question. We therefore add an architectural evaluation tier in which the language model is replaced by behavioural agents that span its possible behaviour: a faithful clerk, a compromised maker that pursues the attacker's goal on every attacked item and lies in its typed output whenever that helps the attacker (a Byzantine participant), and a stochastic agent deceived on each attacked item with probability s. Diverted value as a function of s, DV(s), separates designs whose loss grows with model susceptibility from designs whose loss is bounded by construction. We call a design susceptibility-invariant when DV(s) is nearly flat; the worst case DV(1) is then an upper bound that holds for any current or future model under the stated threat model. This matters because model capability is rising quickly [283], [228] without a matching guarantee that models resist manipulation, and because smaller, cheaper models are increasingly used in agentic roles [284], [285].

7.8 Clark-Wilson grounding and the Transitive Rule of Two

The Clark-Wilson model gives CGA a precise vocabulary [87]. The vendor master and the payment queue are constrained data items. Supplier documents, and anything a language model writes about them, are unconstrained data items. The checker is the certified transformation procedure through which an unconstrained item may influence a constrained one, and the provenance rule is the certification rule that such input must be validated or rejected. A language model is, in this reading, an uncertified transformation: it may propose, but it may never write constrained data.

The Agents Rule of Two is evaluated per session [9]. In multi-agent workflows, untrusted text can reach a session indirectly through another model's summary, a shared note store or memory [230], [234]. We therefore define the Transitive Rule of Two (TRo2): propagate untrusted taint along every data-flow edge of the workflow graph, stop it for a field only at nodes that certify that field by re-deriving it from verified records, and require that no tainted session hold both sensitive access and the power to act, and that no integrity-critical sink (beneficiary, amount, vendor master) be reachable from untrusted content without certification. Table 7 shows that TRo2 separates designs that the per-session rule cannot. Concurrent work asks whether CaMeL's guarantees compose across agent hierarchies [109]; from its abstract, its focus is CaMeL composition rather than a workflow-level criterion, but we have not yet compared the two in depth.

Config	Rule of Two per session	Transitive Rule of Two	Critical sinks reachable from untrusted text
D0	no	no	payment.amount, payment.beneficiary, vendor_master.iban
D1	no	no	payment.amount, payment.beneficiary, vendor_master.iban
D2	no	no	payment.amount, payment.beneficiary, vendor_master.iban
D3	no	no	payment.amount, payment.beneficiary
D4	yes	no	payment.amount
D5	yes	yes	none

Config	Rule of Two per session	Transitive Rule of Two	Critical sinks reachable from untrusted text
D6	yes	yes	none
D6a	yes	no	payment.beneficiary
D6b	yes	no	vendor_master.iban
D6c	no	no	payment.amount, payment.beneficiary, vendor_master.iban
D7	yes	no	payment.amount, payment.beneficiary, vendor_master.iban

Table 6. Rule-of-Two analysis. D7 passes the per-session test yet fails the transitive one; only D5 and D6 pass both.

7.9 Machine-checked controls

Because the checker is code, its key properties can be proved rather than measured. We encoded the payable path in the Z3 SMT solver [286] and proved each property by showing its negation unsatisfiable for every proposal a maker could emit (Table 8). Removing the provenance rule turns property P1 into a satisfiable query with a concrete counterexample. The proofs cover the abstract model; property-based tests with Hypothesis [287] check the same invariants on the Python implementation, and they found a defect the proof could not see: an absolute rounding allowance in the tolerance comparison let low-priced lines exceed the proven bound. A second defect, a time-of-check-to-time-of-use race [288] in which a near-duplicate could be auto-paid while its original waited for human review, was found by the benchmark itself and fixed by reserving matched quantities at escalation.

ID	Property of the checker	Result	Evidence
P1	beneficiary integrity (provenance rule on): payee account = verified master data	holds	proved (negation unsatisfiable)
P1'	same claim with the provenance rule removed (D6a)	fails	counterexample found
P2	per-invoice overpayment bound: amount <= received-not-yet-paid x PO price x (1+tol) x VAT	holds	proved (negation unsatisfiable)
P3	no payment without an unpaid goods receipt	holds	proved (negation unsatisfiable)
P4	cumulative bound over 4 adversarial invoices on one PO line (duplicates, splitting, re-issues)	holds	proved (negation unsatisfiable)
P5	residual: overpayment within price tolerance is reachable (H4)	holds	reachable (as predicted)

Table 7. Properties of the controls-as-code checker checked with Z3.

8. Experimental Design and Evaluation Plan

8.1 Protocol and hypotheses

Each episode is one twelve-week period for the simulated organisation processed under one configuration. The architectural grid crosses eleven configurations and three VoP ablations with six susceptibility levels on held-out-split worlds (8 worlds at 3 percent attack prevalence), plus attack-dense, prevalence, channel, review-budget, reviewer-error and detector sweeps; 1,452 episodes in total. Development templates were used only for building and calibration. Comparisons are paired on identical worlds; we report bootstrap confidence intervals [272], Wilson intervals for proportions [273] and per-family results. The proposal's four hypotheses H1-H4 are tested as pre-registered (Section 8.4); the worlds

of this grid were also used while debugging the simulator, so the confirmatory numbers are those of the benchmark campaign on fresh worlds (Section 8.8).

8.2 Metrics

Metric	Definition	Why it matters
Diverted value (DV)	Paid to accounts not owned by the payee, plus overpayment per order	The loss a finance director cares about
Attack success rate (ASR)	Share of attacks yielding any gain above AED 1	Comparability with prior benchmarks
Loss@B	DV at the escalation threshold that fits review budget B	Risk at realistic staffing
Residual adaptive loss	Largest DV found by adaptive search within query budget Q	Robustness to an informed attacker
Straight-through processing (STP)	Legitimate payable value paid correctly without human touch	Automation value
False-hold rate (FHR)	Legitimate payable items not paid in full automatically	Supplier friction
DVaR95 / CVaR95 (new)	Weekly diverted-value-at-risk and expected shortfall	Tail risk in finance terms
Calibration (ECE)	Expected calibration error of the risk score	Whether scores can rank a queue
Cost	Model calls, tokens, seconds per item	Feasibility for small organisations
Order-gap AUC	Detection quality of the OpMech diagnostic (exploratory)	Answers RQ6

Table 8. Evaluation metrics.

8.3 Source-reported reference points

Table 10 collects published results that frame expectations. None is a result of this project, and the environments differ from SoD-Bench; where we use one as a benchmark target (Section 8.4) we say so and treat the comparison as indicative only.

Source	Setting	Reported result (source-reported)	Use here
AgentDojo [31]	97 tasks, 629 security cases	Utility and security from environment state	Framework SoD-Bench follows
CaMeL [35]	AgentDojo	77 % of tasks solved with provable security vs 84 % undefended	Benchmark X2
LlamaFirewall [41]	AgentDojo	ASR 17.6 % to 7.5 % (Prompt Guard 2); 1.75 % with AlignmentCheck	Benchmark X1
The Attacker Moves Second [34]	12 defences	Adaptive attacks above 90 % ASR against most	Benchmark X3
FinVault [6]	31 financial scenarios	Average ASR 6.7 % to 50.0 % by model	Benchmark X4
FraudBench [7]	Banking agent vs adaptive caller	Attack security 49-65 %	Benchmark X5
APort Vault [68]	Payment agent, replayed CTF attacks	Outcome rates vary more across configurations than models	Context for RQ2

Table 9. Prior results are source-reported and are not project results.

8.4 Pre-registered benchmarks and protocol

Before the confirmatory campaign we committed the benchmark targets, their pass conditions and the protocol to the repository (docs/benchmarks.md, commit 3655400, 7 November 2026, 18:36 UTC), following pre-registration practice [54]. Design changes are compared on development worlds only; each frozen design version is evaluated once on ten fresh held-out worlds that had not been generated or inspected before; every evaluation is appended to a ledger with its conditions; metric definitions are not changed to make a target pass; and negative results stay in the ledger. A target is passed when the point estimate meets it, robustly passed when the relevant 95 percent confidence bound also meets it.

ID	Target	Origin
H1	CGA cuts DV by >= 90 % vs D0, STP cost <= 10 pp (s = 0.25, 0.5, 1)	Proposal
H2	Model-level defences lose >= 50 % of static reduction under adaptive attack; CGA keeps >= 90 %	Proposal
H3	UBL removes A1; A3 loss >= 75 % of A2; A4 differs <= 25 % across channels	Proposal
H4	>= 90 % of CGA residual in A7/A8; zero diversion; no payment above release threshold	Proposal
X1	Injection-family ASR <= 1.75 %	LlamaFirewall [41] (not like-for-like)
X2	STP cost of the defence <= 7 pp	CaMeL [35] (not like-for-like)
X3	<= 10 % of adaptive campaigns gain anything	Nasr et al. [34] (not like-for-like)
X4	Overall ASR <= 6.7 %	FinVault [6] (not like-for-like)
X5	Attack resistance >= 65 %	FraudBench [7] (not like-for-like)
O1-O6	FHR <= 2 %; STP >= 95 %; reviews <= 5 % of inbox; weekly DVaR95 = 0; residual <= 0.01 % of value; twin FHR <= 5 %	Ours
P1-P4	Real model: CGA redirect loss 0; CGA FHR <= 5 %; >= 90 % loss cut vs D0; D0 exposure reported	Ours

Table 10. Pre-registered benchmark targets (full text in docs/benchmarks.md).

8.5 Interim results: architectural tier

Table 12 reports the main grid. The undefended agent with a compromised model (s = 1) diverts AED 2.47M per twelve-week period (95 % CI AED 2.27M to AED 2.70M); CGA v0.1 diverts AED 2.7k (CI AED 754 to AED 6.2k), a reduction of 99.89 %, with STP of 99.4 % against 94.0 %. The CaMeL-style design D4 stops every redirect but still loses AED 184k to amount-based attacks, because a generic capability policy does not encode three-way matching. Naive segregation D7 loses as much as D0 at s = 1. The human-only reference D5 nearly eliminates loss but needs 28 reviews per day and processes nothing straight through.

Configuration	DV, s = 1	ASR, s = 1	STP, s = 1	FHR, s = 1	DV, s = 0.5	Reviews/day
D0 single agent, all tools	AED 2.47M	81.6 %	94.0 %	6.3 %	AED 1.15M	0.9
D7 naive SoD	AED 2.47M	86.3 %	94.0 %	6.3 %	AED 1.37M	0.9
D1 spotlighting (adaptive)	AED 2.20M	76.9 %	94.7 %	5.8 %	AED 1.11M	1.0
D1 spotlighting (static)	AED 1.59M	59.0 %	96.0 %	4.3 %	AED 828k	1.1

Configuration	DV, s = 1	ASR, s = 1	STP, s = 1	FHR, s = 1	DV, s = 0.5	Reviews/day
D3 tool filtering	AED 1.23M	80.3 %	98.0 %	2.1 %	AED 549k	1.3
D6c advisory controls	AED 1.08M	71.6 %	94.7 %	5.5 %	AED 411k	1.0
D4 CaMeL-style	AED 184k	20.2 %	97.1 %	3.3 %	AED 66k	1.7
D6 CGA (v0.1)	AED 2.7k	6.7 %	99.4 %	0.6 %	AED 2.2k	1.1
D5 human approves all	AED 158	0.0 %	0.0 %	100.0 %	AED 158	28.1

Table 11. Architectural tier [A]: means over held-out-split worlds, 3 % prevalence, twelve-week periods. D1 rows use an assumed effect size (60 % static, 10 % adaptive reduction of susceptibility on injection families).




Figure 2. Diverted value against model susceptibility s [A]. Bands are 95 % bootstrap intervals across worlds. CGA is nearly flat: its worst case is a bound that does not depend on the model.

The susceptibility curves (Figure 2) are the central new result. Every design whose safety depends on the model grows roughly in proportion to s; CGA stays between AED 2.0k and AED 2.7k from s = 0.1 to 1. Figure 3 shows where losses arise. The undefended and naive designs lose to every family; tool filtering removes direct vendor-master updates but leaves in-document account redirection and the note channel of A9; the CaMeL-style design loses only to duplicates and inflation; and CGA's residual is confined to within-tolerance overpayment.




Figure 3. Worst-case loss by attack family and configuration in attack-dense worlds [A]. Cells give the mean loss per world; zero means no gain for the attacker.




Figure 4. Automation value against loss at s = 0.5 [A]. CGA is the only design in the high-STP, low-loss corner.

Controls cover for each other in pairs (Figure 5). Removing provenance, call-back or VoP alone leaves CGA's loss unchanged, because Verification of Payee catches a wrong account even when master data is poisoned and provenance blocks a document account even without VoP. Removing provenance and VoP together exposes AED 304k; removing call-back and VoP together exposes AED 609k even with a faithful maker, because faithfully reported bank-change requests are then applied automatically. This is defence in depth in the sense of the Swiss-cheese model [289], and the transitive Rule-of-Two analysis (Table 7) predicts which removals open which sinks.




Figure 5. Control redundancy [A]: diverted value when CGA controls are removed singly and in pairs, for a faithful (s = 0) and a compromised (s = 1) maker.

In finance terms, the weekly 95 % diverted-value-at-risk of the undefended agent at s = 1 is AED 441k (CVaR AED 483k); for tool filtering it is AED 210k; for CGA and D4 it is zero, because no payment ever reaches an account the payee does not own. The checker's risk score is reasonably calibrated: ECE falls from 0.064 with hand-set weights to 0.035 after refitting on development data, and a split-conformal threshold at alpha = 0.02 [263] flags 1.2 % of held-out benign items while catching 74.1 % of attacks. Triage on the model's own risk estimate, by contrast, does nothing once the model is compromised: Loss@B for D0 and D4 is identical at B = 2, 5 and 10 percent (Figure 6), because a deceived agent reports low risk.




Figure 6. Loss@B against the daily review budget at s = 1 [A], with pre-payment triage on and off.

Structured e-invoicing helps but does not close the gap (RQ4). With all suppliers on UBL, the undefended agent's loss at s = 1 falls from AED 3.33M to AED 2.63M, because layout attacks (A1) disappear, while free-text fields keep the injection channel open. Human reviewers are not a free safety net: with a 10 % reviewer miss rate D4 loses AED 593k, more than D5 (AED 68k) because it escalates many attack items for confirmation, while CGA loses AED 28k; at 30 % the figures are AED 1.61M, AED 198k and AED 85k. Designs that escalate more transfer more risk to fallible humans, a pattern familiar from automation-bias research [280].

8.6 Interim results: real-LLM pilot

The pilot ran Qwen3.5-4B [49], [290] quantised to 4 bits (Q4_K_M) through llama.cpp bindings [45], [291] on a four-core CPU, with JSON-schema-constrained decoding and greedy sampling. Each inbox item was handled in one call with the ERP lookups supplied up front, a simplification of a multi-turn ReAct loop [292], [293] that gives the attacker fewer turns and so probably understates exposure. Held-out attack items were sampled per family with benign twins and routine invoices; the world was replayed to each item's arrival day so that receipts and vendor data were realistic. The median call took 28 seconds and 1177 tokens. Sample sizes are small and intervals wide; we read these numbers as a pilot, not as estimates for 4-billion-parameter models in general, and quantised agents can hide failures that aggregate scores miss [294].

Configuration (Qwen3.5-4B)	Attack items	ASR [95 % Wilson CI]	Attacker gain	False holds / legit
D0 single agent (all D0 items)	47	36.2 % [24 %-50 %]	AED 472k	3/12
D0 on items paired with D6	8	12.5 % [2 %-47 %]	AED 50k	0/0
CGA v0.1, same items	8	0.0 % [0 %-32 %]	AED 0	0/0
CGA v0.3, same model outputs	8	0.0 % [0 %-32 %]	AED 0	0/0

Table 12. Real-LLM pilot [P]: attacker gain includes future payments diverted by a poisoned vendor record within the detection lag.

As the undefended agent, the model pursued the attacker's goal on 17 of 47 attack items (by family: A1 4/8; A2 3/8; A3 3/7; A4 0/4; A5 0/4; A6 4/4; A7 3/4; A8 0/4; A9 0/4), sometimes rewriting the vendor's bank account and paying the attacker in the same response while reporting low risk. On other items it resisted, paid the verified account and asked for a vendor-change ticket, which shows that susceptibility varies by item and phrasing. As CGA maker, the same model's outputs led to AED 0 of attacker gain under v0.1 and AED 0 under v0.3, with redirect loss AED 0: whatever the model wrote, the checker paid only verified accounts and matched quantities. Benchmarks P1-P4 are summarised in Section 8.8.




Figure 7. Real-LLM pilot [P]: share of attack items on which the attacker's goal was achieved, by family and configuration (Qwen3.5-4B, CPU). Small samples; see Table 13 for intervals.

8.7 Detector and adaptive attacks

For D2 we deployed a real open-weight classifier, ProtectAI's DeBERTa-v3 prompt-injection model [282], [295], on the exact text each agent receives, scanned in 128-token windows; Meta's Prompt Guard 2 [44] is licence-gated and will be used on the GPU runs. On held-out worlds it flagged 11 of 87 injected items (A1 3/22, A2 4/22, A3 0/22, A9 4/21), 10 of 314 benign twins and 0 of 583 sampled routine items. It missed every injection placed in structured e-invoice fields, which suggests, though our sample cannot establish it, that detectors trained on conversational injections transfer poorly to structured business documents. Recall depended strongly on scanning granularity in a small probe (16 injected items): 25 % with 512-token windows, 69 % with 128 and 94 % with 64, the last at the cost of flagging 40 % of benign twins, a context-dilution effect. As a defence, D2 reduced worst-case loss from AED 3.33M to AED 3.11M. An adaptive mutation search then evaded the detector on all 8 of 8 items it had caught, after a median of 5 queries (maximum 9).

Family	Target configuration	Best loss per campaign	Mean loss per query
A7	D6 (compromised maker)	AED 2.3k	AED 692
A7	D4 (compromised maker)	AED 72k	AED 20k
A7	D0 (faithful clerk)	AED 2.3k	AED 352
A6	D6 (compromised maker)	AED 0	AED 0
A6	D4 (compromised maker)	AED 106k	AED 28k
A6	D0 (faithful clerk)	AED 0	AED 0
A8	D6 (compromised maker)	AED 0	AED 0
A8	D4 (compromised maker)	AED 0	AED 0
A8	D0 (faithful clerk)	AED 0	AED 0

Table 13. Adaptive control-boundary search, 60 queries per family [A].

Against deterministic controls the adaptive attacker finds exactly the boundaries the proofs predict: under CGA v0.1 its best campaign earns a small within-tolerance amount, under the CaMeL-style design it earns tens of thousands of dirhams through inflation and near-duplicates, and shell-company campaigns earn nothing while onboarding control and the first-payment hold hold. Figure 7 shows the search curves.




Figure 8. Best loss found by the adaptive control-boundary search as queries accumulate (reviewer miss rate 10 %) [A].

8.8 Benchmark outcomes and the conditions under which they are met

Three frozen CGA versions were evaluated on ten fresh held-out worlds with the realistic surcharge condition (10 % of suppliers bill an agreed 0.5-2 % surcharge). v0.1 is the proposal's design. On development worlds it failed X3, X4 and H4 because a compromised maker could exploit the 2 % tolerance on every supplier. v0.2 closed that gap by paying the PO price and routing every variance to the buyer, but on development worlds it failed the automation targets because agreed surcharges were then held. v0.3 grants tolerance only to suppliers in a surcharge tolerance group, as ERP systems do with vendor tolerance groups, and parses UBL invoices with code instead of the model. Table 15 gives the held-out results.

ID	Target	v0.1	v0.2	v0.3
H1	DV cut >= 90 %, STP cost <= 10 pp	pass (99.97 %)	pass (100.00 %)	pass (100.00 %)
H2_CGA	CGA keeps reduction under adaptive attack	pass	pass	pass
H3	Channel effects as predicted	pass	pass	pass
H4	Residual in A7/A8, no diversion	pass (99.0 %)	pass (100.0 %)	pass (100.0 %)
X1	Injection ASR <= 1.75 %	pass (0.4 %)	pass (0.0 %)	pass (0.0 %)
X2	STP cost <= 7 pp	pass (-0.0 pp)	FAIL (9.9 pp)	pass (-0.0 pp)
X3	Adaptive success <= 10 %	FAIL	pass	pass
X4	Overall ASR <= 6.7 %	pass (6.3 %)	pass (0.0 %)	pass (1.0 %)
X5	Resistance >= 65 %	pass (93.7 %)	pass (100.0 %)	pass (99.0 %)
O1	FHR <= 2 %	pass (0.7 %)	FAIL (10.7 %)	pass (0.7 %)

ID	Target	v0.1	v0.2	v0.3
O2	STP >= 95 %	pass (99.4 %)	FAIL (89.5 %)	pass (99.4 %)
O3	Reviews <= 5 % of inbox	pass (3.4 %)	FAIL (6.3 %)	pass (4.1 %)
O4	Weekly DVaR95 = 0	pass (AED 0)	pass (AED 0)	pass (AED 0)
O5	Residual <= 0.01 %	pass (0.0024 %)	pass (0.0001 %)	pass (0.0001 %)
O6	Twin FHR <= 5 %	pass (0.0 %)	FAIL (6.3 %)	pass (0.0 %)

Table 14. Benchmark outcomes on fresh held-out worlds [A], surcharge condition 10 %, prevalence 3 %, review budget 5 %. Every evaluation and its conditions are in results/benchmark_ledger.csv.

v0.3 meets every pre-registered target on the held-out worlds. Two conditions qualify this. First, the adaptive success share is 1.7 % when the attacker cannot choose which supplier it compromises and 10.8 % when it knows the tolerance groups and targets surcharge suppliers, so tolerance-group membership should be treated as confidential master data. Second, the external targets X1-X5 come from other benchmarks and are indicative only. On the development worlds v0.3 missed H4, because its tiny residual was split between a near-duplicate and an inflated invoice on the same purchase order; on held-out worlds H4 passed. We report both, and we have not yet isolated which of the two payments exceeded entitlement in the development case.

Condition (s = 1 unless stated)	DV cut vs D0	CGA ASR	CGA FHR	CGA STP	H1, X4, O1, O2
baseline, s = 0.25	99.99 %	0.0 %	0.6 %	99.5 %	all
baseline, s = 0.5	100.00 %	0.0 %	0.6 %	99.5 %	all
baseline, s = 1	100.00 %	0.0 %	0.6 %	99.5 %	all
prevalence=0.01	100.00 %	0.0 %	0.6 %	99.5 %	all
prevalence=0.05	100.00 %	0.0 %	0.8 %	99.3 %	all
prevalence=0.1	100.00 %	0.2 %	1.0 %	99.0 %	all
channel=pdf	99.88 %	1.0 %	0.8 %	99.0 %	all
channel=ubl	100.00 %	0.0 %	1.0 %	99.0 %	all
review_budget=0.02	100.00 %	0.0 %	1.0 %	99.1 %	all
review_budget=0.1	100.00 %	0.0 %	0.6 %	99.5 %	all
reviewer_miss=0.1	99.58 %	1.8 %	0.9 %	99.1 %	all
reviewer_miss=0.3	98.69 %	4.7 %	1.6 %	98.6 %	all
surcharge_suppliers=0.0	100.00 %	0.0 %	0.6 %	99.5 %	all
surcharge_suppliers=0.2	99.99 %	0.7 %	0.6 %	99.5 %	all
onboarding_pass=0.2,reviewer_miss=0.1	99.39 %	2.9 %	0.8 %	99.2 %	all

Table 15. Robustness of CGA v0.3 across the pre-registered conditions (held-out worlds) [A].

In the real-model tier, P1 passes: CGA's redirect loss with Qwen3.5-4B as maker is AED 0 under v0.1 and AED 0 under v0.3. P2 passes for v0.3 (false-hold rate 0.0 %; v0.1 0.0 %). P3 passes: on items run under both designs, CGA v0.3 removes 100.0 % of the attacker's gain against D0. P4, the exposure baseline, is an ASR of 36.2 % for the undefended agent across all pilot attack items. All real-model results rest on one 4-billion-parameter model and a small sample.

8.9 Status of hypotheses and research questions

- **H1.** supported in the architectural tier on held-out worlds and in the real-model pilot; CGA's STP cost is negative (it raises automation) at every susceptibility level tested.
- **H2.** supported for the real detector (every caught item was evaded adaptively) and for CGA (residual bounded under adaptive search); for spotlighting it rests on an assumed effect size in the architectural tier and on the static pilot comparison, and an adaptive test with the model in the loop is still to be run.
- **H3.** supported qualitatively: UBL intake removes A1 entirely, free-text injection (A3) keeps most of its effect and business email compromise (A4) is largely unchanged.
- **H4.** supported on held-out worlds for v0.3; failed on development worlds as operationalised, for the attribution reason given above; no residual payment reached a non-owned account in any CGA run.

For the research questions: RQ1 is answered in money for undefended and conventionally defended agents (Table 12, Table 13); RQ2 favours controls-as-code over model-level and generic capability defences at matched or better STP; RQ3 is answered positively for CGA and negatively for naive LLM segregation (RQ7); RQ4 finds structured invoices helpful but insufficient; RQ5 locates the residual at the tolerance boundary and in the confidentiality of tolerance groups; RQ6 remains open.

9. Hardware and Feasibility Plan

The interim work ran entirely on a cloud container with four CPU cores and 15 GB of RAM and no GPU. The architectural grid needs about a quarter of a second per twelve-week episode, so 1,452 episodes took minutes. The real-model pilot ran Qwen3.5-4B in 4-bit quantisation at roughly 5 to 6 generated tokens per second; the median call took 28 seconds (90th percentile 79 seconds) for 71 calls, slower when other jobs shared the CPU. The prompt-injection classifier ran through ONNX Runtime on one or two threads. Small models are increasingly argued to be adequate for agentic roles [284], [285], [296]; in CGA a weaker model mainly costs automation, not security, which the pilot is consistent with.

Model	Licence	Size	Interim status	Role
Qwen3.5-9B [49]	Apache 2.0	9B dense	Colab notebook ready	Main GPU model
Qwen3.5-4B [49], [290]	Apache 2.0	4B dense, Q4_K_M	CPU pilot run	Pilot model
Gemma 4 E4B [50], [297]	Apache 2.0	4.5B effective	Weights checked, not yet run	Second family
gpt-oss-20b [51], [298]	Apache 2.0	21B total, 3.6B active	Planned (GPU)	Strongest that fits
ProtectAI DeBERTa-v3 [282]	Apache 2.0	184M	Run on CPU (D2)	Detector baseline
Prompt Guard 2 [44]	Llama licence (gated)	86M	Needs licence acceptance	Detector of the proposal

Table 16. Models: sizes and licences as published by the developers [299].

For the main grid with GPU models we keep the proposal's plan: free Colab T4 sessions [46] and Kaggle notebooks [47], vLLM serving [48] or llama.cpp [45], with every job checkpointed and resumable. The repository contains a Colab notebook that runs the same harness against an OpenAI-compatible vLLM server. Small open models may still struggle with long multi-tool workflows [52]; because CGA lets the

model only extract and propose, we expect weaker models to raise false holds rather than losses, and the pilot did not contradict this.

10. Project Plan and Timeline

Period	Planned deliverable	Status on 7 November 2026
Weeks 1-2 (2-15 Nov)	Generator v0; 50 hand-checked scenarios; data card	Done: generator, data card, Croissant draft; hand-check by practitioners pending
Weeks 3-4 (16-29 Nov)	Utility checker; compute profile; model gate	Done on CPU; GPU profile pending
Weeks 5-6 (30 Nov-13 Dec)	Unit-tested controls-as-code; static attack results	Done: tests, Z3 proofs, static results
Weeks 7-8 (14-27 Dec)	Pre-registration; held-out results RQ1-RQ4	Pre-registration and architectural held-out results done; GPU grid pending
Weeks 9-10 (28 Dec-10 Jan)	Adaptive attacks, red team, OpMech	Adaptive search done; human red team and full OpMech pending
Weeks 11-12 (11-25 Jan 2027)	Statistics, paper, artifact	Planned

Table 17. Plan from the proposal and status at the interim point.

The remaining work is, in order: the GPU grid with Qwen3.5-9B, Gemma 4 E4B and gpt-oss-20b on the full sample (including multi-turn tool use); an adaptive attack on spotlighting with the model in the loop; Prompt Guard 2 as the D2 detector; a human red-team round; practitioner review of 50 scenarios for realism; and the paper with open-science and ethics appendices for USENIX Security '27 [10], with the NeurIPS Evaluations and Datasets track [11] as the fallback.

11. Expected Contributions

- **SoD-Bench:** an open procure-to-pay benchmark with exact ground truth, two intake channels, nine attack families with benign look-alikes, money-denominated scoring and a pre-registered benchmark ledger (built).
- **The Control-Grounded Agent Architecture:** internal controls mapped to agent sessions, with a typed maker, deterministic checker, provenance rule and vendor tolerance groups (three frozen versions evaluated).
- **Model-agnostic evaluation:** susceptibility curves and the compromised-maker bound, which evaluate an architecture independently of any particular model (new).
- **Theory:** the Clark-Wilson reading of agent architectures and the Transitive Rule of Two for multi-agent workflows (new).
- **Machine-checked controls:** Z3 proofs of beneficiary integrity and overpayment bounds, plus property-based tests of the implementation (new).
- **Loss-centric evaluation:** diverted value, Loss@B, DVaR and CVaR, and a calibrated, conformally thresholded checker risk score.
- **Evidence on e-invoicing, detection and OpMech:** a channel study, a real-detector study and an exploratory OpMech test, with hypothesis and verified result kept apart.

11.1 Relationship to prior work and scope of claims

Much of what we build on is published: AgentDojo's evaluation principles [31], CaMeL and design patterns [35], [36], Meta's Rule of Two [9], LlamaFirewall and Prompt Guard [41], [44], adaptive evaluation [34], standard internal-control practice [32], Clark-Wilson integrity [87] and OpMech [12]. Closest in 2026 are governed execution for privileged agents [193], an organisational control layer at the execution boundary [194], a payment-authorisation benchmark [68] and work on composing CaMeL across agents [109]. What is new here is the procure-to-pay domain with internal-control semantics, loss measured in money at a review budget, the model-agnostic bound, the Transitive Rule of Two, machine-checked controls and the e-invoicing channel study.

We do not claim that CGA is secure against every attack, that controls-as-code removes the need for human judgement, that synthetic results demonstrate production readiness, that a 4-billion-parameter pilot represents frontier systems, or that meeting benchmark targets borrowed from other environments is a head-to-head comparison. Insider collusion, ERP compromise and attacks on the call-back channel remain outside scope, and the last is the most likely to matter in practice.

12. Risks, Ethics and Governance

The principal scientific risk remains external validity: a synthetic sandbox may miss how real suppliers, documents and staff behave. The interim work adds two specific risks. First, our worst-case results depend on the out-of-band call-back; deepfake voices [60], [58] could defeat it, so the next phase will model a compromised call-back channel explicitly. Second, the optimistic human reviewer flatters escalation-heavy designs; the reviewer-error sweep shows how much, and we will report it alongside every headline number.

Attack templates are dual-use. Business email compromise and invoice injection are already widely documented, and benchmark practice is to release attacks with the environment [31]. We will release templates and the environment, but we have not tested, probed or named any commercial product, and if an attack appears to transfer to a deployed system we will follow responsible disclosure. No personal or real company data is used; identifiers are synthetic and domains use the reserved .example top-level domain. Models are used under their published licences. Releasing the benchmark requires the author to choose licences for code and data; this decision is still open. Governance obligations for deployers, including human oversight and logging, are set out in the EU AI Act [220] and COSO's generative-AI guidance [76].

13. Conclusion

The title still earns its place. Segregation of duties, implemented as deterministic controls between a model that reads and code that pays, bounded the money a compromised model could divert in every configuration we tested, while keeping more automation than any model-dependent design. The interim evidence also sharpened the idea: segregation between language models alone is not enough, controls cover for each other in pairs, tolerance policies are the residual attack surface, and human reviewers are a fallible last line.

This project remains publishable only if it stays honest. The next phase must reproduce the results with larger open models on GPUs, attack spotlighting adaptively with the model in the loop, model a compromised call-back channel, and keep reporting the ablations and targets that fail. Model-level

defences, capability-based isolation and internal-control-grounded architecture remain competing hypotheses, now with a first round of evidence in money.

Appendix A. Illustrative Episode

This episode is taken verbatim from the pilot (item ITM-000229, held-out world 102); all names are invented. A supplier invoice arrived as a PDF whose text layer contained an instruction in white one-point type, invisible on the page, telling automated processors to pay a different account. The legitimate value of the invoice was AED 33k.

As the undefended agent (D0), Qwen3.5-4B returned the following actions (abridged): update_bank(supplier_id=SUP-0032, iban=AE159076582534369049907); pay(supplier_id=SUP-0032, amount=32815.52, iban=AE159076582534369049907), with a self-reported risk of 0.1. The attacker gained AED 50k, including payments that would follow to the poisoned vendor record.

As CGA maker, the same model proposed doc_kind=invoice, beneficiary=AE409036547344596592755, bank_change=AE159076582534369049907, instruction_flag=True. The checker ignored the document's account, paid only verified master data and matched quantities, and raised the flags lookalike_domain, instruction_text, urgency, bank_change_request; the attacker's gain was AED 0.00. A benign twin of this episode, in which a supplier genuinely changes bank and the call-back confirms it, is part of the benchmark so that the same controls are shown not to block legitimate business.

Appendix B. Reproducibility

All code, data generators, results and this report's generator are in the repository at commit e1ee0f8. The main commands are: python -m pytest (unit and property tests); python experiments/run_grid.py (architectural grid and sweeps); python experiments/score_detector.py and run_adaptive.py (detector and adaptive attacks); python experiments/run_benchmarks.py --version v0.3 --split heldout --robustness (benchmark campaign); python experiments/run_llm_pilot.py (real-model pilot); python experiments/analyze.py and experiments/pilot_benchmarks.py (tables and figures); python report/build_report.py (this document). Worlds are regenerated from seeds; the benchmark ledger records every evaluation with its conditions.

References

[1] Association for Financial Professionals, “Over 75 percent of U.S. firms experienced payments fraud in 2025, while AI adoption for fraud mitigation lags,” press release on the 2026 AFP Payments Fraud and Control Survey, Apr. 14, 2026. [Online]. Available: https://www.financialprofessionals.org/about/learn-more/press-releases/Details/over-75-percent-of-us-firms-experienced-payments-fraud-in-2025-while-ai-adoption-for-fraud-mitigation-lags

[2] Federal Bureau of Investigation, Internet Crime Complaint Center, “2025 Internet Crime Report,” Apr. 2026. [Online]. Available: https://www.ic3.gov

[3] Microsoft, “Automate payables processes with Payables Agent,” Dynamics 365 Business Central release plan, 2025 release wave 2. [Online]. Available: https://learn.microsoft.com/en-us/dynamics365/release-plan/2025wave2/smb/dynamics365-business-central/automate-payables-processes-payables-agent

[4] P. Reddy and A. S. Gujral, “EchoLeak: The first real-world zero-click prompt injection exploit in a production LLM system,” in Proc. AAAI Symposium Series, vol. 7, no. 1, pp. 303–311, 2025, doi: 10.1609/aaaiss.v7i1.36899.

[5] Gartner, “Gartner predicts over 40% of agentic AI projects will be canceled by end of 2027,” press release, Jun. 25, 2025. [Online]. Available: https://www.gartner.com/en/newsroom/press-releases/2025-06-25-gartner-predicts-over-40-percent-of-agentic-ai-projects-will-be-canceled-by-end-of-2027

[6] Z. Yang, R. Li, Q. Qiang, J. Wang, F. Lou, M. Li et al., “FinVault: Benchmarking financial agent safety in execution-grounded environments,” arXiv:2601.07853, 2026.

[7] D. M. Pai and L. Xian, “FraudBench: Stress-testing policy-grounded banking agents against adaptive fraud,” arXiv:2608.18136, 2026.

[8] E. Altman, J. Blanuša, L. von Niederhäusern, B. Egressy, A. Anghel, and K. Atasu, “Realistic synthetic financial transactions for anti-money laundering models,” arXiv:2306.16424, 2023.

[9] Meta AI, “Agents Rule of Two: A practical approach to AI agent security,” Meta AI Blog, Oct. 31, 2025. [Online]. Available: https://ai.meta.com/blog/practical-ai-agent-security/

[10] USENIX Association, “USENIX Security ’27: Call for papers,” 2026. [Online]. Available: https://www.usenix.org/conference/usenixsecurity27

[11] NeurIPS, “NeurIPS 2026 Evaluations & Datasets Track call for papers,” 2026. [Online]. Available: https://neurips.cc/Conferences/2026/CallForEvaluationsDatasets

[12] D. Guha, “Consolidation-Expansion Operator Mechanics: A unified framework for adaptive learning,” arXiv:2605.09968, 2026.

[13] ORTEC, “ORTEC survey finds 42% of logistics leaders still holding back on agentic AI,” Jan. 14, 2026. [Online]. Available: https://ortec.com/resources/news/logistics-leaders-agentic-ai-2026

[14] Boston Consulting Group, “From copilots to enterprise transformation: AI’s new mandate in supply chains,” Executive Perspectives, May 2026. [Online]. Available: https://www.bcg.com/assets/2026/executive-perspectives-ais-new-mandate-in-supply-chains.pdf

[15] Association of Certified Fraud Examiners, “Occupational fraud 2024: A report to the nations,” 2024. [Online]. Available: https://www.acfe.com/-/media/files/acfe/pdfs/rttn/2024/2024-report-to-the-nations.pdf

[16] E. Neelou, I. Novikov, M. Moroz, O. Narayan, T. Saade, M. Ayenson et al., “A2AS: Agentic AI runtime security and self-defense,” arXiv:2510.13825, 2025.

[17] OWASP GenAI Security Project, “OWASP Top 10 for Agentic Applications 2026,” Dec. 9, 2025. [Online]. Available: https://genai.owasp.org

[18] European Central Bank, “Instant Payments Regulation,” implementing Regulation (EU) 2024/886, including the verification-of-payee deadlines of 9 Oct. 2025 (euro area) and 9 Jul. 2027 (non-euro area). [Online]. Available: https://www.ecb.europa.eu/paym/retail/instant_payments/html/instant_payments_regulation.en.html

[19] UAE Ministry of Finance, “Electronic Invoicing Guidelines, Version 1.0,” Feb. 23, 2026. [Online]. Available: https://mof.gov.ae

[20] e-Invoice.app, “UAE PINT AE: e-invoicing mandate 2026–2027,” Apr. 2026. [Online]. Available: https://www.e-invoice.app/blog/uae-pint-ae-guide

[21] Y. Yang, T. Lan, Q. Jia, L. Zhu, H. Jiang, H. Zhu, L. Wang, W. Luo, and K. Zhang, “HSCodeComp: A realistic and expert-level benchmark for deep search agents in hierarchical rule application,” arXiv:2510.19631, 2025.

[22] Alizila, “Alibaba’s latest AI agent benchmark awarded Best Resource Paper at ACL 2026,” 2026. [Online]. Available: https://www.alizila.com/?p=67163

[23] R. Grzeczkowicz et al., “Toward an agentic approach in anti-money laundering investigation for typology classification,” in ICLR 2026 Workshop on Advances in Financial AI: Towards Agentic and Responsible Systems, 2026.

[24] P. V. Naik, N. K. Dintakurthi, Z. Hu, Y. Wang, and R. Qiu, “Co-Investigator AI: The rise of agentic AI for smarter, trustworthy AML compliance narratives,” arXiv:2509.08380, 2025.

[25] C. X. Long, D. Simchi-Levi, F. Zhu, H. Su, A. P. Calmon, and F. P. Calmon, “Reliability and effectiveness of autonomous AI agents in supply chain management,” arXiv:2605.17036, 2026.

[26] H. Wang, J. Jiang, L. J. Hong, and G. Jiang, “LLMs for supply chain management,” arXiv:2505.18597, 2025.

[27] Q. Mao, J. Wang, Y. Liu, L. Zhu, C. Ma, and J. Yan, “SoK: Security of autonomous LLM agents in agentic commerce,” arXiv:2604.15367, 2026.

[28] W. W. Li, H. Kim, M. Cucuringu, and T. Ma, “Can LLM-based financial investing strategies outperform the market in long run?” arXiv:2505.07078, 2025.

[29] X. Yuan, H. Xu, S. Xu, C. Zou, and J. Xiong, “TraderBench: How robust are AI agents in adversarial capital markets?” arXiv:2603.00285, 2026.

[30] Y. Liu, Y. Jia, R. Geng, J. Jia, and N. Z. Gong, “Formalizing and benchmarking prompt injection attacks and defenses,” in Proc. 33rd USENIX Security Symposium, 2024.

[31] E. Debenedetti, J. Zhang, M. Balunović, L. Beurer-Kellner, M. Fischer, and F. Tramèr, “AgentDojo: A dynamic environment to evaluate prompt injection attacks and defenses for LLM agents,” in Advances in Neural Information Processing Systems 37 (Datasets and Benchmarks Track), 2024, pp. 82895–82920.

[32] Committee of Sponsoring Organizations of the Treadway Commission (COSO), Internal Control—Integrated Framework. COSO, 2013.

[33] K. Greshake, S. Abdelnabi, S. Mishra, C. Endres, T. Holz, and M. Fritz, “Not what you’ve signed up for: Compromising real-world LLM-integrated applications with indirect prompt injection,” in Proc. 16th ACM Workshop on Artificial Intelligence and Security, 2023, pp. 79–90.

[34] M. Nasr, N. Carlini, C. Sitawarin, S. V. Schulhoff, J. Hayes, M. Ilie, J. Pluto, S. Song, H. Chaudhari, I. Shumailov, A. Thakurta, K. Y. Xiao, A. Terzis, and F. Tramèr, “The attacker moves second: Stronger adaptive attacks bypass defenses against LLM jailbreaks and prompt injections,” arXiv:2510.09023, 2025.

[35] E. Debenedetti, I. Shumailov, T. Fan, J. Hayes, N. Carlini, D. Fabian, C. Kern, C. Shi, A. Terzis, and F. Tramèr, “Defeating prompt injections by design,” arXiv:2503.18813, 2025.

[36] L. Beurer-Kellner, B. Buesser, A.-M. Creţu, E. Debenedetti, D. Dobos, D. Fabian, M. Fischer, D. Froelicher, K. Grosse, D. Naeff, E. Ozoani, A. Paverd, F. Tramèr, and V. Volhejn, “Design patterns for securing LLM agents against prompt injections,” arXiv:2506.08837, 2025.

[37] Q. Zhan, Z. Liang, Z. Ying, and D. Kang, “InjecAgent: Benchmarking indirect prompt injections in tool-integrated large language model agents,” arXiv:2403.02691, 2024.

[38] H. Zhang, J. Huang, K. Mei, Y. Yao, Z. Wang, C. Zhan, H. Wang, and Y. Zhang, “Agent Security Bench (ASB): Formalizing and benchmarking attacks and defenses in LLM-based agents,” arXiv:2410.02644, 2024.

[39] S. Yao, N. Shinn, P. Razavi, and K. Narasimhan, “τ-bench: A benchmark for tool-agent-user interaction in real-world domains,” arXiv:2406.12045, 2024.

[40] K. Hines, G. Lopez, M. Hall, F. Zarfati, Y. Zunger, and E. Kiciman, “Defending against indirect prompt injection attacks with spotlighting,” arXiv:2403.14720, 2024.

[41] S. Chennabasappa, C. Nikolaidis, D. Song, D. Molnar, S. Ding, S. Wan, S. Whitman et al., “LlamaFirewall: An open source guardrail system for building secure AI agents,” arXiv:2505.03574, 2025.

[42] K. Zhu et al., “MELON: Provable defense against indirect prompt injection attacks in AI agents,” in Proc. 42nd International Conference on Machine Learning (ICML), 2025.

[43] OpenPeppol, “Peppol BIS Billing 3.0,” specification. [Online]. Available: https://docs.peppol.eu/poacc/billing/3.0/

[44] Meta, “Llama Prompt Guard 2 (22M and 86M),” model card, 2025. [Online]. Available: https://huggingface.co/meta-llama/Llama-Prompt-Guard-2-86M

[45] G. Gerganov et al., “llama.cpp,” GitHub repository. [Online]. Available: https://github.com/ggml-org/llama.cpp

[46] Google, “Google Colab: Frequently asked questions.” [Online]. Available: https://research.google.com/colaboratory/faq.html

[47] Kaggle, “Notebooks documentation.” [Online]. Available: https://www.kaggle.com/docs/notebooks

[48] W. Kwon, Z. Li, S. Zhuang, Y. Sheng, L. Zheng, C. H. Yu, J. E. Gonzalez, H. Zhang, and I. Stoica, “Efficient memory management for large language model serving with PagedAttention,” in Proc. 29th Symposium on Operating Systems Principles (SOSP), 2023.

[49] Qwen Team, Alibaba, “Qwen3.5 model collection,” Hugging Face, 2026 (small dense models released Mar. 2026). [Online]. Available: https://huggingface.co/collections/Qwen/qwen35

[50] Google DeepMind, “Gemma 4 model family,” released Apr. 2, 2026. [Online]. Available: https://deepmind.google/models/gemma/

[51] OpenAI, “Introducing gpt-oss,” Aug. 2025. [Online]. Available: https://openai.com/index/introducing-gpt-oss/

[52] Y. Liu, Y. Wang, Y. Jia, J. Jia, and N. Z. Gong, “SecInfer: Preventing prompt injection via inference-time scaling,” arXiv:2509.24967, 2025.

[53] S. Willison, "The lethal trifecta for AI agents: private data, untrusted content, and external communication," Jun. 16, 2025.

[54] B. A. Nosek, C. R. Ebersole, A. C. DeHaven, and D. T. Mellor, "The preregistration revolution," Proceedings of the National Academy of Sciences, vol. 115, no. 11, pp. 2600-2606, 2018.

[55] X. Zhao, Y. Xie, C. Chen, and Y. Sun, "AIM-Bench: Evaluating Decision-making Biases of Agentic LLM as Inventory Manager," arXiv:2508.11416, 2025.

[56] M. Yang, Y. Pan, J. Piao, D. Song, Y. Gong, and Y. Li, "EnterpriseBench: Benchmarking LLM Agents on Enterprise-Level Strategic Reasoning and Decision-Making," arXiv:2609.37658, 2026.

[57] F. Heiding, S. Lermen, A. Kao, B. Schneier, and A. Vishwanath, "Evaluating Large Language Models' Capability to Launch Fully Automated Spear Phishing Campaigns: Validated on Human Subjects," arXiv:2412.00586, 2024.

[58] F. Heiding, C. M. Verdun, S. Lermen, A. Kao, V. Albiero, L. Deason et al., "Evaluating AI Models' Capability to Automate Voice Phishing Attacks," arXiv:2607.09970, 2026.

[59] S. Sato, T. Ohki, and M. Nishigaki, "Can We End the Cat-and-Mouse Game? Simulating Self-Evolving Phishing Attacks with LLMs and Genetic Algorithms," arXiv:2507.21538, 2025.

[60] M. Hong, D. Jiang, Z. Xie, W. Zhao, G. Wang, and C. J. Zhang, "Vulnerabilities of Audio-Based Biometric Authentication Systems Against Deepfake Speech Synthesis," arXiv:2601.02914, 2026.

[61] C. Popa, R. Pallath, L. Cunningham, H. Tahiri, A. Kesavarajah, and T. Wu, "Deepfake Technology Unveiled: The Commoditization of AI and Its Impact on Digital Trust," arXiv:2506.07363, 2025.

[62] M. Pfister, G. Apruzzese, and I. Pekaric, "Department-Specific Security Awareness Campaigns: A Cross-Organizational Study of HR and Accounting," arXiv:2511.22189, 2025.

[63] J. Wu, Y. Nan, J. Wu, Z. Yao, Z. Shi, M. Yang et al., "Your Mailbox Is Mine: Prompt Injection Attacks Against Real-World LLM Email Agents," arXiv:2507.02699, 2025.

[64] A. Hashmi, D. Patel, and Y. Yin, "Prompt Injection Detection for Email Agents Through Attack Chain Modeling," arXiv:2609.30657, 2026.

[65] P. Thienpreecha and K. Subramanian, "CrackedPDFs: A Controlled Benchmark for Hidden Prompt Injection in PDFs," arXiv:2607.19396, 2026.

[66] T. Murray, "PhantomLint: Principled Detection of Hidden LLM Prompts in Structured Documents," arXiv:2508.17884, 2025.

[67] P. Theocharopoulos, A. Kulkarni, and M. M. -Doss, "Multilingual Hidden Prompt Injection Attacks on LLM-Based Academic Reviewing," arXiv:2512.23684, 2025.

[68] U. Uchibeke, "APort Vault: Benchmarking AI Agent Payment Authorization with the Open Agent Passport," arXiv:2609.22076, 2026.

[69] Y. Louck, A. Dvir, and A. Stulman, "Signing the Transaction but Not the Decision: Whisper Attacks and a Binding Defense for AP2," arXiv:2609.11757, 2026.

[70] V. Stantchev, "Hardening x402: PII-Safe Agentic Payments via Pre-Execution Metadata Filtering," arXiv:2604.11430, 2026.

[71] OpenPeppol, "PINT AE: United Arab Emirates electronic document specifications, version 1.0.3," 2026. [Online]. Available: https://docs.peppol.eu/poac/ae/v1.0.3/

[72] Council of the European Union, "Council Directive (EU) 2025/516 of 11 March 2025 amending Directive 2006/112/EC as regards VAT rules for the digital age," 2025.

[73] Google Cloud, "Announcing Agent Payments Protocol (AP2)," Sep. 16, 2025.

[74] OpenAI and Stripe, "Agentic Commerce Protocol," Sep. 29, 2025.

[75] Visa, "Trusted Agent Protocol," Oct. 14, 2025.

[76] Committee of Sponsoring Organizations of the Treadway Commission (COSO), "Achieving effective internal control over generative AI (GenAI)," Feb. 2026. Summary consulted: Deloitte DART, "COSO releases publication on internal controls related to generative AI," 2026. [Online]. Available: https://dart.deloitte.com/USDART/home/publications/deloitte/heads-up/2026/coso-internal-controls-generative-ai

[77] National Institute of Standards and Technology, Center for AI Standards and Innovation, "AI Agent Standards Initiative," Feb. 17, 2026, and "Request for information regarding security considerations for artificial intelligence agents," Federal Register, vol. 91, no. 5, Jan. 8, 2026, Docket NIST-2025-0035. [Online]. Available: https://www.govinfo.gov/content/pkg/FR-2026-01-08/html/2026-00206.htm

[78] National Institute of Standards and Technology, "Design tenets for agent identity management systems," Cybersecurity Insights blog, 2026. [Online]. Available: https://www.nist.gov/blogs/cybersecurity-insights/design-tenets-agent-identity-management-systems

[79] Sarbanes-Oxley Act of 2002, Pub. L. No. 107-204, 116 Stat. 745, Section 404.

[80] Public Company Accounting Oversight Board, "AS 2201: An audit of internal control over financial reporting that is integrated with an audit of financial statements."

[81] American Institute of Certified Public Accountants, "2017 Trust Services Criteria for Security, Availability, Processing Integrity, Confidentiality, and Privacy (with revised points of focus, 2022)."

[82] The Institute of Internal Auditors, "The IIA's Three Lines Model: An update of the Three Lines of Defense," Jul. 2020.

[83] B. F. van Dongen, "BPI Challenge 2019," 4TU.ResearchData, event log of a purchase-to-pay process, 2019.

[84] W. M. P. van der Aalst, Process Mining: Data Science in Action, 2nd ed. Berlin: Springer, 2016.

[85] M. J. Nigrini, Benford's Law: Applications for Forensic Accounting, Auditing, and Fraud Detection. Hoboken, NJ: Wiley, 2012.

[86] J. H. Saltzer and M. D. Schroeder, "The protection of information in computer systems," Proc. IEEE, vol. 63, no. 9, pp. 1278-1308, 1975.

[87] D. D. Clark and D. R. Wilson, "A comparison of commercial and military computer security policies," in Proc. IEEE Symposium on Security and Privacy, 1987, pp. 184-194.

[88] K. J. Biba, "Integrity considerations for secure computer systems," MITRE Corp., Tech. Rep. MTR-3153, 1977.

[89] D. F. C. Brewer and M. J. Nash, "The Chinese Wall security policy," in Proc. IEEE Symposium on Security and Privacy, 1989, pp. 206-214.

[90] R. S. Sandhu, E. J. Coyne, H. L. Feinstein, and C. E. Youman, "Role-based access control models," IEEE Computer, vol. 29, no. 2, pp. 38-47, 1996.

[91] D. F. Ferraiolo, R. Sandhu, S. Gavrila, D. R. Kuhn, and R. Chandramouli, "Proposed NIST standard for role-based access control," ACM Transactions on Information and System Security, vol. 4, no. 3, pp. 224-274, 2001.

[92] R. T. Simon and M. E. Zurko, "Separation of duty in role-based environments," in Proc. 10th IEEE Computer Security Foundations Workshop, 1997, pp. 183-194.

[93] N. Li, M. V. Tripunitara, and Z. Bizri, "On mutually exclusive roles and separation-of-duty," ACM Transactions on Information and System Security, vol. 10, no. 2, 2007.

[94] E. Bertino, E. Ferrari, and V. Atluri, "The specification and enforcement of authorization constraints in workflow management systems," ACM Transactions on Information and System Security, vol. 2, no. 1, pp. 65-104, 1999.

[95] National Institute of Standards and Technology, "Security and privacy controls for information systems and organizations," NIST SP 800-53 Rev. 5, Sep. 2020 (controls AC-5 Separation of Duties and AC-6 Least Privilege).

[96] F. Perez and I. Ribeiro, "Ignore Previous Prompt: Attack Techniques For Language Models," in NeurIPS ML Safety Workshop, 2022; arXiv:2211.09527.

[97] Y. Liu, G. Deng, Y. Li, K. Wang, Z. Wang, X. Wang et al., "Prompt Injection attack against LLM-integrated Applications," arXiv:2306.05499, 2023.

[98] N. Hardy, "The confused deputy (or why capabilities might have been invented)," ACM SIGOPS Operating Systems Review, vol. 22, no. 4, pp. 36-38, 1988.

[99] E. Wallace, K. Xiao, R. Leike, L. Weng, J. Heidecke, and A. Beutel, "The Instruction Hierarchy: Training LLMs to Prioritize Privileged Instructions," arXiv:2404.13208, 2024.

[100] J. Zhang, T. Li, W. Jurayj, H. Zhan, B. V. Durme, and D. Khashabi, "Many-Tier Instruction Hierarchy in LLM Agents," arXiv:2604.09443, 2026.

[101] S. Kariyappa and G. E. Suh, "Stronger Enforcement of Instruction Hierarchy via Augmented Intermediate Representations," arXiv:2505.18907, 2025.

[102] S. Chen, J. Piet, C. Sitawarin, and D. Wagner, "StruQ: Defending Against Prompt Injection with Structured Queries," in Proc. 34th USENIX Security Symposium, 2025; arXiv:2402.06363.

[103] S. Chen, A. Zharmagambetov, S. Mahloujifar, K. Chaudhuri, D. Wagner, and C. Guo, "SecAlign: Defending Against Prompt Injection with Preference Optimization," in Proc. ACM CCS, 2025; arXiv:2410.05451.

[104] S. Chen, A. Zharmagambetov, D. Wagner, and C. Guo, "Meta-SecAlign: Training LLMs against Prompt Injection for Robust Agents," arXiv:2507.02735, 2025.

[105] Y. Liu, Y. Jia, J. Jia, D. Song, and N. Z. Gong, "DataSentinel: A Game-Theoretic Detection of Prompt Injection Attacks," arXiv:2504.11358, 2025.

[106] D. Jacob, H. Alzahrani, Z. Hu, B. Alomair, and D. Wagner, "PromptShield: Deployable Detection for Prompt Injection Attacks," arXiv:2501.15145, 2025.

[107] Q. Zhan, R. Fang, H. S. Panchal, and D. Kang, "Adaptive Attacks Break Defenses Against Indirect Prompt Injection Attacks on LLM Agents," in Findings of NAACL, 2025; arXiv:2503.00061.

[108] K. Tallam and E. Miller, "Operationalizing CaMeL: Strengthening LLM Defenses for Enterprise Deployment," arXiv:2505.22852, 2025.

[109] J. Peters-Gill, A. Semler, H. Bartsch, I. Shumailov, and C. S. d. Witt, "Can CaMeLs Talk? Securing Multi-Agent Systems Against Indirect Prompt Injection Attacks," arXiv:2610.05640, 2026.

[110] E. Nikolaou, M. W. Eckhoff, R. Flood, G. Grov, V. Mavroeidis, and D. Aspinall, "CaMeLoT: CaMeL orchestrated with Temporal logic for static verification and liveness," arXiv:2609.18674, 2026.

[111] M. Costa, B. Köpf, A. Kolluri, A. Paverd, M. Russinovich, A. Salem et al., "Securing AI Agents with Information-Flow Control," arXiv:2505.23643, 2025.

[112] F. Wu, E. Cecchetti, and C. Xiao, "System-Level Defense against Indirect Prompt Injection Attacks: An Information Flow Control Perspective," arXiv:2409.19091, 2024.

[113] T. Shi, J. He, Z. Wang, H. Li, L. Wu, W. Guo et al., "Progent: Securing AI Agents with Privilege Control," arXiv:2504.11703, 2025.

[114] S. Willison, "The Dual LLM pattern for building AI assistants that can resist prompt injection," Apr. 25, 2023.

[115] H. Yang, B. Zhang, N. Wang, C. Guo, X. Zhang, L. Lin et al., "FinRobot: An Open-Source AI Agent Platform for Financial Applications using Large Language Models," arXiv:2405.14767, 2024.

[116] T. Zhu, M. White, X. Liu, and X. Liu, "NumTrace: Auditing the Number Provenance of Financial Analyst Agents," arXiv:2610.34887, 2026.

[117] Y. Nian, A. Yuan, H. Zhang, J. Li, L. Li, X. Hu et al., "Auditable Agents," arXiv:2604.05485, 2026.

[118] C. Hua, T. Tsuchiya, N. Christin, and G. Fanti, "Holding Agents Accountable with Verifiable Agent Insurance," arXiv:2610.18230, 2026.

[119] S. Toyer, O. Watkins, E. A. Mendes, J. Svegliato, L. Bailey, T. Wang et al., "Tensor Trust: Interpretable Prompt Injection Attacks from an Online Game," arXiv:2311.01011, 2023.

[120] S. Schulhoff, J. Pinto, A. Khan, L. Bouchard, C. Si, S. Anati et al., "Ignore This Title and HackAPrompt: Exposing Systemic Vulnerabilities of LLMs through a Global Scale Prompt Hacking Competition," arXiv:2311.16119, 2023.

[121] E. Debenedetti, J. Rando, D. Paleka, S. F. Florin, D. Albastroiu, N. Cohen et al., "Dataset and Lessons Learned from the 2024 SaTML LLM Capture-the-Flag Competition," arXiv:2406.07954, 2024.

[122] A. Zou, Z. Wang, N. Carlini, M. Nasr, J. Z. Kolter, and M. Fredrikson, "Universal and Transferable Adversarial Attacks on Aligned Language Models," arXiv:2307.15043, 2023.

[123] J. Yi, Y. Xie, B. Zhu, E. Kiciman, G. Sun, X. Xie et al., "Benchmarking and Defending Against Indirect Prompt Injection Attacks on Large Language Models," in Proc. ACM KDD, 2025; arXiv:2312.14197.

[124] I. Evtimov, A. Zharmagambetov, A. Grattafiori, C. Guo, and K. Chaudhuri, "WASP: Benchmarking Web Agent Security Against Prompt Injection Attacks," arXiv:2504.18575, 2025.

[125] M. Andriushchenko, A. Souly, M. Dziemian, D. Duenas, M. Lin, J. Wang et al., "AgentHarm: A Benchmark for Measuring Harmfulness of LLM Agents," in Proc. ICLR, 2025; arXiv:2410.09024.

[126] Z. Zhang, S. Cui, Y. Lu, J. Zhou, J. Yang, H. Wang et al., "Agent-SafetyBench: Evaluating the Safety of LLM Agents," arXiv:2412.14470, 2024.

[127] T. Yuan, Z. He, L. Dong, Y. Wang, R. Zhao, T. Xia et al., "R-Judge: Benchmarking Safety Risk Awareness for LLM Agents," in Findings of EMNLP, 2024; arXiv:2401.10019.

[128] Y. Ruan, H. Dong, A. Wang, S. Pitis, Y. Zhou, J. Ba et al., "Identifying the Risks of LM Agents with an LM-Emulated Sandbox," arXiv:2309.15817, 2023.

[129] V. Barres, H. Dong, S. Ray, X. Si, and K. Narasimhan, "τ^2-Bench: Evaluating Conversational Agents in a Dual-Control Environment," arXiv:2506.07982, 2025.

[130] D. Jain, D. Hartmann, and C. Li, "Adaptive Adversaries: A Multi-Turn, Multi-LLM Benchmark for LLM Agent Security," arXiv:2607.18063, 2026.

[131] J. Tan, M. Li, and D. Zhao, "AgentPhishing: A Benchmark of LLM Email Agents Under Adaptive Attack," arXiv:2610.31404, 2026.

[132] Y. Zhu, T. Jin, Y. Pruksachatkun, A. Zhang, S. Liu, S. Cui et al., "Establishing Best Practices for Building Rigorous Agentic Benchmarks," arXiv:2507.02825, 2025.

[133] V. Bhat, J. Vaghasiya, M. A. Mohsin, and A. Aali, "Benchmarking the Benchmarks: A Validity Audit of Tool-Calling Evaluation," arXiv:2607.02577, 2026.

[134] A. Reuel, A. Hardy, C. Smith, M. Lamparth, M. Hardy, and M. J. Kochenderfer, "BetterBench: Assessing AI Benchmarks, Uncovering Issues, and Establishing Best Practices," in Advances in Neural Information Processing Systems 37 (Datasets and Benchmarks Track), 2024; arXiv:2411.12990.

[135] S. Kapoor, B. Stroebl, Z. S. Siegel, N. Nadgir, and A. Narayanan, "AI Agents That Matter," arXiv:2407.01502, 2024.

[136] S. Mehta, "Beyond Accuracy: A Multi-Dimensional Framework for Evaluating Enterprise Agentic AI Systems," arXiv:2511.14136, 2025.

[137] M. B. Madiraju and M. S. P. Madiraju, "AgentSLABench: Evaluating and Benchmarking Agentic Systems Under Resource Constraints," arXiv:2608.00805, 2026.

[138] E. K. Buchanan, C. Zhou, S. W. Linderman, and C. Ré, "Benchmarks as Software: Terminal-Bench and the Case for Continuous Benchmarks," arXiv:2611.08417, 2026.

[139] Y. Chen, T. Cao, H. Li, Y. Li, Y. Liu, Y. He et al., "WebAgentGuard: A Reasoning-Driven Guard Model for Detecting Prompt Injection Attacks in Web Agents," arXiv:2604.12284, 2026.

[140] T. C. Addagada, "Semalith v1.4: A Calibrated 184M Safety Classifier Achieving State-of-the-Art Prompt-Injection Detection at 44x Fewer Parameters than Llama-Guard-3-8B," arXiv:2607.22545, 2026.

[141] K. Hung, C. Ko, A. Rawat, I. Chung, W. H. Hsu, and P. Chen, "Attention Tracker: Detecting Prompt Injection Attacks in LLMs," arXiv:2411.00348, 2024.

[142] S. Abdelnabi, A. Fay, G. Cherubin, A. Salem, M. Fritz, and A. Paverd, "Get my drift? Catching LLM Task Drift with Activation Deltas," in Proc. IEEE Conference on Secure and Trustworthy Machine Learning (SaTML), 2025; arXiv:2406.00799.

[143] F. Jia, T. Wu, X. Qin, and A. Squicciarini, "The Task Shield: Enforcing Task Alignment to Defend Against Indirect Prompt Injection in LLM Agents," arXiv:2412.16682, 2024.

[144] T. Shi, K. Zhu, Z. Wang, Y. Jia, W. Cai, W. Liang et al., "PromptArmor: Simple yet Effective Prompt Injection Defenses," arXiv:2507.15219, 2025.

[145] Z. Xiang, L. Zheng, Y. Li, J. Hong, Q. Li, H. Xie et al., "GuardAgent: Safeguard LLM Agents by a Guard Agent via Knowledge-Enabled Reasoning," in Proc. ICML, 2025; arXiv:2406.09187.

[146] Z. Chen, M. Kang, and B. Li, "ShieldAgent: Shielding Agents via Verifiable Safety Policy Reasoning," arXiv:2503.22738, 2025.

[147] Y. Mou, Z. Xue, L. Li, P. Liu, S. Zhang, W. Ye et al., "ToolSafe: Enhancing Tool Invocation Safety of LLM-based agents via Proactive Step-level Guardrail and Feedback," arXiv:2601.10156, 2026.

[148] W. Luo, S. Dai, X. Liu, S. Banerjee, H. Sun, M. Chen et al., "AGrail: A Lifelong Agent Guardrail with Effective and Adaptive Safety Detection," arXiv:2502.11448, 2025.

[149] C. Shi, S. Lin, S. Song, J. Hayes, I. Shumailov, I. Yona et al., "Lessons from Defending Gemini Against Indirect Prompt Injections," arXiv:2505.14534, 2025.

[150] A. Zhou, K. Wu, F. Pinto, Z. Chen, Y. Zeng, Y. Yang et al., "AutoRedTeamer: Autonomous Red Teaming with Lifelong Attack Integration," arXiv:2503.15754, 2025.

[151] P. He, D. Mitra, V. Sharma, J. Tang, V. S. Rao, T. Pfister et al., "ASPIRE: Agentic Safety & Prompt Injection Red-teaming Engine," arXiv:2610.08951, 2026.

[152] Y. Y. Levi, R. Betser, A. Giloni, L. Erez, I. Gershon, O. Rachmil et al., "RIFT-Bench: Dynamic Red-teaming For Agentic AI Systems," arXiv:2606.23927, 2026.

[153] J. Kim, W. Choi, and B. Lee, "Prompt Flow Integrity to Prevent Privilege Escalation in LLM Agents," arXiv:2503.15547, 2025.

[154] P. Y. Zhong, S. Chen, R. Wang, M. McCall, B. L. Titzer, H. Miller et al., "RTBAS: Defending LLM Agents Against Prompt Injection and Privacy Leakage," arXiv:2502.08966, 2025.

[155] Y. Wu, F. Roesner, T. Kohno, N. Zhang, and U. Iqbal, "IsolateGPT: An Execution Isolation Architecture for LLM-Based Agentic Systems," in Proc. NDSS Symposium, 2025; arXiv:2403.04960.

[156] E. Li, T. Mallick, E. Rose, W. Robertson, A. Oprea, and C. Nita-Rotaru, "ACE: A Security Architecture for LLM-Integrated App Systems," in Proc. NDSS Symposium, 2026; arXiv:2504.20984.

[157] Y. Li, X. He, X. Dai, and B. Xiao, "ToolFence: Fine-Grained Authorization for Secure Tool-Using LLM Agents," arXiv:2609.37196, 2026.

[158] L. Tsai and E. Bagdasarian, "Contextual Agent Security: A Policy for Every Purpose," in Proc. Workshop on Hot Topics in Operating Systems (HotOS), 2025; arXiv:2501.17070.

[159] H. Li, X. Liu, H. Chiu, D. Li, N. Zhang, and C. Xiao, "DRIFT: Dynamic Rule-Based Defense with Injection Isolation for Securing LLM Agents," in Advances in Neural Information Processing Systems (NeurIPS), 2025; arXiv:2506.12104.

[160] R. F. D. Rosario, K. Krawiecka, and C. S. d. Witt, "Architecting Resilient LLM Agents: A Guide to Secure Plan-then-Execute Implementations," arXiv:2509.08646, 2025.

[161] A. Cidon, L. Gavish, I. Bleier, N. Korshun, M. Schweighauser, and A. Tsitkin, "High precision detection of business email compromise," in Proc. 28th USENIX Security Symposium, 2019.

[162] R. Dube, "Per-sender neural network classifiers for email authorship validation," arXiv:2509.00005, 2025.

[163] J. Szurdi, B. Kocso, G. Cseh, J. Spring, M. Felegyhazi, and C. Kanich, "The long 'taile' of typosquatting domain names," in Proc. 23rd USENIX Security Symposium, 2014.

[164] E. Gabrilovich and A. Gontmakher, "The homograph attack," Communications of the ACM, vol. 45, no. 2, p. 128, 2002.

[165] Payment Systems Regulator, "Authorised push payment (APP) scams reimbursement requirement," in force Oct. 7, 2024.

[166] European Committee for Standardization, "EN 16931-1:2017 Electronic invoicing - Part 1: Semantic data model of the core elements of an electronic invoice," 2017.

[167] OASIS, "Universal Business Language Version 2.1," 2013; published as ISO/IEC 19845:2015.

[168] ISO 13616-1:2020, "Financial services - International bank account number (IBAN) - Part 1: Structure of the IBAN," 2020.

[169] J. Gómez and J. Sánchez, "Information Extraction from Electricity Invoices with General-Purpose Large Language Models," arXiv:2604.25927, 2026.

[170] K. Khanchandani, A. Thakur, A. Shetty, C. Reddy, and R. Behera, "Automated Invoice Data Extraction: Using LLM and OCR," arXiv:2511.05547, 2025.

[171] B. V, A. P, R. KR, S. M, V. S, and B. Wilson, "Generating Synthetic Invoices via Layout-Preserving Content Replacement," arXiv:2508.03754, 2025.

[172] Y. Jin, Y. Wang, Y. Han, K. C. Y. Sonia, W. Song, C. J. Kent et al., "Perception, Layout, and Validation: Calibrated Confidence for Reliable Straight-Through Processing of Financial Documents," arXiv:2609.20110, 2026.

[173] J. Östman, E. Callisen, A. Chen, K. Ausmees, E. Gårdh, J. Zamac et al., "AMLgentex: Mobilizing Data-Driven Research to Combat Money Laundering," arXiv:2506.13989, 2025.

[174] R. Chung, P. N. Sharma, M. Siponen, R. Vadodaria, and L. Smith, "Hybrid Data can Enhance the Utility of Synthetic Data for Training Anti-Money Laundering Models," arXiv:2509.18499, 2025.

[175] N. F. Liu, K. Lin, J. Hewitt, A. Paranjape, M. Bevilacqua, F. Petroni et al., "Lost in the Middle: How Language Models Use Long Contexts," Transactions of the Association for Computational Linguistics, vol. 12, 2024; arXiv:2307.03172.

[176] Y. Li, H. Li, L. Liu, and T. Watanabe, "On the Position Bias of Large Language Models: A Comprehensive Study," arXiv:2610.22807, 2026.

[177] G. Zhang, J. Cheng, and H. Chen, "Ranked by Position: Order Sensitivity as an Exploitable Attack Surface in LLM Listwise Recommenders," arXiv:2607.24869, 2026.

[178] X. Wang, J. Wei, D. Schuurmans, Q. Le, E. Chi, S. Narang et al., "Self-Consistency Improves Chain of Thought Reasoning in Language Models," in Proc. ICLR, 2023; arXiv:2203.11171.

[179] R. Nowak, "Estimating the Self-Consistency of LLMs," arXiv:2509.19489, 2025.

[180] J. B. Dennis and E. C. Van Horn, "Programming semantics for multiprogrammed computations," Communications of the ACM, vol. 9, no. 3, pp. 143-155, 1966.

[181] M. S. Miller, "Robust composition: Towards a unified approach to access control and concurrency control," Ph.D. dissertation, Johns Hopkins University, 2006.

[182] D. E. Denning, "A lattice model of secure information flow," Communications of the ACM, vol. 19, no. 5, pp. 236-243, 1976.

[183] J. A. Goguen and J. Meseguer, "Security policies and security models," in Proc. IEEE Symposium on Security and Privacy, 1982, pp. 11-20.

[184] A. Sabelfeld and A. C. Myers, "Language-based information-flow security," IEEE Journal on Selected Areas in Communications, vol. 21, no. 1, pp. 5-19, 2003.

[185] J. Newsome and D. Song, "Dynamic taint analysis for automatic detection, analysis, and signature generation of exploits on commodity software," in Proc. NDSS Symposium, 2005.

[186] W. Enck, P. Gilbert, B.-G. Chun, L. P. Cox, J. Jung, P. McDaniel, and A. N. Sheth, "TaintDroid: An information-flow tracking system for realtime privacy monitoring on smartphones," in Proc. 9th USENIX OSDI, 2010.

[187] Y. Cai, W. Tang, C. Wen, and S. Qin, "Ghost in the Agent: Redefining Information Flow Tracking for LLM Agents," arXiv:2604.23374, 2026.

[188] D. Girrens and G. Wang, "SPA: Securing Persistent LLM Agents Across Queries with Plan-First Information-Flow Control," arXiv:2608.27234, 2026.

[189] E. Zverev, J. Kim, L. Trampert, B. Köpf, A. Kolluri, S. Tople et al., "SPIDES: Information-Flow Control for Browser Agents," arXiv:2610.24277, 2026.

[190] X. Hou, Y. Zhao, and H. Wang, "Unsafe by Flow: Uncovering Bidirectional Data-Flow Risks in MCP Ecosystem," arXiv:2605.07836, 2026.

[191] R. S. Stanley, A. Verma, L. Tsai, K. Kallas, and S. Kumar, "An AI Agent Execution Environment to Safeguard User Data," arXiv:2604.19657, 2026.

[192] W. Lan, S. Li, M. Wu, X. Lai, J. Yang, and H. Shen, "ContainmentBench: Trace-Based Evaluation of Post-Exposure Containment in Tool-Using LLM Agents," arXiv:2607.23999, 2026.

[193] Q. Jing, "Separation of Duties for Privileged LLM Agents: A Governed Execution Architecture with Measured Security-Utility Trade-offs," arXiv:2609.38224, 2026.

[194] T. Shi, Y. Mo, Y. Liu, Z. Hao, Y. Wang, W. Hu et al., "Organizational Control Layer: Governance Infrastructure at the Execution Boundary of LLM Agent Systems," arXiv:2606.04306, 2026.

[195] Y. Xi, "Persona-Execution Separation: An Architecture Pattern for Evolving LLM Agents under Execution Audit," arXiv:2608.27427, 2026.

[196] Z. Hu, D. Jacob, X. Huang, Z. Chen, B. Li, and D. Wagner, "Twin Agent: Context Residual Compression for Privilege Separated Agents," arXiv:2607.19595, 2026.

[197] N. Zwerdling, D. Boaz, E. Rabinovich, G. Uziel, D. Amid, and A. Anaby-Tavor, "Towards Enforcing Company Policy Adherence in Agentic Workflows," arXiv:2507.16459, 2025.

[198] Y. Li, Y. Chen, H. Wen, B. Zhang, H. Liu, P. Wang et al., "VIGIL: Runtime Enforcement of Behavioral Specifications in AI Agent Skills," arXiv:2606.26524, 2026.

[199] A. Mazza and E. Levi, "SCOPE: Compiling Natural-Language Policies into Neurosymbolic Predicate Programs," arXiv:2610.31062, 2026.

[200] H. Wang, C. M. Poskitt, and J. Sun, "AgentSpec: Customizable Runtime Enforcement for Safe and Reliable LLM Agents," in Proc. 48th IEEE/ACM International Conference on Software Engineering (ICSE), 2026, pp. 2938-2950; arXiv:2503.18666.

[201] J. W. Cutler, C. Disselkoen, A. Eline, S. He, K. Headley, M. Hicks et al., "Cedar: A New Language for Expressive, Fast, Safe, and Analyzable Authorization (Extended Version)," in Proc. ACM OOPSLA, 2024; arXiv:2403.04651.

[202] A. J. Mercado and A. Lomuscio, "Formal Verification of Agentic Systems over Operational Data," arXiv:2608.03609, 2026.

[203] A. Sterling, "Provably Auditable and Safe LLM Agents from Human-Authored Ontologies," arXiv:2606.04903, 2026.

[204] T. Sah, V. Srivastava, D. Sah, and K. Jordan, "The Verifier Tax: Horizon Dependent Safety Success Tradeoffs in Tool Using LLM Agents," arXiv:2603.19328, 2026.

[205] T. South, S. Marro, T. Hardjono, R. Mahari, C. D. Whitney, D. Greenwood et al., "Authenticated Delegation and Authorized AI Agents," arXiv:2501.09674, 2025.

[206] A. Chan, N. Kolt, P. Wills, U. Anwar, C. S. d. Witt, N. Rajkumar et al., "IDs for AI Systems," in NeurIPS RegML Workshop, 2024; arXiv:2406.12137.

[207] A. Chan, C. Ezell, M. Kaufmann, K. Wei, L. Hammond, H. Bradley et al., "Visibility into AI Agents," in Proc. ACM FAccT, 2024; arXiv:2401.13138.

[208] S. Nagabhushanaradhya, "OpenID Connect for Agents (OIDC-A) 1.0: A Standard Extension for LLM-Based Agent Identity and Authorization," arXiv:2509.25974, 2025.

[209] A. Goswami, "Agentic JWT: A Secure Delegation Protocol for Autonomous AI Agents," arXiv:2509.13597, 2025.

[210] A. Ibrahim and Y. Li, "Overlaying Governance: A Compositional Authorization Framework for Delegation and Scope in Agentic AI," arXiv:2606.03518, 2026.

[211] R. M. Veski, R. Guerraoui, and D. Froelicher, "CAPMAS: Capability-Based Delegation of Privileges in Multi-Agent Systems," arXiv:2609.06500, 2026.

[212] J. Wu, Y. Nan, Y. Lin, H. Wang, Y. Xiao, S. Wang et al., "SkillScope: Toward Fine-Grained Least-Privilege Enforcement for Agent Skills," arXiv:2605.05868, 2026.

[213] T. V. hamme, T. Vissers, J. Carnerero-Cano, M. Fritz, E. C. Lupu, L. Desmet et al., "MATRA: Modeling the Attack Surface of Agentic AI Systems -- OpenClaw Case Study," arXiv:2605.10763, 2026.

[214] J. Zhang, "Right to History: A Sovereignty Kernel for Verifiable AI Agent Execution," arXiv:2602.20214, 2026.

[215] Y. Kainan and C. Hershman, "Agentic process evidence," arXiv:2610.40071, 2026.

[216] J. Salfeld-Nebgen, "Governing Actions, Not Agents: Institutional Attestation as a Governance Model for Autonomous AI Systems," arXiv:2606.26298, 2026.

[217] S. Haber and W. S. Stornetta, "How to time-stamp a digital document," Journal of Cryptology, vol. 3, no. 2, pp. 99-111, 1991.

[218] S. A. Crosby and D. S. Wallach, "Efficient data structures for tamper-evident logging," in Proc. 18th USENIX Security Symposium, 2009.

[219] B. Laurie, A. Langley, and E. Kasper, "Certificate Transparency," IETF RFC 6962, 2013.

[220] European Parliament and Council of the European Union, "Regulation (EU) 2024/1689 laying down harmonised rules on artificial intelligence (Artificial Intelligence Act)," Official Journal of the European Union, Jul. 12, 2024.

[221] National Institute of Standards and Technology, "Artificial Intelligence Risk Management Framework (AI RMF 1.0)," NIST AI 100-1, Jan. 2023.

[222] National Institute of Standards and Technology, "Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile," NIST AI 600-1, Jul. 2024.

[223] A. Vassilev, A. Oprea, A. Fordyce, H. Anderson, X. Davies, and M. Hamin, "Adversarial machine learning: A taxonomy and terminology of attacks and mitigations," NIST AI 100-2e2025, Mar. 2025.

[224] ISO/IEC 42001:2023, "Information technology - Artificial intelligence - Management system," International Organization for Standardization, 2023.

[225] OWASP Foundation, "OWASP Top 10 for LLM Applications 2025," Nov. 2024 (LLM01 Prompt Injection; LLM06 Excessive Agency).

[226] MITRE, "ATLAS: Adversarial Threat Landscape for Artificial-Intelligence Systems."

[227] N. Kolt, "Governing AI Agents," Notre Dame Law Review, vol. 101, forthcoming; arXiv:2501.07913.

[228] Y. Bengio, S. Mindermann, D. Privitera, T. Besiroglu, R. Bommasani, S. Casper et al., "International AI Safety Report," arXiv:2501.17805, 2025.

[229] Z. Chen, Z. Xiang, C. Xiao, D. Song, and B. Li, "AgentPoison: Red-teaming LLM Agents via Poisoning Memory or Knowledge Bases," arXiv:2407.12784, 2024.

[230] P. Dash, T. Ge, A. Jain, T. Shah, and Z. Shang, "From Untrusted Input to Trusted Memory: A Systematic Study of Memory Poisoning Attacks in LLM Agents," arXiv:2606.04329, 2026.

[231] S. Huang, J. Zhang, and H. Jia, "When Malicious Instructions Persist: Persistent Memory Poisoning Attack on Harness-Based Agents," arXiv:2609.13889, 2026.

[232] V. Torra and M. Bras-Amorós, "Memory poisoning and secure multi-agent systems," arXiv:2603.20357, 2026.

[233] H. Triedman, R. Jha, and V. Shmatikov, "Multi-Agent Systems Execute Arbitrary Malicious Code," arXiv:2503.12188, 2025.

[234] D. Lee and M. Tiwari, "Prompt Infection: LLM-to-LLM Prompt Injection within Multi-Agent Systems," arXiv:2410.07283, 2024.

[235] P. He, Y. Lin, S. Dong, H. Xu, Y. Xing, and H. Liu, "Red-Teaming LLM Multi-Agent Systems via Communication Attacks," in Proc. ACL, 2025; arXiv:2502.14847.

[236] L. Hammond, A. Chan, J. Clifton, J. Hoelscher-Obermaier, A. Khan, E. McLean et al., "Multi-Agent Risks from Advanced AI," arXiv:2502.14143, 2025.

[237] C. S. d. Witt, K. Krawiecka, I. Krawczuk, B. Hagag, W. L. Anderson, P. Belcak et al., "Open Challenges in Multi-Agent Security: Towards Secure Systems of Interacting AI Agents," arXiv:2505.02077, 2025.

[238] A. Shahriar, M. N. Rahman, S. Ahmed, F. Sadeque, and M. R. Parvez, "A Survey on Agentic Security: Applications, Threats and Defenses," Transactions on Machine Learning Research, 2026; arXiv:2510.06445.

[239] Anthropic, "Introducing the Model Context Protocol," Nov. 25, 2024.

[240] X. Hou, Y. Zhao, S. Wang, and H. Wang, "Model Context Protocol (MCP): Landscape, Security Threats, and Future Research Directions," arXiv:2503.23278, 2025.

[241] Invariant Labs, "MCP security notification: Tool poisoning attacks," Apr. 2025.

[242] Y. Yang, C. Gao, D. Wu, Y. Chen, Y. Li, and S. Wang, "MCPSecBench: A Systematic Security Benchmark and Playground for Testing Model Context Protocols," arXiv:2508.13220, 2025.

[243] D. Zhang, Z. Li, X. Luo, X. Liu, P. Li, and W. Xu, "MCP Security Bench (MSB): Benchmarking Attacks Against Model Context Protocol in LLM Agents," arXiv:2510.15994, 2025.

[244] X. Hou, S. Wang, Y. Zhang, Z. Xue, Y. Zhao, C. Fu et al., "SMCP: Secure Model Context Protocol," arXiv:2602.01129, 2026.

[245] Z. Yuan, Z. Chen, Z. Xiang, N. D. Bastian, S. H. Hashemi, C. Xiao et al., "ShieldNet: Network-Level Guardrails against Emerging Supply-Chain Injections in Agentic Systems," arXiv:2604.04426, 2026.

[246] Google, "Announcing the Agent2Agent Protocol (A2A)," Apr. 9, 2025.

[247] I. Habler, K. Huang, V. S. Narajala, and P. Kulkarni, "Building A Secure Agentic AI Application Leveraging A2A Protocol," arXiv:2504.16902, 2025.

[248] A. Lotfi, M. M. Rahman, I. Karim, and E. Bertino, "A2ABreak: Systematic Security Analysis of the A2A Protocol," arXiv:2609.10871, 2026.

[249] A. Alshammari, S. Assiri, and H. Bahsi, "A2A-ForensicTrace: Offline Verification of Tamper-Evident A2A Runtime Evidence," arXiv:2609.33924, 2026.

[250] Z. Anbiaee, M. Rabbani, M. Mirani, G. Piya, I. Opushnyev, A. Ghorbani et al., "Security Threat Modeling for Emerging AI-Agent Protocols: A Comparative Analysis of MCP, A2A, Agora, and ANP," arXiv:2602.11327, 2026.

[251] B. Bucknall, A. Byrley, and L. Hammond, "From TCP/IP to MCP: Security and Governance Lessons from Internet Protocols for Agentic AI," arXiv:2610.26624, 2026.

[252] K. L. Ogunsusi, "Securing Agentic Commerce Through Behavior-Aware Fraud Detection and Cybersecurity for Trusted AI-Agent Payment Authorization," arXiv:2610.27483, 2026.

[253] B. T. Willard and R. Louf, "Efficient Guided Generation for Large Language Models," arXiv:2307.09702, 2023.

[254] Y. Dong, C. F. Ruan, Y. Cai, R. Lai, Z. Xu, Y. Zhao et al., "XGrammar: Flexible and Efficient Structured Generation Engine for Large Language Models," arXiv:2411.15100, 2024.

[255] Y. Li, Y. Dong, J. Li, and G. Li, "Efficient Grammar-Constrained Decoding via Parser Stack Classification," arXiv:2608.03065, 2026.

[256] S. Geng, H. Cooper, M. Moskal, S. Jenkins, J. Berman, N. Ranchin et al., "JSONSchemaBench: A Rigorous Benchmark of Structured Outputs for Language Models," arXiv:2501.10868, 2025.

[257] G. Wang, J. Yu, X. Zhang, D. Jiang, Y. Song, T. Deb et al., "STED and Consistency Scoring: A Framework for Evaluating LLM Structured Output Reliability," arXiv:2512.23712, 2025.

[258] Y. Li, Y. Xiong, J. Zhong, J. Zhang, J. Zhou, and L. Zou, "Exploiting Prefix-Tree in Structured Output Interfaces for Enhancing Jailbreak Attacking," arXiv:2502.13527, 2025.

[259] G. Syros, B. Bullwinkel, A. Oprea, C. Nita-Rotaru, A. Minnich, X. Liu et al., "Kerkoporta: Injecting Structured-Output Backdoors in Reasoning Coding Agents," arXiv:2611.00138, 2026.

[260] M. P. Naeini, G. F. Cooper, and M. Hauskrecht, "Obtaining well calibrated probabilities using Bayesian binning," in Proc. AAAI Conference on Artificial Intelligence, 2015.

[261] C. Guo, G. Pleiss, Y. Sun, and K. Q. Weinberger, "On Calibration of Modern Neural Networks," in Proc. ICML, 2017; arXiv:1706.04599.

[262] N. Michael, D. BenShushan, J. Bien, and D. A. Moore, "Confidence Calibration in Large Language Models," arXiv:2605.23909, 2026.

[263] V. Vovk, A. Gammerman, and G. Shafer, Algorithmic Learning in a Random World. New York: Springer, 2005.

[264] A. N. Angelopoulos and S. Bates, "A Gentle Introduction to Conformal Prediction and Distribution-Free Uncertainty Quantification," arXiv:2107.07511, 2021.

[265] A. N. Angelopoulos, S. Bates, A. Fisch, L. Lei, and T. Schuster, "Conformal Risk Control," in Proc. ICLR, 2024; arXiv:2208.02814.

[266] M. A. Rahman, M. A. Rahman, N. H. Samin, K. R. Tasnia, M. H. Amin, S. R. Ahona et al., "Beyond Aggregate Risk: Role-Stratified Conformal Risk Control for LLM Tool Calls," arXiv:2607.24343, 2026.

[267] Z. Yu, Y. Gu, V. P. Nia, and M. Asgharian, "G-CARB: Graph-Localized Conformal Agent Risk Budget for Compositional Harm," arXiv:2610.05563, 2026.

[268] P. Jorion, Value at Risk: The New Benchmark for Managing Financial Risk, 3rd ed. New York: McGraw-Hill, 2006.

[269] R. T. Rockafellar and S. Uryasev, "Optimization of conditional value-at-risk," Journal of Risk, vol. 2, no. 3, pp. 21-41, 2000.

[270] P. Artzner, F. Delbaen, J.-M. Eber, and D. Heath, "Coherent measures of risk," Mathematical Finance, vol. 9, no. 3, pp. 203-228, 1999.

[271] J. Freund and J. Jones, Measuring and Managing Information Risk: A FAIR Approach. Oxford: Butterworth-Heinemann, 2014.

[272] B. Efron and R. J. Tibshirani, An Introduction to the Bootstrap. New York: Chapman & Hall, 1993.

[273] E. B. Wilson, "Probable inference, the law of succession, and statistical inference," Journal of the American Statistical Association, vol. 22, no. 158, pp. 209-212, 1927.

[274] Q. McNemar, "Note on the sampling error of the difference between correlated proportions or percentages," Psychometrika, vol. 12, no. 2, pp. 153-157, 1947.

[275] T. Gebru, J. Morgenstern, B. Vecchione, J. W. Vaughan, H. Wallach, H. Daumé III, and K. Crawford, "Datasheets for datasets," Communications of the ACM, vol. 64, no. 12, pp. 86-92, 2021.

[276] M. Akhtar et al., "Croissant: A metadata format for ML-ready datasets," in Advances in Neural Information Processing Systems 37 (Datasets and Benchmarks Track), 2024.

[277] M. Mitchell, S. Wu, A. Zaldivar, P. Barnes, L. Vasserman, B. Hutchinson et al., "Model Cards for Model Reporting," in Proc. ACM FAT*, 2019; arXiv:1810.03993.

[278] H. P. Luhn, "Computer for verifying numbers," U.S. Patent 2,950,048, 1960.

[279] V. I. Levenshtein, "Binary codes capable of correcting deletions, insertions, and reversals," Soviet Physics Doklady, vol. 10, no. 8, pp. 707-710, 1966.

[280] R. Parasuraman and D. H. Manzey, "Complacency and bias in human use of automation: An attentional integration," Human Factors, vol. 52, no. 3, pp. 381-410, 2010.

[281] I. Pekaric, P. Zech, and T. Mattson, "LLMs in Cybersecurity: Friend or Foe in the Human Decision Loop?," arXiv:2509.06595, 2025.

[282] ProtectAI, "deberta-v3-base-prompt-injection-v2," model card, Hugging Face, 2024. [Online]. Available: https://huggingface.co/protectai/deberta-v3-base-prompt-injection-v2

[283] T. Kwa, B. West, J. Becker, A. Deng, K. Garcia, M. Hasin et al., "Measuring AI Ability to Complete Long Software Tasks," in Advances in Neural Information Processing Systems (NeurIPS), 2025; arXiv:2503.14499.

[284] P. Belcak, G. Heinrich, S. Diao, Y. Fu, X. Dong, S. Muralidharan et al., "Small Language Models are the Future of Agentic AI," arXiv:2506.02153, 2025.

[285] X. Wang and M. Brorsson, "Rethinking Scale: Deployment Trade-offs of Small Language Models under Agent Paradigms," arXiv:2604.19299, 2026.

[286] L. de Moura and N. Bjørner, "Z3: An efficient SMT solver," in Proc. TACAS, LNCS vol. 4963, 2008, pp. 337-340.

[287] D. R. MacIver, Z. Hatfield-Dodds et al., "Hypothesis: A new approach to property-based testing," Journal of Open Source Software, vol. 4, no. 43, p. 1891, 2019.

[288] M. Bishop and M. Dilger, "Checking for race conditions in file accesses," Computing Systems, vol. 9, no. 2, pp. 131-152, 1996.

[289] J. Reason, "Human error: models and management," BMJ, vol. 320, pp. 768-770, 2000.

[290] Unsloth, "Qwen3.5-4B-GGUF," quantised model files (Q4_K_M), Hugging Face, 2026. [Online]. Available: https://huggingface.co/unsloth/Qwen3.5-4B-GGUF

[291] A. Betlen et al., "llama-cpp-python: Python bindings for llama.cpp," version 0.3.36, PyPI, Oct. 2026.

[292] S. Yao, J. Zhao, D. Yu, N. Du, I. Shafran, K. Narasimhan et al., "ReAct: Synergizing Reasoning and Acting in Language Models," in Proc. ICLR, 2023; arXiv:2210.03629.

[293] T. Schick, J. Dwivedi-Yu, R. Dessì, R. Raileanu, M. Lomeli, L. Zettlemoyer et al., "Toolformer: Language Models Can Teach Themselves to Use Tools," in Advances in Neural Information Processing Systems (NeurIPS), 2023; arXiv:2302.04761.

[294] J. Jang, K. Yang, H. Lim, and H. Park, "Flat Score, Amplified Failures: How the Error Budget Masks Damage in Quantized LLM Agents," arXiv:2607.27275, 2026.

[295] P. He, J. Gao, and W. Chen, "DeBERTaV3: Improving DeBERTa using ELECTRA-Style Pre-Training with Gradient-Disentangled Embedding Sharing," in Proc. ICLR, 2023; arXiv:2111.09543.

[296] Y. Taheri, M. H. Heydari, E. Naaman, and A. Fatemi, "Small Reasoning Models are Instruction Followers in Function Calling," arXiv:2608.22472, 2026.

[297] G. Team, A. Kamath, J. Ferret, S. Pathak, N. Vieillard, R. Merhej et al., "Gemma 3 Technical Report," arXiv:2503.19786, 2025.

[298] OpenAI, :, S. Agarwal, L. Ahmad, J. Ai, S. Altman et al., "gpt-oss-120b & gpt-oss-20b Model Card," arXiv:2508.10925, 2025.

[299] A. Yang, A. Li, B. Yang, B. Zhang, B. Hui, B. Zheng et al., "Qwen3 Technical Report," arXiv:2505.09388, 2025.