

MACHINE LEARNING IN PHYSICS

GRAPH AUTOENCODERS

PART 2

HARRISON B. PROSPER

PHY6937 / PHY4936

Outline


- Recap
- Graph Autoencoder – Part 2
- PyTorch Geometric
- Summary

Lecture based on notes by Dr. Claire David


African Institute of Mathematical Sciences, Cape Town, South Africa.

Recap (1)


- A graph is a data structure that comprises nodes (or vertices) and edges:



- Our goal is to create a function (a GAE) that takes a graph as input, encodes it, and decodes it back to the same graph.



Recap (2): Data Structures



$V[n = 4, d = 3]$

$\text{edge_index}[2, K = 16]$

$K = \text{number of edges.}$

$d = \text{dimension of the input feature vectors.}$

target node index = $\text{edge_index}[0]$

source node index = $\text{edge_index}[1]$

edge features ($\text{edge_weights}[K]$)

$e_{(0,0)}$	$e_{(0,1)}$	$e_{(0,2)}$	$e_{(0,3)}$	$\dots$	$e_{(3,3)}$
-------------	-------------	-------------	-------------	---------	-------------

GRAPH AUTOENCODER PART 2


Graph Autoencoder (1)

Our GAE computations so far are:

- $A = f(V)$ node adjacency (edge weights)
- $X = \sigma(VW_1^T + B_1)$ node embedding
- $X' = AX$ **node attention**

(Edges are defined by $E = (\text{edge_index}, \text{edge_weights})$)

$X' = AX$ is a simple example of the concept of **attention**: each target node “pays attention” to specific nodes in the graph. (in our example, those that are spatially close).



Graph Autoencoder (2)

In addition to the computations,


- $A = f(V)$ node adjacency (edge weights)
- $X = \sigma(VW_1^T + B_1)$ node embedding
- $X' = AX$ node attention

we'll perform another linear transformation:


- $Z = X'W_2^T + B_2$

The matrices W_1 , B_1 , W_2 and B_2 are the parameters of our graph convolution operation, **GNNConv**.

The full model is shown on the next slide.



GAE: Model



PYTORCH GEOMETRIC (PYG)


PyTorch Geometric (1)

The toolkit **PyTorch Geometric (PyG)** solves two problems (among many others):

- How to do matrix algebra with **sparse matrices**.
- How to do **batch processing** of graphs.


In our earlier GNN example, step **2** below used `torch.matmul( $A$ ,  $X$ )`. But in PyG (pi-gee) $X' = AX$ is computed using X and the **edges**.

- 1.** $X = \sigma(VW_1^T + B_1)$ node embedding
- 2.** $X' = AX$ node attention
- 3.** $Z = X'W_2^T + B_2$



PyTorch Geometric (2)

In our 4-node graph example, PyG uses 3 data structures:





PyTorch Geometric (3)

PyG solves the two problems by **serializing** graphs using these data structures. Each node is viewed as an *independent* entity linked to source nodes via the **edge_index** and the associated **edge_weight**.

0	0	0	0	...	3
0	1	2	3	...	3

$e_{(0,0)}$	$e_{(0,1)}$	$e_{(0,2)}$	$e_{(0,3)}$	...
-------------	-------------	-------------	-------------	-----



PyTorch Geometric (4)

Consider the computation of $X' = AX$, where X is a tensor of embedded nodes of shape $[n = 4, h]$. Focus on target node **2**, which is associated with row **2** of matrix A , and consider the feature **0** of matrix X .

$e_{(2,0)}$	$e_{(2,1)}$	$e_{(2,2)}$	$e_{(2,3)}$
-------------	-------------	-------------	-------------


 $\times$

a_{00}
a_{10}
a_{20}
a_{30}

Before the *sum* in the *vertical* direction (dim=0 axis) we collect the products into a column:


$e_{(2,0)}a_{00}$
$e_{(2,1)}a_{10}$
$e_{(2,2)}a_{20}$
$e_{(2,3)}a_{30}$

Each row is a **message** associated with a single attribute, namely, attribute **0** from one of the 4 *source* nodes.



PyTorch Geometric (5)

- This calculation is repeated with every other target node.
- Then the columns of products are stacked *vertically* to form a single column whose length equals K the number of edges in the graph.
- The procedure is repeated for each of the h attributes of the embedded nodes, and the columns are stacked *horizontally*.



PyTorch Geometric (6)

- One thereby arrives at a tensor, comprising all **messages**, of shape $[K, h]$.
- In practice, the messages tensor is constructed by first expanding X into a tensor of shape $[K, h]$ using $X[\text{src_nodes}]$, where $\text{src_nodes} = \text{edge_index}[1]$, and then doing an elementwise product (that is, a **Hadamard product**) between edge_weights and $X[\text{src_nodes}]$.

$e_{(0,0)}a_{00}$	...	$e_{(0,0)}a_{0h-1}$
$e_{(0,1)}a_{10}$		$e_{(0,1)}a_{1h-1}$
$e_{(0,2)}a_{20}$		$e_{(0,2)}a_{2h-1}$
$e_{(0,3)}a_{30}$		$e_{(0,3)}a_{30}$
$\vdots$		$\vdots$
$e_{(3,0)}a_{00}$	...	$e_{(3,0)}a_{0h-1}$
$e_{(3,1)}a_{10}$		$e_{(3,1)}a_{1h-1}$
$e_{(3,2)}a_{20}$		$e_{(3,2)}a_{2h-1}$
$e_{(3,3)}a_{30}$		$e_{(3,3)}a_{3h-1}$

PyTorch Geometric (7)

- Finally, the PyG scatter function

```
scatter(messages, trg_nodes, dim=0,  
reduce='sum' )
```

is used to perform the sum over products per target node and per attribute, thereby arriving at $X' = AX$, which is of shape $[n, h]$.

PyTorch Geometric (8): Sparsity

- The full power of PyG arise from its ability to handle sparse graphs. Suppose our 4-node graph is connected as shown.


- The `edge_index` of the graph is:

target nodes:

0	0	0	1	1	2	2	3
---	---	---	---	---	---	---	---

source nodes:

0	1	2	0	1	0	3	2
---	---	---	---	---	---	---	---



- One point we didn't emphasize but I hope was clear is that many of the links in our example graphs are **bi-directional**!
- The fact that our graph is now sparsely connected, changes nothing about the matrix algebra is done!

Summary

- A graph $G = (X, E)$ comprises nodes X and edges E .
- A disparate array of datasets can be represented as graphs, including molecular structures, particle collision events, social networks, epidemics, etc.

- **PyTorch Geometric** is one of several toolkits that can be used to build and manipulate graphs and build and train sophisticated graph-based models.

